INCH-POUND

MIL-B-48594A (AR)
AMENDMENT 1
1 June 1992

MILITARY SPECIFICATION

BOARD ASSEMBLY, COMPONENT: 11748254

This Amendment forms a part of Military Specification MIL-B-48594A (AR), dated 29 March 1991, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, Add the following military specification:

"MIL-T-28800 - Test Equipment for use with Electrical and Electronic Equipment, General Specification for"

PAGE 2

2.1.1, Delete the following military standard:

"MIL-STD-2000 – Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2, Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

Delete paragraph 3.3.1 in its entirety and substitute:

"3.3.1 Vibration. The component board shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to sinusoidal vibrations, in each of three mutually perpendicular axes, as specified in MIL-T-28800 for Type I, Class 3, Style F test equipment."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

Delete paragraph 3.3.3 in its entirety and substitute:

"3.3.3 Altitude operating. The component board shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

Delete paragraphs 3.3.3.1 and 3.3.3.2 in their entirety.

PAGE 5

Delete paragraph 3.8 in its entirety and substitute:

"3.8 Soldering All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 10

Delete paragraph 4.7.1.1 in its entirety and substitute:

"4.7.1.1 Vibration . This test shall be performed as specified in MIL-T-28800 for Type I, Class 3, Style F test equipment with the exception that Step 4.c Resonance Dwell does not apply. The component board shall be attached to the vibration generator directly or with a fixture, and securely held by its normal means of attachment. After vibration, the component board shall be tested as specified in 4.7.2 and 4.7.3 herein to determine compliance with 3.3.1."

Delete paragraph 4.7.1.3 in its entirety and substitute:

"4.7.1.3 Altitude operating. This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-810 operational checkout shall be as specified in para- for compliance with 3.3.3."

PAGE 13

Delete paragraph 4.8 in its entirety and substitute:

"4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7."

Custodian:
Army–AR

Preparing activity:
Army–AR

(Project 4931-A311)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.