MIL-C-48596A (AR)
AMENDMENT 1
22 September 1987

MILITARY SPECIFICATION

COMPUTER SYSTEM, BALLISTIC, M21: 11732979

This Amendment forms a part of Military Specification MIL-C-48596A (AR) dated 30 June 1981, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, Inspection Equipment, Add "11744800 Reticle Projector (GFP)".

PAGE 20

3.3.23.2, Subparagraph b, Delete "The D (OUT) signal between W2P6-D (+) and W2P6-G (-) shall vary between zero and +12 Vdc when the RPU reticle deflects left and between zero and -12 Vdc when the RPU reticle deflects right." and substitute "The D (OUT) signal between W2P6-D (+) and W2P6-G (-) shall vary between zero and +14.5 Vdc when the RPU reticle deflects left and between zero and -14.5 Vdc when the RPU reticle deflects right."

PAGE 28

Table XIV, Test Equipment, Add: "11 11744800 Reticle Projector (GFP)".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-A362)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.