INCH-POUND

MIL-PRF-15733/38L
w/AMENDMENT 1
04 April 2019
SUPERSEDING
MIL-PRF-15733/38L
14 April 2009

PERFORMANCE SPECIFICATION SHEET

FILTERS, RADIO FREQUENCY INTERFERENCE, HERMETICALLY SEALED, STYLE FL16

PINs M15733/38-0001, -0002, -0004, -0005, are inactive for new design as of 6 October 1980. PINs M15733/38-0003, -0006, and -0008 are inactive for new design as of 14 April 2009. For new design see table III.

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the filters described herein shall consist of this specification sheet and MIL-PRF-15733.




FIGURE 1. Filter and hardware dimensions and circuit diagrams.

AMSC N/A

FSC 5915

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.

Filter dimensions.

Dash number	A		B		C		D		E	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
0001	.290 (7.37)	.310 (7.87)	---	.42 (10.7)	.302 (7.67)	.322 (8.18)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0002	.160 (4.06)	.291 (7.39)	---	.415 (10.54)	.180 (4.57)	.200 (5.08)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0003	.530 (13.46)	.550 (13.97)	---	.385 (9.78)	.177 (4.50)	.197 (5.00)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0004	.160 (4.06)	.180 (4.57)	---	.385 (9.78)	.177 (4.50)	.197 (5.00)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0005	.160 (4.06)	.180 (4.57)	---	.385 (9.78)	.177 (4.50)	.197 (5.00)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0006	.160 (4.06)	.291 (7.39)	---	.415 (10.54)	.302 (7.67)	.322 (8.18)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0007	.210 (5.33)	.230 (5.84)	---	.385 (9.78)	.302 (7.67)	.322 (8.18)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0008	.160 (4.06)	.180 (4.57)	---	.385 (9.78)	.177 (4.50)	.197 (5.00)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0009	.290 (7.37)	.310 (7.87)	---	.385 (9.78)	.177 (4.50)	.197 (5.00)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)
0010	.290 (7.37)	.310 (7.87)	---	.385 (9.78)	.302 (7.67)	.322 (8.18)	.100 (2.54)	.190 (4.83)	.100 (2.54)	.190 (4.83)

FIGURE 1. Filter and hardware dimensions and circuit diagrams - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.

Filter dimensions - Continued.

Dash number	F	G		H 1/		J
	+.010 -.015	Min	Max	±.010	±.010	Mounting thread
0001	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0002	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0003	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0004	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0005	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0006	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0007	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0008	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0009	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A
0010	.115 (2.92)	.190 (4.83)	.210 (5.33)	.060 (1.52)	.080 (2.03)	.250-28 UNF-2A

1/ Optional slot may be supplied .050 (1.27) ±.010 (.25) inches by .070 (1.78) ±.010 (.25) inches.

FIGURE 1. Filter and hardware dimensions and circuit diagrams - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.

Hardware dimensions

Dash number	K		L		M	N		P	
	Min	Max	Min	Max	Thread	Min	Max	Min	Max
0001	.302 (7.67)	.322 (8.18)	.085 (2.16)	.095 (2.41)	.250-28 UNF-2B	.395 (10.03)	.408 (10.36)	.010 (.25)	.030 (.76)
0002	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0003	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0004	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0005	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0006	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0007	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0008	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0009	.302 (7.67)	.322 (8.18)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)
0010	.302 (7.67)	.322 (8.18)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.405 (10.29)	.017 (.43)	.027 (.69)

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Circuit diagram is for information only.
4. All filters shall be supplied with mounting hardware.
5. Terminal thickness shall be .021 (0.53 mm)/.011 (0.28 mm).
6. Terminal identification. The case shall be marked at the threaded end of the filter, with the symbol “L” for dash numbers 0001, 0002, 0004, 0005, 0006, 0008, 0009, and 0010.

FIGURE 1. Filter and hardware dimensions and circuit diagrams - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Weight: 5 grams maximum.

Case: Metal.

Case and hardware finish: In accordance with MIL-PRF-15733. Pure tin finish is prohibited.

Seal: Glass-to-metal.

Terminals: Solderable (see figure 1).

Operating temperature range:

Dash 0001 through 0006, 0008, 0009, and 0010: -55°C to +125°C.

Dash 0007: -55°C to +85°C

Rated voltage: See table I.

Rated current: See table I.

Seal: In accordance with MIL-PRF-15733.

Capacitance to ground: Not specified.

Temperature rise: +25°C maximum.

Insulation resistance: In accordance with MIL-PRF-15733 and the following:

Test temperature: +25°C.

Test potential: Rated dc voltage or 100 volts dc whichever is less.

Insulation resistance shall be not less than:

Dash numbers	Megohms
0001	500
0002 through 0007, 0009, and 0010	100
0008	1,000

Voltage drop: See table I.

Insertion loss: In accordance with MIL-PRF-15733 and the following:

At +25°C: Shall be as specified in table I.

At -55°C and at the maximum operating temperature: Shall be as specified in table I except as follows:

Up to 10 MHz: A degradation of 4 dB from the value specified in table I shall be allowed.

Terminal strength: In accordance with MIL-PRF-15733 and MIL-STD-202-211; test condition A (pull):

Applied force: 5 pounds.

Salt atmosphere (corrosion): In accordance with MIL-PRF-15733 and MIL-STD-202-101; test condition A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.

Shock (specified pulse): In accordance with MIL-PRF-15733 and MIL-STD-202-213; test condition I (100g).

Vibration, high frequency: In accordance with MIL-PRF-15733 and MIL-STD-202-204; test condition D (20g).

Life: In accordance with MIL-PRF-15733 and MIL-STD-202-108.

Qualification inspection: Test condition D (1,000 hours).

Group C inspection:

Dash numbers	Test condition
0001, 0002, 0004 through 0010	B (250 hours)
0003	D (1,000 hours)

Part or Identifying Number (PIN): M15733/38- (dash number from table I).

Marking: Marking shall be as follows:

For dash numbers 0001, 0002, and 0004 through 0010, the filter shall be marked with the following minimum information:

a. Military PIN.

b. Source code.

c. Date code.

d. Terminal identification.

Full marking in accordance with MIL-PRF-15733 shall be marked on the unit package. For dash number 0003, the filter shall be marked with full marking in accordance with MIL-PRF-15733.

Extension of qualification:

Initial qualification to MIL-PRF-15733/38 may be granted based on qualification to MIL-PRF-28861/1 or /3 or MIL-PRF-15733/49 as indicated in table II. Extension of qualification from MIL-PRF-28861/1 or /3 or MIL-PRF-15733/49 to MIL-PRF-15733/38 is permissible under the following provisions:

a. The MIL-PRF-15733/38 part uses the same design and dielectric characteristics as the part upon which extension of qualification is based.

b. The MIL-PRF-28861/1 or /3 or MIL-PRF-15733/49 qualification data verifies that the physical and electrical characteristics of the MIL-PRF-15733/38 parts are satisfied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash number	Circuit	Max current (amps)	Voltage		Voltage drop (volts dc max)	Minimum full load insertion loss (dB) in accordance with MIL-STD-220 at +25°C 1/							
			DC volts	AC 2/		30 KHz	150 KHz	300 KHz	1 MHz	10 MHz	100 MHz	1 GHz	10 GHz
0001 4/	L2	10	50	-	.040	-	-	-	44	60	55	-	-
0002 4/	L2	15	50	-	.12	15	28	33	44	60	-	70	70
0003 4/	Pi	3	150	-	.15	-	7	24	54	80	80	80	80
0004 4/	L2	10	50	-	.08	15	28	33	44	60	-	70	-
0005 4/	L2	10	50 3/	-	.08	15	28	33	44	60	-	70	-
0006 4/	L2	15	50	-	.12	15	28	33	44	60	-	70	70
0007	Pi	15	50	-	.09	70 dB from 420 MHz to 1.0 GHz, inclusive							
0008 4/	L2	15	200	125	.12	-	-	-	6	25	-	60	-
0009	L2	15	250	125	.09	4	15	21	31	50	-	70	80
0010	L2	15	250	125	.09	4	15	21	31	50	-	70	80

1/ Full-load insertion loss measurements shall be performed over the frequency range of 100 kHz to 20 MHz inclusive. Measurements below or above this frequency range shall be performed at no-load.
2/ From dc to 400 Hz.
3/ Voltage rating at +125°C: (Note - derated from 80 V dc at +85°C).
4/ Inactive for new design.

TABLE II. Extension of qualification.

Qualification to MIL-PRF-28861	Will qualify MIL-PRF-15733/38		Qualification to MIL-PRF-15733/49	Will qualify MIL-PRF-15733/38
/01-001	-0002		-0006	-0004
/01-001	-0004		-0006	-0005
/01-001	-0005			
/01-011	-0006			
/01-009	-0008			
/03-015	-0003			

TABLE III. Substitution data for new design.

Inactive PIN	For new design use	
	Specification sheet	PIN
M15733/38-0001	MIL-PRF-28861/1	M28861/01-011TB
M15733/38-0002	MIL-PRF-28861/1	M28861/01-001TB
M15733/38-0003	MIL-PRF-28861/3	M28861/03-015TB
M15733/38-0004	MIL-PRF-28861/1	M28861/01-001TB
M15733/38-0005	MIL-PRF-28861/1	M28861/01-001TB
M15733/38-0006	MIL-PRF-28861/1	M28861/01-011TB
M15733/38-0008	MIL-PRF-28861/1	M28861/01-009TB

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-15733, this document also references the following:

MIL-STD-202-101
MIL-STD-202-108
MIL-STD-202-204
MIL-STD-202-211
MIL-STD-202-213
MIL-STD-220

Amendment notations. The margins of this specification sheet are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - AR, AT, AV
Navy - AS, MC, OS, SH
Air Force - 19

Preparing activity:
DLA - CC

(Project 5915-2019-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:19Z
Check the source to verify that this is the current version before use.