MIL-A-50013B(MU)
12 June 1969
SUPERSEDING
MIL-A-50013A(MU)
26 July 1968

MILITARY SPECIFICATION

ADAPTERS, CLUSTER, BOMB,

750-POUND, M30 AND M30A1

1. SCOPE

1.1 Scope. This specification covers two types of adapters.

1.2 Classification. The adapters shall be of the following types as specified (see 6.2):

Type I - M30.
Type II - M30A1.

2. APPLICABLE DOCUMENTS'

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part os this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

FF-P-386 - Pins, Cotter (Split).
PPP-T-60 - Tape, Pressure-Sensitive Adhesive, Waterproof, for Packaging.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

D14-23-3045 - Adapter, 750-Pound Cluster, M30 and M30A1 - Bill of Material.
B14-17-434 - Packing, 750-Pound Cluster Adapter - Bill of Material.
E14-17-436 - Crate, Wood, Wirebound, Assembly, Detail and Bill of Material.
D14-17-448 - Packing, 750-Pound Cluster Adapter.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing D14-23-3045 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the item shall conform to the specifications and drawings listed on Drawing D14-23-3045 and subsidiary drawings.

3.2 Assembly. The adapter shall be assembled as specified on Drawing D14-23-3046.

3.3 Leakage. The adapter shall not leak when tested as specified in 4.4.4.1.

3.4 Gasket joint. The gasket joint shall not crack or show evidence of separation when tested as specified in 4.4.4.2.

3.5 Preproduction. Prior to the start of regular production, a preproduction sample of adapters shall be produced in accordance with this specification for examination and tests (see 4.3 and 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. The adapter shall be free from contamination (oil, grease or dirt) and damage such as dents, cracks or deformation which could affect its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 10 adapters shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. Each adapter shall be examined in accordance with the classification of defects (4.4.3.3). The AQL's do not apply.

4.3.2.2 For tests. Each adapter shall be tested as specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.3.2 to be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the adapters of one interfix number, produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions, during one week's production.

4.4.2 Sampling for examination and tests. Sampling shall be conducted in accordance with MIL-STD-105. Each adapter shall be tested for leakage in accordance with 4.4.4.1.

4.4.3 Inspection procedure.

4.4.3.1 For examination and test. The sample adapters and the level C preparation for delivery shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.4.3.2 Leakage. Each adapter shall be tested in accordance with 4.4.4.1. No leakage is allowed (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects.

(a) Adapter, 750-pound cluster, M30 and M30A1, assembly (Drawing D14-23-3046).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
*101	Component missing, incorrect or incorrectly assembled	
*102	Thread (1-3/4 - 12 UN - 2B) incorrect (Dwg C14-23-3078)	
103	Shell length incorrect	
104	Hook location or attachment incorrect	
105	Spotweld insufficient edge distance	
106	Well location or depth incorrect (M30A1 only)	
107	Suspension lug incorrectly assembled	
108	Fin orientation marking missing or incorrect	
109	Workmanship (3.6)	
Minor:	AQL 4.0 percent defective	
201	Protective finish missing or incorrect	

*Check prior to assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects (continued).

(b) Gasket, extruded (Drawing C14-23-3144).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 0.65 percent defective	
101	Joint separation	4.4.4.2

(c) Tube, hinge (Drawing B14-23-3033).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Hardness incorrect

(d) Preparation for delivery (Section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Containers or pallets incorrect.
102	Component missing or incorrectly packed.
103	Preservative missing.
104	Corrugated fiberboard pads missing (pallet only).
105	Quantity per pallet or container incorrect.
106	Cotter pin not spread (pallet only).
107	Blocking, bracing or cushioning missing.
108	Strapping loose or missing.
109	Damaged container or pallet.
110	Container closure incorrect.
111	Marking missing, illegible or incorrect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Leakage. This test shall be performed prior to painting. Seal the holes in the upper end plate (Drawing C14-23-1480) with a suitable device. Introduce air into the adapter at a pressure of 20 ± 5 pounds per square inch gage (psig). Submerge the adapter completely in water in a position that will allow the adapter to be revolved around its longitudinal axis. A sufficient concentrate of wetting agent shall be in the water to prevent bubbles from clinging to the surfaces. Observe the adapter for a period of not less than one minute. A steady stream of bubbles denotes a leak.

4.4.4.2 Gasket joint. The gasket shall be gripped at points no more than 2 inches on either side of the vulcanized joint. It shall be clamped in such a way that the pull is evenly distributed. A pull test of 300 pounds per square inch of cross section shall be applied.

5. PREPARATION FOR DELIVERY

5.1 Preservation. Preservation shall be as specified on Drawing D14-23-3046.

5.2 Packing, level C.(Interplant shipment).

5.2.1 Truck shipment only. The gasket shall be coiled so that the outside diameter of the coil does not exceed the inside diameter of the adapter. Secure the coiled gasket together with type III, class 1 pressure-sensitive tape conforming to PPP-T-60, applied at approximately three equidistant locations on the coil. The coiled gasket shall then be inserted inside the adapter, which has been preserved as specified in 5.1 and assembled as specified on Drawing D14-23-3046. A split cotter pin, 0.094-inch nominal diameter by 1-inch long, standard end, conforming to type B of FF-P-386 shall be inserted through the 0.108-inch hole in the end channels (Drawing D14-23-3028). The cotter pin ends shall be spread open to a minimum of 90 degrees. Fourteen of the adapters assembled as above shall be securely fastened on a wood pallet as shown on Drawing D14-17-448. The palletized adapters shall be blocked and braced in the truck so as to prevent movement during shipment.

5.2.2 Truck or other forms of transportation. Five adapters preserved as specified in 5.1, with the same number of gaskets inserted inside the adapters, shall be packed in a wirebound crate as shown on Drawing E14-17-435, which is listed on Drawing B14-17-434.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers and palletized loads shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This item is intended for use in grouping various types of bombs for dispersion by aircraft.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.

(b) The type of adapter required.

(c) The level C packing option.

(d) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.

(2) Name and address of test facility and shipping instructions when testing is performed by the Government.

(3) Time required for the Government to notify the supplier whether or not to proceed with production.

(e) The suspension lugs will be Government furnished.

6.3 Repair of leaky adapters. An adapter found to be leaking may be repaired and resubmitted for test in accordance with 4.4.4.1.

Custodian:

Army - MU

Preparing Activity:

Army - MU(EA)

Project No. 1325-A320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:14Z
Check the source to verify that this is the current version before use.