MIL-C-48087A (AR)
AMENDMENT 5
8 September 1988
SUPERSEDING
AMENDMENT 4
12 March 1987

MILITARY SPECIFICATION

CARTRIDGE, 4.2 INCH, HE, M329A2
W/SUPPLEMENTARY CHARGE
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-48087A (AR), dated 17 June 1982, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Add the following: "12624505 - Packing and marking for box, fiberboard for obturator assembly"

* 2.1.2, Delete "12624505 - Packing and Marking for Box, Fiberboard for Obturator Assembly" and substitute the following:

"12589951 - Packing and Marking for Obturator Assembly
12598564 - Packing and Marking for Box, Wood, Wireboard Pellet Type for Obturator Assembly"

PAGE 7

Table II, Delete in its entirety and substitute the new paragraph, Page 7 included.

PAGE 12

4.4.2.4, Delete in its entirety and substitute the new paragraph, Page 12 included.

* 4.4.2.4, Under Major 106, delete in its entirety and substitute the following:

"Hardness ... 0.40% ... 3..2 ... Gage"

* 4.4.2.4, Under Major 111, delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:12Z
Check the source to verify that this is the current version before use.

TABLE II First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48087A (AR)
AMENDMENT 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge Assembly				
	Examination for Defects	80	100%	3.2	4.4.2.8
	Proving Ground	80	100%	3.5	4.4.3.1/4.5.2
	Obturator				
	Examination for Defects	25	100%	3.2	4.4.2.4
	Obturator Assembly				
	Examination for Defects	50	100%	3.2	4.4.2.14
	Bristle, Strip				
	Examination for Defects	25	100%	3.2	4.4.2.15

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2027-10-22T19:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9391032
4.4.2.4	Obturator				NEXT HIGHER ASSEMBLY 9391030
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of strip bristle well		0.40%	3.2	Gage
102	Width of strip bristle well		0.40%	3.2	Gage/Caliber
103	Thickness at front face (Large) (Four measurements, 90° apart)		0.40%	3.2	Gage/Caliber
104	Thickness at rear face (Small) (Four measurements, 90° apart)		0.40%	3.2	Gage
105	Distance from front face to strip bristle well		0.40%	3.2	Gage/Caliber
106	Separator cut(s) missing		0.40%	3.2	Visual
107	Forward inside diameter		0.40%	3.2	Gage
108	Overall width of obturator		0.40%	3.2	Gage
109	Depth of separator cut		0.40%	3.2	Gage
110	Concentricity of strip bristle well		0.40%	3.2	Gage
111	Evidence of contaminants (foreign materials) in bristle strip well considered capable of interfacing with adhesion		0.40%	3.2	Visual
Minor					
201	Angle at rear obturator		0.65%	3.2	Visual
202	Radii missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-21T19:12Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.2.8, Under Critical defect 3, delete in its entirety and add the following:

"Special a, Metal parts separation (proving ground) ... 80/50 ... 3.5.6 ... 4.4.3.1.2/4.5.2"

* 4.4.2.8, Under Major 105, delete in its entirety and substitute the following:

"Obturator assembly improperly assembled ... 100% ... 3.2 ... Gage"

* 4.4.2.8, Under Major 106, change the word "obturator" to "obturator assembly"

PAGE 22

* 4.4.2.14, Delete in its entirety and substitute the new paragraph, Page 22A and 22B included.

* 4.4.2.15, Delete in its entirety and substitute the new paragraph, Page 22C included.

4.4.2.16, Add new paragraph, Page 22D included.

* 4.4.2.16, Delete "12624505" and substitute "12589951."

4.4.2.17, Add new paragraph, Page 22E included.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:12Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.14	Obturator Assembly		9391030
			NEXT HIGHER ASSEMBLY 9235654

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
a.	Improper orientation of bristle strips when viewing the obturator assembly from rear edge		100%	3.2	Gage
b.	Obturator assembly outside diameter		100%	3.2	Gage/Note 1
Major					
101	Location and depth of separator cuts		0.40%	3.2	Gage
102	Location of staples		0.40%	3.2	Gage
103	Paint missing or rear edge of obturator assembly		0.40%	3.2	Visual
104	Clinched ends of staple shall be below flush with the rubber surface of inside diameter of obturator		0.40%	3.2	Visual
105	Backing material of bristle strip exceeded obturator surface		0.40%	3.2	Gage/Note 2

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-19 12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.14	Obturator Assembly (continued)	2	2	9391030
				NEXT HIGHER ASSEMBLY 9235654

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
106	Crown of each four (4) fastening staples exceeded 0.018 inch max above flush of obturator surface		0.40%	3.2	Gage/Note 2
107	Staple broken or missing		0.40%	3.2	Visual
108	Leg of staple not within the backing material of bristle strip		0.40%	3.2	Visual
109	Bristle Strip ends not stapled within obturator groove		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES: 1. Gaging for outside diameter shall be performed with obturator assembled onto a tapered plug with a diameter of 3.775 inches.
2. Gaging shall be performed with obturator assembled onto a tapered plug with a diameter of 3.769 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the correct version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Bristle, Strip		9391031
			NEXT HIGHER ASSEMBLY 9391030

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width of strip		0.40%	3.2	Gage
102	Length of strip		0.40%	3.2	Gage
103	Height of wire bristles, max (3 places)		0.40%	3.2	Gage
104	Height from the bottom wire bristles to the top backing (3 places)		0.40%	3.2	Gage
105	Angle of wire bristles		0.40	3.2	Gage/Visual Note 1
106	Distance from the end of bristle strip to the first row of wire bristles		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:1. Fifteen wire bristles in one linear inch of the bristle strip shall be inspected, if four or more wire bristles fail to comply with the applicable requirement, the bristle strip shall be classed as defective.

Source: https://assist.dla.mil -- Downloaded: 2020-12-27T19:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Packing and Marking for Box, Fiberboard for Obturator Assembly	1 OF 1	12624505
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Lot number missing		0.65%	5.1/5.2	Visual
202	National stock number missing		0.65%	5.1/5.2	Visual
203	Item nomenclature/part number missing or incorrect		0.65%	5.1/5.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T19:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Obturator During Assembly				9391030
					NEXT HIGHER ASSEMBLY 9235654
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Adhesive missing, or not fully applied (360°) around the strip bristle well		Note A	3.2	Visual
Minor	None defined				

NOTES: A. Ten samples shall be inspected at beginning of 8 hour shift, ten samples shall be inspected at midway of 8 hour shift and ten samples shall be inspected at end of 8 hour shift.

Source: https://assist.dla.mil -- Downloaded: 2026-02-19 12Z
Check the source to verify that this is the current version before use.

PAGE 23

4.4.3.1.2.2, Change "Critical, Metal parts seperation 0 1 0 1" to "Special, Metal parts separation 0 1 0 1"

PAGE 26

5.1 Delete in its entirety and substitute the following:

"5.1 Packaging requirements.

a. Packaging for 4.2 Inch Mortar Ammunition shall be as specified on drawing 9272389.

b. Packaging for obturator assembly shall be as specified on drawing 12624505."

* 5.1.b., Delete in its entirety and substitute the following:

"Packaging and marking for obturator and obturator assembly shall be as specified on drawing 12589951."

5.2 Delete in its entirety and substitute the following:

"5.2 Packing and marking.

a. Packing and marking for 4.2 Inch Mortar Ammunition shall be as specified in drawing 9243973.

b. Packing and marking for obturator assembly shall be as specified in drawing 12624505."

* 5.2.b., Delete in its entirety and substitute the following:

"Packing and marking for obturator and obturator assembly shall be as specified on drawing 12598564."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:12Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AB08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.