MIL-F-81738 (AS)
15 August 1969
Superseding
AS-1178A
26 June 1969

MILITARY SPECIFICATIONS

FLARE, AIRCRAFT, PARACHUTE, MK 45 MOD 0

AND MK 45 AIRCRAFT PARACHUTE FLARE AND DROGUE TRAY

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This specification covers the manufacture and preparation for delivery of the Flare, Aircraft, Parachute, MK 45 Mod 0, the MK 45 Aircraft Parachute Flare and Drogue Tray, and the methods of examination and tests upon which product acceptante shall be based. The flares or Mk 45 drogue trays are a delay type flare, designed for launching from aircraft, which produce a parachute suspended illuminating candle. The flare or Mk 45 drogue tray is classified as Class B Explosive (Code of Federal Regulations 49 CFR 71-78) and IIC Explosive (Coast Guard Rules and Regulations for Military Explosive and Hazardous Munitions CG 108).

1.2 Definitions. The meaning of terms used in this specification shall be as listed in 6.4.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. The following documents, of the issue in effect on the date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-585	Boxes, Wood, Wirebound
PPP-B-591	Boxes, Fiberboard, Wood-cleated
PPP-B-621	Boxes, Wood, Nailed and Lock-corner

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

Military

MIL-P-116	Preservation, Methods of
MIL-E-5272	Environmental Testing Aeronautical and Associated Equipment, General Specifications for
MIL-D-18665	Detonator, Mk 59 Mod 0 and 1
MI-P-20444	Primer, Percussion, M42
MIL-I-45607	Inspection Equipment, Supply and Maintenance of
MIL-C-45662	Calibration System Requirements

Naval Air Systems Command

AS 1179	Fuze, Flare Mk 364 Mod 0

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-331	Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-414	Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1314	Safety Precautions for Explosive Loaded Items

DRAWINGS

Naval Air Systems Command

PL 2141527	Flare, Aircraft, Parachute, Mk 45 Mod 0
PL 2127899	Mk 45 Aircraft Parachute Flare and Drogue Tray
SA 2522999	Fixture, Aircraft Vibration for Flare, Aircraft, Parachute, Mk 24 and Mods

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

(And all PL's, drawings, specifications, standards and publications listed thereon.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

CODE OF FEDERAL REGULATIONS

49 CFR 71-78	Interstate Commerce Commission Rules and Regulations for Transportation of Explosives and Other Dnagerous Articles

(Application for copies should be addressed to Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should cite the latest edition and supplements.)

COAST GUARD RULES AND REGULATIONS

CG 108	Rules and Regulations for Military Explosives and Hazardous Munitions

(Application for copies should be addressed to Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.

3 . REQUIREMENTS

3.1 Inspection and manufacture. The flare or Mk 45 drogue tray shall be manufactured, inspected, tested and packed in accordance with contract documents, Parts List PL 2141527 or PL 2127899, as applicable, and this specification.

3.1.1 Preproduction sample. An acceptable preproduction sample of flares and candle assemblies shall be furnished by the contractor. The flares, their components and all materials shall be of a single type, grade, clam, size and composition which comply with all applicable provisions of this document. The samples shall be manufactured at the same location using the proposed full production methods. The preproduction sample shall not be applied as part of the quentity specified for delivery by the contractor order. (Not applicable to Mk 45 drogue tray).

3.1.1.1 Subsequent preproduction sample. During production a change may occur in procurement, type, grade, or size of magnesium. When an initial change is made, the contractor shall furnish a subsequent preproduction sample which complies with all requirements of this specification.

3.2 Examinations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

3.2.1 Components, assemblies and materials. All components, assemblies and materials of the flare or Mk 45 drogue tray shall meet the requirements of their respective specifications and drawings.

3.2.1.1 Fuze. The fuze shall meet the requirements of the applicable specification.

3.2.1.2 Primer. The primer shall meet the requirements of the applicable specification.

3.2.1.3 Detonator. The detonator shall meet the requirements of the applicable specification.

3.2.2 Flare. The flare shall meet the requirements of this specification.

3.2.3 Mk 45 Drogue Tray. The Mk 45 drogue tray shall meet the requirements of this specification.

3.3 Performance and product characteristics. The flare or Mk 45 drogue tray shall meet the acceptance criteria for performance and product characteristics in the sequence indicated in Table III.

3.3.1 Performance.

3.3.1.1 Sealing. The flare shall withstand a vacuum of 6.0 ± 1.0 inches of mercury (24 inches of mercury absolute pressure) for a minimum period of 60 seconds without signs of the leakage.

* 3.3,1.2 Candle burning. The candle assembly of the flare or Mk 45 drogue tray shall meet the following requirements:

a. Attain a minimum candlepower of 1,000,000 within 10 seconds after ignition.

b. Shall not fall below 1,000,000 candlepower for any period greater than 5 seconds, for a continuous time period of 180 seconds, after initially reaching 1,000,000 candlepower.

c. Produce a minimum average candlepower of 1,650,000 for a continuous time period of 180 seconds, after initially reaching 1,000,000 candlepower.

d. Burning time: 180 seconds minimum (defined as that time period beginning when the candlepower first reaches 1,000,000 and terminating when the candlepower decays to 1,000,000 at burnout.

3.3.1.3 Static functioning. The flare shall meet the following requirements:

a. Shall not eject contents less than 1.5 seconds after pulling lanyard.

b. Ejection of the candle shall not result in ignition.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

c. Function (eject contents).

d. Delay and burning time:

(1) Ejection delay time: Time from pulling the lanyard to ejection of contents shall be within the tolerance specified in Table I.

(2) The candle shall burn for a minimum period of 180 seconds.

TABLE I

FOR STATIC TEST EJECTION DELAY TIMES

Feet of Fall	Seconds	Feet of Fall	Seconds*
500	5.6 ± 2.0	8,000	31.1 ± 6.0
1,000	8.1 ± 3.0	9,000	33.4 ± 6.0
2,000	12.6 ± 3.0	10,0000	35.7 ± 7.0
3,000	16.5 ± 4.0	11,000	37.8 ± 7.0
4,000	20.0 ± 4.0	12,000	39.9 ± 8.0
5,000	23.2 ± 4.0	13,000	42.0 ± 8.0
6,000	26.1 ± 5.0	14,000	44.1 ± 8.0
7,000	28.7 ± 5.0		

*For test locations from 0 to 1500 feet above MSL.

3.3.1.4. Flight functioning. The flare or Mk 45 drogue tray shall meet the following requirements.

a. Shall not eject contents less than 1.5 seconds after pulling of the lanyard.

b. Function (eject, suspend, ignite candle and dump parachute).

c. Parachute shall not dump more than 20 seconds before candle burnout.

d. Delay and burning time:

(1) Ejection delay time: Time from pulling the lanyard to ejection of contents shall be within the tolerance specified in Table II.

(2) The candle shall burn for a minimum period of 180 seconds.

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:02Z
Check the source to verify that this is the current version before use.

TABLE II

FOR FLIGHT TEST EJECTION DELAY TIMES

Feet of Fall	Seconds*	Feet of Fall	Seconds*
500	6.0 ± 2.0	8,000	38.1 ± 6.0
1,000	9.0 ± 3.0	9,000	42.0 ± 6.0
2,000	14.0 ± 3.0	10,000	45.8 ± 7.0
3,000	18.5 ± 4.0	11,000	49.6 ± 7.0
4,000	22.6 ± 4.0	12,000	53.4 ± 8.0
5,000	26.5 ± 4.0	13,000	57.2 ± 8.0
6,000	30.4 ± 5.0	14,000	61.0 ± 8.0
7,000	34.3 ± 5.0		

*Delay times for ejection at 4200 ± 500 MSL.

3.3.2 Durability and environmental.

3.3.2.1 Forty (40) foot drop. The flare shall withstand forty (40) foot drop without exploding, burning or ejecting.

3.3.2.2 Aircraft vibration. The flare shall withstand aircraft vibration without exploding, burning or ejecting.

3.3.2.3 Temperature and humidity. The flare shall withstand temperature and humidity without exploding, burning or ejecting.

3.3.2.4 Low temperature. The flare shall be conditioned at a temperature of -65°F ± 5° for a minimum period of 24 hours without exploding, burning or ejecting.

3.4 Workmanship. The product, in all stages of production, shall be processed under such inspection control as to assure uniformity in quality. All components shall be free of chips, dirt, grit, or other foreign material. The cleaning methods used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents employed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contractor purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification, where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Preproduction sample. The contractor shall deliver a sample of 144 flares and 50 candle assemblies to the destination specified (see 6.2), for examination, testing,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

evaluation, and acceptance as specified in Table III, as applicable. Any production of the item prior to production of an acceptable preproduction sample by the contractor or authorization by the procuring agency shall be at the risk of the contractor. The sample shall be prepared for delivery as specified in Section 5.

4.1.2 Production lot. A production lot shall consist of 501 to 10,000 flares or Mk 45 drogue trays offered for delivery at one time including test samples. The samples shall not be applied as part of the quantity specified for delivery by the contract or purchase order. Sampling, examination, testing and acceptance of production lots shall be performed as specified in the steps given below. Upon rejection of any lot, the next lot, in addition to the applicable sampling plan, shall be examined, tested and accepted for the requirement(s) which caused the rejection, unless the requirement(s) is included in the applicable plan. Each production lot shall contain only primers produced during one year by one manufacturer.

STEP 1. Upon starting production or delivery of an acceptable preproduction sample, as applicable, the first two production lots shall be examined, tested in sequence, and accepted in conformance with Table III, Sampling Plan A.

STEP 2. Production lots other than those defined in Step 1 shall be examined, tested in sequence and accepted in conformance with Table III, Sampling Plan B, except that one lot shall be randomly selected from each five consecutive production lots and examined, tested in sequence and accepted in conformance with Table III alternately selecting Plan A and Plan C.

4.1.3 Test equipment and gages. All test equipment and gages shall be supplied and maintained by the contractor as specified in Specification MIL-I-45607. The contractor shall maintain a calibration system as specified in Specification MIL-C-45662.

4.1.3.1 Test conditions. The maximum allowable tolerances on test conditions specified herein, unless otherwise specified, shall be as follows:

(1) Temperature: Plus or minus 3°C, 5.4°F.

(2) Relative humidity: Plus 5 percent, minus 0 percent.

(3) Vibration amplitude: Plus or minus 10 percent.

(4) Vibration frequency: Plus or minus 2 percent.

4.1.4 Tests and examinations classification. The tests and examinations herein are classified in regard to relative importance as Critical, Major or Minor. Tests and examinations classified as Critical are identified by the symbol (C) and Major by (M). The number following the symbol indicates the serial number of the test or examination. Tests which are not annotated are classified Minor.

4.2 Examinations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

TABLE III
INSPECTION PLANS

PLAN [1]				SECTION REFERENCE	EXAMINATIONS AND TESTS	PREPRODUCTION SAMPLING PLANS		PRODUCTION LOT SAMPLING PLANS	
PRE-PROD	A	B	C		1 2 3	SAMPLE SIZE	ACCEPTANCE CRITERIA [2]	SAMPLE SIZE	ACCEPTANCE CRITERIA [2]
X	X	X	X	4.2.2	Examinations	144 Flares	Critical Ac 0 Re 1 Major Ac 3 Re 4 Minor Ac 7 Re 8	See 4.2.2	See 4.2.2
X	X		X	4.3.2.1 3.3.2.1	Forty (40) Foot Drop Test	5 Flares	Ac 0 Re 1	MIL-STD-105 Inspection Level S-1	Ac 0 Re 1
X	X		X	4.3.2.2 3.3.2.2	Aircraft Vibration Test	13 Flares	Ac 0 Re 1	MIL-STD-105 Inspection Level S-2	Ac 0 Re 1
				4.3.1.3 3.3.1.3	Static Functioning Test		(a&b) Ac 0 Re 1 (c&d) Ac 2 Re 3		(a&b) Ac 0 Re 1 (c&d) AQL 6.5
X	X		X	4.3.2.3 3.3.2.3	Temperature And Humidity Test	13 Flares	Ac 0 Re 1	MIL-STD-105 Inspection Level S-2	Ac 0 Re 1
				4.3.1.3 3.3.1.3	Static Functioning Test		(a&b) Ac 0 Re 1 (c&d) Ac 2 Re 3		(a&b) Ac 0 Re 1 (c&d) AQL 6.5
X	X		X	4.3.1.1 3.3.1.1	Sealing Test	13 Flares	Ac 2 Re 3	MIL-STD-105 Inspection Level S-3	AQL 6.5
				4.3.2.4 3.3.2.4	Low Temperature Test		Ac 0 Re 1		Ac 0 Re 1
				4.3.1.3 3.3.1.3	Static Functioning Test		(a&b) Ac 0 Re 1 (c&d) Ac 2 Re 3		(a&b) Ac 0 Re 1 (c&d) AQL 6.5
X	X	X	X	4.3.1.2 3.3.1.2	Candle Burning Test	50 Candles	(a&b) Ac 5 Re 6	MIL-STD-105 Inspection Level S-4	(a&b) AQL 4.0
						MIL-STD-414 Code Ltr M	(c) AQL 4.0 (d) AQL 4.0	MIL-STD-414 Inspection Level III	(c) AQL 4.0 (d) AQL 4.0
X		X	X	4.3.1.1 3.3.1.1	Sealing Test	50 Flares	Ac 7 Re 8	MIL-STD-105 Inspection Level S-4	AQL 6.5
X		X	X	4.3.1.4 3.3.1.4	Flight Functioning Test	50 Flares	(a) Ac 0 Re 1 (b) Ac 5 Re 6 (c&d) Ac 7 Re 8	MIL-STD-105 Inspection Level II Multiple Sampling Plan	(a) Ac 0 Re 1 (b) AQL 4.0 (c&d) AQL 6.5
X				4.3.2.5	Grouped Data Acceptance	39 Flares	(c&d) Ac 5 Re 6	None	None

NOTES:
1. X - Denotes tests applicable to plan
2. Ac - Acceptance number
   Re - Rejection number

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

4.2.1 Components, assemblies and materials examinations. Prior to final assembly, all components, assemblies and materials used in the flare or Mk 45 drogue tray shall meet the requirements of 3,2.1.

4.2.1.1 Fuze (M101). In the absence of previous inspection of the fuze, inspection shall be performed as specified in Specification AS 1179. (See 6.2)

4.2.1,2 Primer (M102). In the absence of previous inspection of the primer, inspection shall be performed as specified in Specification MIL-P-20444.

4.2.1.3 Detonator (M103). In the absence of previous inspection of the detonator, inspection shall be performed as specified in Specification MIL-D-18665.

4.2.2 Flare examinations (Cl). Examinations shall be made to ascertain that the flares meet the requirements of the NAVAIR drawings listed on PL 2141527, Only flares containing no defective classified characteristics shall be used for further testing or returned to the lot,

4.2.3 Mk 45 drogue tray examinations (C2). Examinations shall be made to ascertain that Mk 45 drogue trays meet the requirements of PL 2127899. Any Mk 45 drogue tray containing no defective classified characteristics shall be used for further testing or returned to the lot.

4.2.4 Packing and marking examinations (C3). The packing and marking examination shall be as specified in the applicable drawings as listed in Section 5. Only packs containing no defects shall be returned to the lot.

4.3 Tests. Random samples of flares or Mk 45 drogue trays shall be selected, tested and accepted as specified in 4.1.1 or 4.1.2, as applicable.

4.3.1 Performance tests.

4.3.1.1 Sealing test (M104). The flare shall be tested in a water tank equipped for observation under vacuum. The water temperature shall be 45 degrees F minimum to 75 degrees F maximum.

CAUTION: The water tank should be equipped so that the flare must be raised above the water level while still under vacuum before releasing the vacuum and removing the flare.

The uppermost surface of the flare, when in a horizontal position, shall be submerged 4 to 6 inches below the water surface and subjected to a vacuum of 6.0 ± 1.0 inches of mercury (24 inches of mercury absolute pressure) for a minimum period of 60 seconds. Leakers are indicated by air bubbles issuing from the flare. Do not mistake the escape of occluded air for leakage. Flares which are not defective may be used for further testing or returned to the lot. Defective are flares failing to meet the requirements of 3.3.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

4.3,1.2 Candle burning test (M105). The candle assembly shall be mounted on a suitable fixture in the fireplace of the photometric tunnel in a vertical position with the ignition end up or down, and 27 inches *3 inches below or above the photometric axis, as applicable to the tunnel. Ignition of the candle shall be by means of a coil of quickmatch, firecracker fuse or equivalent and an electrical squib which is placed on the ignition composition. The squib shall be initiated from outside the tunnel to assure safety of personnel. The candle assembly shall be rotated at a minimum of 10 to a maximum of 15 RPM when ignited until burn out of the composition. There shall be a minimum opening of 40 inches into the fireplace above or below the photometric axis as applicable to tunnel. The tunnel shall have non-reflecting surfaces. The light emitted by the burning candle shall fall upon a sensing element which generates a d.c. voltage proportional to the light intensity. This d.c. voltage shall be applied to a recording instrument such as an oscilloscope or oscillograph capable of recording electrical output with reference to time. If an oscilloscope is used, the tracing of the oscilloscope shall be photographed. Before testing, the equipment shall be calibrated using a projector lamp calibrated by the National Bureau of Standards. From the recording, determine and record the data required by the requirements of 3.3.1.2, Defective are flares failing to meet the requirements of 3.3.1.2.

4.3.1.3 Static functionig test (C4). The flares tested shall be suspended from a 1/2 inch diameter steel rod a minimum height of 36 inches above the surface. The rod shall allow the flare outer container a minimum of 60 inches of free movement upon ejection. The flare is suspended on the rod with two suspension bands, Drawing 2112843-1. The flare delay time shall be set at values randomly selected. The flare shall be initiated by a quick pull on the lanyard with an extension of sufficient length to allow the extension to be pulled around a stake or through a pulley so personnel will be at right angles to the longitudinal axis of the flare and at a safe distance or behind a shield. After ejection the candle shall be mounted in a suitable fixture designed to enable safe functioning by pulling of the cable. Do not look directly at the burning flare. Record the ejection delay time set, ejections of 1.5 second or less from pulling lanyard, actual ejection delay times, ignition of candle, and the burning times of the candle. Defective are flares failing to meet the requirements of 3.3.1.3.

4.3.1.4 Flight functioning test (C5). The flares or Mk 45 drogue trays shall be tested by launching from aircraft. Launching procedures shall have prior approval of the procuring agency. The delay times shall be set depending upon altitudes at launch. The observer shall records fuze separation, functioning, ejections of 1.5 seconds or less from pulling lanyard, suspension, burning time and dumping time of parachute for acceptance purposes. Defective are flares or Mk 45 drogue trays failing to meet the requirements of 3.3.1.4, except those failures attributable to the launching procedures shall be a no-test and an additional unit shall be tested for acceptance purposes. For data purposes the observer shall record, type of launcher, type of aircraft, altitude of aircraft and speed of aircraft at launch. (See 6.3).

4.3.2 Dupability and environmental tests.

4.3.2.1 Forty (40) foot drop test (C6). The flare shall be subjected to the forty (40) foot drop test prescribed in Test 103 of Standard MIL-STD-331, except the flare shall be dropped free-fall without guidance system or associated equipment. Defective are flares failing to meet the requirements of 3.3.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

4.3.2.2 Aircraft vibration test (C7). The flare shall be subjected to the aircraft vibration test prescribed in Specification MIL-E-5272, Vibration Test Procedure XII, at ambient temperature only. The flares shall be assembled to the vibration table using SA Drawing 2522999 for mounting. Defective are flares failing to meet the requirements of 3.3.2.2.

4.3.2.3 Temperature and humidity test (C8). The flare shall be subjected to one 14 day temperature and humditiy cycle prescribed in Test 105 of Standard MIL-STD-331. Defective are flares failing to meet the requirements of 3.3.2.3.

4.3.2.4 Low temperature test (C9). The flare shall be conditioned in a suitable chamber at a temperature of -65°F ± 5°F for a minimum period of 24 hours and shall be static functioned while at that temperature. Defective are flares failing to meet the requirements of 3.3.2.4.

4.3.2.5 Grouped data acceptance. Data obtained from requirements (b) and (c) of the static functioning test shall be grouped for the 39 flares composed of the following groups:

Group (a)	Thirteen (13) flares from the aircraft vibration test of 4.3.2.2
Group (b)	Thirteen (13) flares from the temperature and humidity test of 4.3.2.3
Group (c)	Thirteen (13) flares from the low temperature test of 4.3.2.4

Acceptance shall be as specified in Table III.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Candles.

5.1.1.1 Level A. In addition to the following, Level A packaging shall be in conformance with the Code of Federal Regulations 49 CFR 71-78 for Class B Explosives.

5.1.1.1.1 Unit packaging. Each candle assembly shall be packaged in accordance with Specification MIL-P-116, Method lA13. The cavities at both ends of the candle shall be cushioned as required to prevent damage to the pressed composition. No preservation required.

5.2 Packing.

5.2.1 Flares or Mk 45 Drogue Trays.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

5.2.1.1 Level A. In addition to the following, Level A packing shall be in conformance with the Code of Federal Regulation 49 CFR 71-78.

5.2.1.1.1 Two (2) flares shall be packed in accordance with PL 2127902, (see 6.2).

5.2.1.1.2 No (2) Mk 45 drogue trays shall be packed in accordance with PL 2127903, (see 6.2).

5.2,2 Candle assemblies.

5.2.2.1 Level A. In addition to the following, Level A packing shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.2.2.1.1 Five candles, packaged as specified in 5.1.1.1.1 shall be packed in a wood box in accordance with Specification PPP-13-585, PPP-B-591, or PPP-B-621.

5.3 Marking.

5.3.1 Special marking. Special marking for the shipping boxes shall be in accordance with the Code of Federal Regulations 49 CFR 71-78 for Class B Explosives (Special Fireworks).

5.3,2 Normal marking. In addition to the requirements of the contract or order, shipping boxes shall be marked in accordance with Standard MIL-STS-129.

6. NOTES

6.1 Intended use. The Flare, Aircraft, Parachute, Mk 45 Mod 0 and Mk 45 Aircraft Parachute Flare and Drogue Tray are intended for use to illuminate a large area sufficient y to permit reconnoitering, bombing or location of surface objects.

6.2 Ordering data. Procurement documents shall specify:

a. Title, number and date of this specification,

b. Quantity of flares or Mk 45 drogue trays being ordered,

c. Test facility where preproduction sample is to be shipped for evaluation,

d. QE Laboratory coordinating surveillance,

e. Data information required (see 6.3).

f. When the manufacturer of the flare or Mk 45 drogue tray is manufacturing the Fuze, Flare, Mk 364 Mod 0 the test requirements of Specification AS 1179 may be waived if so desired.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

g. Additional applications: The flare contains a removable fuze and may be assembled with an Army fuze for use by the Army or an Air Force adapter may be assembled into the Mk 364 Mod 0 fuze for use by the Air Force when specified.

6.3 Data. For the information of contractors and contracting officers, any of the data specified in (a) subparagraph below, (b) applicable documents listed in Section 2 of this specification, (c) referenced lower-tier documents, or (d) as required in Section 4 of this specification need not be prepared for the Government unless justified and specified in the contract or order. The data to be furnished shall be listed on DD Form 1423, which shall be attached to and made a part of the contractor order. NAVWEPS Form 4200/15 shall be attached where applicable.

6.3.1 Data cards, Data cards 5“ x 8“ made of white bristol board approximately 110 lbs. ream weight, in accordance with Figure 1 shall be furnished by the contractor for each lot of flares. The contractor shall fill in all required information, including all information for the following components:

Component
Fuze, Flare Mk 364 Mod 0
Primer M42G
Candle
Parachute
Suspension Band
Magnesium (including type, grade, size, etc).
Detonator

The government inspector shall endorse the cards and distribute one each as follows:

a. Procuring activity,

b. SPCC (Code 730), Mechanicsburg, Pa. (if different than the procuring activity),

c. The QE Laboratory coordinating surveillance (see 6.2),

d. The designated test activity (see 6,2).

6.4 Definitions. The meaning of the terms used in this specification shall be as listed below:

6.4.1 Flare. The term “flare” shall mean the Flare, Aircraft, Parachute, Mk 45 Mod 0, PL 2141527.

6.4.2 Mk 45 drogue tray. The term “Mk 45 drogue tray” shall mean the Mk 45 Aircraft Parachute Flare and Drogue Tray, PL 2127899.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

REMARKS

ACCEPTANCE DATA

ORIGINAL TEST ▶	LOCATION	DATE OF TEST	NO. OF SAMPLES	TEST REPORT REFERENCE
RETEST ▶	LOCATION	DATE OF TEST	NO. OF SAMPLES	TEST REPORT REFERENCE

REMARKS: *(Note all defects noticed. Describe reworking, if any. Use top of card if necessary)*

DATE RELEASED	AUTHORITY FOR RELEASE	INSPECTOR

PYROTECHNIC AMMUNITION MANUFACTURING DATA CARD (BACK) NAVORD FORM 1384 (10-44)

(Name of Pyrotechnic Ammunition)	*(Mk.—Mod. and color)*	*(Contract No.)*	*(Assembly Lot No.)*
MANUFACTURER		NUMBER IN LOT	DATE OF MANUFACTURE
SPECIFICATIONS	DRAWING Nos. *(List revisions actually used.)*		
HOW PACKED			

COMPONENT	MANUFACTURED BY	LOT No.	DATE OF MFG.	ADDITIONAL DATA

REMARKS: *(List below all deviations in this lot from specifications and drawings with all references to authorizations for changes and waivers. All changes in procedure, sources of material, or unusual circumstances during manufacture should be noted. Where alternates are allowed, specify which is used. Use back of card if necessary.)*

PYROTECHNIC AMMUNITION MANUFACTURING DATA CARD NAVORD FORM 1384 (10-44)

FIGURE 1.

Source: https://assist.dla.mil -- Downloaded: 202640-23T06:02Z
Check the source to verify that this is the current version before use.

6.4.3 Candle Assembly. The term “candle assembly” shall mean the component depicted on Drawing 2127821.

6.4.4 Fuze. The term “fuze” shall mean the Fuze, Flare Mk 364 Mod 0, PL 2127860.

* 6.4.5 Primer. The term “primer” shall mean the Primer, M42G MIL-P-20444.

6.4.6 Detonator. The term “detonator” shall mean the Detonator Mk 59 Mod 0 MIL-D-18665.

6.5 Conflicting requirements. Conflicting requirements arising between this specification and any specification, publication or drawing listed herein shall be referred in writing to the procuring agency for clarification.

* 6.6 Safety precautions. The safety precautions specified in MIL-STD-1314 shall be observed during loading, assembly, testing and handling operations. The use of this standard shall not be construed as to relieve the contractor or manufacturer of responsibility y for the safety of his operations. The observation of these safety precautions is mandatory at government plants.

* 6.7 Supersession data. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

project No. 1370-N307

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING.

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer

U.S. Naval Ammunition Depot (Code RD)

Crane, Indiana 47522

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:02Z
Check the source to verify that this is the current version before use.