INCH-POUND

MIL-R-82047B
AMENDMENT 1
11 June 1991

MILITARY SPECIFICATION

REFRIGERATORS, MECHANICAL, STORAGE STAND
(FOR BULK MILK DISPENSERS)

This amendment forms a part of MIL-R-82047B, dated 22 October 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2, line 4 and 5: After "cans" add "or containers".

PAGE 2

2.1.1, under "STANDARD/MILITARY": Add the following:

"MIL-STD-167/1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited).

MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.

MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.

MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities."

PAGE 5

3.6.2, line 2: Delete "in" and substitute "of".

Line 5 and 6: Delete "NSF No. 7." and substitute "UL 471."

3.6.3, line 3: delete "seal on the refrigerated storage stand" and substitute "Listing of Food Service Equipment".

AMSC N/A

FSC 4110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:38Z
Check the source to verify that this is the current version before use.

PAGE 6

3.7.3: Delete the first sentence.

PAGE 7

3.10.2, line 5: After "cans" add "or containers".

3.10.6, line 5: Delete "contracted" and substitute "constructed".

PAGE 8

3.13, line 2: Delete "furnished" and substitute "finished".

PAGE 9

Add the following paragraphs:

"3.16 Electromagnetic compatibility. When specified for shipboard use (see 6.2.1), the units shall be designed and equipped for electromagnetic compatibility in accordance with the requirements of MIL-STD-461, Class A4 for surface ships and class A5 for submarines. The equipment shall meet the emission and susceptibility requirements for CE01, CE02, and RE02 (see 4.5.3).

3.17 Inclined operation. When specified for shipboard use (see 6.2.1), the refrigerator dispensers shall operate satisfactorily when inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other, with no spillage of products when tested as specified in 4.5.4.

3.18 Environmental suitability. When specified for shipboard use (see 6.2.1), the refrigerator shall be capable of withstanding ship's vibration and motion. Controls, switches, moving parts and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness or damage when tested as specified in 4.5.5.

3.19 Human factors criteria. Human factors engineering criteria, principles, and practices, as defined in MIL-STD-1472, shall be incorporated into the design of the bulk milk refrigerators. Maintenance and operation activities shall permit safe and efficient performance by the 5th percentile female to the 95th percentile male as defined in sections 5.6 and 5.9 of MIL-STD-1472. Controls and switches shall be selected and integrated into the design of the bulk milk refrigerators so as to meet the applicable requirements of sections 5.2 and 5.4 of MIL-STD-1472. The clearance or free area required around an item shall permit an individual with applicable body dimensions and physical capabilities to safely operate, maintain, remove, or replace that item. When establishing accessibility requirements, both physical and visual access must be provided along with access for the use of any tools, test equipment, or replacement parts needed. When inspecting for defects and performing tests (see section 4), the equipment shall adhere to the human factors engineering considerations listed herein."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:38Z
Check the source to verify that this is the current version before use.

PAGE 10

4.3 through 4.3.3: Delete in their entirety and substitute:

"4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one storage stand. All stands offered for delivery at one time shall be considered a lot for the purpose of inspection.

4.3.1 Sampling for examination. Guidance for inspection level and an Acceptable Quality Level (AQL) as specified (see 6.7.1).

4.3.2 Sampling for tests. Guidance for inspection level and an Acceptable Quality Level (AQL) as specified (see 6.7.2)."

4.4.2: Delete paragraph and substitute:

"4.4.2 Examination. Each storage stand shall be examined for defects listed in table II. Each attribute within each classification of multiple defects shall constitute one defect."

PAGE 12

4.5.2, lines 2 and 4: After "cans" add "or containers".

Add the following paragraphs:

"4.5.3 Electromagnetic interference test. When required for shipboard use, the unit shall be tested by the contractor in accordance with test methods CE01, CE03, and RE02 of MIL-STD-462. The contractor shall furnish written certification that the equipment meets the requirements of MIL-STD-461. Nonconformance with the requirements specified shall constitute failure of the test.

4.5.4 Inclined operational test. Position the bulk milk refrigerator with the base set at an angle of 15 degrees, then operate the bulk milk refrigerator for 30 seconds at each side of the vertical in each of two vertical planes at right angles to each other. At each of these positions, observe for conformance with specified requirements in 3.17. For the test, the bulk milk refrigerator shall be loaded with milk containers.

4.5.5 Shipboard environmental test. The bulk milk refrigerator under normal operating conditions, shall be tested in accordance with MIL-STD-167/1, type I equipment. The bulk milk refrigerator shall be secured to the test machine in the same manner that it will be secured on shipboard. Failure of the bulk milk refrigerator to perform its function during and after testing, or meeting requirements of 3.18 shall constitute failure of this test."

4.6.1, line 2: Delete "4.3.3" and substitute "4.3.2".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:38Z
Check the source to verify that this is the current version before use.

PAGE 13

6.2.1: Add the following:

"h. When bulk milk refrigerator is for shipboard use, see 3.16, 3.17 and 3.18."

PAGE 14

Add new paragraphs as follows:

"6.7 Sampling procedures.

6.7.1 Sampling for examination. Recommended Inspection Level is II and Acceptable Quality Level is 2.5 (see 4.3.1).

6.7.2 Sampling for tests. Recommended Inspection Level is S-4 and Acceptable Quality Level is 2.5 (see 4.3.2)."

Custodians:

Navy - YD
Air Force - 99

Review Activities:

Navy - MC, MS, SA, SH
Air Force - 82
DLA - GS

User Activity:

Navy - CG

Preparing Activity:

Navy - YD

(Project 4110-0425)

Source: https://assist.dla.mil - Downloaded: 2026-10-23T06:38Z
Check the source to verify that this is the current version before use.