INCH-POUND

MIL-S-52256C(ME)
AMENDMENT 1
27 February 1992

MILITARY SPECIFICATION

SURVEYING INSTRUMENT; AZIMUTH GYRO, LIGHTWEIGHT

This amendment forms a part of MIL-S-52256C(ME), dated 24 August 1990, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, under"SPECIFICATIONS", after "FEDERAL", add:

"A-A-52298 - Tripod, Surveying: Extension-Leg Type."

PAGE 2

Under SPECIFICATIONS, MILITARY, delete "MIL-V-173", "MIL-T-14091", and "MIL-C-22751" in their entirety and add:

"MIL-C-22750 - Coating, Epoxy, Vox-compliant.
MIL-P-23377 - Primer Coatings: Epoxy, Chemical and Solvent Resistant."

2.1.2, delete in its entirety.

PAGE 4

3.4.1, line 1, delete "42" and substitute "44".

3.4.2, line 1, after "All", add "gyroscope".

3.4.3, line 2, after "power", add "with panel illumination on and theodolite lighting attachments operating".

PAGE 5

3.5.8.1, line 1, delete "electrical" and substitute "electronic" in two places.

AMSC N/A FSC 6675
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:11Z
Check the source to verify that this is the current version before use.

PAGE 6

3.6.1.4, delete the first sentence and substitute "Two 24-volt DC nickel-cadmium battery packs shall be furnished, so one can be charged while the other is in use.".

3.6.1.5, line 4, delete "component" and substitute "sub-assembly".

3.6.1.6, line 3, delete "The lights shall be adjustable from 0.07 to 0.35 cd/m^2."

3.7, line 2, delete "MIL-T-14091" and substitute "A-A-52298".

After 3.7, add the following:

"3.7.1 Tripod base. When specified (see 6.2), a tripod base shall be supplied to securely position the steel points of the tripod shoes and prevent them from damaging floors."

3.8.1, line 2, delete "mm" and substitute "mil".
Line 6, delete "Accessory equipment compatible with the system shall be furnished and shall include an eyepiece prism, an eyepiece sun filter, a lens brush, plumb bob assembly, and a circle adjusting wrench."

3.8.2, line 4, delete "The telescope shall transit at the objective end with the prismatic eyepiece attached."

PAGE 8

3.8.4.5, add at the end "Power for the illumination is fed from the auto-collimation box."

3.8.4.6, line 15, delete "mm" and substitute "mil".

After 3.8.4.7, add the following:

"3.8.4.8 Sunshade. Sunshade is needed to prevent stray reflections in the telescope."

3.8.5, line 5, delete "mm" and substitute "mil".

3.8.5.1, line 2 and line 5, delete "mm" and substitute "mil".

3.8.5.2, line 2, line 3, and line 4, delete "mm" and substitute "mil".

3.8.5.3, line 3, delete "mm" and substitute "mil".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

and shall connect to a receptacle on the battery case. The hand lamp shall

PAGE 9

3.8.6, line 7, delete "A different color between the horizontal circle and vertical circle is permissible." and substitute "The horizontal and vertical circles shall have backgrounds of different colors."

3.8.6.1.1, line 4, delete "mm" and substitute "mil".

PAGE 10

3.8.8.2, line 2, delete "The device shall be accurate within 0.06 mm." and substitute "The device has an overall accuracy of 0.06 mil or 12 arc seconds. The accuracy of the pendulum is 1 arc second over a range of ±6 arc minutes."

3.8.8.3, line 3, delete "mm" and substitute "mil".

PAGE 11

3.12, line 3, delete "mm" in two places and substitute "mil".

3.14, delete in its entirety and substitute:

"3.14 Fungus and moisture resistance. The electronics shall be protected in accordance with MIL-STD-454, requirements 4 and 31."

PAGE 12

3.14.1, delete in its entirety.

3.15, line 4, after "FED-STD-595", delete "except the" and substitute ". The".

Line 5, delete "coating shall be in accordance with MIL-C-22751" and substitute "shall have a primer coating in accordance with MIL-P-23377, type I, class 1 or 2, followed by a top coating in accordance with MIL-C-22750, type I,".

3.18, add at end:

"k. Spare bulbs for panel illumination, circle lighting attachment, auto-collimation eyepiece and target rod."

PAGE 14

4.3.1.1, line 6, delete "mm" in two places and substitute "mil".

4.3.1.4, line 3, delete "mm" and substitute "mil".
Line 15, delete "instrument" and substitute "test report".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

PAGE 15

4.6.1, 108, after "3.4.2", add "3.6.1.3".

PAGE 16

143, after "(3.14", delete "and 3.14.1".
After 147, add:

"148. Tripod base not as specified (see 3.7.1).
149. Sunshade not as specified (see 3.8.4.8)."

PAGE 17

4.7.1, line 2, delete "4.5.2" and substitute "4.6.2".
Line 9, delete "4.6.11" and substitute "4.7.11".

PAGE 18

4.7.2.2, line 5, delete "4.7.2" and substitute "4.7.11".
Line 6, delete "3.5.2" and substitute "3.12".

4.7.2.3, line 6, delete "3.5.1 or".

4.7.2.4, line 6, delete "3.5.2" and substitute "3.12".

PAGE 19

4.7.2.5, line 7, delete "3.5.1 or".

PAGE 20

4.7.6.1, line 6, delete "4.6.2" and substitute "4.7.2".

4.7.6.2, line 5, delete "-65" and substitute "-40".

PAGE 21

4.7.11, line 2, delete "4.5.2" and substitute "4.6.2".

4.8 and 4.8.1, delete in their entirety.

PAGE 22

6.1, add at end: "It is also used to determine geographic north, and to ensure proper alignment of aircraft inertial navigational units."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.

6.2, add at end:

m. When tripod base is required (see 3.7.1).

PAGE 23

6.4, line 3, delete "4.6.1" and substitute "4.7.1".

Custodian:
Army - ME

Review activity:
DLA - GS

Preparing activity:
Army - ME

Project 6675-A024

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:11Z
Check the source to verify that this is the current version before use.