MILITARY SPECIFICATION SHEET

SURVIVAL KIT CONTAINER, AIRCRAFT SEAT,
WITHOUT OXYGEN, RSSK-9A

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the rigid seat survival kit described herein shall consist of this specification and the latest issue of MIL-S-81040(AS).

1. SCOPE

1.1 Scope. This specification covers the detail requirements for a rigid seat survival kit containing survival equipment and is designated RSSK-9A.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-6117	Terminal, Cable Assemblies, Swaged Type
MIL-H-6875	Heat Treatment of Steels (Aircraft Practice), Process for
MIL-F-21840	Fastener Tapes, Hook and Pile, Synthetic
MIL-S-81040	Survival Kit Container, Aircraft Seat, Without Oxygen, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-29 04:50Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

MS14175	Dropline/Boot Assembly, Rigid Seat Survival Kit
MS27983	Fastener, Snap, Style 4

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

NAVAL AIR DEVELOPMENT CENTER

CL204D2	Bracket Assembly, AN/URT-33 Radio Beacon

NAVAL AIR SYSTEMS COMMAND

1434AS100	Rigid Seat Survival Kit Index, RSSK-9
1434AS101	Rigid Seat Survival Kit Assembly, RSSK-9
1434AS102	Container Bottom and Lid, Rigid Seat Survival Kit, RSSK-9
1434AS103	Restraint/Lap Belt Subassembly Ejection Seat to RSSK-9
1434AS104	Cushion, Comfort, Rigid Seat Survival Kit, RSSK-9

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Qualification. The RSSK-9A rigid seat survival kits shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.3). Qualification will be in accordance with groups as listed in Drawing 1434AS100.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified, a sample shall be subjected to first article inspection (see 4.4).

3.3 Materials and components. Materials and components shall be as specified in the general specification and the applicable specifications, standards, and drawings specified herein.

3.4 Design and construction. The design and construction of the RSSK-9A shall be as specified in the general specification and as specified herein.

3.4.1 Operation. Operation of the RSSK-9A shall be as specified in the general specification.

3.4.2 Kit components. The components of the RSSK-9A shall be as specified in the general specification and shall consist of, but not be limited to, the following:

a. Basic container.

b. Comfort cushion.

c. RSSK to torso harness restraint assembly.

d. Release handle and container locking mechanism.

e. Container dropline assembly.

f. Radio beacon bracket.

3.4.2.1 Basic container. The basic container of the RSSK-9A shall be designed as specified in the general specification and shall conform to the general design and critical dimensions of Drawing 1434AS101. The container shall have a hinge mechanism keyed for alignment on the forward edge of the thigh section. The hinge assembly shall not permit separation of the lid from the container when subjected to the loads specified in the general specification or herein.

3.4.2.1.1 Container bottom. The container bottom of the RSSK-9A shall be as specified in the general specification and shall conform to the envelope dimensions and general design of Drawing 1434AS102. The container shall have two negative "g" fittings to retain the container to the seat during negative "g" maneuvers.

3.4.2.1.2 Contoured lid. The contoured container lid of the RSSK-9A shall be as specified in the general specification and shall conform to the envelope dimensions and general design of Drawing 1434AS102.

3.4.2.2 Comfort cushion. The comfort cushion of the RSSK-9A shall be as specified in the general specification and shall conform to the envelope dimensions and general design of Drawing 1434AS104.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.

3.4.2.3 RSSK to torso harness restraint assembly. The RSSK to torso harness restraint assembly shall be as specified in the general specification and shall conform to the general design of Drawing 1434AS103.

3.4.2.4 Release handle and container locking mechanism. The release handle and container locking mechanism of the RSSK-9A shall be as specified in the general specification and shall conform to the general design of 1434AS102. The lid locking latches shall become mechanically integral with the locking mechanism in the bottom of the container when the container is locked. The mechanism shall open when the release handle is pulled. The color of the handle shall be yellow approximately matching color number 33538 of FED-STD-595.

3.4.2.5 Container dropline. The container dropline assembly shall be as specified in the general specification. The container dropline shall have one end permanently attached to the lid through the footman brackets and the other end attached to the container bottom through the footman brackets.

3.4.2.6 Radio beacon bracket. The radio beacon bracket shall be as specified in the general specification and shall be installed as specified in Drawing CL204D2.

3.4.3 Design load requirements. Unless otherwise specified herein, the design load requirements of the RSSK-9A shall be as specified in the general specification.

3.4.3.1 Swaging. Swaging shall be accomplished in accordance with MIL-T-6117 and shall be carefully performed. Each swaging shall be proof tested as specified in MIL-T-6117 to 100 pounds or three times the maximum operating load, whichever is greater.

3.5 Performance. Unless otherwise specified herein, the RSSK-9A shall meet all the performance requirements of the general specification.

3.5.1 Static loads. The RSSK to torso harness assembly, when tested as specified in 4.8.1, shall pass the requirements specified in the general specification.

3.5.2 Crash load. The RSSK, when tested as specified in 4.8.2, shall meet the requirements specified in the general specification.

3.5.3 Windblast load. The RSSK-9A, when tested as specified in 4.8.3, shall sustain the windblast loads without damage or malfunction.

3.5.4 Component interchange. The container lid and bottom, when tested as specified in 4.8.4, shall mate and lock while utilizing each of the release handles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.

3.6 Size. The RSSK-9A rigid seat survival kit shall conform to the contour of the ejection seat bucket with 1/4 inch minimum clearance between the seat kit and the seat bucket around the periphery of the seat kit. Drawing 1434AS102 provides critical control dimensions to establish proper kit to seat attachment.

3.7 Weight. The weight of the RSSK-9A furnished under this specification shall be a maximum of 18.6 pounds.

3.8 Interchangeability. The interchangeability of the RSSK-9A shall be as specified in the general specification.

3.9 Markings. In addition to the identification and markings specified in the general specification, the kit shall contain the following decalcomania markings:

a. The markings, located under the inspection slots shall indicate the lock and unlock positions of the container locking mechanisms and directions for manual unlock.

b. The markings, located under the handle housing shall be a warning note to reset actuator assembly if the handle will not lock in place.

3.10 Workmanship. The workmanship shall be as specified in the general specification and herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The classification of inspection shall be as specified in the general specification.

4.3 Qualification inspection. The number of samples, tests and examinations for qualification inspection shall be as specified in the general specification and herein.

4.4 First article. The number of samples, tests and examinations for the first article inspection shall be as specified in the general specification and herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection. The quality conformance inspection shall be as specified in the general specification.

4.6 Quality conformance verification inspection. The quality conformance verification inspection shall be as specified in the general specification.

4.7 Test requirements. The requirements for examinations and tests shall be as specified in the general specification and herein.

4.8 Inspection methods. The inspection methods for the RSSK-9A shall be as specified in the general specification, except as otherwise noted herein.

4.8.1 Static loads. The RSSK to torso harness assembly shall be subjected to the static loads test, condition I, as specified in paragraph 4.8.5.1 of the general specification. The RSSK to torso harness assembly shall pass the requirements specified in 3.5.1.

4.8.2 Crash loads. The RSSK shall be subjected to the crash load test as specified in the general specification. The kit lid shall be rotated from the "Z" axis forward and upward to 45 ±2 degrees and the 30 g load applied "eyeballs down" with a time duration of 100 milliseconds. The RSSK shall pass the requirements specified in 3.5.2.

4.8.3 Windblast loads. The rigid seat survival kit shall be subjected to the dynamic parameters of windblast loading specified below. The purpose of the exposure is to simulate the affects of windblast after man-seat separation. Prior to each test, the seat kit shall be securely interfaced to an appropriate torso harness. This system shall be donned on a simulated 50th percentile dummy. A partial dummy may be utilized if the torso and thigh features are provided. The windblast profile described below shall be performed once at each of the attitude conditions listed. One seat kit shall experience all three tests. Dynamic turning shall be utilized during each windblast. Initial positions and motion are specified as follows:

WINDBLAST PROFILE

Windblast number	Initial position	Turning motion
1	Torso in vertical seat position and facing directly into airstream	Yaw 90° starboard
2	Torso prone with head facing into airstream	Yaw 90° port
3	Torso prone with feet facing into into airstream	Yaw 90°

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.

DYNAMIC PARAMETERS

Peak velocity	250 ± 20 knots equivalent air speed (KEAS)
Rise time	80 ± 20 milliseconds (ms)
Total duration	1.5 seconds minimum

Photographic coverage of each windblast exposure test shall include a minimum of two high speed motion picture cameras. The minimum camera speed shall be 600 feet per second. Still photography and camera position shall be utilized as directed by the acquiring activity. The RSSK-9A shall pass the requirements specified in 3.5.3. Following this test, the kit shall be subjected to and pass the requirements of the release handle and the bench actuation tests specified in the general specification.

4.8.4 Component interchange. Three contoured container lids, from RSSK-9A seat kits submitted under contract, shall be interchanged with three container bottoms. The kits shall pass the requirements specified in 3.5.4.

5. PACKAGING

5.1 Packaging. Packaging shall be as specified in the general specification.

6. NOTES

6.1 Intended use. The rigid seat survival kit designated RSSK-9A is intended for use with the applicable ejection seat as specified in the general specification.

6.2 Ordering data. The ordering data shall be as specified in the general specification with the inclusion of the following:

a. Specific location of the indicator activator hole and the radio beacon bracket.

6.3 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing Activity:
Navy - AS
(Project No. 1660-N465)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-81040/2B(AS)	Survival Kit Container, Aircraft Seat, w/o Oxygen, RSSK-9A

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.