The documentation and process conversion measures necessary to comply with this amendment shall be completed by 11 January 1997.

INCH POUND

MIL-S-19500/225E
AMENDMENT 2
11 October 1996
SUPERSEDING
AMENDMENT 1
8 February 1995

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON,
TYPES 2N1711, 2N1711S, 2N1890, 2N1890S, JAN AND JANTX

This amendment forms a part of MIL-S-19500/225E, dated 15 April 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

*4.3.2, delete and substitute as follows:

"4.3.2 Thermal impedance $Z_{\Theta JX}$ measurements (for qualification only). The $Z_{\Theta JX}$ measurements shall be perfromed in accordance with MIL-STD-750, method 3131.

a). I_M measurement current ..... 10 mA

b). I_H forward heating current ..... 50 mA minimum

c). t_H heating time ..... 10 ms

d). t_{MD} measurment delay time ..... 100 μs minimum

e). V_{CE} collector - emitter voltage ..... 10 V dc

The maximum limit for $Z_{\Theta JX}$ under these test conditions is $Z_{\Theta JX}$ (max) = 58°C/W"

*4.3.2.1, delete in its' entirety.

PAGE 4

*4.4.1, delete and substitute as follows:

"4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-S-19500, and table I herein. The test conditions for $Z_{\Theta JX}$ shall be those used in 4.3.2."

*4.4.2, subgroup E2, conditions, delete "V_R" and substitute "V_{CBO}".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:45Z
Check the source to verify that this is the current version before use.

PAGE 5

*TABLE I, subgroup 2, thermal impedance test, limits max column, delete "4.5" and substitute "58".

PAGE 6

TABLE I, subgroup 2, base emitter saturated voltage, max limits, delete "9.0" and substitute "0.9".

PAGE 7

*TABLE I, subgroup 4, small -signal short-circuit output admittance, limits min column, delete "0"; limits max. column, delete "0.5", unit column, delete " μΩ".

PAGE 8

*Note 2, delete ".2 ns" and substitute "2 ns".

PAGE 9

*4.5.2, a., delete "28 mA" and "47 mA" and substitute "30 mA" and "50 mA" respectively; f., delete "Maximum limit shall be $R_{\Theta JC}$ = 58°C/W." and substitute "t_{md} measurment delay time = 100 μs maximum"; add new note g as follows: "g. I_m measuremnt current = 10 mA."; add new note h as follows: h. maximum limit shall be $R_{\theta JC}$ = 58°C/W."

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, AV, MI, SM
Navy - AS, CG, MC
Air Force - 13, 19, 85, 99

Preparing activity:
DLA - ES

(Project 5961-1854)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:45Z
Check the source to verify that this is the current version before use.