The documentation and process conversion measures necessary to comply with this document shall be completed by 31 August 2022.

INCH-POUND
MIL-PRF-19500/225L
w/AMENDMENT 3
31 May 2022
SUPERSEDING
MIL-PRF-19500/225L
w/AMENDMENT 2
20 October 2020

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, NPN, SILICON,
TYPES 2N1711, AND 2N1890, JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, low-power transistors. Three levels of product assurance (JAN, JANTX, and JANTXV) are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. The device packages for the encapsulated device types are as follows: (2N1711 and 2N1890) Three terminal round metal can TO-205AD (formerly TO-39) and TO-205-AA (formerly TO-5) in accordance with figure 1.

1.3 Maximum ratings. Unless otherwise specified T_A = +25°C.

Type (1)	P_T (2) T_C = +25°C	P_T (2) T_A = +25°C	$R_{\theta JA}$ (3)	$R_{\theta JC}$ (3)	I_C	V_{CBO}	V_{CER} R_{BE} = 10 Ω	V_{CEO}	V_{EBO}	T_J and T_{STG}
	W	W	°C/W	°C/W	mA dc	V dc	V dc	V dc	V dc	°C
2N1711	3.0	0.8	175	30	500	75	50	30	7	-65 to +200
2N1890	3.0	0.8	175	30	500	100	80	60	7	

(1) Also applies to the corresponding "S" suffix device.
(2) For derating see figure 2 and figure 3.
(3) For thermal impedance curves see figure 4 and figure 5.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics.

Limits	h_{FE1} (1)	h_{FE2} (1)	$\|h_{fe}\|$	$V_{CE(SAT)}$	$V_{CE(SAT)}$	$V_{CE(SAT)}$
	V_{CE} = 10 V dc I_C = 10 μA dc	V_{CE} = 10 V dc I_C = 150 mA dc	f = 20 MHz V_{CE} = 10 V dc I_C = 50 mA dc	2N1711, S (1) I_C = 150 mA dc I_B = 15 mA dc	2N1890, S (1) I_C = 150 mA dc I_B = 15 mA dc	2N1890, S (1) I_C = 50 mA dc I_B = 5.0 mA dc
				V dc	V dc	V dc
Min	20	100	3.5			
Max		300	12	1.5	5.0	1.2

(1) Pulsed (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level.

1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", and "JANTXV".

1.5.2 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.2.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "1711", and "1890".

1.5.3 Suffix symbols. The following suffix letters are incorporated in the PIN in the order listed in the table as applicable:


	For no suffix devices, dimension LL is 1.500 inches (38.10 mm) minimum, and 1.750 inches (44.45 mm) maximum (TO-205-AA, formerly TO-5).
S	For S suffix devices, dimension LL is .500 inch (12.70 mm) minimum, and .750 inch (19.05 mm) maximum (TO-205-AD, formerly TO-39).

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

Dimensions					
Symbol	in	in	mm	mm	Notes
	Min	Max	Min	Max	
CD	.305	.335	7.75	8.51	
CH	.240	.260	6.10	6.60	
HD	.335	.370	8.51	9.40	
LC	.200 TYP		5.08 TYP		7
LD	.016	.021	0.41	0.53	6
LL					7, 9, 10
LU	.016	.019	0.41	0.48	7
L_1		.050		1.27	7
L_2	.250		6.35		7
P	.100		2.54		5
Q		.050		1.27	
r		.010		0.254	8
TL	.029	.045	0.74	1.14	4
TW	.028	.034	0.71	0.86	3
α	45° TP		45° TP		6

Term 1	Emitter	
Term 2	Base	
Term 3	Collector	



NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Beyond r maximum, TW must be held to a minimum length of .021 inch (0.53 mm).
4. TL measured from maximum HD.
5. CD shall not vary more than ±.010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
6. Leads at gauge plane .054 - .055 inch (1.37 - 1.40 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at a maximum material condition (MMC) relative to the tab at MMC. The device may be measured by direct methods or by gauge and gauging procedure.
7. LU applies between L_1 and L_2. LD applies between L_2 and LL minimum. Diameter is uncontrolled in L_1 and beyond LL minimum.
8. r (radius) applies to both inside corners of tab.
9. For transistor types 2N1711S and 2N1890S, LL is .500 inch (12.70 mm) minimum, and .750 inch (19.05 mm) maximum (TO-205-AD, formerly TO-39).
10. For transistor types 2N1711 and 2N1890, LL is 1.500 inches (38.10 mm) minimum, and 1.750 inches (44.45 mm) maximum (TO-205-AA, formerly TO-5).
11. In accordance with ASME Y14.5, diameters are equivalent to ϕx symbology.

FIGURE 1. Physical dimensions (TO-205-AA and TO-205AD).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1 (TO-5 and TO-39).

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.6 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.7 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (list applicable JANTX and JANTXV levels). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurement JANTX and JANTXV level
3c (1)	Thermal impedance (see 4.3.2), method 3131 of MIL-STD-750.
9	Not applicable.
11	h_{FE2}; I_{CBO1}
12	See 4.3.1.
13	ΔI_{CBO1} = 100 percent of initial value or 5 nA dc; whichever is greater; Δh_{FE2} = ±15 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

4.3.1 Burn-in conditions. Burn-in conditions are as follows: V_{CB} = 10 - 30 V dc. Power shall be applied to achieve T_J = +135°C minimum using a minimum P_D = 75 percent of P_T maximum, T_A ambient rated as defined in 1.3.
NOTE: No heat sink or forced air cooling of the devices shall be permitted.

4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{MD} t_{SW} (V_C and V_H where appropriate). See table II, group E, subgroup 4 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein. The test conditions for $Z_{\theta JX}$ shall be those used in 4.3.2.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified in 4.4.2.1 herein.

4.4.2.1 Group B inspection, JAN, JANTX, and JANTXV. Group B inspection for quality levels JAN, JANTX, and JANTXV shall be conducted in accordance with the conditions specified in table E-VIC (small die flow) of MIL-PRF-19500 and herein. All catastrophic failures during CI shall be analyzed to the extent possible to identify root cause and corrective action. Whenever a failure is identified as wafer lot or wafer processing related, the entire wafer lot and related devices assembled from the wafer lot shall be rejected unless an appropriate determined corrective action to eliminate the failure mode has been implemented and the devices from the wafer lot are screened to eliminate the failure mode.

Step	Method	Condition
1	1026	Steady-state life: 1,000 hours minimum, V_{CB} = 10 V dc, power shall be applied to achieve T_J = +150°C minimum using a minimum of P_D = 75 percent of maximum rated P_T as defined in 1.3. n = 45 devices, c = 0. The sample size may be increased and the test time decreased so long as the devices are stressed for a total of 45,000 device hours minimum, and the actual time of test is a minimum of 340 hours.
2	1048	Blocking life, T_A = 150°C, V_{CB} = 80 percent of rated voltage, without going over the maximum rated V_{CE}, 48 hours minimum. n = 45 devices, c = 0.
3	1032	High-temperature life (non-operating), t = 340 hours, T_A = +200°C. n = 22, c = 0.

* 4.4.2.3 Group B sample selection. Samples selected from group B inspection shall be in accordance with all of the following requirements:

a. Samples shall be selected from an inspection lot that has been submitted to and passed table I, subgroup 2, conformance inspection.

b. When the final lead finish is solder, or any plating prone to oxidation at high temperature, the samples for life test (Step 1) may be tested prior to the application of final lead finish.

c. Separate samples may be used for each step.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and as follows.

Subgroup	Method	Condition
C2	2036	Lead fatigue: Test condition E.
C5	3131	$R_{\theta JA}$ and $R_{\theta JC}$ only, as applicable (see 1.3 and 4.3.2).
C6		Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

4.4.3.3 Group C sample selection. Samples for subgroups in group C shall be chosen at random from any inspection lot containing the intended package type and lead finish procured to the same specification which is submitted to and passes table I tests herein for conformance inspection. Testing of a subgroup using a single device type enclosed in the intended package type shall be considered as complying with the requirements for that subgroup.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table II herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

	Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
		Method	Conditions		Min	Max	
	Subgroup 1 2/						
*	Visual and mechanical examination 3/	2071					
	Solderability 3/ 4/	2026	n = 15 leads, c = 0				
	Resistance to solvents 3/ 4/ 5/	1022	n = 15 devices, c = 0				
	Salt atmosphere (corrosion)	1041	n = 6 devices, c = 0, (For laser marked devices only)				
	Temp cycling 3/ 4/	1051	Test condition C, 25 cycles. n = 22 devices, c = 0				
*	Hermetic seal 5/ 4/ 6/ Fine leak Gross leak	1071	n = 22 devices, c = 0				
	Electrical measurements 4/		Table I, subgroup 2				
	Bond strength 3/ 4/	2037	Precondition T_A = +250°C at t = 24 hours or T_A = +300°C at t = 2 hours n = 11 wires, c = 0				
	Decap internal visual (design verification) 4/	2075	n = 4 devices, c = 0				
	Subgroup 2						
	Thermal impedance 7/	3131	See 4.3.2	$Z_{\theta JX}$			°C/W
	Breakdown voltage, collector to emitter	3011	Bias condition D; I_C = 30 mA dc; pulsed (see 4.5.1).	$V_{(BR)CEO}$			
	2N1711, 2N1711S				30		V dc
	2N1890, 2N1890S				60		V dc
	Breakdown voltage, collector to emitter	3011	Bias condition B; I_C = 100 mA dc; pulsed (see 4.5.1). R_{BE} = 10 Ω.	$V_{(BR)CER}$			
	2N1711, 2N1711S				50		V dc
	2N1890, 2N1890S				80		V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued.						
Collector to base cutoff current	3036	Bias condition D	I_{CBO1}			
2N1711, 2N1711S 2N1890, 2N1890S		V_{CB} = 60 V dc V_{CB} = 80 V dc			10 10	nA dc nA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 5 V dc	I_{EBO1}		5.0	nA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO2}			
2N1711, 2N1711S 2N1890, 2N1890S		V_{CB} = 75 V dc V_{CB} = 100 V dc			100 100	µA dc µA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 7 V dc	I_{EBO2}		100	µA dc
Collector-emitter saturation voltage 2N1711, 2N1711S 2N1890, 2N1890S	3071	I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$		 1.5 5.0	 V dc V dc
Collector-emitter saturation voltage	3071	I_C = 50 mA dc; I_B = 5 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$			V dc
2N1890, 2N1890S					1.2	V dc
Base emitter saturation voltage	3066	Test condition A, I_C = 150 mA dc, I_B = 15 mA dc, pulsed (see 4.5.1).	$V_{BE(sat)1}$		1.3	V dc
Base emitter saturation voltage 2N1890, 2N1890S	3066	Test condition A, I_C = 50 mA dc, I_B = 5 mA dc, pulsed (see 4.5.1).	$V_{BE(sat)2}$		 0.9	V dc V dc
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 µA dc pulsed (see 4.5.1).	h_{FE1}	20		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 150 mA dc pulsed (see 4.5.1).	h_{FE2}	100	300	

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued.						
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 500 mA dc pulsed (see 4.5.1).	h_{FE3}			
2N1711, 2N1711S				50		
Subgroup 3						
High temperature operation		T_A = +150°C				
Collector to base cutoff current	3036	Bias condition D	I_{CBO3}			
2N1711, 2N1711S		V_{CB} = 60 V dc			10	µA dc
2N1890, 2N1890S		V_{CB} = 80 V dc			15	µA dc
Low temperature operation		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 mA dc, pulsed (see 4.5.1).	h_{FE4}	35		
Subgroup 4						
Small-signal short-circuit forward current transfer ratio	3206	V_{CE} = 5 V dc; I_C = 1 mA dc; f = 1 KHz	h_{fe1}	80	200	
		V_{CE} = 10 V dc; I_C = 5 mA dc; f = 1 KHz.	h_{fe2}	90	270	
Magnitude of small-signal short- circuit forward current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 50 mA dc; f = 20 MHz	$\lvert h_{fe} \rvert$	3.5	12	
Small-signal short- circuit input impedance	3201	V_{CB} = 10 V dc; I_C = 5 mA dc f = 1 kHz	h_{ib}	4	8	ohms
Small-signal short-circuit input admittance	3216	V_{CB} = 10 V dc; I_C = 5 mA dc f = 1 kHz	h_{ob}			
2N1711, 2N1711S				0.0	1.0	µmhos
2N1890, 2N1890S				0.0	.3	µmhos

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Small-signal open-circuit reverse voltage transfer ratio	3211	V_{CB} = 10 V dc; I_C = 5 mA dc; f = 1 kHz	h_{rb}			
* 2N1711, 2N1711S					$5x10^{-4}$	
* 2N1890, 2N1890S					$1.5x10^{-4}$	
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0 mA dc 100 kHz ≤ f ≤ 1 mHz	C_{obo}			
2N1711, 2N1711S				8	25	pF
2N1890, 2N1890S				5	15	pF
Pulse response	3251	Test condition A, except test circuit and pulse requirements. See figure 6 herein.	$t_{on} + t_{off}$		30	ns
Subgroup 5, 6, and 7						
Not applicable						


1/ For sampling plan see MIL-PRF-19500.
2/ For resubmission of failed test in subgroup 1 of table I, double the sample size of the failed test or sequence of tests. A failure in table I, subgroup 1 shall not require retest of the entire subgroup. Only the failed test shall be rerun upon submission.
3/ Separate samples may be used.
4/ Not required for JANS devices.
5/ Not required for laser marked devices.
6/ This hermetic seal test is an end-point to temp-cycling in addition to electrical measurements.
7/ This test required for the following end-point measurement only:
Group B, step 1.
Group C, subgroup 2.
Group E, subgroups 1 and 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) - for qualification or re-qualification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles	
Hermetic seal Fine leak Gross leak	1071		
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2			45 devices c = 0
Intermittent life	1037	Intermittent operation life: V_{CB} = 10 V dc, 6,000 cycles Adjust device current, or power, to achieve a minimum ΔT_J of +100°C.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 4			
Thermal impedance curves		See table E-IX of MIL-PRF-19500, group E, subgroup 4.	
Subgroup 5			
Not applicable			
Subgroup 6			11 devices
Electrostatic discharge (ESD)	1020		
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.




NOTES:

1. This is the true inverse of the worst case thermal resistance value. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ 200°C) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ 150°C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125°C, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 2. Temperature-power derating for 2N1711, 2N1711S, 2N1890, and 2N1890S (TO-5 and TO-39).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.



NOTES:

1. This is the true inverse of the worst case thermal resistance value. All devices are capable of operating at $\leq T_J$ specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 3. Temperature-power derating for 2N1711, 2N1711S, 2N1890, and 2N1890S (TO-5 and TO-39).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.




FIGURE 4. Thermal impedance graph ($R_{\theta JA}$) for 2N1711, 2N1711S, 2N1890, and 2N1890S (TO-5 and TO-39).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.






FIGURE 5. Thermal impedance graph ($R_{\theta JC}$) for 2N1711, 2N1711S, 2N1890, and 2N1890S (TO-5 and TO-39).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.






WAVEFORM AT "A"
FROM LUMATRON Hg PULSE
GENERATOR OR EQUIVALENT



WAVEFORM AT "B"



NOTES:

1. The rise time (T_r) of the applied pulse shall be 2.0 ≤ ns, duty cycle ≤ 2 percent, and the generator source impedance shall be 50 Ω.
2. Sampling oscilloscope: $Z_{in} \geq 100$ kΩ, $C_{in} \leq 12$ pF, rise time ≤ 2 ns.

FIGURE 6. Pulse response (turn-on plus turn-off) measurement circuit and waveforms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.

6.5 List of PINs.

6.5.1 PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

*

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level
JAN2N1711	JANTX2N1711	JANTXV2N1711
JAN2N1711S	JANTX2N1711S	JANTXV2N1711S
JAN2N1890	JANTX2N1890	JANTXV2N1890
JAN2N1890S	JANTX2N1890S	JANTXV2N1890S

6.6 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - AR, AV, MI, SM
Navy - AS, MC
Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2022-027)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:44Z
Check the source to verify that this is the current version before use.