[Metric]
A-A-1817D
December 3, 1993
SUPERSEDING
A-A-1817C
May 11, 1990

COMMERCIAL ITEM DESCRIPTION

BOOKCASE (STEEL, CONTEMPORARY STYLE)

The General Services Administration has authorized the use of this commercial item description.

1. Scope. The contemporary style bookcases are for heavy duty office use.

2. Salient characteristics.

2.1 Classification. The bookcases shall be of the types, sizes, and colors specified.

Types

I - With laminate tops.
II - Without laminate tops.

Sizes

1 - 762 mm W x 330 mm D x 1206.5 mm H for type I and 1181.1 mm H for type II, all dimensions are minimum.
2 - 762 mm W x 330 mm D x 731 mm H for type I and 717.5 mm H for type II, all dimensions are minimum.

Colors - In accordance with Federal Standard No. 595, see 2.5.

Black - B
Parchment - P
Gray - G

2.2 Requirements.

2.2.1 Adjustable shelves. The size 1 bookcase shall have two adjustable shelves, allowing three openings, 304.8 mm in height, minimum clearance. The size 2 bookcase shall have one adjustable shelf, allowing two openings, one 304.8 mm in height, minimum clearance. The shelf adjusting devices shall not be visible on

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.

the exterior of the case. Shelf supports shall be provided.

2.2.2 Metal gauge.
2.2.2.1 Size 1. All exterior metal and shelves shall not be less than 20 gauge 0.8975 mm. Interior bracing may be of a smaller gauge. The exterior metal and shelves shall be formed on all sides or otherwise treated so as to eliminate cutting hazards.

2.2.2.2 Size 2. All exterior metal and shelves shall not be less than 0.5975 mm. Interior bracing may be of a smaller gauge. The exterior metal and shelves shall be formed on all sides or otherwise treated so as to eliminate cutting hazards.

2.3 Tops. Type I tops shall be self-edged, high pressure (HP) laminated plastic on plywood or particleboard with a backing sheet on the bottom. The color shall be walnut grain per GSA sample No. FSS-L-01002. Alternatively, the manufacturer may provide his equivalent, commercial, walnut grain, HP laminated plastic, subject to the contracting officer's approval. Overall thickness of the top shall be 19 mm minimum. Type II tops shall be steel.

2.4 Legs. The legs shall be a minimum 22 mm square, stainless or chromium plated steel, with a polished finish. They shall have adjustable glides and the exposed length of the legs shall be a minimum of 152 mm from the base frame to the bottom of the fully retracted glides. The glides shall be easily adjustable by hand. The glides shall have a minimum adjustment of 12.5 mm. The bookcase shall be designed so that the legs are attached to the case by other means than friction, to prevent the legs from falling out.

2.5 Finish. The finish shall be semi-gloss baked enamel. Colors shall match Fed. Std. No. 595 black (27040), parchment (within the range delimited by 26586 and 26405), or gray (26134), as specified. Alternatively, the manufacturer may provide his commercial black, parchment, or gray baked enamel finish, subject to the approval of the contracting officer.

2.6 Assembly. The bookcases shall be fully assembled. Shelves, legs and any attaching hardware may be shipped unattached but secured to the bookcase.

3. Performance.

3.1 Tests. The bookcases shall comply with the following tests which will be required as part of the First Article Inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.

3.1.1 Chromium plating test. The chromium plated steel test samples shall be tested for corrosion with the 5 percent neutral salt spray at 35°C in accordance with ASTM Test Method B-117. The test period shall not be less than 48 hours. After the specified exposure is completed, the specimen shall be visually examined to assure that the plating shows no evidence of peel, chip, uneven color, powder film, pits, or stain. Widely scattered spots of corrosion are permitted; however, none of these spots of corrosion shall exceed 1.6 mm along the greatest dimension.

3.1.2 Shelf test (static). This test shall be performed on both the size 1 and size 2 bookcases. The complete bookcase shall be placed on a level surface. Only one shelf shall be used. It shall be adjusted to the approximate mid-point (top-to bottom). A load of 9.1 kg shall be placed on the shelf at both of the extreme sides for 5 minutes to assure that the shelf supports are fully engaging the shelf. This load shall then be removed. A dial indicator or equivalent measuring device shall be placed at the center of the front edge of the shelf. An evenly distributed non-rigid load totaling 68 kg shall be placed on the shelf and remain undisturbed for 15 minutes. Deflection shall then be recorded. The shelf shall not be deflected more than 4.8 mm. The load shall then be removed and the permanent distortion recorded. The shelf shall not have more than a 0.7 mm permanent set.

3.1.3 Leg attachment test. Each leg of the bookcase shall be tested as follows. The bookcase shall be inverted and restrained from movement. Two inches from the bottom of the leg under test, a force of 890 N shall be applied against the outside of the leg toward the center of the bookcase. This force shall be held against the leg not less than ten minutes. At the end of the ten minute time limit, the force shall be removed from the leg. Permanent distortion of the leg shall not exceed 4.75 mm. There shall be no weakening of the leg's attachment to the bookcase. A dial indicator or equivalent measuring device shall be used for the above test.

3.1.4 Drop test. The glides shall be fully retracted. One end of the bookcase shall then be raised 152 mm and dropped onto the floor. Repeat the drop test on the other end of the bookcase. The bookcase shall then be examined. There shall be no broken welds, loose mechanical attachments, or visual, permanent distortion.

3.1.5 Leg security test. With the bookcase in an upside

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.

position, an upward vertical pull of a 67 N force shall be applied to each leg for one minute. Any movement exceeding 2 mm after the test shall be cause for rejection.

3.2 Identification label. The label shall have the contractor's name or trademark, contract No., NSN (if specified), and year and month of manufacture legibly marked with permanent dark ink. The label shall be affixed to the back or inside back of the bookcase. It shall not be removable by hand without defacement after being affixed for 4 hours.

3.3 Workmanship. Edges and corners shall be eased. The metal shall be free of sharp edges and burrs to prevent injury to personnel. The baked enamel finish shall be smooth without runs, grit, wrinkles, tackiness, or separation of color. The chromium elating shall be free of pits, blisters, stains and brush and grind marks. There shall be no other defects adversely affecting appearance or serviceability.

4. Quality Assurance Provisions.

4.1 Responsibility for inspection. The contractor shall be responsible for the performance of all inspection and testing in fulfillment of all requirements specified herein. Unless otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities approved by the Government as suitable for the performance of inspections and tests required by this CID. The Government reserves the right to perform any or all of the inspections and/or tests set forth in this CID, as deemed necessary to provide assurance of supply conformance to prescribed requirements.

4.2 First article requirements. Unless otherwise specified by the contract or purchase order, a sample of the finished product shall be made available by the contractor for first article testing. Inspection of the First Article shall verify conformance to all of the requirements herein.

4.3 Quality conformance inspection. A sample of the finished product shall be selected in accordance with paragraph 4.6 of this CID for quality conformance verification. The sample shall be examined to verify that the requirements referenced in sections 1, 2, and 3 have been met. Any non conformance with the above requirements shall be considered a defect. All defects found shall be classified as major/minor in accordance with paragraphs 4.4 and 4.5 of this CID.

4.4 Major defects. The following conditions of non-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.

conformance with the stated requirements of the CID shall be considered as major defects which may potentially affect the safety, functionality, durability, usability, and life of the purchased items.

No evidence of passing the chromium plating test, shelf test, leg attachment test, and drop test.
No evidence of passing the leg security test.
Dimensions not as specified.
Parts fractured, buckled, bent, punctured, or malformed.
Rivets loose or not set properly.
Sharp edges.
Preservation, packaging, and packing not in accordance with the requirements of the contract or purchase order.
Identification marking missing, wrong, or illegible.

4.5 Minor defects. Non-conformance listed below shall be considered as minor defects affecting the appearance of the finished item.

Rough or slivered surface.
Burrs.
Rough tool markings.
Oversized holes.
Pitted, stained, or blistered surfaces.
Foreign matter embedded in the finish.
Painted surfaces contain sags or runs.
Components Laid parts covered with film.
Parts, components, overall covered, not free of grease, dirt dust, epoxy, stains, etc.

4.6 Sampling for inspection. The sampling plan shall be in accordance with MIL-STD-105 with an inspection level II, Acceptable Quality Level (AQL) of 6.5 percent defective for minor defects and an inspection level of S-2, AQL of 2.5 percent defective for major defects.

4.7 Testing. For testing in accordance with Section 3 of this CID, the special level S-2 of MIL-STD-105, with an AQL of 2.5 percent defective, shall apply.

5 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.

6 Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.

7. Standards. The issues in effect of MIL-STD-105, ASTM Test Method B-117, and Fed. Std. 595 on the date of solicitation shall be used to determine compliance with the stated requirements.

8. Notes.

8.1 Ordering data. Purchasers should specify type, size, and color.

8.2 ASTM standards. Copies of the American Society for Testing and Materials (ASTM) Test Method B-117 are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

8.3 Military standards. Copies of MIL-STD-105 are available from the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

8.4 Federal standards. Copies of Federal Standard No. 595 are available from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

8.5 Plastic laminate sample. A sample of the decorative plastic laminate can be obtained from the Engineering Division, Furniture Commodity Center, Federal Supply Service, Washington, DC 20406 or from the Business Service Center in the nearest General Services Administration Regional Office.

8.6 Finish sample. A sample panel of the baked enamel finish can be obtained from the Business Service Center, Federal Supply Service, General Services Administration, Washington, DC 20407, or from the Business Service Center in the nearest General Services Administration Regional Office.

8.7 The commercial item certification clause is not required in the solicitation, when this commercial item description is used for procurement.

PREPARING ACTIVITY

GSA - FSS/3FNE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.