[Metric]
A-A-2779A
October 2, 1995
Superseding
A-A-2779
December 15, 1991

COMMERCIAL ITEM DESCRIPTION
MARKER, TUBE & FLAT TYPE
FLUORESCENT / NON-FLUORESCENT
HIGHLIGHTER

This Commercial Item Description is approved by the Commissioner, Federal Supply Service, General Services Administration, for use by all federal agencies.

1. **Scope:** This Commercial Item Description covers fluorescent and non-fluorescent markers, tube or flat type, (felt, fiber or porous plastic nib) for use in highlighting printed text.

2. **Classification:**

Type:	I - Non-Fluorescent Highlighter
	II - Fluorescent Highlighter
	III - Fluorescent Highlighter Set
Class:	A - Tube Type
	B - Flat Type

3. **Salient Characteristics:**

3.1 Type I markers shall be a tube type, non-fluorescent ink, which shall be furnished with a non-replaceable felt, fiber or porous plastic nib, capillary fed ,writing instrument with protective cap. The marker shall have a minimum write out of 300 meters (984.0 feet).

3.2 Type II markers shall be either tube or flat type, fluorescent ink, furnished with a non-replaceable felt, fiber or porous plastic nib, capillary fed writing instrument with protective cap. The marker shall have a minimum write out of 300 meters (984.0 feet).

3.3 Type III markers shall be either tube or flat type (set), fluorescent ink, furnished with a non-replaceable felt, fiber or porous plastic nib, capillary fed, writing instrument with protective cap.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

3.4 All markers shall be a non-refillable type with ink held in the reservoir by an absorbent material (no free flowing liquid). The marker shall be equipped with a tight fitting plastic or metal protective cap to provide protection against evaporation and leakage. The marker shall be made of plastic or metal or a combination of these materials and the cap or body shall be colored to identify the color of ink.

3.5 The markers shall be furnished in the following colors: Blue, Green, Pink, Yellow, Orange, and Magenta as specified in paragraph 8.3 (Notes).

3.6 The overall length of Types I, II and III markers shall be not less than 11.6cm (4.9 inches), with the cap in place.

3.7 The manufacturer's name or trademark shall be exhibited on the marker. Placement of these permanent markings shall be at the option of the manufacturer, provided they are prominently displayed.

3.8 Clip Caps. When flat type markers are specified, they shall be provided with a metal or plastic clip type cap.

3.9 Shelf Life. The markers shall have a minimum shelf life of eighteen (18) months after delivery and shall be capable of withstanding normal usage and handling.

3.10 Workmanship. The markers shall be free from defects or imperfections of manufacture which may affect their durability, appearance or serviceability or present a hazard to the user. The surface of the marker shall be of uniform appearance and shall be free from rough or sharp edges, burrs, blisters, scratches and other defects.

4. Regulatory Requirements:

The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. Quality Assurance Requirements:

5.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and therefore as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

5.2 Examination and Testing.

5.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3/ American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein.

5.2.2 End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. In process controls shall not be substituted for end item performance testing.

5.2.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. The sample unit shall be either one marker or marker set. Sampling shall be in accordance with the American National Standards Institute (ANSI)/ American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

5.2.4 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level for visual,dimensional defects, and performance testing shall be S-2 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

6. Performance Tests: Unless otherwise specified, the tests shall be conducted in an atmosphere of 21° ± 3°C (64.5°-75.2°F) and a relative humidity of 50% ± 5%. Test paper shall be in accordance with A-A-2804A, type III white bond paper having a pH of 5.0 with a basis weight of 60 grams per square meter (16 pound, 17 x 22 - 500). A tolerance of 5% is allowable. Paper for the Machine Writing Test shall have an additional requirement of 160 - 140 seconds maximum smoothness on both sides using the Sheffield method per the most current TAPPI T538 test method. Alternately, paper conforming to JCP-O-60 can be used as an alternate source.

6.1 Drying Time. Place a sheet of paper on a smooth, flat surface and partially cover with a second sheet of paper. Place a 200 gram weight, approximately 31.75 mm (1.25 inches) in diameter, on top of the second sheet. Write a line on the exposed portion of the bottom sheet, allow to dry three seconds, and immediately draw the top sheet and the weight across the writing at a rate of approximately 101.6 mm (4.0 inches) per second. The writing shall not smear or smudge.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:25Z
Check the source to verify that this is the current version before use.

6.2 Machine Write Test. The machine tests shall be conducted on a Anja W-10B, K&L machine broad tip marker tester, or equivalent, with parameters set according to the manufacturer's testing procedures.

7. Packaging:

7.1 Preservation, packing, and marking shall be specified in the contract or order.

8. Notes:

8.1 Part Identification Number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

This example describes a part numbering system for CID A-A-2779A:

A-A-2779A 1 B

Class: A - Class A - Tube
B - Class B - Flat

Type: 1 - Type I - Non-Fluorescent Highlighter
2 - Type II - Fluorescent Highlighter
3 - Type III - Fluorescent Highlighter Set

8.2 Applicable Documents. Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

8.2.1 Technical Association of the Pulp and Paper Industry (TAPPI).
T479 method may be obtained from TAPPI, Technology Park, P.O. Box 105113, Atlanta, Georgia, 30348-5113.

8.2.2 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

8.2.3 Application for copies of (ANSI) Z1.1, Z1.2 and Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control. PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

8.2.4 JCP Specifications may be obtained from Chief Paper Procurement Section, MMPP, US Government Printing Office, North Capital and H Street, NW, Washington DC 20401.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

8.3 Ordering Information. Purchaser should select the required options permitted herein, and include the following information in procurement documents:

A. Title, number, and date of this commercial item description.
B. Purchasers shall specify the type, class and color of ink required (See Classification).
C. Purchasers shall specify arrangement for inspection and inspection facilities, if other than specified.
D. Purchasers shall specify packaging, packing, and any special marking for shipment, if other than required.
E. Purchasers shall specify identification marking, if other than required.
F. Purchasers shall specify if bar code marking is not required.
G. Purchasers shall specify palletization, if required.

8.4 National Stock Number Listing.

Non Fluorescent Highlighter	Fluorescent Highlighter
7520-01-386-2381	7520-01-159-1585
7520-01-386-2387	7520-01-166-0682
7520-01-386-2388	7520-00-460-7598
7520-01-386-2401	7520-00-904-4476
	7520-01-383-7929
	7520-01-383-7924
	7520-01-351-9146
	7520-01-351-9143

Fluorescent Highlighter Set

7520-01-238-1728
7520-01-383-7938
7520-01-383-7943

MILITARY INTERESTS:
NONE: DoD has determined that no military activity has an interest in this commercial item description.

PREPARING ACTIVITY
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.