INCH-POUND

A-A-52057
January 19, 1990

COMMERCIAL ITEM DESCRIPTION

REFRIGERATED BASE, SELF-CONTAINED, DRAWER TYPE

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers four types of refrigerated bases as follows (see 5.2):

Type 1 - Two full height drawers
Type 2 - Three full height drawers
Type 3 - Four half height drawers
Type 4 - Six half height drawers

1.2 Part identification number. The part identification number shall consist of the commercial item description number and type number as follows:

A-A-52059 - I
- I: Type
- A-A-52059: CID number

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The refrigerated base shall contain two side by side refrigerated drawer sections for types 1 and 3, and three side by side refrigerated drawer sections for types 2 and 4, and a self-contained refrigeration unit for all types. The refrigerated base is to be used as a cooking equipment stand.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014.

AMSC N/A FSC 4110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

2.1.1 Refrigerated base. Maximum overall dimensions of the base shall be 105 inches long, 35 inches wide, and 27 inches high when legs are in fully extended position for types 2 and 4 maximum overall dimensions 78 inches long, 35 inches wide and 27 inches high when legs are in fully extended position for types 1 and 3. The exterior and interior shall be fabricated of 300 series stainless steel. The space between exterior and interior surfaces shall be insulated. The stainless steel top shall be reinforced or shall have a steel subtop to support a minimum of 500 pounds of cooking equipment. Each drawer section shall contain one full height drawer for type 1 and type 2 and two half height drawers for type 3 and type 4. The drawers shall be sized to accommodate 12 inches x 20 inches pans. Drawers shall be of the self closing type. Drawer openings shall have full perimeter breaker strips to prevent heat transfer between the metal interior liner and the outer cabinet. Insulation between the exterior and the interior wall shall be of sufficient amount so that no condensation will form on the exterior of the refrigerated base when operational test is performed (see 3.3.3). The refrigerated base shall be equipped with a minimum of six, 6 inch fully adjustable stainless steel legs. The refrigerated base shall be equipped with an automatic defrost system.

2.1.2 Refrigeration unit. The refrigeration unit shall be an integral part of the complete refrigerated base. The refrigeration unit shall be completely self contained, precharged, and wired. A minimum 1/4 hp hermetically sealed compressor shall be provided and the refrigeration unit shall be capable of maintaining an average temperature of 36°F to 40°F in an ambient temperature of 90°F. Refrigeration unit shall be for operation on a 120 volt, 60 Hz, 1-phase electrical system. When specified (see 5.2), units procured for Germany shall have a refrigeration unit for operation on a 220 volt/ 50 Hz electrical system, and units procured for the United Kingdom shall have a refrigeration unit for operation on a 240 volt/ 50 Hz electrical system. Maximum wattage for types 1 and 3 shall be 1080 watts and 1275 watts for types 2 and 4.

2.2 Codes and standards. The refrigerated base shall comply with Underwriters Laboratories Inc. Standard No. 471 and National Sanitation Foundation Standard No. 7.

2.3 Identification marking (Government unique requirements, see 5.4). Each refrigerated base shall have the manufacturer's name, contract number, and national stock number embossed or engraved on the exterior surface of the refrigerated base. Use of "stick-on" or removable labels is prohibited.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the currentversion before use.

3.2 End item examination. The contractor is responsible for assuring that the product offered conforms to the stated requirements. Sampling inspection shall be in accordance with MIL-STD-105. The inspection level shall be II and the AQL shall be 4.0. The sample unit shall be one complete end item. The defects are as follows:

Any missing component
Not fabricated of materials specified
Not constructed as specified
Any burr, sliver, sharp edge, rough die, tool, gauge, trim, or grind marks
Any component fractured, bent, buckled, dented, punctured, or malformed
Fastening devices missing
Welding not smooth and free of cracks, burn holes, or undercuts
Legs not adjustable
Refrigeration unit not of size specified

3.3 End item testing. One refrigerated base from the production lot shall be tested as specified below. Any test failure shall be cause for rejection of the lot.

3.3.1 Load test. The refrigerated base shall support a 500 pound load evenly distributed over the complete top for a period of 8 hours. Any permament deformation, breakage, or looseness of parts shall constitute failure of this test.

3.3.2 Refrigerant leakage test. With the refrigeration system "OFF", the complete refrigeration system shall be tested for leaks with an electronic leak detector. If any leaks are found it shall constitute failure of this test.

3.3.3 Operational test. The refrigerated base shall be placed in an ambient of 90°F with relative humidity between 75 percent and 85 percent. Temperature sensing devices in the interior of the refrigerated base shall be located in each drawer to provide data on average temperature. The refrigeration unit shall be placed into operation to reduce the average interior temperature to 38°F. At this point, the refrigeration unit shall continue to be operated for a period of 2 hours to determine if an average interior temperature of 38°F $\pm$ 2°F can be maintained. During the 2 hours, the average interior temperature shall be checked every 10 minutes and if the temperature of 38°F $\pm$ 2°F cannot be maintained, it shall constitute failure of this test. Also, if during the 2 hour test any condensation forms on the exterior of the refrigerated base, this will constitute failure of the test (see 2.1.1).

3.4 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the currentversion before use.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

3.5 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or as specified (see 5.2).

4.2 Commercial packaging and packing. Each base shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Marking. Marking of unit pack, shipping container, and unit load shall be in accordance with ASTM D 3951.

5. NOTES

5.1 Intended use. The drawer-type refrigerated bases covered by this commercial item description are intended for use in kitchens to store cold food under sandwich make-up stations or under griddle areas.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.1).
c. Type electrical requirements (see 2.1.2).
d. Type of packaging and packing required (see 4.1)

5.3 Sources of documents.

5.3.1 Sources of nongoverment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the currentversion before use.

UL Standard No. 471 - Commercial Refrigerators and Freezers, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

NSF Standard No. 7 - Food Service Refrigerators and Storage Freezers, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 82, 50
DLA- GS

User activities:

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

(Project 4110-0434)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.