INCH-POUND

A-A-52058
January 19, 1990

COMMERCIAL ITEM DESCRIPTION

OVEN, WARMING, FOOD, PASS-THROUGH, ELECTRIC


The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1. Classficiation. This commerical item description covers two types of food warming cabinets as follows (see 5.2):

Type I - Two compartment
Type II - Five compartment

1.2. Part identification number. The part identification number shall consist of the commercial item description number and type number as follows:



2. SALIENT CHARACTERISTICS

2.1 Design and construction.

2.1.1 Type I. The type I food warming cabinet shall include two side by side electrically heated pass-through compartments. Maximum overall dimensions shall

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

be 56 inches wide, 34 inches deep, and 29 inches high. The cabinet exterior and interior shall be fabricated of minimum 20 gauge, 300 series of ASTM A 167 type stainless steel. The space between the exterior and interior surfaces shall be insulated. The insulation shall be such that with the internal temperature of the cabinet at 200°F, the average temperature of the exterior surface shall not exceed the ambient temperature by more than 30°F. Each of the two compartments shall be sized to accommodate eight 12 inches x 20 inches x 4 inches deep pans. Compartment doors shall consist of two vertical halves which open and close simultaneously. The cabinet shall be equipped with an ON-OFF switch, indicator lights, thermostat, NSF approved 6 inch legs, and sheath type strip heaters to provide a heat range of 100°F to 300°F. Sheath type strip heaters shall be removable for inspection and maintenance. All other electrical and mechanical components shall be accessible for maintenance and service from the front or back of the cabinet without the necessity to remove the cabinet from its location or an enclosed installation.

2.1.2 Type II. The type II food warming cabinet shall include five vertically arranged electrically heated pass-through compartments. Maximum overall dimensions shall be 20 inches wide, 29 inches deep, and 74 inches high. The cabinet exterior and interior shall be fabricated of minimum 20 gauge, 300 series of ASTM A 167 type stainless steel. The space between the exterior and interior surfaces shall be insulated. The insulation shall be such that with the internal temperature of the cabinet at 200°F, the average temperature of the exterior surface shall not exceed the ambient temperature by more than 30°F. Each of the five pass-through compartments shall be sized to accommodate three 12 inches x 20 inches x 2 inches deep pans. Compartment doors shall be hinged on the bottom and shall be equipped with a built-in stop to hold the door in a horizontal position to act as a shelf when open. The doors shall be constructed and fastened so as not to separate from the compartment walls when used to support a 50 pound load during repeated use cycles (see 3.3.4). The cabinet shall be equipped with an ON-OFF switch, indicator lights, thermostat, NSF approved 6 inch legs, and sheath type strip heaters to provide a heat range of 100°F to 300°F. Heating elements shall be accessible for inspection and maintenance. Sheath type strip heaters shall be removable for inspection and maintenance. All other electrical and mechanical components shall be accessible for maintenance and service from the front or back of the cabinet without the necessity to remove the cabinet from its location or an enclosed installation.

2.2 Electrical requirements. Unless otherwise specified the food warming cabinet shall be for operation on 208 volts, 60 Hz, 1-phase electrical system, and shall be provided with a 6 foot three-wire cord. When specified (see 5.2), units procured for Germany shall operate on a 220 volt/50 Hz electrical system, and units procured for the United Kingdom unit shall operate on a 240 volt/50 Hz electrical system. Maximum wattage for both type I and type II shall be 3000 watts.

2.3 Codes and standards. The food warming cabinets shall comply with Underwriters Laboratories Inc. Standard No. 197 and National Sanitation Foundation Standard Nos. 2 and 4. Satisfactory evidence that these requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

have been met shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 3.4).

2.4 Identification marking (Government unique requirements, see 5.4). Each food warming cabinet shall have the manufacturer's name, contract number, and national stock number embossed or engraved on the exterior surface of the cabinet. Use of "stick-on" or removable labels is prohibited.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 End item examination. The contractor is responsible for ensuring that the product conforms to the stated requirements. Sampling inspection shall be in accordance with MIL-STD-105. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 4.0. The sample unit shall be one complete end item. The defects are as follows:

Any component missing
Not fabricated of materials specified
Not constructed as specified
Any burr, sliver, sharp edge, rough die, tool, gauge, trim, or grind marks
Any component fractured, bent, buckled, dented, punctured, or malformed
Fastening devices missing
Welding not smooth and free of cracks, burn holes, or undercuts
Manufacturer's identification marking missing or incomplete
Heating elements not accessible

3.3 End item testing. One food warming cabinet from the production lot shall be tested as specified below. Any test failure shall be cause for rejection of the lot.

3.3.1 Functional test. The food warming cabinet shall be operated as required by the manufacturer's manual to verify that all electrical and mechanical components function as specified.

3.3.2 Performance test. In a minimum ambient temperature of 80°F and with the temperature control set to 200°F, the cabinet shall be operated for 10 hours. When the internal temperature reaches the control setting, temperature readings shall be recorded every 15 minutes. Failure of the cabinet to maintain conditions within 10°F of the 200°F control setting over any period of 2 hours shall constitute failure of this test. During the 200°F test, the temperature

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

of each exterior surface shall be taken at three widely separated points at 30-minute intervals to insure that the average exterior surface temperature does not exceed 30°F above the ambient temperature. If any exterior surface's average temperature exceeds 30°F above the ambient, it shall constitute a failure of the test.

3.3.3 Electrical usage test. During the performance test in 3.3.2, readings shall be taken every 30 minutes to determine the watts used, and if the wattage exceeds 3000 watts for either type I or type II, it shall constitute failure of the test.

3.3.4 Type II door load test. A door in the open position shall be loaded with 50 pounds evenly distributed for a period of 8 hours. Any permanent deformation, breakage, or looseness of parts of parts of the door, hinges, or cabinet shall constitute failure of the test.

3.4 Certification compliance examination. Certifications, certified test reports or listing marks for standards, submitted in accordance with 2.3 shall be examined and validated as proof of compliance. Prior to Government approval of first shipment the contractor shall submit to the contracting officer or his authorized representative for approval certification that the cabinets he proposes to furnish meet the applicable requirements of UL and NSF as follows:

3.4.1 UL. Acceptable evidence of meeting the requirements of UL shall be the UL listing mark, or a certified test report from a recognized independent testing laboratory acceptable to the Government, indicating that the cabinets offered have been tested and conform to UL Standard No. 197.

3.4.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished cabinet, or

(2) A certification for the cabinet issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report acceptable to the contracting officer with the advice of the Army Surgeon General from an independent testing laboratory, indicating the cabinets have been tested and conform to the specified NSF Standards.

3.5 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

3.6 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or as specified (see 5.2).

4.2 Commercial packaging and packing. Each cabinet shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Marking. Marking of unit pack, shipping container, and unit load shall be in accordance with ASTM D 3951.

5. NOTES

5.1 Intended use. The cabinet is intended for use in kitchens to keep food warm prior to serving.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.1).
c. Type of electrical requirements (see 2.2)
d. Type of packaging and packing required (see 4.1)

5.3 Sources of documents.

5.3.1 Sources of nongoverment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, and ASTM A 167 - Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip, are available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

UL Standard No. 197 - Commercial Electric Cooking Appliances, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

NSF Standard No. 4 - Commercial Cooking and Hot Food Holding Equipment and Standard No. 2 - Food Service Equipment, are available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 84, 50
DLA- GS

User activities:

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

(Project 7310-0773)

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:05Z
Check the source to verify that this is the currentversion before use.