INCH-POUND

A-A-52059
January 19, 1990

COMMERCIAL ITEM DESCRIPTION

DISPENSER, BEVERAGE, MECHANICALLY COOLED, ICE/CARBONATED DRINK, COUNTERTOP

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers a countertop dispenser for ice and carbonated drinks as specified.

1.2 Part identification number (pin). The part identification number shall consist of the commercial item description number A-A-52059.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The dispenser shall have maximum overall dimensions of 37 inches high, 30 inches wide, and 30 inches deep. The dispenser cabinet shall be fabricated of 300 series stainless steel or shall be one piece rotationally molded polyethylene. The ice storage bin shall have a minimum ice storage capacity of 90 pounds. The storage bin shall be insulated. The storage bin shall have an easily removale cover for manual loading of the ice. The storage bin shall be provided with a safety device to stop the ice bin auger from operating when the bin cover is open. The storage bin shall be provided with a minimum 1-inch diameter drain. The front of the cabinet shall be equipped with six electric post-mix dispensing valves and one ice dispensing valve. When specified (see 5.2) for army use, one of the dispensing valves shall be capable of dispensing chilled drinking water. A removable drain pan and perforated tray shall be provided under the dispensing valves. The drain

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:05Z
Check the source to verify that this is the current version before use.

pan shall be removable without any special tools and shall have a drain hole capable of being left open or closed. National Sanitation Foudation, approved, 6-inch adjustable legs shall be provided. The dispenser shall be equipped with an integral ice-waterbath or cold plate beverage cooling system and shall have a capacity of 600, 6-once, 40°F drinks per hour.

2.2 Electrical requirements. Unless otherwise specified the dispenser shall be for operation on a 120 volt, 60 hertz, 1-phase electrical system. When specified (see 5.2), units procured for Germany shall operate on a 220 volt/ 50 Hz electrical system, and units procured for the United Kindgom unit shall operate on a 240 volt/ 50 Hz electrical system.

2.3 Codes and standards. The dispenser shall comply with Underwriters Laboratories Inc. Standard No. 471 and National Sanitation Foundation Standard No. 18.

2.4 Identification marking (Government unique requirements, see 5.4). Each dispenser shall have the manufacturer's name, contract number, and national stock number embossed or engraved on the outer housing of the dispenser. Use of "stick-on" or removable labels is prohibited.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 End item examination. The contractor is responsible for ensuring that the product conforms to the stated requirements. Sampling inspection shall be in accordance with MIL-STD-105. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units shall be 4.0. The sample unit shall be one complete end item. The defects are as follows:

Any component missing
Not fabricated of materials specified
Not constructed as specified
Any burr, sliver, sharp edge, rough die, tool, gauge, trim, or grind marks
Any component fractured, bent, buckled, dented, punctured, or malformed
Fastening devices missing
Welding not smooth and free of cracks, burn holes, or undercuts

3.3 End item testing. One dispenser from the production lot shall be tested as specified below. Any test failure shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:05Z
Check the source to verify that this is the current version before use.

3.3.1 Ice storage bin capacity test. Weigh out 90 pounds of ice (cube, cubelet, chunklets, or nuggets; not flaked or crushed ice) and then manually load the storage bin with the ice. If all 90 pounds of the ice cannot fit into the storage bin, it shall constitute failure of this test.

3.3.2 Drink capacity test. The dispenser shall be readied for operation and with product, water, and ambient temperature at 75°F, the test shall begin. Dispense ten 6-ounce drinks per minute for 1 hour. Every 10 minutes, check to determine if the temperature of the drink is 40°F or lower. If any drink is above 40°F, it shall constitute failure of this test.

3.4 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

3.5 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or as specified (see 4.2).

4.2 Commercial packaging and packing. Each dispenser shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Marking. Marking of unit pack, shipping container, and unit load shall be in accordance with ASTM D 3951.

5. NOTES

5.1 Intended use. The dispenser is intended for use in the serving line of military dining facilities to dispense ice and soft drinks.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When chilled water dispensing valve is required (see 2.1).
c. Type of electrical requirements required (see 2.2).
d. Type of packaging and packing required (see 3.1)

5.3 Sources of documents.

5.3.1 Sources of nongoverment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

UL Standard No. 471 - Commercial Refrigerators and Freezers, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

NSF Standard No. 18 - Manual Food and Beverage Dispensing Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Navy - SH
Air Force - 84, 50
DLA- GS

User activities:

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

(Project 7310-0774)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.