INCH-POUND

A-A-52062
January 31, 1990

COMMERCIAL ITEM DESCRIPTION

TABLE, FOOD PREPARATION, WITH SINK

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers two types of tables as follows (see 5.2):

Type 1 - Right hand sink
Type 2 - Left hand sink

1.2 Part identification number (PIN). The part identification number shall consist of the commercial item description number and the type number as follows:

A-A-52062 - 1
- 1 — Type
- A-A-52062 — CID number

2. SALIENT CHARACTERISTICS

2.1 Design and construction.

2.1.1 Table. The table shall be 72 inches long ± 1 inch, 30 inches wide ± 1/2 inch, and 35 inches high ± 1 inch when bullet feet are in fully retracted position. The undershelf shall be located 9 to 13 inches from the floor and fabricated of 300 series stainless steel; the thickness shall be 16 gauge (minimum) with 1-1/2 inch (minimum) turned down edges. The undershelf shall be

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

adjustable and removable for shipping. The undershelf shall have three holes of such size and spacing to accommodate two 1/2 inch diameter water supply lines (hot and cold water) leading to the sink mounted combination valve and spout. One 1-1/2 inch diameter waste line shall be die stamped in the undershelf in proper alignment with the installed sink. The tabletop shall be fabricated of 300 stainless steel with a thickness of 14 gauge (minimum) and turned down no drip edges. The tabletop shall have a 4 inch (minimum) turned up backsplash with turned back edges. The tabletop and undershelf shall be polished to a number 3 finish or better and shall be reinforced with 14 gauge (minimum) corrosion resistant steel structural members secured to the underside to ensure a level sound deadened working surface. Tables shall be designed to receive attachments to support an overhead utensil rack. Table legs shall be a minimum of 1-5/8 inch diameter, 16 gauge (minimum) 300 series stainless steel tubing and shall be equipped with 1 inch adjustable stainless steel bullet feet. Legs shall be capable of being disassembled for ease of shipping. Tables shall be equipped with six legs. Leg brace tubing shall be minimum 1-1/2 inch outer diameter O.D. stainless steel. Fasteners shall be fabricated from stainless steel.

2.1.2 Sink. The sink shall be 19 inches long ± 1 inch, 15 inches wide ± 1 inch, and 8 inches deep ± 1 inch. The sink shall be fabricated of 14 gauge (minimum) 300 series stainless steel and shall be assembled to the tabletop with a continuous weld. The sink shall be polished smooth to a number 3 finish or better. The sink shall be located 5 inches from the specified side and shall have coved corners. The sink shall be equipped with a splash mounted gooseneck faucet with a 3-1/2 inch basket strainer and drain with a lever type shutoff and shall have a 1-1/2 inch diameter tail pipe, 3-1/2 inches long. The sink faucet shall be equipped with lever type handles. The underside shall be fabricated in such a manner to deaden the sound.

2.1.3 Load and lateral force requirements. The table with sink shall support a 400 pound load when tested in accordance with 3.4.1. The table with sink shall be capable of resisting a static force of 100 pounds when tested in accordance with 3.4.2.

2.2 Codes and standards. Tables shall conform with requirements of National Sanitation Foundation (NSF) Standard No. 2.

2.3 Identification marking (Government unique requirements, see 5.4). Each table shall have the manufacturer's name, contract number, and national stock number embossed or engraved on the under side of the tabletop. Use of "stick-on" or removable labels is prohibited.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be one of the following:

(a) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished table.

(b) A certification for the table issued by NSF under their special one-time contract evaluation/certification service.

(c) A certified test report from a recognized independent testing laboratory, acceptable to the Government agency for which the table is being procured, that the table has been tested and conforms to NSF Standard No. 2.

3.3 End item examination. The contractor is responsible for assuring that the product conforms to the stated requirements. Sampling inspection shall be in accordance with MIL-STD-105. The inspection level shall be II and the AQL shall be 4.0. The lot size shall be expressed in units of tables. The sample unit shall be one complete table. The defects are as follows:

Not finished as specified
Any component missing
Any burr, sliver, sharp edge, rough die, tool, gauge, trim, or grind marks
Not fabricated of materials specified
Not constructed as specified
Any component fractured, bent, buckled, dented, punctured, or malformed
Bullet feet not adjustable
Fastening devices missing
Welding not smooth and free of cracks, burn holes, or undercuts
Manufacturer's identification marking missing or incomplete
Faucet and drain not as specified

3.4 End item testing. One table from the production lot shall be tested as specified below. Any test failure shall be cause for rejection of the lot.

3.4.1 Load test. The table with sink shall support a load as shown in figure 1, evenly distributed over a 2 foot by 2 foot portion of the tabletop mid-section for a period of 8 hours. Any permanent deformation, breakage, or looseness of parts shall constitute failure of the test.

3.4.2 Lateral force test. The table with sink shall be capable of resisting a static force centrally applied as shown in figure 2 for five cycles in the direction indicated. Any deformation, breakage, or looseness of parts shall constitute failure of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

3.4.3 Leakage test. With drain shut, the sink shall be filled with water to the overflow level and allowed to stand for 1 hour. Any leakage from the sink shall constitute failure of the test.

3.5 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

3.6 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or as specified (see 5.2).

4.2 Commercial packaging and packing. Each table shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Marking. Marking of unit pack, shipping container, and unit load shall be in accordance with ASTM D 3951.

5. NOTES

5.1 Intended use. The table covered by this commercial item description is intended for use in kitchens for the preparation of food.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.1).
c. Type of packaging and packing required (see 4.1)

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

5.3.1 Sources of nongoverment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

NSF Standard No. 2 - Food Service Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 84, 50
DLA- GS

User activities:

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

(Project 7320-0860)

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the currenversion before use.