INCH-POUND

A-A-52063
February 6, 1990

COMMERCIAL ITEM DESCRIPTION

GRIDDLE, WITH OVERHEAD BROILER, ELECTRIC

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers an electric griddle with overhead broiler.

1.2 Part identification number (PIN). The part identification number shall consist of the commercial item description number, A-A-52063.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The griddle with broiler shall consist essentially of two cooking sources: a griddle and an overhead quartz broiler.

2.1.1 Griddle. The griddle section shall consist of a griddle top supported by a wraparound stainless steel body that houses the heating elements, thermostats, and grease drawer with 4 inch adjustable tubular stainless steel legs. The griddle surface shall be a minimum of 800 square inches with a nominal length of 36 inches. The griddle surface top shall have a grease trough which shall enable the grease to drain into the grease drawer. The grease drawer shall be constructed in such a manner to prevent overflow and shall have a handle to facilitate removal. The griddle surface shall be steel, highly polished, 1 inch thick $\pm$ 1/16 inch. The off/on switch and control knobs shall be mounted on the front of the griddle frame. The griddle temperature shall be controlled by three individual thermostats. The thermostat dials shall be graduated in intervals of 25°F and shall have a minimum operating range of 175°F to 450°F. The grill shall be equipped with a splash guard at the sides and back of the griddle surface. The splash guard shall be at least 3 inches high.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

2.1.2 Broiler. The overhead broiler shall be located at the left side of the griddle surface and shall be 24 inches wide. The broiler shall be housed in a hood and shall be equipped with six 1000-watt quartz heaters. When the hood is in the raised position, the broiler shall be off. When the hood is lowered, the quartz broiler shall be activated. The housing for the broiler shall be stainless steel.

2.2 Electrical requirements. The complete unit shall operate on a 208-volt, 60-hertz, 3-phase electrical system, and shall be provided with a 6-foot three-wire cord. When specified (see 5.2), units procured for Germany shall operate on a 220-volt/50-hertz electrical system, and units procured for the United Kingdom unit shall operate on a 240-volt/50-hertz electrical system. Power consumption shall be a minimum of 16,000 watts and a maximum of 24,000 watts.

2.3 Codes and standards. The grill with overhead broiler shall comply with Underwriters Laboratories Inc. Standard No. 197 and National Sanitation Foundation Standard No. 4.

2.4 Data name plate (Government unique requirement, see 4.4). The griddle shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying; (b) Identification tags; (c) Information not required and (d) Optional marking information shall not apply. The data plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the griddle by rivets, screws, or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified, see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the griddle.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be one of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished griddle with broiler.

(2) A certification for the griddle and broiler issued by NSF under their special one-time contract evaluation/certification service.

(3) A certified test report from a recognized independent testing laboratory acceptable to the Government agency for which the griddle and broiler are being procured that the griddle and broiler have been tested and conform to NSF Standard No. 4.

3.3 UL. Acceptable evidence of meeting the applicable requirements of UL 197 shall be the UL listing mark or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the griddle and broiler offered conform to the applicable requirements of UL 197.

3.4 End item examination. The contractor is responsible for assuring that the product offered conforms to the stated requirements. Sampling inspection shall be in accordance with MIL-STD-105. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0. The lot size shall be expressed in units of griddles. The sample unit shall be one complete griddle. The defects are as follows:

Any missing component
Any burr, sliver, sharp edge, rough die, tool, gauge, trim, or grind marks
Not constructed as specified
Not fabricated of materials specified
Any component fractured, bent, buckled, dented, punctured, or malformed
Fastening devices missing
Welding not smooth and free of cracks, burn holes, or undercuts
Manufacturer's identification marking missing or incomplete
Controls not accessible from the front
Switches and controls not provided
Thermostat dials not graduated
Grease trough not provided
Grease pan not provided
Legs not adjustable

3.5 End item testing. One griddle with broiler from the production lot shall be tested as specified below. Any failure shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

3.5.1 Load test. The griddle surface shall be uniformly loaded with 25 pounds per square foot for 15 minutes. Inability of the unit to support this load shall be cause for rejection.

3.5.2 Thermostat test. The thermostat shall be tested for accuracy within limits specified by the manufacturer. Failure of the unit to function within those limits is cause for rejection.

3.6 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

3.7 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or as specified (see 4.2).

4.2 Commercial packaging and packing. Each griddle shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Marking. Marking of unit pack, shipping container, and unit load shall be in accordance with ASTM D 3951.

5. NOTES

5.1 Intended use. The griddle covered by this commercial item description is intended for use in kitchens to simultaneously grill and broil various foods.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type of electrical requirements (see 2.2).
c. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.4).
d. Type of packaging and packing required (see 4.1).

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:05Z
Check the source to verify that this is the current version before use.

5.3 Sources of documents.

5.3.1 Sources of nongoverment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103
UL Standard No. 197 - Commercial Electric Cooking Appliances, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

NSF Standard No. 4 - Commercial Cooking and Hot Food Holding Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:05Z
Check the source to verify that this is the currenversion before use.