INCH-POUND

A-A-52064
February 6, 1990

COMMERCIAL ITEM DESCRIPTION

RANGE, ELECTRIC, TWO BURNER

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers two types of ranges as follows (see 5.2):

Type I - Modular
Type II - Freestanding

1.2 Part identification number (PIN). The part identification number shall consist of the commercial item description number and the type number as follows:

A-A-52064 - I
Type
CID number

2. SALIENT CHARACTERISTICS

2.1 Design and construction.

2.1.1 Type I ranges. Type I ranges shall be designed so as to mount on an accessory stand or for counter installation, as specified (see 5.2). Ranges shall have 300 series stainless steel fronts, sides, and backs. The range shall be 13 inches wide (maximum) by 39 inches deep (maximum) by 20 inches high

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

(maximum). Ranges shall be provided with a 3 inches (minimum) high stainless steel back splash and a grease trough running lengthwise across the front. The range shall be equipped with a grease chute permitting the grease to drain into a grease drawer located under the cooking surface. The range top shall consist of two round cast hot plates (9 inch nominal diameter) each controlled by infinite heat switches and front mounted dials. The hot plates shall operate within a temperature range of 800°F to 950°F. An indicator light shall show when each heating element is energized.

2.1.2 Type II ranges. Type II ranges shall be constructed as in 2.1.1 except the range shall be contained in a freestanding body with an overall height (measured to the cooking surface) of 30 inches to 32 inches exclusive of 6 inch stainless steel tubular adjustable legs.

2.2 Electrical requirements. Unless otherwise specified, the range shall operate on a 208/240-volt, 60-hertz, 3-phase electrical system, and shall be provided with a 6-foot three-wire cord. When specified (see 5.2), units procured for Germany shall operate on a 220-volt/50-hertz electrical system, and units procured for the United Kingdom unit shall operate on a 240-volt/50-hertz electrical system. Maximum wattage for both type I and type II shall be 4000 watts.

2.3 Codes and standards. Ranges shall conform to Underwriters Laboratories Inc. Standard No. 197 and National Sanitation Foundation Standard No. 4.

2.4 Data name plate (Government unique requirement, see 5.4). The range shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying; (b) Identification tags; (c) Information not required and (d) Optional marking information shall not apply. The data plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the range by rivets, screws, or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified, see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the range.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be one of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished range.

(2) A certification for the range issued by NSF under their special one-time contract evaluation/certification service.

(3) A certified test report from a recognized independent testing laboratory acceptable to the Government agency for which the electric range is being procured that the range has been tested and conforms to NSF Standard No. 4.

3.3 UL. Acceptable evidence of meeting the applicable requirements of UL 197 shall be the UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the range offered conforms to the applicable requirements of UL 197.

3.4 End item examination. The contractor is responsible for assuring that the product offered conforms to the stated requirements. Sampling inspection shall be in accordance with MIL-STD-105. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0. The lot size shall be expressed in units of ranges. The sample unit shall be one complete range. The defects are as follows:

Any missing component
Any burr, sliver, sharp edge, rough die, tool, gauge, trim, or grind marks
Not constructed as specified
Not fabricated of materials specified
Any component fractured, bent, buckled, dented, punctured, or malformed
Fastening devices missing
Welding not smooth and free of cracks, burn holes, or undercuts
Manufacturer's identification marking missing or incomplete
Controls not accessible from the front
Switches and controls not provided
Thermostat dials not graduated
Grease trough not provided

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

Grease drawer not provided
Legs not adjustable

3.5 End item testing. One range from the production lot shall be tested as specified below. Any failure shall be cause for rejection of the lot.

3.5.1 Heat-time test. The manufacturer shall demonstrate that the range hot plates shall reach a temperature of 800°F to 950°F in a maximum of 30 minutes. Failure shall constitute cause for rejection.

3.5.2 Dials and switches. Controls shall be checked for operation. Any failure or malfunction shall be cause for rejection.

3.6 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

3.7 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or as specified (see 5.2).

4.2 Commercial packaging and packing. Each range shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Marking. Marking of unit pack, shipping container, and unit load shall be in accordance with ASTM D 3951.

5. NOTES

5.1 Intended use. The ranges covered by this commercial item description are intended for use in kitchens for top surface cooking.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.1).
c. Whether type I ranges are to mount on an accessory stand or are for counter installation (see 2.1.1).
d. Type of electrical requirements (see 2.2).
e. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.4).
f. Type of packaging and packing required (see 4.1).

5.3 Sources of documents.

5.3.1 Sources of nongoverment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

UL Standard No. 197 - Commercial Electric Cooking Appliances, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

NSF Standard No. 4 - Commercial Cooking and Hot Food Holding Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:05Z
Check the source to verify that this is the current version before use.

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 84, 50
DLA- GS

User activities:

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

(Project 7310-0776)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.