INCH-POUND

A-A-52066
February 15 1990

COMMERCIAL ITEM DESCRIPTION

RACK, DISPENSING, CAN

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers can dispensing racks.

1.2 Part identification number (PIN). The PIN shall consist of the commercial item description number as follows A-A-52066.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The can dispensing rack shall be of welded aluminum angle or tubular construction. Can dispensing racks shall have either cross bracing or reinforced corners to insure rigidity. Can dispensing racks shall be 47 inches deep (maximum) by 37 inches wide (maximum) by 89 inches high (maximum) and shall hold a minimum of 150 No. 10 cylindrical cans or 30 cases (minimum) when tested as specified in 2.4.1. Cans shall rest between angle guides, be unloaded from the front, and shall be gravity fed. Can dispensing racks shall be mounted on feet designed for the purpose. Can guides should have a minimum [illegible] of 1 inch.

2.2 Codes and standards. The can dispensing rack shall comply with National Sanitation Foundation Standard No. 2.

2.3 Data name plate (Government unique requirement, see 5.4). The can dispensing rack shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Method of applying; (b) Identification tags; (c) Information not required, and (d)

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge corrosion resisting metal and attached to the can dispensing rack by rivets, screws, or by welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Date
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified, see [illegible])

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the can dispensing rack.

5. QUALITY ASSURANCE

5.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 NSF. Acceptable evidence of meeting the requirements of NSF Standard No. 2 shall be one of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished can dispensing rack, or

(2) A certification for the can dispensing rack issued by NSF under their special one-time contract evaluation certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the government agency for which the can dispensing rack is being procured indicating that the can dispensing rack has been tested and conforms to NSF Standard No. 2.

3.3 End item examination. The contractor is responsible for assuring that the product conforms to the stated requirements. Sampling inspection shall be in accordance with MIL-STD-105. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0. The sample unit shall be one complete can dispensing rack. The defects are as follows:

Any burr, sliver, sharp edge, rough die, tool, gauge, trim, or grind marks
Not constructed as specified
Not fabricated of materials specified
Any component fractured, bent, buckled, dented, punctured, or malformed
Fastening devices missing
Welding not smooth and free of cracks, burn holes, or undercuts
Manufacturer's identification marking missing or incomplete

3.4 [illegible] testing. One can dispensing rack from the production lot shall be tested as specified below.

3.4.1 Loaded rack test. The can dispensing racks shall be loaded with [illegible] No. 10 cans filled to capacity with water and allowed to remain in a static condition for 8 hours. At the end of 8 hours, the racks shall be examined for any structural defects. Cans shall be capable of being removed easily from each row of the can dispensing rack without binding at the end of the 8 hour period. Any structural deficiencies or inability of the cans to be removed easily shall be cause for rejection of the lot.

3.5 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376 and all other requirements of this CID are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

3.6 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging and packing. Packaging and marking shall be commercial or as specified (see 6.2).

4.2 Commercial packaging and packing. Each can dispensing rack shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Marking. Marking of unit packs, shipping containers, and unit loads shall be in accordance with ASTM D 3951.

5. NOTES

5.1 Intended use. The can dispensing rack covered by this commercial item description is intended for use in kitchens to store and dispense canned foods.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.3).
c. Type of packaging and packing required (see 4.1)

5.3 Sources of documents.

5.3.1 Sources of nongovernment information documents

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

NSF Standard No. 2 - Food Service Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 84
DLA- GS

User activities:

Army - C
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

(Project 7920-0859)