INCH-POUND
A-A-52070B
21 April 2017
SUPERSEDING
A-A-52070A
19 August 2003

COMMERCIAL ITEM DESCRIPTION

CORD, PLUMB BOB

The General Services Administration has authorized the use of this Commercial Item Description in preference to MIL-F-14052.

1. SCOPE. This Commercial item Description (CID) is in preference to MIL-C-43258.

2. SALIENT CHARACTERISTICS

2.1 Description. The braided cord shall be fabricated from nylon, polyester, or flax fibers to meet the physical properties specified in table I. If fabricated from flax fibers, the cord shall have a hard polished, smooth dressed finish. The cord shall be natural white or orange in color.

TABLE I. Physical requirements for braided plumb bob cord.

Characteristics	Requirements	Test methods
Number of individual strands (carriers)	8	Visual
Direction of individual strand twists	4 strands “S” twist 4 strands “Z twists	Visual Visual
Diameter, inch (min.)	.046 (3/64)	6002 1/
Length per pound, feet (min.)	1,350	6004 1/
Breaking strength, pounds (min.)	36	6005 1/

1/ FED-STD-191 test method

2.2 Put-up. The cord shall be furnished without knots or splices in 25 ± l yard lengths and shall be put up on pressed wood fiberboard (tempered cardboard), plastic, or wood surveyor’s blocks (winders) measuring approximately 2.375 (2-3/8) by 4.750 (4-3/4) inches overall. Each length of cord shall be continuous throughout, shall contain no loose ends and shall be wound so that each turn and layer is free from entanglement.

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support – Industrial Hardware Division (ATTN: Code FHTE), 700 Robbins Avenue, Philadelphia, PA 19111-5096 or email trpsptspecspa@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Quality conformance .inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-1916.

3.3 Visual examination. Each lot of fiber rope assemblies shall be inspected in accordance with MIL-STD-1916, inspection level II. The assemblies shall be examined for consumer type defects, as follows:

End cut, chafing, or damaged; broken or loose end or strand; unevenly braided resulting in open place, break in continuity of braid, or soft spot; finish other than specified; color other than specified; not put-up as specified.

The lot size shall be expressed in units of blocks (winders), and the sample unit shall be one block (winder). The inspection level shall be II.

3.4 Dimensional examination. The finished cord shall be measured for the dimensions specified in table I. The lot size shall be expressed in units of blocks (winders), and the sample unit be one block (winder). The inspection level shall be S-3.

4.1 PACKAGING.

4.1 Packaging. Forty-eight blocks (winders) of cord shall be unit packed in a snug fitting fiberboard box conforming to style RSC, type CF, class domestic, grade 275 of ASTMD1974/D1974M and ASTM-D5118/D5118M. The approximate inside dimensions of the box shall be 14.500 (14-1/2) inches in length, 9.500 (9-1/2) inches in width, and 7.500 (7-1/2) inches in depth. Approximate dimensions shall be furnished as a guide only.

4.2 Packing. One hundred ninety-two blocks (winders) of cord, unit packed as specified, shall be packed in a snug fitting RSC style corrugated fiberboard shipping container. The approximate inside dimensions of the shipping container shall be 19.000 inches in length, 15.000 inches in width and 15.000 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with ASTM-D1974/D1974M, Section 6, Methods of Box Closure, para. 6,2, Closure Methods for Regular Slotted Containers.

4.3 Palletization. When specified (see 5.2) plumb bob cord, packed as specified, shall be palletized on a 4-way entry pallet in accordance with load type 1a of MIL-STD-147. Each prepared load shall be loaded by means C and D, or F and C, and pallet pattern shall be number 4 in accordance with MIL-STD-147.

4.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

5. NOTES

5.1 Intended use. The cord is intended for plumb bob use on surveying equipment.

5.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document
b. When palletization is required (see 3.3)

5.3 Sources of documents.

5.3.1 Source for Government documents. Copies of this CID or Military and Federal documents are available online at: ASSIST Online (https://assist.dla.mil) or ASSIST Quick Search (http://quicksearch.dla.mil).

5.3.2 Source of Information for nongovernmental document. Copies of ASTM-D1974/D1974M, Fiberboard Boxes, Methods of Closing, Sealing, and Reinforcing and ASTM D5118/D5118M, Standard Practice for Fabrication of Fiberboard Shipping Boxes, are available from:

ASTM International
100 Barr Harbor Drive
West Conshohocken PA 19428-2959

5.4 Changes from previous issues. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

MILITARY ACTIVITIES:

Custodians:
Army – GL
Navy - MC

Preparing activity:
DLA - IS

(Project 4020-2015-003)

Reviewer:
Army – MD

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.