INCH-POUND

A-A-52076
July 27, 1990

COMMERCIAL ITEM DESCRIPTION

BOOT, INTERMEDIATE COLD/WET

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers one type of boot in whole and half sizes 5 through 14, and in widths B, C, D, EE, and EEE.

2. SALIENT CHARACTERISTICS.

2.1 Description. The boots shall be fully lined, insulated, and waterproof. A size 9D boot shall be 10 ± 1 inches in height, as measured upward on the outside from the tread area of the breast of the heel to the top of the boot. The size 9D boot shall weigh a maximum of 38 ounces. Height and weight shall vary proportionally with size. The top of the boot shall have a 1 inch cushioned collar for comfort, and shall protect against cold from entering from the top of the boot. The upper shall be made from black leather. The seam sealant for the upper in the vamping, backstay, and inseam areas shall be water resistant rubber or synthetic resin adhesive. The inside quarter lining or inside gusset of each boot shall be marked with the correct boot size and width.

2.2 Leather. The upper leather shall be from 5 to 5-1/2 ounces full grain waterproof leather. The leather shall be drum dyed black with a grain surface finish that when scuffed, may be restored to uniformity by simple brushing or application of commercial polish containing silicone.

2.3 Lasts. The lasts shall be Jones & Vining model 1-3048, style 701 or equal (see 5.4), in the sizes and widths as specified (see 5.2).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-ES, Natick, MA 01760-5014.

AMSC N/A FSC 8430

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

2.4 Lining. The boot shall have a waterproof sock consisting of Thinsulate polyolefin/microfiber/polyester staple nonwoven insulation or equal (see 5.5). This shall be sandwiched between a Goretex polytetrafluorethylene film or equal (see 5.6) and thermoplastic adhesive. This shall be laminated to nylon tricot and a quilted nonwoven lining of 100 percent heterofil, point-bonded polyamide fibers. The seam sealing tape shall consist of three layers: tricot knit, microporous polytetrafluorethylene film and thermoplastic adhesive.

2.5 Lacing system. The lacing system shall consist of two to five pairs of corrosion-resistant AA eyelets, and six pairs of solid metal D-rings consisting of rivets, washers, and D-rings with a single top eyelet. The D-rings shall be anodized black or tumble coated with not less than two coats of black enamel. The closure system shall be designed for quick donning and doffing. An open hook closure system shall not be acceptable.

2.6 Laces. The boot laces shall be 72-inch heavy-duty texturized nylon.

2.7 Sole. The vinyl storm welt shall be attached to a 10-iron midsole and a 4-iron rubber midsole prior to the application of the slip-resistant lug sole, style 148 black Kletterlift Vibram sole or equal (see 5.7), and the inside 30 degree bevel breasted spring heel using the Goodyear welt process or stitchdown process. The toe area of the outsole shall be securely stitched.

2.8 Counter. The counter shall be water resistant and designed to fit the curvature of the last.

2.9 Insole. A Poron 4000 insole or equal shall be used (see 5.8).

2.10 Shank. The shank shall be 5/8-inch wide double rib 19 gage steel.

2.11 Boxtoe. The boxtoe shall conform to the boxtoe requirements of MIL-S-13192 or equal.

2.12 Bottom fill. The bottom fill shall be 1/8-inch closed-cell foam.

2.13 Instruction tag (Government unique requirements). Instruction tags, to be tied to the finished boots, shall be printed on 5-1/4 by 6-1/2 inch tag stock folded in the middle to form 5-1/4 by 3-1/4 inch printed pages in book form. A punch hole shall be made in the top near the folded edge for insertion of the lace. The instruction tags shall be printed using the data specified below (see 5.9).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

A-A-52076

INSTRUCTION TAG

BOOT, INTERMEDIATE COLD/WET

FACTS

These Intermediate Cold/Wet Boots (ICWB) have been designed to protect your feet from cold injury and frost bite in areas where moisture and cold are critical factors, and where the mean monthly temperature ranges between 14 and 68 degrees F. The boots should not be worn where temperatures fall below +10 degrees F. (Note: For temperatures below +10 degrees F, the Boots, Cold Weather, Insulated, Rubber, Black or White, Vapor Barrier boots, should be worn.)

If your feet begin to get cold, button up all your graments and excercise the entire body by swinging the arms, stamping the feet, and rapid movement of the toes.

TRENCH FOOT AND FROSTBITE are serious cold injuries which can cause panful and permanent disability. These injuries can be prevented by proper care of your feet. No boot will keep your feet from freezing in cold/wet conditions if you remain motionless for several hours. Wear the ICWB properly and DO NOT BECOME A COLD WEATHER CASUALTY.

INSTRUCTIONS FOR USE

1. Wear with: 1 pair socks, wool, cushion sole.

2. Sizes. The boots are supplied in whole and half sizes 5 through 14, and in widths B(N), C(NR), D(R), EE(W), and EEE(XW). In some instances it may be necessary to select a slightly larger size than normally worn in order to allow for normal swelling of the feet.

3. Pull on boots, seating heel firmly in place, then lace. Boots should fit snugly but not tightly. There should be approximately 1/2 inch additonal length at toe.

4. Carry extra socks. Change socks often, at least once daily. Remove boots and dry feet as often as possible. Neglect of feet can make you a casualty.

5. When your boots become soiled or dirty, simply brush or wipe them clean with a damp cloth. Let them dry naturally at room temperature (do not dry next to a radiator). Waterproofing is not required, however use of conditioners such as mink oil will help to maintain the natural condition of the leather and extend the service life of the boots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

3.3 End item visual examination. Each lot of boots shall be examined for consumer type defects, defined as follows:

Defects in pairing, design, material, workmanship, and finish.

Any defect shall be scored as major when seriously affecting serviceability or appearance and minor when affecting serviceability or appearance but not seriously. The lot size shall be expressed in units of boots. The sample unit shall be one completely fabricated boot and the selection shall be by pairs. The inspection level shall be II, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

3.4 Sock lining test. Each sock shall be tested, before insertion into the boot, for waterpermeability as follows:

a. Inflate the sock with air to 1.0 pounds per square inch gauge static air pressure (measured inside the sock) and clamp the top of the sock to seal from air leakage.

b. Submerge inflated sock in a water bath such that the toe of the sock is at least 5 inches below the water surface for 2 seconds. Remove from bath and wipe entire sock surface with hand.

c. Re-submerge inflated sock to the same position for at least 15 seconds.

d. While submerged, the sock shall be inspected for air leakage at any single location on the exterior of the sock. Failure shall result upon the detection of an air bubble more than once every 7 seconds.

4. PACKAGING

4.1 Packaging. Each pair of boots shall be packaged in a fiberboard shoe box.

4.2 Packing. Six pairs of boots shall be packed in a fiberboard box conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

4.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G.

4.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The boots are intended for wear by Military Personnel in wet-cold climates down to -10°F.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Size and width required (see 1.1).
c. When palletization is required (see 4.3).

5.3 Sources of documents.

5.3.1 Source of government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Lasts. A last manufactured by Jones & Vining, 166 Forbes Rd, P.O. Box 755, Braintree, MA 02184, has been found to meet the requirements of 2.3.

5.5 Nonwoven insulation. A lining material manufactured by 3M, Building 220-7W, 3M Center, St. Paul, MN 55144 under the designation "Thinsulate", has been found to meet the requirements of 2.4 for nonwoven insulation.

5.6 Film lining. A film manufactured by W.L. Gore & Associates, P.O. Box 1130, Elkton, MD 21921 under the designation "Goretex", has been found to meet the requirements of 2.4 for a film lining.

5.7 Sole. A sole manufactured by Quabaug Corp., North Brookfield, MA 01535 under the designation "Vibram", has been found to meet the requirements of 2.7 for a sole.

5.8 Insole. An insole manufactured by Rogers Corporation, Poron Division, East Woodstock, CT 06244 under the designation "Poron", has been found to meet the requirements of 2.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

5.9 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

User activity:

Air Force - 45

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

(Project 8430-0396)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.