INCH-POUND

A-A-52077
August 15, 1990

# COMMERCIAL ITEM DESCRIPTION

## PILLOWS, BED (FEATHER)

The General Services Administration has authorized the use of this commercial item description in preference to Types Ia, II, III, and IV, Classes 1 and 2, of V-P-356.

## 1. CLASSIFICATION

1.1 Classification. This commercial item description covers one type and size of pillow.

## 2. SALIENT CHARACTERISTICS

2.1 Description. The feather pillows shall be filled with small, whole waterfowl feathers. The feathers shall be washed, dried, and sterilized, as well as dust and odor-free. The feathers shall be new (not previously used or reclaimed). The pillow ticking shall be cotton, and shall be downproof and featherproof. The pillow is intended to be laundered. The color of the ticking shall be white, or when specified (see 5.2), shall be white with a woven blue warp stripe. The feather filling and ticking materials shall conform to the requirements listed in table I.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any pertinent data which may improve this document should be sent to. Commander, U.S. Army Natick Research, Development, and Engineering Center ATTN: STRNC-ES, Natick, MA 01760-5014

AMSC N/A FSC 7210

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

TABLE I. Material components requirements

| Characteristic | Requirement | Test Method |
|---|---|---|
| Feather component: | | FED-STD-148 |
| Composition | 90 percent min. whole waterfowl feathers<br>90 percent min. feather length shall be less than 4 inches<br>10 percent max extraneous components, which include damaged feathers, down and feather fibers, residue, and not more than 2% land fowl feathers | Method 2 |
| Oxygen number | 10 maximum | Method 4 |
| Ticking component: | | ASTM |
| Weight | 6 5 ounces per square yard min. | D 3776 |
| Fabric count | Twill, 70 warp by 44 filling min. | D 3775 |
| Breaking strength | 110 pounds warp, min.<br>60 pounds filling, min. | D 1682 |

2.2 Pillow cover. The pillow cover shall be seamless, front and back. The seams shall be lockstitched and overedged sufficiently to prevent feather migration.

2.3 Size and weight. The pillows shall conform to the finished dimensions and weights specified in table II.

TABLE II. Pillow size and weight.

| Characteristic | Requirement |
|---|---|
| Finished width (inches) | 20.0 ± 0.5 |
| Finished length (inches) | 26.0 ± 0.5 |
| Finished total weight (ounces) | 35.0 minimum |
| Weight of feather filling (ounces) | 30.0 minimum |

2.4 Labels.

2.4.1 Identification and instruction label. Each pillow shall have a combination identification and instruction label sufficient to accomodate the following information printed in bold letters not less than 1/8 inch in height:

Nomenclature
National stock number
Contract number and date



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

CARE INSTRUCTIONS

Wash in accordance with U.S. Army Natick R, D & E Center's Formula IV (see 5.4).

2.4.2 State label requirements. When required, each pillow shall have a label attached conforming with the legal requirements of the state in which it is manufactured. When allowed under state law, the information required under state regulations may be combined in the identification and instruction label.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

3.3 End item visual examination. Each lot of pillows shall be examined for consumer type defects, defined as follows:

Defects in design, construction, or workmanship; open seam; any hole, needle chew, cut or tear, or any spot or stain clearly noticeable; offensive or objectionable odor; label missing or not as specified.

The lot size shall be expressed in units of pillows. The sample unit shall be one pillow. The inspection level shall be II, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

3.4 End item dimensional examination. The pillows shall be examined for conformance to the finished size and weight as specified in 2.3. Any dimension or weight not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of pillows. The sample unit shall be one pillow. The inspection level shall be S-3, and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

3.5 Regulatory requirements. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent practicable.

4. PACKAGING

4.1 Packaging. Each pillow shall be inserted in a snug-fitting, clear polyethylene film bag of 0.00125 inch thickness (± 20 percent tolerance). The identification label attached to each pillow shall be positioned so that the



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

printed information can be easily read. The bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and the formed edges of the bag. The final closure of the bag shall be heat sealed with the heat seal made as close as possible to the open end. Open vents of approximately 1 inch at each side of the closure or a 1/2 inch hole in each of the opposite corners of the bag shall be provided for the escape of excess air. Alternatively, the final closure of the bag shall be accomplished by folding over and securing the open end to the bag with pressure-sensitive tape.

4.2 Packing. Ten pillows of like description, packaged as specified in 4.1, shall be packed in a fiberboard shipping container conforming to style FTC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Pillows shall be packed flat, two in length and five in depth, within a shipping container Inside dimensions of each shipping container shall be 40 inches in length, 26 inches in width, and the depth dependent upon the compression applied to pillows. Each with the appendix of PPP-B-636, except that the strapping shall be applied three girthwise and one lengthwise.

4.3 Palletization. When specified (see 5.2), pillows, packed as specified, shall be palletized in accordance with MIL-STD-147

4.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The pillows are primarily intended for use by the United States Government.

5.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. Color of ticking required (see 2.1).
c. When palletization is required (see 4.3).

5.3 Sources of documents.

5.3.1 Sources of nongovernment association documents.

ASTM D 1682 - Tests for Breaking Load and Elongation of Textile Fabrics
D 3775 - Test for Fabric Count of Woven Fabric
D 3776 - Test for Weight (Mass) per Unit Area of Woven Fabric, are available from:

American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.

5.3.2 Source of government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Formula IV. Copies of care instructions may be obtained from:

U.S. Army Natick Research, Development and Engineering Center
ATTN: STRNC-IUC
Natick, MA 01760-5014

MILITARY INTERESTS.

Custodians

Army - GL
Navy - NU
Air Force - 99

Review Activities

Army - MD
Air Force - 82
DLA-CT

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 7210-0293



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:05Z
Check the source to verify that this is the current version before use.