MILITARY SPECIFICATION

BRACKET PUSHING, BOW ATTACHMENT, 12-TON PNEUMATIC HALF FLOAT

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a pushing-bracket for attachment to a 12-ton pneumatic half float for maneuvering with a bridge erection boat.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards, form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood.

MILITARY

MIL-T-704	- Treatment and Painting of Materiel.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5420
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U. S. Military Property.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing with Appropriate Test Methods.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

ME

TA13220E4475.	- Bracket, Pushing Assy, 12-Ton Pneumatic Half Float.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY (AWS)

A5.1	- Carbon Steel Covered Arc-Welding Electrodes.
A5.18	- Carbon Steel Filler Metals for Gas Shield Arc Welding.
D1.1	- Structural Welding Code - Steel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJeune Road, PO Box 351040, Miami, FL 33126.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specifications sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The pushing-bracket shall be as shown in Top Assembly TA13220E4475 and as specified herein.

3.2 First article.

3.2.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or deviations of pushing brackets from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnish pushing brackets conforming to this specification.

3.3 Material. Material shall be as specified herein and as shown in Top Assembly TA13220E4475. Material not specified shall be selected by the contractors and shall be subject to all provisions of this specification.

3.3.1 Welding electrodes. Welding electrodes shall conform to AWS A5.1 or A5.18, classification and size as required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

3.3.2 Material deterioration prevention and control. The pushing brackets shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operation and storage environment to which the pushing brackets may be exposed.

3.3.2.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889. Dissimilar metals will be protected from one another as called out on the drawings.

3.3.2.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with each component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.2.3 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components in the pushing-bracket may be newly fabricated from recovered materials to the maximum extent practicable, provided the pushing-bracket produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces, and parts shall not be incorporated in the pushing-bracket.

3.4 Treatment and painting. The pushing-bracket shall be cleaned, treated and painted in accordance with MIL-T-704, type B.

3.5 Identification marking. The pushing-bracket shall be identified in accordance with MIL-STD-130.

3.6 Workmanship. All parts, components and assemblies of the pushing-bracket, including welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux and other harmful, extraneous material. External surfaces shall be free from burrs, sharp edges, and corners, except when sharp edges and corners are required.

3.6.1 Steel fabrication. Steel used in the fabrication of the pushing-bracket shall provide original quality surface finish and shall be free from kinks and sharp bends. Steel having an eroded surface is not acceptable. The forming material shall be done by methods that will not cause damage to the metal. Shearing and chipping shall be done neatly and accurately. Corners shall be square and true. Burned surfaces of flame-cut material shall be free of slag. Precautions shall be taken to avoid overheating, and heated metals shall be allowed to cool slowly except where heat treatment is required. All bends of major character shall be made with metal dies or jigs to insure uniformity of shape.

3.6.2 Welders and welding.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

3.6.2.1 Welders. Before assigning any welder or automatic welding equipment operator to welding work covered by this specification, the contractor shall obtain certification that the welder or operator has passed qualification tests as prescribed by either of the following listed codes for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined by the particular code:

AWS D1.1 Structural Welding Code - Steel.
ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualification.

The certification shall be made available for review by the contracting officer or the contracting officer's representative. The Government reserves the right to require recertification of any welder or welding operator.

3.6.2.2 Welding. The surface of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded metal-arc or gas metal-arc (GMAW) process and shall conform to the provisions of the American Welding Society publication, D1.1-Structural Welding Code Steel. All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness or the part. Work shall be positioned for flat welding when practicable. Before welding over previously deposited weld metal, all traces of slag shall be removed, and the deposit and adjoining base metal shall be wire brushed clean.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, inspection level II.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the defects specified in 4.5.1. AQL shall be 1.0 percent for major defects and 6.5 for minor defects.

4.5 Inspection procedure.

4.5.1 Examination. The pushing-bracket shall be examined for the following defects:

Major

101. Material not as specified.
102. Contractor does not have documentation available for identification of material, material finishes, or treatment.
103. Used, rebuilt or remanufactured components, pieces and parts are incorporated in the pushing-bracket.
104. Welding electrodes not as specified.
105. Weld defects such as flux inclusions, spatter, undercutting, porosity, incorrect size, or lack of fusion with parent metal.
106. Materials are not resistant to corrosion or deterioration or treated to be made resistant to corrosion or deterioration for the applicable storage and operating enviornment as specified.
107. Dissimilar metals as specified in MIL-STD-889 are not effectively insulated from each other as specified
108. Bracket not true to dimensions, lines; contains twists, bends, holes, or other imperfections.
109. Welding and weldments not in accordance with requirements (see AWS D1.1).
110. Components missing or not as specified.
111. Treatment and painting not as specified (see 3.4).
112. Workmanship not as specified (see 3.6).
113. Steel or steel surfaces not as specified.
114. Welder certification not as specified.
115. Welding not as specified.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

Minor

201. Identification marking illegible, incomplete, incorrect or missing (see 3.5).

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 1.0 percent defective.

116. Box not close-fitting and in accordance with the referenced document for level A or B.
117. Components not blocked and braced as specified for level A or B.
118. Strapping not zinc coated for level A.
119. Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Packing Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each complete pushing-bracket shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional. The contents shall be blocked and braced within the box in accordance with MIL-STD-1186. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall be zinc coated.

5.1.2. Level B. Each complete pushing-bracket shall be packed as specified in 5.1.1 for level A except the box shall be domestic type and strapping need not be zinc coated.

5.1.3 Level C. Each complete pushing-bracket shall be packed in a manner to assure carrier acceptance and safe delivery to destination at lowest rating in a container complying with Uniform Freight Classification rules or with National Motor Freight Classification rules.

5.2 Marking. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Indented use. The pushing-brackets are intended for use as attachments to the beam outriggers of 12-ton pneumatic floats and used as a bumper assembly when floats are being maneuvered by bridge erection boats.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Time frame required for submission of first-produced pushing-bracket (see 3.2.1).
c. Level of packing required (see 5.1).

6.3 First article. When a first article inspection is required, the items should be a first produced pushing-bracket. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the first article.

6.4 Subject term (key word) listing.

Bracket pushing
Bow attachment
Pneumatic half float

6.5 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 5420-A343

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Belvoir RDE Center
STRBE-TSE
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-52690A(ME)	Bracket Pushing, Bow Attachment, 12-Ton Pneumatic Half Fl

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: ____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS ... CUT ALONG THIS LINE.)

Class 2 Attachment

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:29Z
Check the source to verify that this is the current version before use.