INCH-POUND

MIL-DTL-55302/144C
w/AMENDMENT 1
16 March 2011
SUPERSEDING
MIL-DTL-55302/144C
22 March 2005

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE WITH PIN CONTACTS, 2 FEMALE KEYING GUIDES, 1.516 INCHES LENGTH, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.




FIGURE 1. Connector, receptacle (.100 inch spacing).

AMSC N/A FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.006	0.15	.100	2.54	.248	6.30
.012	0.30	.122	3.10	.252	6.40
.016	0.41	.142	3.61	.305	7.75
.023	0.58	.153	3.89	.317	8.05
.024	0.61	.189	4.80	1.200	30.48
.050	1.27	.200	5.08	1.516	38.51
.071	1.80				

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Standoffs are located between each cable hole and between each hole and contact hole set.

FIGURE 1. Connector, receptacle (.100 inch spacing) – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




FIGURE 2. Recommended hole patterns.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Inches	mm
.004	0.10
.030	0.76
.050	1.27
.060	1.52
.070	1.78
.100	2.54
.106	2.69
.110	2.79
.118	3.00
.200	5.08
.218	5.54
.240	6.10
.320	8.13
1.20	30.48


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).

FIGURE 2. Recommended hole patterns - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




SUBPART A
FLEXIBLE CABLES




SUBPART B
SEMIRIGID CABLES




SUBPART C
90° FLEXIBLE CABLES




SUBPART D
90° SEMIRIGID CABLES



SUBPART E
90° PCB MOUNTING CABLES




SUBPART F
VERTICAL MOUNTING PCB



SUBPART G
SOLDER POSTS TWISTED BRAID

FIGURE 3. Coaxial configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.020	0.51	.139	3.53
.03	0.8	.155	3.94
.063	1.60	.157	3.99
.071	1.80	.158	4.01
.076	1.93	.165	4.19
.079	2.01	.177	4.50
.094	2.39	.185	4.70
.095	2.41	.189	4.80
.100	2.54	.271	6.88
.110	2.79	.303	7.70
.122	3.10	.317	8.05
.126	3.20	.343	8.71
.138	3.51	.374	9.50

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).

FIGURE 3. Coaxial configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




FIGURE 4. Contact and keying arrangements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




FIGURE 5. Connector terminations.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.010	0.25	.063	1.60	.177	4.50
.014	0.36	.100	2.54	.200	5.08
.020	0.51	.118	3.00	.217	5.51
.025	0.64	.126	3.20	.236	5.99
.056	1.42	.155	3.94	.490	12.45
.062	1.57	.173	4.39		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Solder tail accepts no. 22 AWG wire.
5. Crimp contact accepts no. 22-26 AWG wire.
6. Contact with .025 $inch^2$ (0.64 mm^2) wrappost.

FIGURE 5. Connector terminations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.004	0.10	.374	9.50
.008	0.20	.510	12.95
.116	2.95	.600	15.24
.187	4.75	1.020	25.91
.197	5.00	1.200	30.48

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Floating mount panel thickness .085 (2.16 mm) maximum.

FIGURE 6. Recommended panel cutouts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configurations: See figures 1 through 6.

Contact identification: See figure 4.

Contact retention: Coaxial and power: 11.25 pounds minimum.
Signal: 4 pounds minimum.

Mating and unmating force (per contact):	Coaxial	Power	Signal
(Min)	7.2 ounces	3.6 ounces	0.7 ounce
(Max)	36 ounces	18 ounces	3.6 ounces

Values for each connector to be addition of contacts according to contact type.

Contact resistance: 12 milliohms maximum.

Dielectric withstanding voltage:

Sea level: 1,000 V rms, 60 Hz.

High altitude: 300 V rms, 60 Hz.

Current rating:

Power contacts: 25 amperes at 25°C.

Coaxial contacts: .5 ampere at 25°C.

Signal contacts: 3 amperes at 25°C.

Keying: Moldings and mounting hardware provide 16 or 36 polarizing positions according to choice of 4 or 6 way capability. Keys are constructed in accordance with MIL-DTL-55302/154. Connectors are supplied with hex pins in the “1” and “A” positions, except for 1/4-turn locking styles, which are keyed in “F” and “6” positions. When required, connectors can be easily keyed to desired position by using a simple wrench.

Hood types: In accordance with MIL-DTL-55302/155.


Mounting hardware: In accordance with MIL-DTL-55302/154.

Mating connectors: In accordance with MIL-DTL-55302/149.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): Consists of the letter M, the basic number of the specification sheet, and a dash number compiled as follows:

Example:



Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/149
MIL-DTL-55302/154
MIL-DTL-55302/155

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2010-121)

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.