INCH-POUND

MIL-C-82894(OS)
9 February 1994

MILITARY SPECIFICATION

CARTRIDGE, FIRE EXTINGUISHER, CCU-126/A

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the manufacture and acceptance of the CCU-126/A Fire Extinguisher Cartridge, referred to herein as cartridge.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

UU-C-282	Chipboard
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-676	Boxes Setup
PPP-C-1797	Cushioning Material, Resilient, Low Density, Unicellular, Polypropylene Foam

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 8420), 101 Strauss Avenue, Indian Head, MD 20640-5035 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or sending a letter.

AMSC N/A FSC 1377
DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	Preservation, Methods of
MIL-B-117	Bags, Sleeves and Tubing
MIL-I-23659	Initiators, Electrical, General Design Specification For

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-453	Inspection, Radiographic
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-1168	Ammunition Lot Numbering

(Unless otherwise indicated, copies of military specifications, standards and handbooks are available from: Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

NAVAL AIR SYSTEMS COMMAND (CAGE Code 30003)

5184837	Ignition Charge
DL 834AS450	Cartridge, Aircraft Fire Extinguisher CCU-126/A Assembly, Loaded
838AS102	Powder, Smokeless

PUBLICATIONS

NAVAL AIR SYSTEMS COMMAND (CAGE Code 30003)

NAVAIRINST 4200.25	Engineering Reviews of Technical Data Packages for Flight Replenishment Parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

(Application for copies of NAVAIR drawings and instructions should be addressed to the Commanding Officer, Naval Air Technical Services Facility (Code 3121), 700 Robbins Avenue, Philadelphia, PA 19111.)

NAVAL SUPPLY SYSTEMS COMMAND

NAVSUPINST 4030.28 Logistics, Packaging Of Material

(Application for copies should be addressed to the Commanding Officer, Naval Aviation Supply Office, Cog I Support Branch (Code 03441), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

CODE OF FEDERAL REGULATIONS (CFR)

49 CFR 100-199 *Transportation*

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 545 *Standard Method for* Determining Image Quality In Direct Thermal Neutron Radiographic Examination

(Application for copies of ASTMs should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When more than 24 months have elapsed since production of the latest accepted lot, a first article sample (see 6.3) of 33 cartridges shall be produced using

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

the same procedures and methods proposed for production. The sample shall be tested as specified in 4.2.2.

3.2 Flight critical part. The CCU-126/A Fire Extinguisher Cartridge (Drawing 834AS450) is a flight critical item and shall be identified and produced as such in accordance with NAVAIRINST 4200.25A.

3.3 Conformance to documents and materials. The CCU-126/A Fire Extinguisher Cartridge covered by this specification shall be manufactured in accordance with DL 834AS450 and all documents listed thereon. All materials used in the manufacture of the cartridges shall conform strictly to the specifications referred to on the respective drawings. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 Primary components. The ignition charge (Drawing 5184837) and the smokeless powder (Drawing 838AS102) are primary components. Only one lot of each primary component shall be used in a cartridge lot. One primary component lot may be used in more than one cartridge lot.

3.5 Cartridge requirements. The entire lot of production cartridges shall be inspected as specified in table I. Failure of any cartridge to meet the requirements of table I shall result in rejection of the cartridge.

TABLE I. Non-Destructive tests.

Test Sequence	Test Paragraph	Test Requirement
1. Visual	4.3.1	3.5.1 & 3.7
2. Bridge circuit resistance	4.3.2	3.5.2
3. Radiographic	4.3.3	3.5.3
4. Leakage	4.3.4	3.5.4

3.5.1 Visual. Each cartridge shall be free of visible defects when inspected in accordance with 4.3.1.

3.5.2 Bridge circuit resistance. Each cartridge's bridge circuit resistance shall be 1.00 ± 0.15 ohms when measured in accordance with 4.3.2.

3.5.3 Radiographic inspection. Radiographic inspection (see 4.3.3) shall verify proper assembly, presence of parts, proper crimping and sealing and proper electrical connections. Film interpretation of the radiographs shall verify the presence and correct positioning of all parts and explosives (see 4.3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

3.5.4 Leakage. The leakage rate of each cartridge shall not exceed 1.0×10^{-5} cc/sec of air when tested in accordance with 4.3.4.

3.6 Cartridge sampling inspection. Cartridges from each first article test sample shall meet the applicable requirements of 3.5 and 3.6 as defined in table II. Cartridges from each lot acceptance test sample shall meet the applicable requirements of 3.5 and 3.6 as defined in table III.

TABLE II. First article test plan.

Test Sequence	Test Paragraph	Requirement Paragraph	Sample Group					
			I	II	III	IV	V	VI[1]
1. Visual	4.3.1	3.5.1 & 3.7	6	6	6	6	6	3
2. Bridge circuit resistance	4.3.2	3.5.2	6	6	6	6	6	3
3. Radiographic	4.3.3	3.5.3	6	6	6	6	6	3
4. Leakage	4.3.4	3.5.4	6	6	6	6	6	3
5. No-Fire[2]	4.3.5	3.6.1	6					
6. Static discharge[2]	4.3.6	3.6.2	6					
7. Stray voltage[2]	4.3.7	3.6.3	6					
8. Shock[3]	4.3.8	3.6.4		6	6	6	6	
9. TSHA[3]	4.3.9	3.6.5		6	6	6		
10. Vibration[3]	4.3.10	3.6.6		6	6			
11. Salt fog[3]	4.3.11	3.6.7		6				
12. Function test:	4.3.12	3.6.8						
-65°F			2	2	2	2	2	
70°F			2	2	2	2	2	
200°F			2	2	2	2	2	

[1] Investigative sample. Any investigative sample cartridge used shall pass the inspections as shown in the table before being subjected to any other tests.

[2] A bridge circuit resistance test shall be conducted following specified test.

[3] A visual, bridge circuit resistance, leakage, and radiographic inspection shall be conducted following specified test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

TABLE III. Lot acceptance inspections and tests.

Inspection/Test	Test Paragraph	Requirement Paragraph	Quantity
Visual inspection	4.3.1	3.5.1 & 3.7	Test & Retain Sample
Bridgewire resistance test	4.3.2	3.5.2	Test & Retain Sample
Radiographic inspection	4.3.3	3.5.3	Test & Retain Sample
Leakage test	4.3.4	3.5.4	Test & Retain Sample
No-fire test	4.3.5	3.6.1	Test Sample
Function test: -65°F 70°F 200°F	4.3.12	3.6.8	 1/3 Test Sample[1] 1/3 Test Sample 1/3 Test Sample

[1] Odd cartridges shall be conditioned at -65°F.

3.6.1 No-Fire. The cartridge shall not fire when subjected to a direct current of one ampere at one watt of power for 5 minutes minimum in accordance with 4.3.5.

3.6.2 Static discharge. The static discharge shall not fire or dud the cartridge when tested in accordance with 4.3.6.

3.6.3 Stray voltage. Stray voltage shall not fire or dud the cartridge when tested in accordance with 4.3.7.

3.6.4 Shock. The cartridge shall not incur damage from the shock test of 4.3.8.

3.6.5 Temperature, shock, humidity and altitude. The cartridge shall not incur damage or deformation from the temperature, shock, humidity and altitude test of 4.3.9.

3.6.6 Vibration. The cartridge shall not incur damage or deformation from the vibration test of 4.3.10.

3.6.7 Salt fog. The cartridges shall not incur detrimental deformations including corrosion, peeling, chipping, or blistering of the finish, nor exposure of the base metal as a result of the salt fog test of 4.3.11.

3.6.8 Function. The cartridge, when tested in accordance with 4.3.12, shall provide sufficient power to fully rupture the retaining disc of the container, permitting full and rapid discharge of the fire extinguishing agent. There shall be no mechanical failure or

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

distortion that would impair removal of the cartridge.

3.6.8.1 Ignition time. The cartridge shall fire within 25 milliseconds (ms) with application of 5.00, +0.25, -0.00 amps, when tested in accordance with 4.3.12.1.

3.6.8.2 Misfire. There shall be no misfire.

3.7 Workmanship. The cartridge shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be directed to dimensions, finishes, crimping, sealing, and assembly operations.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Production inspection (see 4.2.1)

b. First article inspection (see 4.2.2)

c. Lot acceptance inspection (see 4.2.3)

4.2.1 Production. The entire lot of production cartridges manufactured under the contract shall be inspected and screened for defects as defined in table I. Cartridges failing to meet the requirements referenced in table I and 3.5 shall be rejected and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

4.2.2 First article. Unless otherwise specified in the contract or purchase order (see 6.2), a first article sample of 33 cartridges shall be subjected to first article testing. Twenty four of these cartridges shall be expended in the tests listed in table II and three cartridges shall be retained for investigative purposes. Any damage inflicted by the environmental treatments, which would adversely affect the performance of the item in service application shall be cause for rejection of the first article sample. Any further production prior to notification by the contracting agency of first article sample acceptability shall be at the contractor's risk. The first article sample shall not be applied as part of the quantity specified for delivery by the contract. Failure of any cartridge to comply with the requirements of table II, 3.5 and 3.6 shall be cause for rejection of the first article represented.

4.2.3 Lot acceptance inspection. Lot acceptance shall consist of the examinations and tests specified in table III. Failure of any sample cartridge to comply with the requirements of table III, 3.5 and 3.6 shall be cause for rejection of the lot represented.

4.2.3.1 Sample size. A random sample from each production lot, including the retained sample for investigative purposes, shall be selected in accordance with table IV for lot acceptance inspection. Test sample cartridges and cartridges retained for investigative purposes shall not be applied as part of the quantity specified for delivery by the contract or purchase order.

TABLE IV. Lot acceptance sampling.

Lot Size	Test Sample Size	Retained Sample Size
2 thru 50	8	2
51 thru 90	13	6
91 thru 150	20	10
151 thru 280	32	10
281 thru 500	50	10
501 thru 1200	80	10

4.3 Inspection and tests.

4.3.1 Visual inspection. Each cartridge produced under the contract shall be visually inspected for proper construction and finishing as specified in 3.7. Particular attention shall be directed to dimensions, finishes, crimping sealing, and assembly operations. The cartridge shall be free of visible defects as noted in 3.5.1. Failure of any cartridges to comply with the requirements of 3.5.1 and 3.7 shall be cause for rejection of the lot or first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

4.3.2 Bridge circuit resistance. The resistance of each cartridge, from pigtail terminal to case, shall be measured with an accuracy of one percent using equipment which subjects the bridge circuit to a current of 5 milliamperes maximum. Failure of any cartridges to comply with the requirements of 3.5.2 shall be cause for rejection of the lot or first article.

4.3.3 Radiographic inspection. Each assembled cartridge shall be x-rayed and n-rayed in accordance with MIL-STD-453 and ASTM E 545-91, respectively. Any observable imperfections in assembly shall be cause for rejection. The cartridge shall be positioned on its side for the most revealing exposure. All cartridges shall be identified with serial numbers, beginning at 001, prior to x-ray and n-ray examination. The cartridges for examination shall be arranged on trays or boards in consecutive numerical order by serial number and each radiographic plate shall carry a permanent identification of the items displayed thereon. The radiographic plate identification shall include the NAVAIR drawing number, the complete lot number (as stamped on the items), contract number, and the span of serial numbers displayed. Missing serial numbers shall be identified. Radiographic plates of the entire cartridge production lot shall accompany the ballistic sample to the activity conducting the production lot acceptance test (see 4.2.1). Results shall be examined for conformance to 3.5.3. Failure of any cartridges to comply with the requirements of 3.5.3 shall be cause for rejection of the lot or first article.

4.3.4 Leakage test. Each cartridge in the production lot shall be leak tested with air in a dry gas leak tester. Failure of any cartridges to comply with the requirements of 3.5.4 shall be cause for rejection of the lot or first article.

4.3.5 No-Fire test. A direct current of not less than one ampere supplying a minimum of one watt of power shall be applied from pigtail terminal to the case for a period of 5.0, +0.5, -0.0 minutes. Failure of any cartridges to comply with the requirements of 3.6.1 shall be cause for rejection of the lot or first article.

4.3.6 Static discharge. The cartridge shall be subjected to a static discharge test by being connected to a 500 ± 5 percent picofarad capacitor charged to 25,000 ± 500 volts and a 5,000 ± 5 percent ohm resistor connected in a 500 microhenry total inductance series circuit. The cartridge shall be subjected to the static discharge between the pigtail terminal and case. Failure of any cartridges to comply with the requirements of 3.6.2 shall be cause for rejection of the lot or first article.

4.3.7 Stray voltage. The cartridge shall be subjected to 2,000 pulses of direct current from pigtail terminal to the case. Each pulse shall be 300 milliseconds applied at a rate of two per second. Each pulse shall have a minimum amplitude of 100 ± 5 milliamperes. The cartridges shall be conditioned for a minimum of 12 hours at 70 ± 5°F prior to testing. Failure of any cartridges to comply with the requirements of 3.6.3 shall be cause for rejection of the lot or first article.

4.3.8 Shock test. Mount the cartridges in the device of intended use or in a suitable test vehicle. If the test is conducted using a suitable test vehicle, the degree of support

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

shall be the same as that afforded by the device of intended application. The shock pulse shall be applied to the initiator's mounting points in both directions along each of three mutually perpendicular axes. The shape of each shock pulse shall approximate as nearly as possible a half sine wave. The amplitude of each shock pulse shall exceed 200 g's for 1.5 ± 0.4 milliseconds and it shall exceed 65 g's for 9.0 ± 0.9 milliseconds. Failure of any cartridges to comply with the requirements of 3.6.4 shall be cause for rejection of the lot or first article.

4.3.9 Temperature-Shock/Humidity/Altitude (TSHA). The TSHA test shall be conducted in accordance with the temperature-shock/humidity/altitude test of MIL-I-23659, omitting the reference to table I of MIL-I-23659. Failure of any cartridges to comply with the requirements of 3.6.5 shall be cause for rejection of the lot or first article.

4.3.10 Vibration test. The cartridge shall be subjected to vibration testing in accordance with MIL-STD-810B, Method 514.2-II, Curve H, except that each resonant and cycling period shall be divided equally at -65°F, 70°F, and 200°F. Failure of any cartridges to comply with the requirements of 3.6.6 shall be cause for rejection of the lot or first article.

4.3.11 Salt fog test. Six (6) cartridges shall be subjected to the salt fog test in accordance with Procedure 1 of MIL-STD-810. The cartridges shall be exposed to a 5% salt solution for a 48-hour period while in a hanging position. Failure of any cartridges to comply with the requirements of 3.6.7 shall be cause for rejection of the lot or first article.

4.3.12 Function test. Cartridges shall be conditioned for a period of not less than 4 hours nor more than 24 hours at the specified temperatures. The cartridges shall be removed from the conditioning chamber and test fired within 5 minutes. If any cartridge is not fired within 5 minutes after removal, it shall be reconditioned at the specified temperature for an additional 4 hours and then tested. The cartridges shall be initiated using a current of 5.00, +0.25, -0.00 amperes. The cartridge shall be fired in the Aircraft Fire Extinguisher Container Assembly. Failure of any cartridges to comply with the requirements of 3.6.8 shall be cause for rejection of the lot or first article.

4.3.12.1 Ignition time. The ignition time, which is defined as the time from the first application of current until the first sign of loss of circuit continuity, shall meet the requirements of 3.6.8.1.

4.3.12.2 Misfires. A cartridge that does not fire under the conditions specified in 4.2.3 shall be considered defective, and the lot considered unacceptable, unless the misfire is clearly attributable to faulty test equipment or procedure.

4.3.12.3 Retest. There shall be no retests.

4.3.12.4 Test failure. If the test failure is attributed to any specific cause excluding the cartridge, the original test results shall be discarded and that test re-conducted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

4.3.13 Inspection of packaging. Packaging, packing, and marking shall be visually examined for conformance to section 5.

5. PACKAGING

5.1 Preservation, packaging, and packing. Preservation, packaging, and packing shall be Level A and shall be in accordance with 49 CFR 171-178 and NAVSUPINST 4030.28. The contractor shall also comply with all applicable regulations.

5.1.1 Level A packaging. Level A preservation and packaging shall be as specified in a or b as follows:

a. Place each cartridge in one barrier bag conforming to MIL-B-117, Type I, Class E, Style 1, size 4 x 6 inches. Evacuate excess air and seal.

b. Package two cartridges in a container conforming to PPP-B-676, Type I, Variety 1, Class C, Style 4, size 5 1/4 x 4 3/8 x 1 1/4 inches with two 1 5/8 x 3 1/4-inch cells and 7/16 inch air cells on all sides formed by partitions conforming to UU-C-282. Add cushioning per PPP-C-1797, Type II or equivalent if required to establish a tight fit. Close container and apply label.

5.1.2 Level A packing. Initiators, packaged as described in 5.1.1, shall be packed in a wooden box conforming to PPP-B-621, Class II, Style 2, Grade A, size 18 x 10 x 11 1/4 inches (interior dimensions). Unless otherwise specified in the contract (see 6.2), the number of inner containers packed in the outer container shall be at the option of the supplier. Use material conforming to PPP-C-1797 or equivalent to fill voids and insure a tight fit. Close and reinforce box according to PPP-B-621. A tight pack is mandatory.

5.2 Marking.

5.2.1 Standard markings. Unless otherwise specified in the contract or purchase order (see 6.2), the marking information of the inner and outer containers shall be as specified below:

a. Inner Container Marking

(1) NSN 1377-01-377-9215-M178
(2) Cartridge, Aircraft Fire Extinguisher CCU-126/A
(3) NAVAIR Drawing No. 30003-834AS450
(4) Quantity
(5) Lot number in accordance with MIL-STD-1168
(6) DOT Explosive Class 1.4

b. Outer Container Marking

(1) NSN 1377-01-377-9215-M178

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

(2) Cartridge, Aircraft Fire Extinguisher CCU-126/A
(3) NAVAIR Drawing No. 30003-834AS450
(4) Quantity
(5) Gross weight and cube
(6) Lot number in accordance with MIL-STD-1168
(7) Contract/purchase order number
(8) WARNING: CARTRIDGES, POWER DEVICES
UN#0323

Additionally, the above specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129.

5.2.2 Special markings. Additional special markings of outer containers shall be in accordance with 49 CFR 171-178.

5.2.3 Bar coding. Bar code markings shall be in accordance with MIL-STD-129, Appendix G and shall include two messages: the NIIN and the lot number, shelf life expiration date, and quantity, which shall be encoded in a single message. The bar code label shall be applied to the outer container.

5.3 Explanation of terms. For the purpose of this specification NAVSUPINST 4030.28, Paragraphs 1-4, 2-2, 2-3, and Appendix A, when applicable, shall be used to clarify packaging terms.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended Use. The cartridge is intended for use in releasing fire extinguishing agent into the area surrounding an aircraft engine in the event of fire. This cartridge will be used in the C-130 series fire extinguishing systems.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2).

c. Production lot test activity (see 4.1 and 4.2.1).

d. Whether first article inspection is required and, if so, specify the test activity (see 4.2.2).

e. Number of inner containers per pack if not optional (see 5.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

f. Marking if other than as specified (see 5.2.1).

g. That the safety requirements of the "Contractor's Safety Manual for Ammunition, Explosives and Related Dangerous Material" (DOD 4145.26M) are applicable (see 6.5).

6.3 First article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first production items, standard production item from the contractor's current inventory (see 3.1) and the number of items to be tested as specified in 4.2.2. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Loaded assembly hazard information.

DOD, DOT, NATO Hazard Classification - Class 1, Division 4
United Nation Serial Number - 0323
Storage Compatibility Grouping - S
DOD Markings - Cartridge, Aircraft Fire Extinguisher CCU-126/A

6.5 Safety precautions. The safety precaution requirements of the "Contractor's Safety Manual for Ammunition and Explosives," DOD 4145.26M, are applicable and should be specified in the contract as required by the Federal Acquisition Regulation (FAR) 23.3.

NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety requirements of "Ammunition and Explosives Ashore" OP 5 are applicable.

6.6 Subject term (key word) listing.

Aircraft engine compartment
Cartridge activated devices
Electric initiator
Fire extinguishing system
Ignition charge

Preparing Activity:
Navy - OS
(Project 1377-NE48)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-82894	1994 FEBRUARY 9

3. DOCUMENT TITLE
CARTRIDGE, FIRE EXTINGUISHER, CCU-126/A

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
COMMANDER INDIAN HEAD DIVISION, NSWC	(1) Commercial 301-743-4510/4358	(2) AUTOVON 354-4510/4358
c. ADDRESS (Include Zip Code) 101 STRAUSS AVENUE CODE 8420 INDIAN HEAD, MD 20640-5035	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:30Z
Check the source to verify that this is the current version before use.