MIL-D-60388B (PA)
21 March 1975
SUPERSEDING
MIL-D-60388A (MU)
15 October 1971

MILITARY SPECIFICATION

DETONATOR, FLASH, M87
PARTS FOR,
LOADING, ASSEMBLING AND PACKING

This Specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers parts for, loading, assembling and packing for one type of detonator designated as Detonator, Flash, M87.

2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Packaging Methods of
MIL-P-223 - Powder, Black
MIL-A-2550 - Ammunition, General Specification For
MIL-P-14100 - Primer Stab, M55, Loading, Assembling and Packing

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

MIL-STD-650 - Explosives; Sampling, Inspection and Testing
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGING DRAWINGS

9217523 - Detonator, M87
9258182 - Box, Set Up, Packing, Ammunition, Inner for Small Explosive Components
9258183 - Box, Set Up, Packing, Ammunition, Outer for Small Explosive Components
9258184 - Box, Packing, Ammunition for Small Explosive Components

INSPECTION EQUIPMENT DRAWINGS

8816367 - Firing Pin Guide
8827934 - Adapter, Ball, Primer Sensitivity Testing Fixture
8855292 - Fixture, Functioning Test
8855295 - Disc
8855298 - Bushing
8867811 - Holder, Primer
9200012 - Pin, Firing

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

(* For meaning of asterisk see paragraph 6.6).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Detonator.-The detonator shall comply with all requirements specified on Drawing (dwg.) 9217523 and with all requirements specified in applicable specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

3.3 Moisture content

3.3.1 Lead azide.-The moisture content of the lead azide used in loading the detonator shall not exceed 0.50 percent.

3.3.2 Black Powder. - The moisture content of black powder used in loading the detonators shall not exceed 0.50 percent when tested as specified in MIL-P-223.

*3.4 Functioning. - Output. - The detonator shall function on the first attempt under an applied energy of 31.60 inch ounces and shall cause a 3/16 inch diameter perforation in a .065 inch min thick coined lead disc.

3.5 Workmanship.-All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing components shall be dry.

3.6 First Article Inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

*4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Govern-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

ment. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission. - Prior to the start of regular production, the contractor shall submit a first article sample (see 6.1c) to a Government approved facitity as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2 and 4.2.3. The first article sample shall consist of three hundred fifteen (315) loaded primers and 50 complete sets of parts (i.e., 50 each of every component),

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and material, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of conformance for materials. A sample containing know defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specfication such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Components will be subjected by the Government to any or all of the examinations and tests specified in this specification and any or all require ments of the applicable drawings.

4.2.3 Rejection.-If any component fails to comply with any of the applicable requirements the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any component to comply with any of the stated requirements.

4.2.4 Loaded Detonators. - A sample of three hundred fifteen (315) loaded detonators shall be submitted in accordance with 4.2.1, and tested as specified in 4.3.3.3.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded detonator assemblies shall contain:

a. Parts from one lot interfix number from one manufacturer.

b. Primer mixture from one batch or blending of batches which results in homogeneity of all primer mixtures used in loading the entire detonator lot.

c. Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling MIL-STD-105 Inspection Level II except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraphs of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4

4.3.2.1 Disc, detonator (see dwg. 9217525 covering a detail of dwg. 9217523).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Diameter	Gage	01001
102.	Thickness	Gage	01002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	01003

*4.3.2.2 Disc, detonator closing (see dwg. 9217526 covering a detail of dwg. 9217523).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Diameter	Gage	02001
102.	Thickness	Gage	02002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	02003

4.3.2.3 Cup, (see dwg. 9217524 covering a detail of dwg. 9217523).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Diameter of hole, min	Gage	03001
102.	Concentricity of flash hole with outside diameter	Gage	03002
103.	Thickness through bottom	Gage	03003
Minor:	AQL 2.50 percent		
201.	Length	Gage	03004

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

202.	Outside diameter	Gage	03005
203.	Inside diameter	Gage	03006
204.	Diameter of hole, maximum (max)	Gage	03007
205.	Evidence of poor workmanship (see 3.5)	Visual	03008

4.3.2.4 Assembly, prior to loading (see dwg. 9217523).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Coating on interior of cup missing or inadequate	Visual	04001
102.	Coating compound on exposed surface of disc	Visual	04002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	04003

4.3.2.5 Assembly (see dwg. 9217523).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Cup cracked or split	Visual	05001
Major:	AQL 1.00 percent		
101.	Length	Gage	05002
102.	Diameter	Gage	05003
103.	Disc loose, punctured, torn or wrinkled to such a degree that the contents are exposed	Visual	05004
104.	Color of lacquer incorrect	Visual	05005
105.	Cup damaged except as described in critical above	Visual	05006
106.	Crimp not full 360 degrees	Visual	05007
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	05008

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

4.3.2.6 Box, set-up, inner, after loading and prior to closing slide cover (see dwg. 9258182).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Filler and cushion assembly missing	Visual	06001
2.	Filler and cushion assembly improperly assembled	Visual	06002
3.	Stiffener missing	Visual	06003
4.	Slide cover assembled reversed	Visual	06004
Major:	AQL 0.40 percent		
101.	Release paper missing	Visual	06005
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	06006
202.	Evidence of poor workmanship (see 3.5)	Visual	06007

4.3.2.7 Box, set-up, outer, with inner set-up boxes assembled and prior to assembling top and sealing strip (see dwg. 9258183).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Red surfaces on inner set-up boxes do not alternate on same side of outer set-up box	Visual	07001
2.	Stiffener not facing one direction	Visual	07002
Major:	None defined.		
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	07003
202.	Evidence of poor workmanship (see 3.5)	Visual	07004

*4.3.2.8 Box, packing, ammunition prior to assembling cover and strapping (see dwg. 9258184).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Bags containing set-up boxes damaged	Visual	08001
102.	Cushioning material incomplete or missing from around outer set-up boxes	Visual	08002
103.	Marking missing, misleading or unidentifiable	Visual	08003
104.	Barrier bag seal incomplete or improperly positioned	Visual	08004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	08005

4.3.2.9 Box, packing, ammunition (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Strapping missing, broken, loose or improperly fastened	Visual/ Manual	09001
102.	Box damaged	Visual	09002
103.	Marking missing, incomplete or illegible	Visual	09003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	09004

4.3.3 Testing

4.3.3.1 Moisture content of lead azide (see 3.3) - Major defect - Code No. 05009.-The moisture content of the lead azide shall be determined for each lot at the time of loading. A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

sample shall be selected and tested as specified in 4.4.1. If the moisture content is in excess of the percentage specified and if the loading has not begun, the lot of lead azide shall be rejected. If loading has begun, action on the unloaded lead azide shall be as specified above and all detonators loaded with the questionable lead azide shall be rejected.

4.3.3.2 Moisture content of black powder (see 3.3). - Major defect - Code No. 05010. - The moisture content of the black powder shall be determined for each lot at the time of loading. A sample shall be selected and tested as specified in MIL-P-223. If the moisture content is in excess of the percentage specified in 3.3, the lot shall be rejected.

4.3.3.3 Functioning Output (see 3.4) - Major defect - Code No. 05011. - A sample of 315 detonators shall be selected at random from each lot. If 3 or more detonators fail to comply with the requirements specified the lot shall be rejected. If one or two defectives are found, a second sample of 315 detonators shall be selected at random and tested. If in the combined first and second sample a total of 4 or more defectives are found, the lot shall be rejected. The test shall be performed as specified in 4.4.2 using test equipment as specified in 4.3.4.

4.3.3.4 Heat seal test of sealed bag (see dwg. 9258183) - Major defect - Code No. 08006.-Sampling, acceptance criteria and test procedures for this test shall be as specified in Specification MIL-P-116.

4.3.4 Inspection equipment.-Inspection equipment required to perform the inspection prescribed in this specification is identified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval.

4.4 Test methods and procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

4.4.1 Moisture content of lead azide. - The moisture content of the lead azide shall be determined in accordance with MIL-STD-650 Method 101.6 except that a two gram sample shall be used and the dish shall be covered with a sheet of polytetrafluoroethylene.

4.4.2 Functioning

*4.4.2.1 Output. - The detonator shall be assembled to the test fixture so that the output end of the M55 primer (see MIL-D-14100) is facing the sensitive end of the detonator. A steel ball 1 3/16 inches in diameter and weighing 3.95 ounces, maximum, shall be dropped on the firing pin to function the M55 Primer (which has been inserted in primer holder dwg. 8867811) from a height of 8 inches maximum. The height of drop shall be measured as height from the top of the firing pin to the bottom of the ball. A detonator that fails to fire, or fails to create a hole in the coined lead disc of the required size shall be classed defective. Method of inspection shall be in accordance with dwgs. 8816367, 8827934, 8855292, 8855295, 8855298, 8867811 and 9200012.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level C. - Minimum Military Package. - The detonators shall be packaged and marked in accordance with dwg. 9258182 and dwg. 9258183.

5.2 Packing

5.2.1 Level C. - Packing shall be as specified on 9258184.

5.3 Marking. - Marking of all packaging and packing shall comply with dwgs. 9258182, 9258183, and 9258184.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Commander, Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Submission of test data and ammunition data cards. - In addition to the normal distribution of records, for loaded item procured by the Department of the Army, one copy of all ballistic test data and ammunition data cards shall be forwarded to the following:

Commander
Picatinny Arsenal
ATTN: SARPA-QA-A-M
SARPA-ADEP-2
Dover, New Jersey 07801

6.5 Check test for possible deterioration.-The following test is designed to prevent the loading of detonators which have

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

deteriorated, into a major ammunition item. The test shall be performed on detonators from each lot which have been stored under normal conditions for more than two years or adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are loaded does not require that the check test be performed, the contracting office in that contract. The contracting officer will arrange for the contractor to be reimbursed for expenses incurred in the performance of the check test for possible deterioration.

6.5.1 Functioning.-A sample of 315 detonators shall be selected at random from each lot. If 4 or more detonators fail to comply with the requirement specified, the lot shall be rejected. If more than one defective is found, a second sample of 315 shall be selected at random and tested. If in the combined first and second sample a total of 5 or more defectives are found the lot shall be rejected. The test shall be performed as specified in 4.3.3.3 using test equipment as specified in 4.3.4 and 4.4.2.1.

6.6 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inadequacies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-097

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.