MILITARY SPECIFICATION

TEST SET, LASER RANGEFINDER, TS-3620( )/GVS-5

This specification is approved for use by the Electronics Command, Department of the Army and is available for use by all departments and agencies of the Department of Defense

1 SCOPE

1.1 Scope This specification covers the Test Set, Laser Rangefinder, TS-3620( )/GVS-5 (See 6.4)

2 APPLICABLE DOCUMENTS

2.1 Issues of documents The following documents, of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein

SPECIFICATIONS

FEDERAL

MIL-P-7.	Pallets, Materials-Handling General Construction Requirements'
QQ-S-781	Strapping, Steel, Flat and Seals
PPP-B-585	Box, wood Wirebound
PPP-B-601	Box, Wood, Cleated Plywood
PPP-B-621	Box, wood, Nailed and Lock-Corner
PPP-B-636	Box, Fiberboard
PPP-B-640	Box, Fiberboard Corrugated, Triple-Wall
PPP-F-320	Fiberboard, Corrugated and One Solid, Sheet Stock, Container Grade and Cut Shapes
PPP-S-760	Strapping, Nonmetallic (and Connectors)
PPP-T-97	Tape, Pressure-Sensitive Adhesive Filament Reinforced

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, US Army Electronics Command, ATTN DRSEL-RD-TS-S, Fort Monmouth, New Jersey 07703 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426 appearing at the end of this document or by letter.

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	Preservation-Packaging, Methods of
MIL-P-11268	Parts, Materials, and Processes Used in Electronic Equipment
MIL-M-13231	Marking of Electronic Items
MIL-F-14072	Finishes for Ground Electronic Equipment
MIL-P-19644	Plastic Molding Material (Polystyrene Foam Expanded Bead)
MIL-P-19834	Plate, Identification, Metal Foil, Adhesive Backed
MIL-T-21200	Test Equipment for Use With Electronic and Electrical Equipment, General Specification for
MIL-P-26514	Polyurethane Foam, Rigid or Plastic, for Packaging

STANDARDS

FEDERAL

FED-STD-356	Commercial Packaging of Supplies and Equipment

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-147	Palletized and Containerized Unit Loads, 40 inch x 48 inch Pallets, Skids, Runners or Pallet Type Base
MIL-STD-252	Classification of Visual and Mechanical Defects for Equipment, Electronic, Wired, and Other Devices
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-810	Environmental Test Methods
MIL-STD-1472	Human Engineering Design Criteria for Military Systems, Equipment and Facilities

DRAWINGS

US ARMY ELECTRONICS COMMAND

DL SM-B-852427	Test Set, Laser Rangefinder Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The Test Set is designed to provide a "GO-NO GO" test and to act as an optical signal generator and laser output monitor for troubleshooting the Laser Rangefinder MX-9838( )/GVS-5. Storage compartments in the Test Set cover house the AC line cord for the Test Set and a power adaptor cable for the Laser Rangefinder The alignment bracket, which adapts the Laser Rangefinder to the Test Set, is also stored in the cover.

3.2 First article When specified in the contract or purchase order, the contractor shall furnish First Article units in accordance with 4.3 First Article samples shall be tested for conformance with specification requirements prior to regular production.

3.3 Construction. The Test Set shall be constructed in accordance with the requirements of this specification and with the drawings listed in ECOM Data List, DL-SM-B-852427, (including the requirements for parts, materials and processes thereon)

3.3.1 Safety features. The equipment shall provide for personnel safety in accordance with MIL-STD-454, Requirement 1

3.3.1.1 Radioactive materials Radioactive material shall not be used (e.g. luminous dials/markings, electron tubes, surge arrestors and lenses).

3.3.1.2 Edge rounding. All exposed edges and corners shall be rounded.

3.3.2 Conformance to MIL-T-21200. Unless otherwise specified herein the test set shall conform to all the requirements of MIL-T-21200 for class 3 equipment.

3.4 Parts, materials and processes, general Materials, parts, and processes shall be in accordance with MIL-F-11268

3.5 Finish. The equipment shall be finished in accordance with MIL-F-14072 and the equipment drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

3.6 Nameplates and product marking.

3.6.1 Nameplates Each nomenclatured item shall be marked with a serialized nameplate conforming to MIL-P-19834 Type 1.

3.6.2 Marking The equipment shall be permanently and legibly marked for identification in accordance with MIL-M-13231.

3.7 Weight. The maximum total weight of the Test Set, Laser Rangefinder TS-3620( )/GVS-5 shall not exceed 30 pounds (see 4.6).

3.8 Compatibility. The Test Set shall be compatible electrically and mechanically with Laser Rangefinder MX-9838( )/GVS-5 (see 4.7).

3.9 Performance characteristics.

3.9.1 Test Set Laser Rangefinder TS-3620( )/GVS-5. The Test Set shall have the following performance characteristics when operated with a 115 VAC ±10 percent, 50 to 420 Hz source after a 20 minute warmup (see 4.8.1).

3.9.1.1 1 TGT mode. The Test Set shall, with the Mode switch in Position 1, generate a single optical output pulse with the following charcteristics after receipt of the Laser Rangefinder MX-9838( )/GVS-5 output pulse.

Pulse width	-	10 ±5 nsec
Power output	-	25 ±10 nwatts
Delay	-	4800 ±200 meters

3.9.1.2 2 TGT mode The Test Set shall, with the Mode switch in Position 2, generate two optical output pulses with the following characteristics after receipt of Laser Rangefinder MX-9838( )/GVS-5 output pulse.

Pulse width		-	10 ±5 nsec
Power output		-	25 ±10 nwatts
Delay	TGT 1	-	4800 ±200 meters
	TGT 2	-	TGT 1 + 100 ±50 meters

3.9.1.3 RCVR 1 pulse mode. The Test Set shall, with the Mode switch in Position 3, generate single optical output pulses with the following characteristics at a 50 ±10 Hz rate.

Pulse width	- 10 ±5 nsec
Power output	- 50 ±20 nwatts

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

3.9.1.4 RCVR 2 pulse mode. The Test Set shall, with the Mode switch in Position 4, generate a pair of optical output pulses with the following characteristics at a 50 ±10 Hz rate.

Pulse width	-	10 ±5 nsec
Power output	-	25 ±10 nwatts
Pulse separation	-	100 ±50 meters

3.9.1.5 Laser pulse monitor mode. The Test Set shall, with the Mode switch in Position 5, allow monitoring of the received laser pulses at the LASER PULSE jack. With this jack terminated in 50 ohms, a 2 volt pulse shall correspond to approximately 25 millijoules.

3.9.1.6 NORMAL power output indicator. The Test Set shall display a normal laser power indication for all input optical pulses with energy levels greater than 9.0 millijoules. It shall not display the normal power indication for all input pulses with energy levels below 8.0 millijoules.

3.9.1.7 LOW power output indicator. The Test Set shall display a low laser power indication for all input optical pulses with energy levels greater than 6.0 millijoules except that the normal power indication shall override the low power indicator. No indication shall be displayed for input optical pulses with energy levels less than 5.0 millijoules.

3.9.2 Cable Assembly, Adapter AN/GVS-5( ). The adapter cable assembly shall have the performance characteristics specified in Drawing SM-D-852433 (see 4.8.2).

3.9.3 Component and subassembly performance characteristics. The components and subassemblies of the Test Set, Laser Rangefinder, TS-3620( )/GVS-5 shall have the performance characteristics specified in the following drawings (see 4.4.1).

Test Specification Power Supply Board	SM-A-852448
Test Specification Electronics Board	SM-A-852447
Test Specification Xmt/Rcv Board	SM-A-852449
Test Specification Xmt/Rcv Assembly	SM-A-852451

3.10 Service conditions. The equipment shall meet the following environmental conditions.

3.10.1 Altitude. The equipment shall operate without degradation in specified performance at altitudes up to 10,000 feet (3050 m) above sea level. It shall withstand air transportation at altitudes to 40,000 feet (12,000 m) in its combination case without any degradation in specified performance (see 4.10.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

3.10.2 Temperature.

3.10.2.1 Operating The equipment shall operate without degradation in specified performance at ambient air temperatures from 0 degrees C (32 degrees F) to 55 degrees C (131 degrees F) (see 4.10.2).

3.10.2.2 Storage The equipment shall withstand storage at ambient temperatures ranging from -57 degrees C (- 70 degrees F) to +71 degrees C (+160 degrees F) (see 4.10.2).

3.10.3 Vibration The equipment shall not suffer damage or fail to provide specified performance when subjected to vibration levels given in paragraph 4.10.3.

3.10.4 Shock The equipment shall not suffer damage or fail to provide specified performance when subjected to the shocks given in paragraph 4.10.4.

3.10.5 Humidity The equipment shall be operable without degradation in specified performance and shall sustain no physical damage that would affect performance or maintenance requirements, during and after prolonged exposure to relative humidities as high as 94 +4 percent at ambient air temperatures as high as 65 degrees C (+ 149 degrees F). Fogging on the inside glass or optical surfaces of instruments shall not occur (see 4.10.6).

3.10.6 Rain. The Test Set in its transit case with covers closed and latched shall not ingest any water when tested in accordance with paragraph 4.10.5

3.11 Maintainability The maintainability of the Test Set, Laser Rangefinder shall not be degraded as a result of any changes to the drawings listed in paragraph 3.3

3.12 Interchangeability. Like units, assemblies, subassemblies and replaceable parts shall conform to requirement 7 of MIL-STD-454 (see 4.11).

3.13 Government loaned property Unless otherwise specified in the contract or purchase order the Government will provide the following items for use in the quality assurance tests of Section 4

NSN	Nomenclature	Quantity
	Rangefinder, Laser AN/GVS-5( )	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

3.14 Human factors engineering. Design configuration as affecting operation, maintainability, and handling shall be maintained through compliance of configuration criteria to the requirements of MIL-STD-1472.

3.15 Workmanship. The equipment including all components and parts shall be manufactured and finished to ensure uniform quality and freedom from defects. Workmanship shall conform to all applicable portions of MIL-P-11268 and Requirement 9 of MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Inspections covered by subsidiary documents (see 4.4).

c. Quality conformance inspections.

(1) Quality conformance inspection of equipment before packaging (see 4.5).

(2) Quality conformance inspection of preparation for packaging (see 4.14).

4.3 First article. Unless otherwise specified in the contract or purchase order, the First Article inspection shall be performed by the contractor (see 3.2).

4.3.1 First article units. The contractor shall furnish two First Article units of the Test Set, Laser Rangefinder, TS-3620( )/GVS-5.

4.3.2 First article inspection. The First Article inspection shall consist of the inspections specified in Table I and shall be performed in the order specified therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

TABLE I First Article Inspection

Inspections	Req Para	Test Para	Order of Tests 2/ Unit 1	Unit 2
1 Inspections covered by subsidiary documents	3.3.1, 3.4, 3.5, 3.6	4.4	Inspections to be performed on all units. 1/	
2 Group A	See Table II		Inspections to be performed on all units. 1/	
3 Group B	See Table III		Inspections to be performed on all units. 1/	
4. Group C (Environmental)				
Altitude	3.10.1	4.10.1	1	
Temperature	3.10.2	4.10.2	2	
Vibration	3.10.3	4.10.3		2
Shock	3.10.4	4.10.4		3
Humidity	3.10.5	4.10.6	3	
Rain	3.10.6	4.10.5		1

1/ The inspections 1 through 3, in order shown shall be performed on the First Article units before subjecting the unit to any other inspection requirements specified in the table

2/ The numbers in the unit columns in the table specify the order of inspection for the indicated unit

4.3.3 First article data The First Article test plan and test report(s) shall be as required in the contract or purchase order

4.4 Inspections covered by subsidiary documents The following shall be inspected under the applicable subsidiary documents as part of the inspection required by this specification, and the inspection requirement specified in the contract or purchase order

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

Item	Where Required
Safety	3.3.1
Parts, Materials and Processes	3.4
Finish	3.5
Nameplates and Marking	3.6

4.4.1 Component and subassembly inspections. The contractor shall perform inspections and tests on the following assemblies in accordance with the drawings listed (see 3.9.3).

Power Supply Board	SM-A-852448
Electronics Board	SM-A-852447
Xmt/Rcv Board	SM-A-852449
Xmt/Rcv Assy	SM-A-852451

4.5 Quality conformance inspection of equipment before packaging. The contractor shall perform the inspections specified in 4.4, 4.4.1, 4.5.1 and 4.5.2. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. The Government will review and evaluate the contractor's inspection procedures and examine the contractor's inspection records. In addition, the Government, at its discretion may perform all or any part of the specified inspections to verify the contractor's compliance with the requirements. Test equipment shall be made available by the contractor for Government inspection.

4.5.1 Group A inspection. Each unit on contract or purchase order shall be inspected for conformance to all inspection and test requirements of Table II. Discrete lots shall be formed from units that pass this inspection. Lots of conforming units shall be verified by the supplier utilizing the sampling procedures of MIL-STD-105. Factors of lot composition not defined herein, or in the contract, shall be in accordance with MIL-STD-105. Each lot shall be subject to sampling inspection, utilizing the procedures of MIL-STD-105 and using the AQL's indicated in Table II of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

TABLE II. Group A Inspection

Inspection 1/	Req Para	Insp Para	Insp Criteria	AQL % Defective Major	AQL % Defective Minor
Visual and Mechanical					
Test Set, Laser Rangefinder TS-3620( )/GVS-5	3.3	4.12	100%	1	4
Unit Performance					
Test Set, Laser Rangefinder TS-3620( )/GVS-5	3 9 1	4 8 1	100%	1	2/
Adapter Cable	3 9 2	4.8 2	100%	1	2/

1/ The tests shall be conducted at standard conditions specified in Para 4.9.

2/ All defects are major.

4 5.1.1 Order of inspection within Group A. Group A inspection shall be performed in an order satisfactory to the Government

4 5 2 Group B inspection. Group B inspection shall be performed on inspection lots that have passed Group A inspection and on samples selected from units that have been subjected to and met the Group A inspection This inspection shall conform to Table III and to the special inspection levels of Table I of MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

TABLE III. Group B Inspection

	Inspection 1/	Req Para	Insp Para	AQL Percent Defective
1	Compatibility	3.8	4.7	4.0
2.	Interchangeability	3 12	4.11	6.5
3.	Weight	3.7	4.6	4.0

1/ The tests shall be conducted at standard conditions specified in Para 4 9

4.5.2.1 Group B sampling plans. The Group B sampling plans, for the AQLs listed in Table III, shall be as follows

AQL	Inspection Level
6 5 Percent	S-4
4.0 Percent	S-4

4.5.2.2 Order of inspection within Group B. Group B inspection shall be performed in an order satisfactory to the Government

4.5.3 Group C inspection. Group C inspection shall be performed on units that have passed Group A and Group B inspection The inspections shall consist of the inspections specified in Table IV Samples shall be selected in accordance with 4 5.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

TABLE IV. Group C Inspection

Inspection	Req Para	Insp Para
Subgroup I		
Altitude	3.10.1	4.10.1
Temperature	3.10.2	4.10.2
Humidity	3.10.5	4.10.6
Subgroup II		
Rain	3.10.6	4.10.5
Vibration	3.10 3	4.10.3
Shock	3.10.4	4 10 4

4 5 3.1 Sampling for Group C inspection. Two sample units shall be selected at random, one sample for each subgroup in Table IV, from the first fifty production units and thereafter from every 200 production units or fraction thereof greater than or equal to one-half. If the fraction is less than one-half, the selection of Group C samples for the preceding test shall be from units which include the remaining fraction.

4.5.3.2 Order of inspection within Group C. Group C inspection shall be performed in the order specified in Table IV

4.5 3 3 Group C failures. Actions required relative to Group C failures shall be as specified in the contract or purchase order.

4.5 4 Reinspection of conforming Group C sample units. Unless otherwise specified, sample units which have been subjected to and passed Group C inspection may be accepted on the contract provided all damage is repaired and the sample units are resubjected to and pass Croup A inspections.

4 6 Weight The equipment shall be weighed on a calibrated scale and the weight shall not exceed that specified in 3 7

4.7 Compatibility The Test Set shall be tested for compatibility in accordance with the paragraph entitled "Functional Tests" of Drawing SM-A-852450 (see 3.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

4.8 Performance characteristics.

4.8.1 The Test Set shall be tested in accordance with Drawing SM-A-852450 (see 3.9.1)

4.8.2 The cable assembly, adapter AN/GVS-5 shall be tested in accordance with drawing SM-D-852433 (see 3.9.2)

4.9 Standard conditions. Unless otherwise specified, inspections shall be performed at room temperature of 25 degrees ± 5 degrees C (77 degrees ±10 degrees F) and humidity not to exceed 90 percent.

4.10 Service test (environmental conditions). Unless otherwise specified, the service conditions test shall be conducted in accordance with MIL-STD-810. Tests and inspections shall be conducted as specified in Table V.

TABLE V. Verification Test Schedule

Functional Parameter Verified and Applicable Specification Paragraph	ENVIRONMENTAL TEST																							
	Altitude			High Temp			Low Temp			Humidity			Shock			Vibration			Rain					
	Pre	During	Post	Pre	During	Post	Pre	During	Post	Pre	During	Post	Pre	During	Post	Pre	During	Post	Pre	During	Post			
2 Target Mode (Para 3.9.1.2)	X	X	X	X	X	X	X	X	X	X	X	X	X		X	X		X	X		X			
Receiver 1 Pulse Mode (Para 3.9.1.3)	X	X	X	X	X	X	X	X	X	X	X	X	X		X	X		X	X		X			
Receiver 2 Pulse Mode (Para 3.9.1.4)	X	X	X	X	X	X	X	X	X	X	X	X	X		X	X		X	X		X			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

4.10.1 Altitude test. The altitude test shall be conducted in accordance with Method 500.1 Procedure I of MIL-STD-810. The equipment shall be subjected to a simulated altitude of 40,000 feet (12,000 m) above sea level for one hour in a nonoperating transport mode. The chamber pressure shall then be increased to simulate an altitude of 10,000 feet (3050 m) and an operational test performed in accordance with Table V (see 3.9.1).

4.10.2 Temperature.

4.10.2.1 High temperature test The high temperature test shall be conducted in accordance with Method 501.1 Procedure II of MIL-STD-810. Step 7 operating temperature shall be 55 degrees C (131 degrees F). The operational test shall be performed in accordance with Table V (see 3.9.2)

4.10.2.2 Low temperature test. The low temperature test shall be conducted in accordance with Method 502.1 Procedure I, of MIL-STD-810. The Step 2 storage temperature shall be held for two hours after temperature stabilization Step 4 operating temperature shall be 0 degrees C (+32 degrees F), and an operational test shall be performed in accordance with Table V (see 3.9.2).

4.10.3 Vibration test. The test set shall be subjected to sinusoidal vibration having a constant double amplitude of 0.015 inch (0.04 cm) while the frequency is uniformly varied between 10 Hz and 55 Hz The rate of frequency change shall be logarithmic and shall be traversed (10-55-10) in 30 minutes One cycle of vibration shall be conducted along three mutually perpendicular major axes of the test set An operational test in accordance with Table V shall be performed at the conclusion of this test In addition the unit shall not sustain any physical damage.

4.10.4 Shock test. The shock test shall be conducted in accordance with Method 516.2 Procedure 1 of MIL-STD-810. The number of shocks shall be reduced from 18 to 6 (one shock in each direction along three mutually perpendicular major axes). The shock pulse shape shall be in accordance with Figure 516.2-2 with an amplitude of 15Gs and a time duration of 11 ms (see 3.9.4).

4.10.5 Rain test. The test item shall be tested for simulated rain in accordance with Method 506.1 Procedure 1 of MIL-STD-810. Operation, in accordance with Table V, shall be conducted before and after the two-hour test. The orientation of the test set shall be changed every 30 minutes so that each side is equally exposed to the simulated rain (see 3.9.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

4.10.6 Humidity test. The humidity test shall be conducted in accordance with Method 507.1 Procedure II of MIL-STD-810. The unit shall be subjected to a 24 hour drying cycle, a 24 hour conditioning cycle and 5 continuous 48 hour cycles with humidity maintained at 94 percent and the temperature cycling between 30 degrees C (80 degrees F) and 65 degrees C (149 degrees F) The unit shall be operated during the last 5 hours of the last cycle in accordance with Table V (see 3 9.5).

4.10 7 Failure criteria Any unit which does not successfully pass the verification test schedule of Table V during and/or upon completion, as required by Table V, of any environmental test shall be considered a failure.

4 11 Interchangeability The mechanical dimensions and electrical performance of parts shall be physically and electrically interchangeable among the unit(s) Mechanical dimensions and electrical performance required by the equipment drawings shall be measured to determine compliance with the interchangeability requirements of 3 12.

4 12 Visual and mechanical. Prior to assembly into the unit(s), assemblies, modules, and printed circuit boards shall be examined for compliance with the equipment drawings All external moveable controls shall be operated mechanically. Assembled units shall be examined for compliance with equipment drawings, workmanship, and marking requirements The equipment shall be examined for the defects listed in MIL-STD-252

4 13 Human engineering verification Maintenance of the design configuration to the requirements of paragraph 3 14 shall be verified by visual and mechanical inspection.

4 14 Quality conformance inspection for packaging Packaging shall be tested in accordance with MIL-P-116 to determine conformance to the requirements of Section 5 The rough handling test will be performed only when specified (see 6.2c).

5 PACKAGING

5.1 Preservation. Preservation shall be level A, B or Commercial as specified (see 6.2b)

5 1 1 Level A

5 1.1.1 Cleaning. Test Set, Laser Rangefinder, TS-3620( )/GVS-5 shall be cleaned in accordance with process C-1 of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

5.1.1.2 Drying. Test Set, Laser Rangefinder TS-3620( )/GVS-5 shall be dried in accordance with applicable procedure of MIL-P-116.

5.1 1.3 Preservative application None required.

5.1 1.4 Unit packing. Unit packing shall be in accordance with the methods prescribed in MIL-P-116 as specified herein

5.1.1.4.1 Technical literature. Each technical literature shall be unit packed method IC-1.

5.1.1 4.2 Test Set, Laser Rangefinder TS-3620( )/GVS-5 Each test set shall be individually unit packed method III as follows place and secure the test set, AC power cable assembly, alignment bracket assembly and the adapter cable assembly within the spaces provided in the case Close the cover and secure the fasteners Cushion the case on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF, class weather-resistant, variety SW, grade W5c, designed and fabricated to protect all projections and absorb the shock of impact in handling and transit. As an alternate, cushioning material may be fabricated of plastic molding material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514 Place the cushioned case within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, unit packed as specified in 5.1 1.4.1, on top of the contents, directly under the lid of the box Close the box in accordance with the appendix of the box specification.

5.1 2 Level B Cleaning, drying, preservative application and unit packing shall be as specified in 5.1.1.

5.1.3 Commercial preservation Preservation shall be as specified in FED-STD-356.

5.2 Packing. Packing shall be level A, B or Commercial, as specified (see 6.2b). Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents

5.2 1 Level A. A quantity of Test Set Laser Rangefinder TS-3620( )/GVS-5, unit packed as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-601, overseas type, PPP-B-621, style 4 class 2, or PPP-B-585, style 2 or 3, class 2 When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

5.2.1.1 Unitization Palletization shall be required when Containers specified in 5.2.1 do not require skids, quantities per destination comprise a pallet load, and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers packed as specified in 5 2 1, except that container strapping may be omitted, shall be placed on a pallet, load type 1, conforming to MIL-STD-147 The pallet shall conform to NN-P-71, type IV, group I or II woods The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film

5.2.2 Level B A quantity of Test Set, Laser Rangefinder, TS-3620( )/ GVS-5, unit packed as specified in 5 1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-640, class 2, style E, or PPP-B-636, type CF, class weather-resistant The gross weight of boxes conforming to PPP-B-640 shall not exceed 250 pounds Closure shall be in accordance with the appendix of the applicable box specification Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97 and PPP-S-760, respectively, selection of the material and application shall be in accordance with the appendix of the applicable box specification When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71, group I or II woods. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film When a single unit is shipped to a single destination no packing is required, the unit container shall serve as the shipping container Reinforcing shall be as specified above

5 2 2 1 Unitization Palletization shall be required when quantities per destination comprise a pallet load A quantity of Test Set, Laser Rangefinder TS-3620( )/GVS-5, unit packed as specified in 5 2, shall be placed on a pallet, load type 1, conforming to MIL-STD-147 The pallet shall conform to NN-P-71, type IV, group I or II woods A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least 12 inches to accommodate marking requirements The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5s or W3c The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film

5 2 3 Commercial packing. Packaging shall be in accordance with FED-STD-356.

5 3 Marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

5.3.1 Military marking. In addition to any special marking required by the contract or order, interior packs and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial marking. In addition to any special marking required by the contract or order, interior packs and exterior shipping containers shall be marked in accordance with FED-STD-356.

6. NOTES

6.1 Intended use. Test Set, Laser Rangefinder, TS-3620( )/GVS-5 is intended to provide a test capability for the Laser Rangefinder MX-9838( )/GVS-5.

6.2 Ordering data. Procurement documents should specify

a. Title, number, and date of this specification and any amendment thereto

b. Level A, Level B or Commercial preservation and packing (see Section 5).

c. When rough handling is required (see 4.14)

d. Marking and shipping requirements.

e. First article inspection.

(1) Number of units

(2) First article test plan and test report(s) required.

f. Place of final inspection

6.3 Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or preparing activity for recommended disposability methods

6.4 Nomenclature. The parentheses in the nomenclature will be deleted or replaced by a letter identifying the particular design, for example TS-3620( )/GVS-5. The contractor should apply for nomenclature in accordance with the applicable clause in the contract (see 1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

6.5 Government-loaned property The contracting officer should arrange to loan the property listed in 3.13.

Custodian

Army-EL

Preparing activity

Army-EL

Project No 6625-A703

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS This sheet is to be filled out by personnel, either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side staple in corner and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements

SPECIFICATION MIL-T-[illegible](EL) TEST SET, LASER RANGEFINDER, TS-3620( )/CVS-5

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO (If "Yes" in what way?)

4 REMARKS (Attach any pertinent data which may be of use in improving this specification If there are additional papers attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity Optional) | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U S Army Electronics Command
ATTN ~~AMSEL-XX~~ DRSEL-RD-TS
Fort Monmouth, New Jersey 07703

To detach this form, cut along this line

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.