[INCH-POUND]
A–A–59789/14
8 March 2008


COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

HOLDER, ELECTRICAL CARD, WEDGE RETAINERS, 5 PIECE, FOR COLD PLATE APPLICATIONS, .375 X .375 INCH BODY SIZE, WITH TWO MOUNTING HOLES, VISUAL LOCK INDICATION, AND SCREW RETENTION, SCREW ACTUATED

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring 5 piece card holders described herein shall consist of this document and the latest issue in effect of A–A–59789.

CLASSIFICATION/PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see NOTES).



Example: AA59789/14JH65V is the PIN for a hard black anodized finished, 6.5 inch (165.1 mm) long card holder with visual lock indication and a retained actuating screw. The card holder also features two tapped mounting holes for use with 4-40 UNC 2B fasteners, a lockwasher and flat washer under the screw head, and a screw self-locking element for added resistance to loosening from shock vibration.

SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card firmly in place providing high resistance to shock and vibration while providing maximum thermal transfer.

Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein and meet the general requirements specified in CID A–A–59789. Card holders shall also have a screw retention feature to prevent unintentional disassembly of the card holder.

Material. Unless otherwise specified herein, the card holder materials shall be as specified in A–A–59789.

Actuating screw hex drive socket. The across flats dimension for hex drive socket shall be .140 inch (3.60 mm) for mounting options “R” and “V” and .118 inch (3.0 mm) for mounting option “Y”.

Cold plate slot width. The recommend cold plate slot width to accommodate the circuit card assembly with attached card holder is .425 inch (10.80 mm) plus the thickness of the printed board of the circuit card assembly (see A–A–59789).


Installation torque. The recommended nominal installation torque is as follows: 16 inch-pounds (1.8 N-m) for assemblies of configuration “A” and “F” and 20 inch-pounds (2.3 N-m) for assemblies of configurations “J” and “N”.

Configuration. The configuration of card holders shall be as specified in table I. The details of a particular configuration consist of those on figures 1, 2, and 3; and may include those on figures 4 or 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

TABLE I. Configurations.

Configuration	Applicable figures	Hardware options
A	1, 2, and 3	No added hardware
F	1, 2, 3, and 4	Lockwasher and flat washer
N	1, 2, 3, and 5	Screw self-locking element
J	1, 2, 3, 4, and 5	Lockwasher, flat washer, and screw self-locking element



Inches	mm	Inches	mm	Inches	mm
.24	6.1	.330	8.38	.470	11.94
.30	7.6	.375	9.26	.500	12.7

NOTES:
1. Dimensions are in inches. Millimeters are given for information only.
2. Unless otherwise specified, tolerances are for ±.02 inch (0.51 mm) for two place decimals and ±.010 inch (0.25 mm) for three place decimals.
3. Tolerance for the mounting hole spacing is ±.005 inch (0.13 mm).
4. The across flats dimension for actuating screw hex drive socket shall be .140 inch (3.60 mm) or .118 inch (3.0 mm) for the corresponding mounting option (see hex drive socket details).
5. Configuration shown uses captive nut on rear wedge. Alternate design using threaded insert shall be acceptable.

FIGURE 1. Relaxed and expanded dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

Screw retention locknut (see figure 2). Card holders shall have a screw retention locknut intended to prevent unintentional disassembly of the card holder. The locknut shall be fabricated of a corrosion resistant material.




FIGURE 2. Screw retaining self-locking nut (corrosion resistant) details.

Visual lock indicator (see figure 3). Card holders shall have a visual indicator to show when the card holder is in its relaxed (unlocked) state. When the card holder is in the unlocked (relaxed) state, the end of the actuating screw shall display a red band on the side of the screw. When the actuating screw on the card holder has been tightened (assembly expanded) so that the assembly is in the locked position, this red band shall be concealed.




FIGURE 3. Visual lock indicator.

Finish. The wedge body finish designator shall be as specified in A–A–59789. The finishes available for this CID specification sheet are as follows: “B” (black anodize), “P” (electrodeposited nickel), “H” (hard black anodize), or “D” (hard black anodize with dry film lubricant). When present, flat washers, lockwashers, and retention nuts shall be compatible with the specified finish.

Length, expanded, and relaxed dimensions. The length designator shall be as specified in A–A–59789. The lengths available for this CID specification sheet are listed in table II. The length, expanded, and relaxed dimensions shall be as specified on figure 1.

TABLE II. Additional assembly dimensions (see figure 1). 1/

PIN length designator	Dimension “length” ±.02 (0.5)	Dimension “M” ±.005 (0.13)
50	4.80 (121.9)	1.00 (25.4)
55	5.30 (134.6)	1.00 (25.4)
60	5.80 (147.3)	1.00 (25.4)
65	6.30 (160.0)	1.00 (25.4)

1/ Dimensions are in inches. Millimeters, in parenthesis, are given for information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

Mounting. Mounting designators “R” (rivet mount holes with counterbore and countersink), “S” (tapped 2-56 holes), “V” (tapped 4-40 holes), or “Y” (tapped metric M3 x 0.5 holes) shall be as specified in A–A–59789. See figure 1 for mounting hole spacing requirements. Card holders using mounting option “R” may be shipped unassembled.

Rivet mount holes. The holes used for rivet mounting shall be .134/.139 inch (3.40/3.53 mm) diameter, countersunk 100 degrees by .190/.200 inch (4.83/5.08 mm) diameter through holes with a counterbore of .190/.200 inch (4.83/5.08 mm) diameter by .300 inch (7.62 mm) deep.

Rivets. This card holder uses rivet style B as specified in A–A–59789 when rivet mounting is used.

Configuration hardware options. Card holders can have the following hardware options. See table I for the correct PIN configuration identifier.

Lockwasher and flat washer (see figure 4). A lockwasher and flat washer located under the screw head will provide for additional resistance to loosening from shock and vibration. Card holders requiring a lockwasher and flat washer shall include configuration identifier “F” or “J” in the PIN (see table I).




FIGURE 4. Lockwasher and flat washer details.

Screw self-locking element (see figure 5). The use of a screw self-locking element will provide prevailing torque for resistance to loosening from shock vibration. Card holders requiring a screw self-locking element shall include configuration identifier “J” or “N” in the PIN (see table I).




FIGURE 5. Screw self-locking element details.

Lockwasher, flat washer, and screw self-locking element. Card holders requiring a lockwasher, flat washer, and screw self-locking element option shall include configuration identifier “J” in the PIN (see table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Source of documents.

Commercial Item Description

A–A–59789 – Holder, Electrical Card, Wedge Retainers, 5 Piece, For Cold Plate Applications, General Requirements For.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111–5094.)

Other Publications

AEROSPACE INDUSTRIES ASSOCIATION (AIA)

AIA/NAS 1283 – Fasteners, Male Threaded, Self–locking.

(Application for copies should be addressed to the Aerospace Industries Association, 1250 Eye Street, NW, Suite 1200, Washington, DC 20005–3924 or at URL: http://www.aia-aerospace.org.)

Ordering data. Ordering data is as specified in A–A–59789.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Manufacturer CAGE	Manufacturer name and address	Manufacturer contact information
52094	Calmark Corporation 4915 Walnut Grove Avenue San Gabriel, CA 91776–2099	Telephone: (626) 287–0451 Facsimile: (626) 287–7350 E-mail: sales@calmark.com URL: www.calmark.com

Part number supersession data. These CID specification sheet PINs supersede the following manufacturer's part numbers as shown in table III. The CID PINs listed in table III are only for length designator "50". See table IV for CID PIN construction using other available lengths for this CID specification sheet. This information is being provided to assist in reducing proliferation in the Government inventory system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data.

PIN designator AA59789/14	Vendor similar designator or type part number 1/ CAGE 18915	PIN designator AA59789/14	Vendor similar designator or type part number 1/ CAGE 52094
AB50V	VA251–4.80T4R	AP50V	VEN251–4.80T4R
AB50R	VA251–4.80HR	AP50R	VEN251–4.80HR
AB50S	VA251–4.80T2R	AP50S	VEN251–4.80T2R
AB50Y	MVA251–4.80TM3R	AP50Y	MVEN251–4.80TM3R
FB50V	VWA251–4.80T4R	FP50V	VWEN251–4.80T4R
FB50R	VWA251–4.80HR	FP50R	VWEN251–4.80HR
FB50S	VWA251–4.80T2R	FP50S	VWEN251–4.80T2R
FB50Y	MVWA251–4.80TM3R	FP50Y	MVWEN251–4.80TM3R
NB50V	VA251–4.80T4LR	NP50V	VEN251–4.80T4LR
NB50R	VA251–4.80HLR	NP50R	VEN251–4.80HLR
NB50S	VA251–4.80T2LR	NP50S	VEN251–4.80T2LR
NB50Y	MVA251–4.80TM3LR	NP50Y	MVEN251–4.80TM3LR
JB50V	VWA251–4.80T4LR	JP50V	VWEN251–4.80T4LR
JB50R	VWA251–4.80HLR	JP50R	VWEN251–4.80HLR
JB50S	VWA251–4.80T2LR	JP50S	VWEN251–4.80T2LR
JB50Y	MVWA251–4.80TM3LR	JP50Y	MVWEN251–4.80TM3LR
AH50V	VHA251–4.80T4R	AD50V	VHD251–4.80T4R
AH50R	VHA251–4.80HR	AD50R	VHD251–4.80HR
AH50S	VHA251–4.80T2R	AD50S	VHD251–4.80T2R
AH50Y	MVHA251–4.80TM3R	AD50Y	MVHD251–4.80TM3R
FH50V	VWHA251–4.80T4R	FD50V	VWHD251–4.80T4R
FH50R	VWHA251–4.80HR	FD50R	VWHD251–4.80HR
FH50S	VWHA251–4.80T2R	FD50S	VWHD251–4.80T2R
FH50Y	MVWHA251–4.80TM3R	FD50Y	MVWHD251–4.80TM3R
NH50V	VHA251–4.80T4LR	ND50V	VHD251–4.80T4LR
NH50R	VHA251–4.80HLR	ND50R	VHD251–4.80HLR
NH50S	VHA251–4.80T2LR	ND50S	VHD251–4.80T2LR
NH50Y	MVHA251–4.80TM3LR	ND50Y	MVHD251–4.80TM3LR

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data. – Continued.

PIN designator AA59789/14	Vendor similar designator or type part number 1/ CAGE 18915	PIN designator AA59789/14	Vendor similar designator or type part number 1/ CAGE 52094
JH50V	VWHA251–4.80T4LR	JD50V	VWHD251–4.80T4LR
JH50R	VWHA251–4.80HLR	JD50R	VWHD251–4.80HLR
JH50S	VWHA251–4.80T2LR	JD50S	VWHD251–4.80T2LR
JH50Y	MVWHA251–4.80TM3LR	JD50Y	MVWHD251–4.80TM3LR

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59789.

TABLE IV. Example of PIN with available length designators.

PIN designator AA59789/14	Vendor similar designator or type part number 1/ 2/ CAGE 52094	PIN designator AA59789/14	Vendor similar designator or type part number 1/ 2/ CAGE 52094
JH50V	VWHA251–4.80T4LR	JH55V	VWHA251–5.30T4LR
JH55V	VWHA251–5.80T4LR	JH65V	VWHA251–6.30T4LR

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A–A–59789.

2/ Other lengths are available on request.

MILITARY INTERESTS:

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

Review activity:
Air Force – 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – FSS

Preparing Activity:
DLA – CC

Project 5998–2007–007

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.