INCH – POUND

A-A-59790
21 JUNE 2006

COMMERCIAL ITEM DESCRIPTION

BALANCER, VEHICLE WHEEL (ELECTRIC)

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE. This commercial item description (CID) covers a stationary, torque motor driven truck and vehicle wheel balancer for tube-type or tubeless tires used on trucks and vehicles. The operator driven vehicle should be capable of operation within the accuracies, limits, and specifications herein.

2. SALIENT CHARACTERISTICS.

2.1. Design and construction. The wheel balancer shall be capable of servicing tires with diameters to 47 inches (maximum), rim widths of 4.5 to 20 inches, rim diameters of 16 to 28 inches (maximum) and tire weights of 440 lbs. (maximum). It shall accommodate Dayton style and Budd style rims. Resolution of the unit shall be +0.01 ounces, 1.4 degrees. The wheel balancer shall be provided with a wheel lift or tire lifter capable of lifting up a minimum of 350 lbs. to the threaded shaft of the wheel balancer. The lift shall be air or mechanical in operation and shall be provided as a permanently fixed unit or as a separate unit that operates with the wheel balancer.

2.2. Type. The wheel balancer shall be electrically powered and shall be designed to be used at depots and tire shops by personnel of average mechanical skill.

2.3 Noise. The wheel balancer shall not, under any operating condition, exceed 84 dBA (slow scale) under the maximum load conditions when measured at not more than four feet from the perimeter of the unit.

2.4 Electrical power requirements. The wheel balancer shall be powered by a 110 VAC or 220 VAC, 60 Hz, single phase unless otherwise specified.

2.5 Life. The operational life of the wheel balancer shall be at least twenty years.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: WR-ALC/ENEP, 295 Byron St., Warner Robins AFB, GA 31098-1611 or emailed to Priest.Blackstock@robins.af.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil .

AMSC N/A FSC 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

2.6 Corrosion resistance. The wheel balancer shall be corrosion resistant.

2.7 Maintainability. A minimum number of parts and tools shall be required to maintain the wheel balancer during its life cycle. The electric motor shall be enclosed to prevent environmental contamination. Removable panels shall be a part of the design to afford access to the electric motor.

2.8 Finish. The wheel balancer shall be finished to the manufacturer's best commercial practice.

2.9 Accessories. The wheel balancer shall include all the necessary tools, adapters, and attachments. An operation and repair parts manual shall be furnished as specified in the contract. Standard equipment should include the following for use on tires of the type specified in paragraph 2.1, consisting of the following: Allen wrench, weight hammer, threaded stud, accessory pegs, hood, hood hardware, hood spring, caliper, small cone, medium cone, large cone, truck cone, truck cone spacer, back cone spring, pressure drum, large hub nut wrench, small hub nut wrench, and hub nut.

3. REGULATORY REQUIREMENTS.

3.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). Used, rebuilt, or remanufactured components shall not be incorporated in the vehicle wheel balancer.

4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product conformance. The product provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be substantially the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

4.2 Commercial item requirement. The vehicle wheel balancer furnished must meet the "commercial item" definition, as specified in FAR 2.101, as of the date of award. The offeror/contractor shall identify all modifications made to their commercial model in order to meet the performance and descriptive requirements of the CID or the referenced documents. Concerning the offered item, the offeror/contractor shall identify any enhancements or improvements to the performance requirements of paragraph 3 of the CID or the referenced documents.

4.3 Inspection requirements and testing.

4.3.1 Classification of tests. The inspection and testing of the vehicle wheel balancer shall be conducted in accordance with paragraphs 2.1 through 2.9.

4.3.2 Wheel balance test. A truck tire shall be balanced in order to ensure that the vehicle wheel balancer complies with paragraph 2.1 through 2.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

4.3.3 Noise test. The vehicle wheel balancer shall be tested to demonstrate that the noise level of the unit meets the noise requirement of 84 dBD.

4.3.4 Verification. Prior to delivery of the first vehicle wheel balancer, the offeror/contractor shall demonstrate or test at his/her facility, each requirement of the CID or referenced documents.

4.3.5 Production units. All production units delivered under this contract shall have the same parts, part numbers, configuration, materials, and process as those of the approved bid sample. In addition, production units shall be fabricated from the same parts and part numbers (original manufacturer's part numbers) being that those components and part numbers were utilized on the approved bid sample. No substitute part numbers will be allowed.

4.3.6 Safety. The vehicle wheel balancer shall comply with Federal OSHA requirements in effect as of the date of the contractual document. The Federal OSHA regulations shall take precedence in the event of conflict with state or local OSHA regulations.

5. PACKAGING

5.1 Preservation, Packaging, Packing, Labeling, and Markings. Preservation, packaging, labeling, and marking shall be specified in the contract or order (see 6.2).

6. NOTES

6.1 Sources of documents.

6.1.1 FAR. The Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402 or online at http://www.arnet.gov/far.

6.2 Ordering data. The purchaser must specify the following at the time of purchase:

a. Title, number, and revision letter, and date of this document.
b. Packaging requirements (see 5.1)
c. Safety (see 4.3.6)

6.3 Part or Identification Number. The following part or identification numbering procedure is for government purposes only and does not constitute a requirement for the offeror/contractor.

6.4 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard 376 and all other requirements of this CID are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

made to the contracting officer to determine if the product is acceptable. The contract officer has the option of accepting or rejecting the product.

6.5 Nomenclature. National stock number (NSN), part number and cage number of the unit(s) that meets the requirements of this CID:

NSN 4910-01-309-1751RN	P/N 6401	Cage 57791
NSN 4910-01-509-9714	P/N PD03LEEE144	Cage 98752

6.6 Subject term (key word) listing.

Corrosion resistant
National stock number
Wheel balancer

MILITARY INTERESTS

Custodians:
Air Force – 99
Army – AT
Navy – YD

Review Activity:
DLA – CC

Preparing Activity:
Air Force – 84

Agent:
Air Force - 99

(Project 4910-2006-001)

Note: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.