[INCH−POUND]
A−A−59812B
27 October 2020
Superseding
A−A−59812A
26 November 2015

COMMERCIAL ITEM DESCRIPTION

HOLDER, ELECTRICAL CARD, METAL CARD GUIDE, MULTIPLE PIECE,
GENERAL REQUIREMENTS FOR

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers the general requirements for a family of metal card guides (hereafter referred to as card guides) intended for use to guide and hold circuit card assemblies into their installed positions. Card guides covered by this CID are for moderate heat transfer and vibration applications. Requirements for specific card guides are covered in the individual CID specification sheets. Card guides covered by this CID are intended for commercial/industrial applications.

2. CLASSIFICATION/PART OR IDENTIFICATION NUMBER (PIN). This CID uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see 7.1).

AA59812	/02	*	* *	*	*
CID number	Applicable CID specification sheet	Configuration (see 3.3)	Length (see 3.4 and table I)	Material (see 3.5 and table II)	Finish (see 3.6 and table III)

3. SALIENT CHARACTERISTICS.

3.1 CID specification sheet. The family of card guides for use on circuit card assemblies shall be in accordance with the requirements specified herein and the applicable CID specification sheet. In the event of conflict between this general CID and the applicable CID specification sheet, the latter shall govern.

3.2 Interface and physical dimensions. Card guides shall be as specified herein and in the applicable CID specification sheet. NOTE: Tolerances, unless otherwise specified, are ±.02 inch (0.5 mm) for two place decimals and ±.010 (0.25 mm) for three place decimals.

3.3 Configuration. The card guide configuration shall be as specified in the applicable CID specification sheet. The card guide configuration designator(s) from the applicable CID specification sheet shall be included in the PIN.

3.4 Length. Unless otherwise specified in the applicable CID specification sheet, overall length shall be as defined in table I. Overall length designator from table I shall be included in the PIN.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218, or electronic mail at 5998.Documents@dla.mil. Since contact information can change, you may want to verify the currency of the address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 5998

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

TABLE I. Standard lengths.

Length designator	Card guide overall length dimension "L" 1/		Length designator	Card guide overall length dimension "L" 1/	
	Inches	(mm)		Inches	(mm)
10	1.0	(25)	60	6.0	(152)
15	1.5	(38)	65	6.5	(165)
20	2.0	(51)	70	7.0	(178)
25	2.5	(64)	75	7.5	(191)
30	3.0	(76)	80	8.0	(203)
35	3.5	(89)	85	8.5	(216)
40	4.0	(102)	90	9.0	(229)
45	4.5	(114)	95	9.5	(241)
50	5.0	(127)	A0	10.0	(254)
55	5.5	(140)	A5	10.5	(267)

1/ See the applicable CID specification sheet for the actual lengths used.

3.5 Material. The materials shall be as specified herein and the applicable CID specification sheet. Unless otherwise specified in the applicable CID specification sheet, materials shall be as defined in table II.

3.5.1 Insert material.

3.5.1.1 Beryllium copper, temper TD01 (formerly 1/4 H). Beryllium copper shall be as defined in ASTM B194, temper TD01, or equivalent. The temper of the beryllium copper shall be TD01. Card guides using beryllium copper as an insert material shall include a suffix "B" in the PIN.

3.5.1.2 Stainless steel. Stainless steel shall be as defined in SAE AMS 5517, or equivalent. Card guides using stainless steel as an insert material shall include a suffix "C" in the PIN.

3.5.1.3 Phosphor bronze. Phosphor bronze shall be as defined in ASTM B103/B103M or ASTM B139/B139M, or equivalent. Card guides using phosphor bronze as an insert material shall include a suffix "P" in the PIN.

TABLE II. Card guide insert material.

Material designator	Material type	Applicable specification	Paragraph
B	Beryllium copper	ASTM B194, temper TD01	3.5.1.1
C	Stainless steel	SAE AMS 5517	3.5.1.2
P	Phosphor bronze	ASTM B103/B103M or ASTM B139/B139M	3.5.1.3

3.5.2 Housing material. The housing material shall be aluminum alloy 6061 temper T6 in accordance with ASTM B221, SAE AMS-QQ-A-200/8 or equivalent.

3.6 Finish.

3.6.1 Insert finish.

3.6.1.1 Beryllium copper and phosphor bronze inserts. Beryllium copper and phosphor bronze inserts do not require any finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

3.6.1.2 Stainless steel inserts. Stainless steel inserts shall be passivate cleaned as defined in ASTM A967/A967M, or equivalent.

3.6.2 Housing finish. Unless otherwise specified in the applicable CID specification sheet, the housing finish shall be as defined in table III. Housing finish designator from table III shall be included in the PIN.

3.6.2.1 Black anodized. Black anodized finish provides good surface corrosion protection and medium abrasion resistance. Black anodize finish shall be in accordance with MIL-A-8625, type II, class 2 or equivalent. Black anodized finish assemblies shall include a suffix "B" in the PIN.

3.6.2.2 Clear anodized. Clear anodized finish provides good surface corrosion protection and medium abrasion resistance. Clear anodize finish shall be in accordance with MIL-A-8625, type II, class 2 or equivalent. Clear anodized finish assemblies shall include a suffix "C" in the PIN.

3.6.2.3 Gold anodized. Gold anodized finish provides good surface corrosion protection and medium abrasion resistance. Gold anodize finish shall be in accordance with MIL-A-8625, type II, class 2 or equivalent. Gold anodized finish assemblies shall include a suffix "G" in the PIN.

3.6.2.4 Chemical film, clear. Clear chemical film finish provides corrosion prevention on aluminum and aluminum alloys. Clear chemical film finish shall be in accordance with MIL-DTL-5541, class 3 or equivalent. Clear chemical film finish card guides shall include a suffix "F" in the PIN.

3.6.2.5 Chemical film, gold. Gold chemical film finish provides corrosion prevention on aluminum and aluminum alloys. Gold chemical film finish shall be in accordance with MIL-DTL-5541, class 1A or equivalent. Gold chemical film finish card guides shall include a suffix "Y" in the PIN.

3.6.2.6 No finish. Card guides with no finish applied to the housing shall include a suffix "N" in the PIN.

TABLE III. Housing finishes.

Finish designator	Finish	Applicable specification (or equivalent)	Paragraph
B	Anodize, black	MIL-A-8625, type II, class 2	3.6.2.1
C	Anodize, clear	MIL-A-8625, type II, class 2	3.6.2.2
G	Anodize, gold	MIL-A-8625, type II, class 2	3.6.2.3
F	Chemical film, clear	MIL-DTL-5541, class 3	3.6.2.4
Y	Chemical film, gold	MIL-DTL-5541, class 1A	3.6.2.5
N	No finish		3.6.2.6

3.7 Marking. Card guides supplied to this CID shall be marked with the manufacturer's standard commercial PIN. The part number marked on the unit pack shall be the CID PIN.

3.8 Recycled, recovered, environmentally preferable materials, or biobased. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.9 Workmanship. Card guides shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, quality assurances practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5.2 Inspection requirements. Inspection and acceptance of material shall be in accordance with the requirements cited in the contract or order.

6. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for of PIN format example.

7.2 Commercial and Government Entity (CAGE) code. For ordering purposes, inventory control, and submission of these card guides to DLA Land and Maritime under the Parts Management Advisory Team (PMAT) evaluation program, CAGE code 58536 should be used.

7.3 Source of documents.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL−DTL−5541	−	Chemical Conversion Coatings on Aluminum and Aluminum Alloys.
MIL−A−8625	−	Anodic Coatings for Aluminum and Aluminum Alloys.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

FEDERAL REGULATIONS

FAR	−	Federal Acquisition Regulations (FAR).

(Copies of these documents are available online at https://www.acquisition.gov/browse/index/far.)

ASTM INTERNATIONAL (ASTM)

ASTM B103/B103M	−	Standard Specification for Phosphor Bronze Plate, Sheet, Strip, and Rolled Bar
ASTM B139/B139M	−	Standard Specification for Phosphor Bronze Rod, Bar, and Shapes
ASTM B194	−	Standard Specification for Copper-Beryllium Alloy Plate, Sheet, Strip and Rolled Bar
ASTM B221	−	Standard Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles, and Tubes
ASTM A967/A967M	−	Standard Specification for Chemical Passivation Treatments for Stainless Steel Parts

(Copies of these documents are available online at https://www.astm.org.)

SAE INTERNATIONAL (SAE)

SAE AMS−QQ−A−200/8	−	Aluminum Alloy 6061, Bar, Rod, Shapes, Tube, and Wire, Extruded - UNS A96061
SAE AMS 5517	−	Steel, Corrosion Resistant, Sheet and Strip 18Cr - 8Ni (301) Cold Rolled, 125 ksi (862 MPa) Tensile Strength - UNS S30100

(Copies of these documents are available online at https://www.sae.org.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

7.4 Ordering data. The contract or order should specify the following:

a. CID document number, revision, and CID PIN.

b. Product conformance provisions.

c. Packaging requirements.

7.5 Government users. To acquire information on obtaining these card guides from the Government inventory system, contact DLA Land and Maritime Call Center (NAB), P.O. Box 3990, Columbus, OH 43218−3990, DSN 661−7766 or 1−877−DLA−CALL (1−877−352−2255).

7.6 Guidance on use of alternative parts with less hazardous or non-hazardous materials. This specification provides for a number of alternative plating materials via the PIN. Users should select the PIN with the least hazardous material that meets the form, fit, and function requirements of their application.

7.7 Assistance. Questions or comments pertaining to this document should be addressed to DLA Land and Maritime, ATTN: VAC, P. O. Box 3990, Columbus, OH 43218–3990; telephone (614) 692−0526; DSN 850−0526; facsimile (614) 693−1642; or electronic mail address 5998.Documents@dla.mil. This document is available for downloading at World Wide Web URLS https://landandmaritimeapps.dla.mil or https://quicksearch.dla.mil.

7.8 Subject term (key word) listing.

Circuit card assemblies
Housing finish
Insert material

7.9 Changes from previous issue. The margins of this CID specification are marked with bars to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

MILITARY INTERESTS:

Custodians:
Army − CR
Navy − EC
Air Force − 85
DLA − CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA − FSS

Preparing Activity:

DLA − CC

Project 5998−2020−027

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.