INCH-POUND

MIL-F-44422
AMENDMENT 1
12 January 1994

MILITARY SPECIFICATION

FIBER ROPE ASSEMBLY, INSERTION/EXTRACTION

This amendment forms a part of MIL-F-44422, dated 27 December 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2, lines 3, 4 and 5: Delete "+5%" and substitute "+10%".

PAGE 5

TABLE I, in last 2 columns opposite "Circumference in inches at load P": Delete "± 1/8" and substitute "±3/16".

PAGE 6

3.5.2, lines 1 thru 17: Delete and substitute:

"bottom of the first loop, and then enter again through the center of the main rope three picks up from the bottom of the first loop to form the first loop. Each white loop shall consist of 10 inches (± 1 inch) of exposed rope. After the white rope has been passed back through the center of the main rope forming a loop, it shall be passed back through the center of the main rope one pick up, and then passed through the center of itself where it last entered the main rope. The white rope will then be passed through the center of the main rope two picks up from the top of the last loop, then passed back through the center of the main rope two picks up from the last exit, then passed back through the center of itself, and passed back through the center of the main rope one pick up from where it had last passed through itself, forming the bottom of the second loop. The same procedure shall be followed to make the second and third white loops. After making the third loop, the white nylon rope shall be passed through the center of the main

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:58Z
Check the source to verify that this is the current version before use.

rope three and one-half picks up from the top of the third loop, and then eye spliced around the outer half of the main rope. Each eye splice in the white nylon rope shall consist of four full and two half tucks."

3.5.3: Delete and substitute:

"3.5.3 Safety line rope. The black nylon safety line rope shall pass through the center of the main rope one and one-half picks above, and on the same side as, the upper eye splice of the extraction loops rope. The black nylon safety line rope shall then pass through the two securing passes of the extraction loops rope, on the same side of the main rope, then through the center of the main rope, one and one-half picks above the lower eye splice of the extraction loops rope. After passing through the main rope, the safety line rope will then be passed through the securing passes on the opposite side of the first two, and the rope will then be spliced to itself with a short splice between the top eye and the top securing pass. After being spliced together, the safety line rope shall extend out as far as all three extraction loops, when all three extraction loops are fully extended out at the same time, and shall not interfere with the extraction loops.".

PAGE 8

4.3, line 2: Delete "4.4.5" and substitute "4.4.4".

Line 3: Delete "4.4.6" and substitute "4.4.5".

4.4.1.1, line 3: Delete "IV" and substitute "III".

PAGE 9

4.4.2, line 3: Delete "V" and substitute "IV".

4.4.3, line 2: Delete "V" and substitute "IV".

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:58Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL

Preparing activity:

Army - GL

(Project 4020-0345)

Review activities:

DLA - IS
Navy - MC, SH

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:58Z
Check the source to verify that this is the current version before use.