INCH-POUND

MIL-F-44425(GL)
31 July 1991

MILITARY SPECIFICATION

# FRAME SECTION, TENT, FIVE SOLDIER CREW

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers a frame, equipped with a fabric frame bag, for the five soldier crew tent.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used to improve this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-7582 - Frame Assembly, Five Soldier Crew Tent
5-4-7604 - Bag Assembly, Frame

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials. The materials for the frame and frame bag shall be as specified herein and as shown on the applicable drawings. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Construction. The construction of the frame and frame bag shall conform to the applicable drawings (Drawing 5-4-7582 for the frame and Drawing 5-4-7604 for the frame bag) and as specified herein.

3.3.1 Welding. All welding shall be complete, sound, smooth, uniform, and free from burn-through area, pits, slag inclusion, porosity, crack, fracture, weld spatter, flash, or excess flux deposit. Rough or projecting edges shall be ground smooth prior to finishing.

3.3.2 Castings and tubing. Castings and metal tubing shall be clean and free from pits, blowholes and scale.

3.3.3 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except when caught in other stitching or turned under in a hem. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.3.3.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box-x) and continue a minimum of 1 inch beyond the defective area on to the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.4 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met, and at least three or more tying, overlapping, or backstitches are used to secure the ends of stitching.

3.3.5 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a length of not more than 1/4 inch.

3.4 Assembly/disassembly of frame. The frame assembly shall be capable of being assembled/disassembled when tested as specified in 4.5.1.

3.5 Workmanship. The frame and frame bag shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.



Source: https://assist.dla.mil -- Downloaded: 202610-22T01:59Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The assembly/disassembly test (see 4.5.1), shall be performed for four (4) complete assembly/disassembly cycles for the first article inspection only. Any nonconformance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Insepction shall be made of the operations and requirements listed below to establish conformance with the specified requirements. Whenever a nonconformance is noted, correction shall be made to the items affected and to the operation.

a. Welds are sound, smooth, uniform and free from burn through area, pits, slag, inclusion, porosity, crack, fracture, flash and excess flux deposit (see 3.3.1).

b. Castings and aluminum tubing are free from pits, blowholes and scale (see 3.3.2).

4.4.3 End item visual examination.

4.4.3.1 End item visual examination for frame. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of frames. The sample unit shall be one completely fabricated frame. The inspection level shall be I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects, and 10 for total (major and minor combined) defects.

TABLE I. End item visual defects, frame

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Finish | Color of finish is not as specified | 101 | |
| | Not finished | 102 | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects, frame (cont'd)

| Examine | Defect | Classification Major | Classification Minor |
|---|---|---|---|
| Finish (cont'd) | Not continuous and not uniform (e.g., sag, pinhole, blister, wrinkle, foreign matter imbedded in finish, wet or tacky finish | | 201 |
| | Any run exceeding 1 inch in length | 103 | |
| | Area of no film: | | |
| | - bare metal showing in area more than 1/2 square inch | 104 | |
| | - bare metal showing in area 1/2 square inch or less | | 202 |
| | Area of thin film: | | |
| | - primer shows through in area 1 square inch or more | 105 | |
| | - primer shows through in area of less than 1 square inch | | 203 |
| | Scratch or scuff exposing bare metal: | | |
| | - 1 inch or more in longest dimension | 106 | |
| | - less than 1 inch in longest dimension | | 204 |
| | NOTE: Defects in finish attributable to flexing of movable joints during examination will not be scored as a defect. However, the supplier shall touch up areas of finish damaged during flexing of movable joints. | | |
| Construction and workmanship | Any part or component not fabricated of applicable referenced materials | 107 | |
| | Any component or part missing | 108 | |
| | Any component not fabricated as specified | 109 | |
| | Any component split, punctured, fractured, twisted, malformed, bent out of shape | 110 | |
| | Sharp edge or burr | | 205 |
| Welding | Missing | 111 | |
| | Not sound, not smooth, not uniform or has burn through area, pits, slag inclusion, porosity, crack, fracture, flash or excess flux deposit | | 206 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects, frame (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Cable swaging | Missing | 112 | |
| | Not tight on cable, loose or allows cable to slip on itself | 113 | |
| | Not crimped completely | | 207 |
| Casting | Not clean or has pits, blowholes and scale | | 208 |
| Marking for identification | Missing, illegible, incorrect, or improper size or location | | 209 |

4.4.3.2 End item visual examination for frame bag. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of frame bags. The sample unit shall be one completely fabricated frame bag. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects, 6.5 for major and minor A combined defects, and 15 for total (major, minor A, and minor B combined) defects.

TABLE II. End item visual defects, frame bag

| Examine | Defect | Classification Major | Minor A | Minor B |
|---|---|---|---|---|
| Fabric | Cut, tear or hole: | | | |
| | - greater than 1/8 inch in length or diameter | 101 | | |
| | - more than 1 hole not greater than 1/8 inch | 102 | | |
| | Broken or missing yarn; multiple floats clearly visible at normal inspection distance (approximately 3 feet) | | 201 | |
| | NOTE: Any opening larger than 1/8 inch shall be classified under one cut, tear or hole. | | | |
| Hardware - general | Any required component improperly installed causing failure to serve intended purpose | 103 | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, frame bag (cont'd)

| Examine | Defect | Classification Major | Minor A | Minor B |
|---|---|---|---|---|
| Seams and stitching | Open seams: | | | |
| | - 1/2 inch or less | | | 301 |
| | - more than 1/2 inch | 104 | | |
| | NOTE: A seam shall be classified as an open seam when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur. | | | |
| Seam and stitch type | Not specified seam or stitch type | 105 | | |
| | Seam twisted, pleated or badly puckered (unless otherwise classified herein) | | | 302 |
| | Any line of stitching not beginning or ending where specified (unless otherwise classified herein) | | | 303 |
| | Any seam not finished as specified | | | 304 |
| Raw edge (on edge required to be finished) | More than 1/2 inch in length when securely caught in stitching | | | 305 |
| | NOTE: Raw edge not securely caught in stitching shall be classified as an open seam. | | | |
| Thread breaks, skipped stitches or runoffs | On stitching other than box-x stitching, overstitched less than 1 inch in each direction beyond defective stitching area for 301 | | | 306 |
| | On box-x overstitched less than 1/2 inch in each direction beyond the defective stitching area | | | 307 |
| | NOTE: Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams. | | | |
| Boxstitching | Incomplete: | | | |
| | - one row of stitching omitted | | 202 | |
| | - two or more rows of stitching omitted | | 203 | |



Source: https://assist.dla.mil -- Downloaded: 202610-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, frame bag (cont'd)

| Examine | Defect | Classification Major | Minor A | Minor B |
|---|---|---|---|---|
| Bartacking | Bartacking less than specified length by more than 1/16 inch | | | 308 |
| Stitching ends | Overstitched less than 1 inch on stitch type 301 (except where ends are held down by other stitching, turned under in a hem, or where stitching is performed automatically) | | 204 | |
| | Secured with less than 3 tying, overlapping or backstitches when automatick stitching is performed | | 205 | |
| Rows of stitching | One or more required rows of stitching omitted: | | | |
| | - affecting serviceability seriously | 106 | | |
| | - affecting serviceability but not seriously | | | 309 |
| Bartacks | One or more bartacks omitted | 107 | | |
| | Any bartack not as specified or not in specified location | | | 310 |
| | Loose stitching, incomplete or broken | | | 311 |
| Stitch tension | Tension loose, resulting in loose bobbin or top thread | | | 312 |
| | Tension tight, resulting in puckering of material | | | 313 |
| Stitches per inch | Less than minimum specified: | | | |
| | - one stitch | | | 314 |
| | - two or more stitches | | 206 | |
| | More than maximum specified: | | | |
| | - one stitch | | | 315 |
| | - two or more stitches | | 207 | |

NOTE: Variation in the number of stitches per inch, caused by the operator speeding up the machine in order to sew over heavy places or heavy seams or in turning corners, shall be classified as follows:

a. Within the minor "A" defect classification - minor "B" defect



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, frame bag (cont'd)

| Examine | Defect | Classification Major | Minor A | Minor B |
|---|---|---|---|---|
| Stitches per inch (cont'd) | b. Within the minor "B" defect classification - no defect | | | |
| Stitching margin | Larger or smaller than specified by more than 1/16 inch: | | | |
| | - for more than 2 inches but not more than 4 inches in length | | | 316 |
| | - for more than 4 inches in length | | 208 | |
| Components and assembly | Any component part omitted or not fabricated of applicable referenced material | 108 | | |
| General | Any other construction details not performed as specified | 109 | | |
| Cleanness | Grease or oil stains | | | 317 |
| | Thread ends not trimmed to 1/4 inch or less | | | 318 |

4.4.4 End item dimensional examination.

4.4.4.1 End item dimensional examination, frame. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of frames. The sample unit shall be one frame. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4.2 End item dimensional examination, frame bag. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of frame bags. The sample unit shall be one frame bag. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 4.0.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

4.4.5 End item testing. Frames shall be tested as specified in 4.5.1 for compliance with 3.4. The lot size shall be expressed in units of tent frames. The sample unit shall be one tent frame. The inspection level shall be S-3. The lot shall be rejected if there is a test failure.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |
| Materials | Any component missing, damaged, or not as specified |
| Workmanship | Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling<br>Bulged or distorted container |
| Content | Number per container is more or less than required |

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

| Examine | Defect |
|---|---|
| Finished dimensions | Length, width, or height exceeds specified maximum requirement |
| Palletization | Pallet pattern not as specified<br>Load not bonded as specified |
| Weight | Exceeds maximum load limits |
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |

4.5 Method of inspection.

4.5.1 Assembly/disassembly test. The complete frame assembly shall be assembled/disassembled tested as follows:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

a. The frame shall be unpacked and completely assembled in accordance with Drawing No. 5-4-7676 and inspected for defects.

b. After assembly set-up is completed, the tent shall be completely disassembled and repacked into the frame bag.

The inability to assemble/disassemble frame shall be considered a test failure.

## 5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation. The frame section shall be folded compactly and secured. The ends of the folded assembly shall be wrapped or cushioned to prevent damage to the finish. All pins shall be secured with tape and wrapped or cushioned to prevent damage to the finish.

5.1.2 Commercial preservation. Components of each frame section shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing. One complete frame (Drawing #5-4-7582), preserved as specified in 5.1, shall be packed in a close-fitting shipping container conforming to overseas type, style A, grade B of PPP-B-601. Inside dimensions of the box shall approximate 38 inches in length, 8 inches in width, and 8 inches in depth. Each box shall be closed and strapped in accordance with the appendix of PPP-B-601.

5.2.2 Level B packing. One complete frame (Drawing #5-4-7582), preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, grade V3c of PPP-B-636. Approximate inside dimensions shall be 38 inches in length, 8 inches in width, and 8 inches in depth. Each box shall be closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. Complete frame, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), complete frames packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV or V in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 53 in accordance with the appendix of MIL-STD-147.



Source: https://assist.dla.mil -- Downloaded: 202610-22T01:59Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The frame is used to support a five soldier crew tent which is approximately 10 2/3 feet long, 10 2/3 feet wide and 65 inches high.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Shelters

Custodian:

Army - GL

Review activity:

DLA - CT

Preparing activity:

Army - GL

(Project 8340-A555)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | MIL-F-44425(GL) | 1991 July 31 |

**3. DOCUMENT TITLE**
FRAME SECTION, TENT, FIVE SOLDIER CREW

**4. NATURE OF CHANGE** *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

**5. REASON FOR RECOMMENDATION**

**6. SUBMITTER**

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION |
|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON<br>(If applicable) |
| | 7. DATE SUBMITTED (YYMMDD) |

**8. PREPARING ACTIVITY**

| a. NAME | b. TELEPHONE (Include Area Code) (1) Commercial | (2) AUTOVON/DSN |
|---|---|---|
| U.S. Army Natick RD&E Center | 508-651-4531 | 256-4531 |
| c. ADDRESS (Include Zip Code)<br>Commander, U.S. Army Natick RD&E Center<br>ATTN: STRNC-UXT<br>Natick, MA 01760-5017 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 | |

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T04:59Z
Check the source to verify that this is the current version before use.