INCH-POUND

MIL-H-44428A
18 December 1991
SUPERSEDING
MIL-H-44428(GL)
7 August 1991

MILITARY SPECIFICATION

HOOD, GAS MASK, SPECIAL PURPOSE, TOXICOLOGICAL AGENTS PROTECTIVE, M3

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of special purpose hood to provide military personnel protection against toxicological agents. The hood is to be used over a gas mask and with the Coverall, Toxicological Agents Protective, M3. This is a special purpose Life Support Clothing and Equipment (LSC&E) item. All Government administrative and surveillance procedures applicable to LSC&E items shall be invoked in accordance with the contract or purchase order (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5019 by using the Standardization Documents Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-50083	-	Bag, Plastic, Folded Garment
V-T-285	-	Thread, Polyester
DDD-L-20	-	Label: For Clothing, Equipage and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-1797	-	Cushioning Material, Resilient, Low Density Unicellular, Polypropylene Foam
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-B-371	-	Braid, Textile, Tubular
MIL-B-543	-	Buckles, Tongueless and Web Strap
MIL-F-10884	-	Fasteners, Snap
MIL-C-12189	-	Cloth, Coated: Butyl Coated, Toxicological Agents Protective
MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage, General Specification For
MIL-T-43566	-	Tape, Textile, Cotton, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-191	-	Textile Test Methods
FED-STD-751	-	Stitches, Seams, and Stitching

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-6-103 - Cord Lock, Acetal Body and Nylon Wheel
2-6-104 - Cord Lock, Single Cord

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Guide samples. Samples, when furnished, are solely for guidance and information to the contractor (see 6.4). Variations from this specification may appear in the sample, in which case this specification shall govern.

3.3 Materials. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Coated cloth. The coated cloth shall be butyl coated nylon cloth conforming to MIL-C-12189.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

3.3.2 Bias binding. The bias binding for the snout rings shall be 3/4 to 1-1/8 inch wide and cut from the coated fabric specified in 3.3.1.

3.3.3 Strapping. The strapping used to seal the seams shall be 3/4 + 1/8, -0 inch wide and shall be made from the coated fabric specified in 3.3.1, straight or bias cut.

3.3.4 Cement. The cement used to adhere the strapping to the seams shall be clear and of the self-curing neoprene or butyl base type. The cement, when applied and tested as specified in 4.4.1, shall not crack or flake when subjected to the cold crack test, and the hydrostatic resistance of the cement coated cloth shall be not less than 90 percent of the actual hydrostatic value of the butyl coated cloth prior to cementing.

3.3.5 Thread, polyester. The thread for all stitching shall conform to type I, class 1, sub-class A of V-T-285. The size shall be as specified in table I. The thread shall be dyed Olive Drab S-1, C.A. 66022.

3.3.6 Tape, cotton. The cotton tape shall conform to type I, class 1a, 1/2 inch wide of MIL-T-43566, except the tape shall be dyed Olive Drab 7.

3.3.7 Braid. All braid shall be texturized polyester conforming to class 2 of MIL-B-371 and shall be dyed Olive Drab 7. The type shall be as specified below.

3.3.7.1 Braid for neck drawcord. The braid for the neck drawcord shall be type II. The ends of the braid shall be resin dipped or tipped 3/4 $\pm$ 1/8 inch to prevent raveling.

3.3.7.2 Braid for eye holes and snout drawcords. The braid for the eye holes and snout drawcords shall be type VII. The ends of the braid shall be stitched (see table I, operation 3c) or resin dipped or tipped 3/4 $\pm$ 1/8 inch to prevent raveling.

3.3.8 Buckle. The buckle shall be tongueless, one-bar, 5/8 inch, conforming to type I, style 2, class 1, construction B of MIL-B-543 or as an alternate shall be tongueless, two-bar, 5/8 inch conforming to type II, style 3, class 1 of MIL-B-543.

3.3.9 Snap fasteners. The snap fasteners shall conform to style 2A, finish 2 of MIL-F-10884. The size of the button and the eyelet components shall be selected by the contractor and shall be of sufficient length to provide a firm clinch.

3.3.10 Cord lock. The cord lock for the neck drawcord shall conform to Drawing 2-6-104 or as an alternate shall conform to Drawing 2-6-103.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

3.3.11 Identification label. Each hood shall have an identification label conforming to type IV or VI, class 1 of DDD-L-20 with the following exceptions:

Type IV label (stamped)
(a) A vinyl base black indelible ink shall be used.
(b) Letters shall be sans-serif, extra bold, monotone style, 14 points (caps only).

Type VI label (cloth)
(a) The label shall be printed prior to impregnation or coating.
(b) Only chlorine bearing vinyl resin composition shall be used for impregnation or coating.
(c) The label shall measure 2-3/4 by 1-1/2 inches minimum and the legend shall be printed parallel to the small dimension.
(d) All colorfastness and writing tests are not applicable.

3.4 Design. The design of the hood shall be as shown in figure 1.

3.5 Figures. Figures 1 and 2 are furnished for information only. If there are any inconsistences between the written document and the figures, the written document shall control.

3.6 Patterns. Standard patterns, which provide a seam allowance of 3/8 inch for all lapped seams unless otherwise specified in table I, will be furnished by the Government. The standard patterns shall not be altered in any manner and are to be used only as a guide for cutting the contractor's working patterns which shall be identical to the standard patterns.

3.6.1 List of pattern parts. The component parts for the hood shall be cut from the material specified in a manner to ensure that the heavy side of the coated material faces outside when hood is assembled and in the quantity indicated below:

Material	Item	Nomenclature	Cut parts
Cloth, coated, butyl coated, toxicological agents protective	1	Snout rings	2
	2	Front neck	1
	3	Back neck	1
	4	Front, left and right	2
	5	Back, left and right	2
	6	Snouts	2

3.7 Construction. The construction shall conform to the requirements specified in table I and herein. The hood shall be assembled with the heavily coated side of the cloth and strapping facing to the outside.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

3.7.1 Stitches, seams, and stitching. All stitches, seams, and stitching shall conform to FED-STD-751. The type of seam, stitching and stitches per inch shall be as specified in table I. Seam allowances shall be maintained with seams sewn so that no raw edges, run-offs, twists, pleats, puckers, or open seams occur.

3.7.1.1 Type 301 stitching. Unless otherwise specified, ends of all 301 stitching, except when caught in other seams or stitching, shall be backstitched or overstitched 3/8 inch minimum. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.7.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 3/8 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive runoff or skipped stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 3/8 inch back of the defective area, continue over the defective area and continue a minimum of 3/8 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs the ends of the stitching are not required to be backstitched.

3.7.1.2 Use of automated apparel equipment. Automated apparel equipment may be used to perform any of the operations specified in table I, providing that the seam and stitch type are as specified and the finished component conforms to the required configuration. When a government furnished shaper pattern is forwarded, the component shall conform to that pattern.

3.7.1.3 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4 inch.

3.7.1.4 Bartacking. Bartacking shall be 1/2 $\pm$ 1/16 inch in length and 1/8 $\pm$ 1/32 inch in width and shall contain 14 to 18 stitches, unless otherwise specified. Bartacking shall be free from thread breaks and loose or tight stitching.

3.7.2 Application of seam strapping.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

3.7.2.1 Preparation of seam area for strapping. Before applying the cement; the seam, the area along the seam where the strapping makes contact, and the surface of the strapping to be adhered, shall be thoroughly cleaned with a suitable cleaning agent which does not degrade the butyl coating.

3.7.2.2 Strapping of seams. The seams, where required, shall be strapped on both the inside and the outside using the cement specified in 3.3.4. Each individual seam shall be strapped with a continuous length of strapping with the strapping centered on the seam. Where ends of strapping meet, a 1 $\pm$ 1/4 inch overlap shall be made. Whenever strappings intersect, they shall be overlapped. When the strapping is centered over the seam and pressed into position, the cement line shall not extend more than 3/4 inch on either side of the strapping.

3.7.3 Setting of snap fasteners. A hole shall be prepunched to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent materials and no more than two splits shall occur in the button or eyelet barrel.

3.8 Manufacturing operations requirements. The hood shall be made in accordance with all operations listed in table I. The contractor is not required to follow the exact sequence of operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

NO.	TABLE I. MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
1.	Cutting. a. The hood components shall be cut in strict accordance with patterns furnished which show size, directional lines and proper assembling of all parts. No pin tickets shall be used. The snout rings, straps, strapping, head loops and patches may be cut from ends. The use of drill holes is prohibited. NOTE: Cut to assure that the heavy coated side of material is as specified in 3.6.1 and 3.7. b. The strapping shall be cut from the coated cloth and shall be 3/4 +1/8, -0 inch wide. c. The bias binding for the snout rings shall be cut from the coated cloth specified in 3.3.2. The width shall be 3/4 to 1-1/8 inches.						
2.	Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3.1 shall be removed from production and replaced with non-defective and properly matched components.						
3.	Cutting fittings. a. Cut thirteen draw string loops from 1/2 inch cotton tape 1-1/2 ± 1/8 inches in length. b. Tubular braid, type II: Cut one length 50 ± 1/2 inches long for neck drawcord and either dip or tip						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE I. (cont'd)

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
3.	Cutting fittings. (cont'd) both ends with resin to prevent raveling (see 3.3.7.1). c. Tubular braid, type VII: Cut four pieces, two 20 ± 1/4 inches long for the snout drawcords and two 25 ± 1/4 inches long for the eyeholes. The ends of the braid shall be either finished with five rows of adjacent stitching or shall be dipped or tipped with resin to prevent raveling (see 3.3.7.2).	301	-----	8-10	B	B	
	d. Cut three head loops from coated cloth 2-1/2 ± 1/8 inches long and 1-1/8 ± 1/8 inches wide. e. Cut 17 round patches from coated cloth 1-1/2 ± 1/8 inches in diameter. f. Cut from coated cloth four 1/2 ± 1/16 inch by 1-3/4 ± 1/8 inches rectangular patches with corners rounded.						
4.	Make left and right snouts. a. Turn under ends of four 1/2 inch wide tape loops 1/4 to 3/8 inch and bartack to each snout on outer surface in location shown on pattern ± 1/8 inch. The marks on pattern indicate the center of each loop. Orientation of the loops shall be such that the folded ends of each loop are parallel to the small end of the snouts after the seaming operation in 4.b. The bartacks shall be placed 1/8 +1/16, -0 inch from the turned under edges of the tape.	Bartack	-----	14-18 per bartack	E	E	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

NO.	TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
4.	Make left and right snouts. (cont'd)						
	b. With tape loops on inside surface superimpose side edges of snouts evenly on each other within 1/16 inch and stitch with row of stitching located 3/8 ± 1/16 inch from edge. Turn and top stitch with row of stitching located 1/16 to 1/8 inch from cut edges of snouts.	301	LSq-2	8-10	B	B	
	or						
	c. As an alternate to the above, join side edges of snouts using seam type LSb-2 with 3/8 ± 1/16 inch seam allowance, stitch gauge 3/16 to 5/16 inch and stitch margin 1/16 to 1/8 inch from folded edge. Raw edges shall be on inside of snouts.	301	LSb-2	8-10	B	B	
	d. Bind the inner edge of the snout rings with the ends overlapped 1/4 inch minimum. Stitch 1/16 inch from inner edge of binding.	301	BSc-1	8-10	B	B	
	e. With outer surface of snouts facing out superimpose outer edge of snout rings on the edge of the snouts at the smallest end. With the edges of the snouts and snout rings aligned within 1/16 inch stitch with row of stitching located 1/4 ± 1/16 inch from edge. Turn and top stitch 1/16 to 1/8 inch from folded edge of snout rings. NOTE: The seam formed above shall not be strapped.	301	LSq-2	8-10	B	B	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE I. (cont'd)

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
5.	Form eyeholes in front pieces (typical left and right).						
	a. With inner surface of front piece facing up, position a 25 inch length of tubular braid around the periphery of the eyehole. The braid shall be stitched around the periphery of the eyehole starting and stopping at the intersections of the eye tab. The free ends of the braid shall hang loose at the intersections of the eye tab 8 ± 1/2 inches. The edge of the braid shall extend beyond the edge of the eyehole 1/8 to 3/16 inch and the stitch margin shall be 1/16 to 1/8 inch from the edge of the eyehole.	301	SSa-1	8-10	B	B	
	b. Turn each side edge of eye tab back 1/8 to 3/16 inch and stitch 1/16 inch from the outer edge.	301	EFa-1	8-10	B	B	
	c. Fold eye tab fully back onto inside surface of front piece and stitch across end 1/8 to 3/16 inch from edge of tab.	301	EFa-1	8-10	B	B	
	d. Pass ends of braid through the tunnel formed by the eye tab.						
6.	Make three head loops.						
	Apply cement across width of head loop strips and fold in half lengthwise with side edges aligned within 1/16 inch and press together firmly.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

NO.	TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
7.	Assemble left and right fronts, snouts and back pieces.						
	a. With outside surfaces facing each other, superimpose left and right fronts evenly, within 1/16 inch, along the edges for forming the center joining seam. Stitch along those edges with stitching located 1/4 to 5/16 inch from edges. During the stitching operation fold a head loop evenly in half within 1/16 inch and position between the fronts with the ends of the loop even with the front pieces and centered within 1/8 inch of the location shown on the pattern. Turn and top stitch with stitching located 1/8 ± 1/16 inch from folded edge.	301	LSq-2	8-10	E	E	
	b. With one snout turned inside out, position around opening in front piece with pattern marks aligned within 1/4 inch. Align edges of snouts and opening in front piece within 1/16 inch and stitch around periphery with stitch margin 1/4 ± 1/16 inch. NOTE: The outside surfaces of the snouts and front piece, where stitched together shall face each other.	301	LSq-2 (Step a)	8-10	E	E	
	c. Turn snouts right side out and top stitch 1/16 to 1/8 inch from folded edge of snouts.	301	LSq-2 (Step b)	8-10	E	E	
	d. With outside surfaces facing each other, superimpose left and right back pieces evenly, within 1/16 inch, along the edges for forming the center joining	301	LSq-2	8-10	E	E	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE I. (cont'd)

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
7.	Assemble left and right fronts, snouts and back pieces. (cont'd)						
	seam. Stitch back pieces together with stitching located 1/4 to 5/16 inch from edges. Turn and top stitch with stitching located 1/8 ± 1/16 inch from folded edge.						
	e. With the outside surfaces of the joined fronts and backs facing each other, superimpose the edges evenly within 1/16 inch and stitch along the edges with stitch margin 1/4 to 5/16 inch. During the stitching operation two head loops shall be caught in the seam. The loops shall be evenly folded in half within 1/16 inch and positioned between the front and back pieces with the ends even with the edges and centered within 1/8 inch of the locations shown on the pattern. Turn the joined front and back right side out and top stitch 1/8 ± 1/16 inch from folded edge.	301	LSq-2	8-10	E	E	
	f. Fold the bottom edge of the joined fronts and backs to the inside 1/4 to 3/8 inch and stitch 1/8 to 3/16 inch from the folded edge.	301	EFa-1	8-10	B	B	
8.	Make shoulder adjusting strap assemblies and attach to hood.						
	a. For short strap cut the basic material 4 ± 1/4 inches long by 1-1/8 ± 1/8 inches wide. Apply cement across width of strap, fold strap evenly in half across the width within 1/16 inch and press together firmly. Assemble strap to buckle and install female snap fastener as shown in figure 2.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE I. (cont'd)

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
8.	Make shoulder adjusting strap assemblies and attach to hood. (cont'd)						
	NOTE: As an option the folded strap may be stitched prior to installing fastener.						
	b. For long strap cut the basic material 19-1/2 ± 1/2 inches long by 1-1/8 ± 1/8 inches wide. Apply cement across width of long strap, fold strap evenly in half across the width within 1/16 inch, and press together firmly. Thread one end of strap through the buckle and box stitch across width of strap with a box pattern 3/8 ± 1/16 inch long and 1/8 to 3/16 inch wide, or as alternate, bartack.	301 or Bartack	-----	8-10 14-18 per bartack	E E	E E	
	c. Assemble the short and long straps by threading the straps through the buckles as shown in figure 2.						
	d. Attach free ends of shoulder strap assemblies to back of hood in location shown on pattern, ± 1/8 inch and as shown on figures 1 and 2 with a 3/8 to 1/2 inch box - X stitch pattern. Location shown on pattern is the center of the width of the strap.	301	-----	8-10	E	E	
9.	Install male snap fasteners in hood.						
	Install two male snap fasteners to front of hood at bottom in location shown on pattern, ± 1/8 inch. Stud component shall be on outside surface.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

NO.	TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
10.	Strapping of seams and application of patches prior to attachment of neck component. a. Securely cement and strap all inside and outside seams with strapping. Outside straps at sides, center, front and center back shall be turned over bottom hem and extend 1/4 inch minimum up onto inside surface of hood. Slit outside strapping on sides of head loops. Hem at bottom of hood shall not be strapped. b. On the inside surfaces of the hood components, cement the round patches over the back of the snap fasteners and attachment points for tape loops and adjusting straps. Cement the rectangular patches over the ends of the eyehole tabs and also the stitching on outside surface of hood.						
11.	Make neck component and assemble to hood.						
	a. With outer surfaces facing each other join the back and front neck pieces along the side edges. Edges shall be aligned within 1/16 inch and stitch margin shall be 1/4 to 5/16 inch. Turn and top stitch each seam with stitching located 1/8 ± 1/16 inch from folded edge.	301	LSq-2	8-10	E	E	
	b. Turn under ends of five 1/2 inch wide tape loops 1/4 to 3/8 inch and bartack to outer surface of neck component in location shown on pattern, ± 1/8 inch. The marks on pattern indicate the center of each loop. Bartack to be placed 1/8 +1/16, -0 inch from the turned under edges of the tape.	Bartack	-----	14-18 per bartack	E	E	

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

NO.	TABLE I. (cont'd) MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
11.	Make neck component and assemble to hood. (cont'd) c. Securely cement and strap the side seams on the inside and outside surfaces. d. Join neck component to inside of hood with row of stitching located 3/16 ± 1/16 inch from edge of neck. Top edge of neck shall be positioned in location shown on patterns within 1/8 inch with the back facing the back of the hood and the side seams of the hood neck components aligned within 3/8 inch.	301	SSa-1	8-10	E	E	
12.	Strapping of neck component attachment seam. Securely cement and strap inside and outside of seam for attaching neck component to hood.						
13.	Insert snout drawcord. Thread 20 inch length snout drawcords through the loops on the snouts with the free ends even and laying over the snouts joining seam. Knot ends together.						
14.	Insert neck drawcord. Thread 50 inch neck drawcord through loops in neck-piece, draw both ends of cord side by side through each hole of the cord lock, and knot ends together. Cord lock to hang at front when threaded.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE I. (cont'd)

NO.	MANUFACTURING OPERATIONS REQUIREMENTS	STITCH TYPE	SEAM AND STITCHING TYPE	STITCHES PER INCH	THREAD		
					NEEDLE	BOBBIN/ LOOPER	COVER
15.	Attach label.						
	a. Stitch four edges of cloth label to a 3-1/4 by 2 inch piece of butyl coated fabric. Cement the label assembly to the inside front of neckpiece near bottom.	301	SSa-1	8-10	E	E	
	or						
	b. The label may be stamped directly on the fabric in the same location.						
	or						
	c. Label may be stamped on a 3-1/4 by 2 inch piece of butyl coated fabric and cemented in the same location as specified in 15.a.						
16.	Cleaning.						
	Remove all stains and spots.						

NATICK Form 903
1 Dec 76 EDITION OF 1 OCT 76 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

3.9 Performance.

3.9.1 Strapping adhesion. After application of the strapping as specified in 3.5.2, the strapping adhesion shall meet the requirements of table II when tested as specified in 4.4.1 and 4.4.4, as applicable.

TABLE II. Strapping adhesion

Characteristic	Minimum requirement
Adhesion, pounds per inch of width:	
Initial	3.0
After water immersion	2.0
After heat aging	2.0

3.9.2 Leakage. The hood shall not leak when tested as specified in 4.4.4.

3.10 Functional performance. Conformance with design requirements as stipulated in this specification shall be determined on the basis of satisfactory functional performance of the hood, when the hood is worn over the M40 special purpose gas mask when examined as specified in 4.4.3.2 (see 6.4). Functional performance is defined as follows:

a. The hood shall be compatible with the M40 special purpose gas mask in all respects, i.e., all vision and respiratory component parts of the hood shall fit the counterpart components of the gas mask.

b. Accessory component parts of the hood, whose function is that of adjustment or closure, e.g., shoulder adjusting straps, snouts and eyehole closure components and studs and snap fasteners shall function readily so that the hood may be donned, adjusted, all closures made and the hood removed without difficulty or injury to the hood or gas mask.

3.11 Repairs in coating on finished hood. Areas containing coating defects may be repaired by application of two round, superimposed, 1-1/2 ± 1/4 inch diameter patches with one patch on the inside surface of the material and the other on the outside surface of the material. The patches shall be made of the coated cloth specified in 3.3.1 and shall be adhered with the cement specified in 3.3.4. The lightly coated side of the patch shall be cemented to the hood and the patch shall extend a minimum of 1/2 inch beyond all edges of the damaged area. The patch shall be smoothly and evenly adhered over its entire area, and shall be well adhered to the coated cloth so that, when subjected to flexing action between the hands, will show no lifting of the edge, and no cracking, flaking, or removal of the cement or patch. The repaired area shall show no stiffening or tackiness which would effect the serviceability of the hood. Repairing of fabric coating defects by methods other than patching are not authorized.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

3.11.1 Location and number of repairs. Repairs not exceeding four in number may be made, provided not more than two repairs are made on any one pattern part.

3.12 Workmanship. The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels. Utmost care shall be taken during component and subassembly fabrication to ensure quality workmanship and safety of the service person using the item.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3, and tested as specified in 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document. In addition, testing shall be performed on the material listed in table III for the characteristics shown. The sample shall consist of a 1 pint composite of the cement. The number of cement containers to be sampled in making up the composite shall be based on inspection level S-1. Any test failure shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE III. Component tests

Component and lot expressed in terms of	Characteristic	Specification reference		Requirements applicable to		Number determinations per unit	Results reported as	
		Requirement	Test method	Individual unit	Lot aver		Pass or fail	Numerically to nearest
Cement (1 gallon)	Material identification	3.3.4	1/	-	-	-	-	-
	Cold crack at -20°F	3.3.4	4.5.2	X	-	1	X	-
	Hydrostatic resistance	3.3.4	4.5.3	-	X	5	-	1 percent psi
	Adhesion after water immersion	3.7.1	4.5.1.2 2/	-	X	5	-	0.1 lb. per inch of width
	Adhesion after heat aging	3.7.1	4.5.1.3 2/	-	X	5	-	0.1 lb. per inch of width

1/ A certificate of compliance shall be submitted and will be acceptable for the stated requirement.

2/ Two 4 inch wide by 1 yard long samples of coated cloth specified in 3.3.1 shall be joined using seam and stitch type specified in operation 7.a. of table I. The seamed samples shall then be strapped on one side only with a 1 inch strip of strapping material specified in 3.3.3 utilizing the cement composite and using the strapping procedures specified in 3.7.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. Inspection of the hood and its components shall be made during the manufacturing operations to ascertain that construction details which cannot be examined on the finished product are in accordance with specified requirements. The in-process inspection shall include inspection of the working patterns to assure that they conform to the standard patterns, inspection of the cut parts covered by patterns to ascertain that the parts are free of material defects and damages that are classified as defects in 4.4.3.1 and are cut properly with respect to size and heavy coated side requirements, that stitching for attaching neck components is correct and that the diameter of the holes for the snap fasteners is smaller than the outside of the button and eyelet barrels. Whenever nonconformance is noted, corrections shall be made to the components affected and lot in-process. Parts which cannot be corrected shall be removed from production.

4.4.2.1 Inspection of hood components prior to strapping. The neck component prior to strapping of seams and prior to attachment to the hood with attached shoulder adjusting strap assemblies, and the hood prior to strapping of seams shall be examined for the defects listed in table IV. The lot size shall be expressed in units of individual hoods with attached shoulder adjusting strap assemblies with unattached neck component. The sample unit shall be one hood with attached shoulder adjusting strap assemblies with unattached neck component. The inspection level shall be S-4 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 15.0 for total (major and minor combined) defects.

TABLE IV. Hood component defects prior to strapping

Examine	Defect	Classification Major	Minor
Open seam	1/2 inch or less		201
	More than 1/2 inch	101	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive runoffs or skipped stitches occur.		
Runoff (see open seam)			
Seam and stitch type	Wrong seam or stitch type	102	
Stitch tension	Loose, resulting in loose bobbin or top thread		202
	Excessively tight, resulting in puckering of material		203

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE IV. Hood component defects prior to strapping (cont'd)

Examine	Defect	Classification Major	Minor
Stitches per inch	One to two stitches less than minimum specified		204
	Three or more stitches less than minimum specified	103	
	More than the maximum number of stitches per inch:		
	- but not weakening material		205
	- resulting in weakening of material	104	
Thread breaks and skipped stitches (on type 301 stitching)	Thread breaks or two or more consecutive or skipped stitches not overstitched or backstitched		206
Stitching ends (on type 301 stitching)	Ends of stitching not secured as specified (except when caught in other stitching or turned under in a hem)		207
Rows of stitching	Any row missing	105	
Needle chews	Any needle chew	106	
Stitch margin	Not within specified tolerance		208
Bartacks	Any bartack omitted	107	
	Any bartack not as specified or not in specified location		209
	Loose stitching, incomplete or broken stitching		210

4.4.2.2 End item critical defect examination. Every end item, prior to the examinations in 4.4.3, shall be examined for the critical defects listed in table V. Any end item found to contain one or more critical defects shall be rejected.

4.4.3 End item examination.

4.4.3.1 End item visual examination. The end items shall be examined for the defects listed in table V. The lot size shall be expressed in units of hoods. The sample unit shall be one hood. The inspection level shall be II

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 15.0 for total (major and minor combined) defects. The finding of one or more critical defects shall be cause for rejection of the lot.

TABLE V. End item visual defects

Examine	Defect	Classification Critical	Major	Minor
Braid or tape	Cut edge		101	
	Frayed edge			201
Coated fabric, including strapping and patches	Cut, tear, or hole	1		
	Abrasion mark or scratch which extends through the coating to a point where base fabric yarns or fabric weave can be seen	2		
	Uncoated area	3		
	Pit, blister, tunnel, or delamination of coating	4		
	Lump or imbedded foreign matter which protrudes so as to be readily abraded from material or easily removed	5		
	Crease or wrinkle which when flattened by pulling manually results in delamination of coating from base fabric	6		
	Spot, stain, or streak more than 1 inch in combined direction which cannot be readily removed with naptha or water			202
	Brittle area which when bent results in a crack	7		
NOTE:	A pick glass may be used to determine the degree of deficiency. If any of the above conditions occur on a reinforcement patch, hem, or adjustment strap, it shall be classified as a minor defect.			
Hardware (general)	Broken or malformed, corroded area, burr, or sharp edge		102	
	Finish omitted			203

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE V. End item visual defects (cont'd)

Examine	Defect	Classification Critical	Major	Minor
Hardware (general) (cont'd)				
Snap fasteners	Any fastener not functioning properly, i.e., fails to snap closed, provide a secure closure, or to open freely		103	
	Clinched excessively tight, cutting adjacent material		104	
	Clinched loosely, permitting either component to rotate freely:			
	- but not to the degree that either component can be expected to become detached during use			204
	- to the degree that components can be expected to become detached during use		105	
	More than two splits in eyelet or button barrel			205
	Incorrect style		106	
NOTE:	The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.			
Buckle	Not as specified		107	
Design and construction	Any characteristic not in accordance with specified requirements	8		
	Heavily coated side not on exterior of hood		108	
	Any reinforcement patch omitted		109	
Repairs	Patch diameter less than 1-1/4 inches		110	
	Patch diameter greater than 1-3/4 inches			206

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE V. End item visual defects (cont'd)

Examine	Defect	Classification Critical	Major	Minor
Repairs (cont'd)	More than two patches per pattern part			207
	More than four patches per hood			208
	Damaged area patched on one side only		111	
	Heavily coated side of patch cemented to the hood			209
	Patch extends less than 1/2 inch beyond all edges of the damaged area		112	
	Patches not superimposed by more than 1/4 inch			210
	Edges of patch separate from hood or cement cracks or flakes when hand flexed as specified in 3.11 resulting in edges of patch not adhered:			
	- for a distance of 1/16 inch inward and 1/2 inch or more around periphery of patch			211
	- for a distance of more than 1/16 inch but not more than 3/16 inch inward and 1/2 inch or more around periphery of patch		113	
	- for a distance of more than 3/16 inch inward regardless of distance around periphery of patch	9		
	Patch not smoothly and evenly adhered		114	
	Patch area excessively stiff or tacky affecting serviceability	10		
	Any unauthorized repair, e.g., coating or cement applied to defect in fabric coating in lieu of patching	11		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE V. End item visual defects (cont'd)

Examine	Defect	Classification Critical	Major	Minor
Component and assembly	Any component omitted, damaged, not as specified, not firmly affixed or misplaced to such a degree that:			
	- injury to wearer may result	12		
	- serviceability is seriously affected		115	
	- serviceability is affected but not seriously			212
	Any end of braid not resin dipped, stitched, or tipped as applicable			213
Strapped seams	Any open seam resulting in a through hole	13		
	Any seam strapped on only one side	14		
	Any loose strapping, i.e., any area not cemented unless otherwise specified herein	15		
	Any blister or delamination in central area of strapping but edges are securely affixed and the bonded portion of strapping is securely cemented to fabric			214
	Strapping on one side does not completely cover stitching on seam		116	
	Strapping not centered			215
	Width of strapping not uniform			216
	Piecing of strapping on individual seams		117	
	Any ends of strapping that meet, not overlapped 1 ± 1/4 inch		118	
	Seam area covered by strapping not smooth and free from puckers or twists		119	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

TABLE V. End item visual defects (cont'd)

Examine	Defect	Classification Critical	Major	Minor
Strapped seams (cont'd)	Any opening at edge of strapping 1/16 inch or more but does not extend to stitching			217
	Any opening extending to the stitching:			
	- on one side only		120	
	- on both sides in same area	16		
	NOTE: Extent of opening (or tunnel) may be determined by the insertion of any blunt end instrument suitable for this purpose. Penetration of the instrument shall cease immediately if resistance is met.			
Unstrapped seams	Any open seam, skipped stitches, or runoff stitches on hem:			
	- 1 inch or less			218
	- more than 1 inch		121	
	Any open seam, skipped stitches or runoff on the binding seam or snout ring seam:			
	- 1/2 inch or less			219
	- more than 1/2 inch		122	
Workmanship	Cement line extends more than 3/4 inch on either side of strapping on major portion of seam			220
	Any cemented area not fully cured		123	
Marking or labels	Missing, incomplete, incorrect, not legible, not specified type or size, not in proper location, or not accomplished in the specified manner			221

4.4.3.2 Examination of hood for functional performance. The hoods shall be examined in accordance with the procedure below to determine conformance with design requirements. The lot size shall be expressed in units of hoods. The sample unit shall be one completely fabricated hood. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

inspection level shall be S-1. Any failure to conform to the functional performance requirements specified in 3.10 shall be cause for rejection of the lot.

a. The hood shall be placed over the gas mask and necessary adjustments and closure made. This involves the following operations: Secure the eyeholes around the goggles portion of the mask by means of the tubular braid, which should be drawn taut, knotted, and then allowed to fall freely inside the face portion of the hood; secure the snouts to the gas mask canister by means of the snout drawcords.

b. During this process, the inspector shall note the following details:

(1) Rupture, deformation, loosening, or detachment of any component during adjustments or closure operations.

(2) Misalignment of eyeholes causing impairment of vision through the mask goggles.

(3) Obstruction of the canister caused by misfit of the snouts on the canister.

(4) Slippage of the canister through the snout rings.

c. The hood shall be removed from the gas mask by the reverse operations detailed in "a." above.

d. During removal of the hood, the inspector shall note details in reverse order as outlined in b. (1) and b. (2).

4.4.4 End item testing. The end items shall be tested for the characteristics listed in table VI. The lot size shall be expressed in units of hoods. The sample unit shall be two completely fabricated hoods. The inspection level shall be S-2. The lot shall be unacceptable if one or more sample units fail to meet any requirement specified.

TABLE VI. End item tests

Characteristic	Requirement paragraph	Test method	Number of determinations per sample unit	Results reported as
Initial adhesion of strapping	3.9.1	4.5.1.1	5	Numerically to nearest 0.1 lb.
Leakage	3.9.2	4.5.4	1	Pass or fail

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, loose strapping, inadequate stapling, or improper taping Bulged or damaged container
Content	Number of hoods per shipping container is more or less than specified

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Adhesion of strapping.

4.5.1.1 Initial adhesion. After the specimen has aged 48 hours, the adhesion of strapping shall be determined as specified in Method 5962 of FED-STD-191, except that adhesion shall be the average of the three lowest individual load resistance registered in pounds on the autographic chart

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

divided by the width of the seam in inches. Each of the five test specimens should be taken from a different part of the item. The adhesion of strapping should be conducted on the heavily coated side (outside) of the garment.

4.5.1.2 Adhesion after water immersion. The specimen shall be immersed for 2 hours in boiling water, removed, immersed for 15 minutes in water at $75^{\circ}F \pm 5^{\circ}F$, removed from the water and while still dripping wet, tested for strapping adhesion as specified in 4.5.1.1.

4.5.1.3 Adhesion after heat aging. The specimen shall be exposed for 7 days in a circulating air oven at $158^{\circ}F \pm 2^{\circ}F$, removed from the oven, conditioned for 24 hours at $70^{\circ}F \pm 2^{\circ}F$ and 64 $\pm$ 2 percent relative humidity and then tested for strapping adhesion as specified in 4.5.1.1.

4.5.2 Cold crack of cement film. Test specimens of the coated cloth specified in 3.3.1, measuring 8 by 8 inches minimum, shall be cleaned on one side only by wiping with a suitable cleaning agent which does not degrade the butyl coating. The cleaned area shall then be coated with two layers of the cement specified in 3.3.4. Test specimens shall then be conditioned for 4 hours at room temperature and dusted until tack free. Specimens shall be tested as specified in Method 5874 of FED-STD-191 except that testing temperature shall be $-20^{\circ}F$ and specimens shall be exposed to this temperature for not less than 4 hours before testing. When performing tests, the cement side shall be considered the heavily coated side.

4.5.3 Hydrostatic resistance. Ten 8 inch by 8 inch specimens shall be randomly selected from a 1 yard piece of the coated cloth specified in 3.3.1. Five specimens shall be tested for hydrostatic resistance as specified in Method 5512 of FED-STD-191. The remaining five specimens shall be cement coated as specified in 4.5.2 and tested for hydrostatic resistance in accordance with Method 5512. The side without the cement coating shall be exposed to the water.

4.5.4 Leakage test. Press the top of the hood down to form a pocket approximately 10 inches in diameter and 6 inches deep. The eyepiece openings shall form part of the rim of the pocket. Pour water carefully into this pocket without getting any of the water into the eyepiece opening. Let the water stand for 5 minutes. Carefully empty the pocket without spilling any water on the inside of the hood. Turn hood inside out with dry hands and inspect for evidence of water leakage.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, as specified (see 6.2).

5.1.1 Level A preservation. Each hood shall have all metal components cushioned. The cushioning material shall have a minimum thickness of 1/8 inch and shall conform to type I of PPP-C-1797. When taping of cushioning

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

material is performed, the tape shall be 1 inch wide and conform to type III, grade B of PPP-T-45. When tape is applied, it shall not come in contact with the hood. The hood shall be folded to approximately 15-1/2 by 9-1/2 inches and shall be inserted into a plastic bag conforming to A-A-50083.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Twenty hoods, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, grade V2s of PPP-B-636. Inside dimensions of the box shall be approximately 19-1/2 inches in length, 16 inches in width and 13 inches in depth. Each box shall be closed, waterproofed and reinforced in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Twenty hoods, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Inside dimensions of the box shall be approximately 19-1/2 inches in length, 16 inches in width and 13 inches in depth. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing. Hoods, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), hoods, packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 95 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The hood is intended for use over the M40 Special Purpose Mask and with the Coverall, Toxicological Agents Protective, M3. The ensemble provides protection against toxicological agents.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Special provisions for verification inspection of Life Support Clothing and Equipment (see 1.1).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article sample is required (see 3.1, 4.3 and 6.3).
e. Level of packing (see 5.2).
f. Type and class of unit load specified (see 5.2.1).
g. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
h. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Samples. For access to samples, address the contracting activity issuing the invitation for bids or request for proposal or as directed by the contracting activity. Any M40 gas mask will be provided for functional test on award of contract (see 3.10).

6.5 Subject term (key word) listing.

Chemical protection
Coveralls
Headgear
Life Support
LSC&E
M40 special purpose gas mask

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 11, 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

(Project 8415-0850)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.




FIGURE 1. HOOD, GAS MASK, SPECIAL PURPOSE, TOXICOLOGICAL AGENTS PROTECTIVE, M3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.




FIGURE 2. HOOD, GAS MASK, SPECIAL PURPOSE, TOXICOLOGICAL AGENTS PROTECTIVE, M3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8 In block 1, both the document number and revision letter should be given
2. The submitter of this form must complete blocks 4, 5, 6, and 7
3. The preparing activity must provide a reply within 30 days from receipt of the form

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER	2 DOCUMENT DATE (YYMMDD)
	MIL-H-44428A	1991 December 18

3 DOCUMENT TITLE

HOOD, GAS MASK, SPECIAL PURPOSE, TOXICOLOGICAL AGENTS PROTECTIVE, M3

4 NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible Attach extra sheets as needed)*

5 REASON FOR RECOMMENDATION

6. SUBMITTER

a NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8 PREPARING ACTIVITY

a NAME	b TELEPHONE (Include Area Code)	
U.S. Army Natick RD&E Center	(1) Commercial 508-651-4532	(2) AUTOVON/DSN 256-4532
c ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-IRT Natick, MA 01760-5019	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041 3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP2, JUL 91 *Previous editions are obsolete* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.