INCH-POUND

MIL-S-44429
5 September 1991

MILITARY SPECIFICATION

SLEEPING BAG SYSTEM, FOR INTERMEDIATE COLD WEATHER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a complete intermediate cold weather, sleeping bag system consisting of intermediate cold weather sleeping bag, waterproof and moisture vapor permeable sleeping bag cover, and a nylon stuff bag to carry the system.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5019 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment, Equipage; General Specification For
MIL-B-44306 - Bag, Stuff, Sleeping System
MIL-C-44307 - Cover, Bivy, Sleeping System
MIL-S-44309 - Sleeping Bag, For Sleeping Systems

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 System components. The components of the sleeping bag system shall be as specified in 3.1.1 through 3.1.3.

3.1.1 Sleeping bag. The sleeping bag shall conform to type II of MIL-S-44309.

3.1.2 Bivy cover. The sleeping bag cover shall conform to MIL-C-44307.

3.1.3 Stuff bag. The system stuff bag shall conform to MIL-B-44306.

3.2 System compatibility. The sleeping bag and the sleeping bag cover (bivy) shall be compatible. The bivy cover shall attach to the sleeping bag by the means provided without excessive force or distortion of the component material.

3.3 Workmanship. All components of the sleeping bag system shall comply with the workmanship requirements specified in the applicable documents and drawings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 Compatibility examination. The bivy cover shall be attached to the sleeping bag by the means provided. The assembled items shall be laid out straight and flat, with the head opening facing upward. The assembled items shall be examined for the defects listed below. The lot size shall be expressed in units of sleeping bag systems. The sample unit shall be one assembled sleeping bag system. The inspection level shall be S-3 and the finding of any defects shall cause rejection of the lot.

Examine	Defect
Fit of bivy cover to sleeping bag	Excessive force required to secure snap fasteners due to misalignment, fabric tension, or dimensions out of tolerance. Excessive bulge or twist due to misalignment of snap fasteners or dimensions out of tolerance.
Securing of bivy cover flap	Flap cover too short or location of snap fasteners out of alignment or dimensions out of tolerance.

4.2.3 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling. Bulged or distorted container.
Content	Not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

4.2.4 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defects
Finished dimensions	Length, width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Load not bonded as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial (see 6.2).

5.1.1 Level A preservation. One stuff bag shall be put inside a sleeping bag. The sleeping bag shall have all fasteners closed. A bivy cover shall be attached to the sleeping bag by means provided. The sleeping bag shall then be laid out straight and compactly rolled from the foot to the head, and secured by means of stretch wrapping or tied with cotton tape toward the ends of each rolled bag.

5.1.2 Commercial. Each sleeping bag system shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. One complete sleeping bag system preserved as specified in 5.1, shall be packed in a close-fitting end-opening fiberboard container conforming to style RSC-L, grade V2s of PPP-B-636. Inside dimensions of each shipping container shall approximate 11 inches in length, 10 inches in width, and 26 inches in depth. The flutes of the box and liner shall run parallel to the score line of the opening of the box (see PPP-B-636, figure 2). The height of the liner shall be the full inside width of the box. Each shipping container shall be closed in accordance with method V and reinforced as specified in the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

other materials (all, however, be procured on a local basis from qualified

5.2.2 Level B packing. One complete sleeping bag system preserved as specified in 5.1, shall be packed in a close-fitting, end-opening fiberboard container conforming to style RSC-L, type CF, variety DW, class domestic, grade 275 of PPP-B-636. Inside dimensions of each shipping container shall approximate 11 inches in length, 10 inches in width, and 26 inches in depth. The flutes of the box and liner shall run parallel to the score line of the opening of the box (see PPP-B-636, figure 2). The height of the liner shall be the full width of the box. Each shipping container shall be closed in accordance with method II, as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. Each sleeping bag system preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), sleeping bag systems packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I, (4-way entry), type IV, or V of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 35 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special markings required by the contract or purchase order, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The sleeping bag system is intended for use in intermediate cold weather conditions by personnel of the Department of Defense.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:59Z
Check the source to verify that this is the currentversion before use.

6.3 Subject term (keyword) listing.

Bivy cover
ICWSS
Moisture vapor premeable
Stuff bag

Custodians:

Army - GL
Air Force - 99
Navy - NU

Review activities:

Army - MD
DLA - CT

Preparing activity:

Army - GL

(Project 8465-0077)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-44429	1991 September 5

3. DOCUMENT TITLE

SLEEPING BAG SYSTEM, FOR INTERMEDIATE COLD WEATHER

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4532	256-4532
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-IRT Natick, MA 01760-5019	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:59Z
Check the source to verify that this is the current version before use.