INCH-POUND

MIL-DTL-44416
INT. AMENDMENT 1(GL)
4 April 1995

DETAIL SPECIFICATION

VEST, AIRCREW SURVIVAL

This interim amendment forms a part of MIL-V-44416(GL), dated 28 February 1991, and is approved for use by all departments and agencies of the Department of Defense.

Page 2

2.1.1, under "SPECIFICATIONS, MILITARY", Delete:
"MIL-C-7219 - Cloth, Duck, Nylon" and substitute:
"MIL-K-818 - Knife Pocket, General purpose. MIL-C-44043 - Cloth, Ballistic, Nylon, Light-weight, Water-repellent treated".

Page 3

2.1.1, under "SPECIFICATION MILITARY", Delete:
"MIL-C-83429 - Cloth, plain and basket weave, aramid".

FSC 8470

AMSC N/A

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

3.3, line 2, after "drawings", Delete the period and add: "and patterns."

3.3.3, Delete: "Cloth, duck, nylon. The nylon cloth used for the radio pocket back shall conform to type III, class 1 of MIL-C-7219. The color shall be Olive Green 106." and substitute: "Cloth, ballistic, nylon, light-weight, water-repellent treated. The cloth used for lining the radio pocket and radio pocket back shall conform to class 2, of MIL-C-44043."

3.3.8 Webbing, textile, textured or multifilament nylon., line 3, Delete: "type III" and substitute: "type IV".

3.3.10 Tape and webbing nylon., line 4, Delete: "type IV" and substitute: "type III".

3.3.12 Fasteners, slide, interlocking., at the end, Add: "The slide fastener pull shall have a hole with sufficient size to accommodate a 1/4 inch wide thong. The thong shall have a minimum length of 3 inches folded."

Add as new paragraph:

"3.3.12.1 Tape, slide fastener. The slide fastener tape shall be 100% polyester, 3/4 +1/16 -1/32 inch wide; the color shall be Olive Green 106, and shall conform to V-F-106. The colorfastness requirement shall not apply."

Add as new paragraph:

"3.3.12.2 Slides. The slide shall be black, 3/4 inch wide, brass and conform to ITW Waterbury, part #00171-22. A quantity of two is required per vest."

3.3.14, line 4, after "see", Delete: "6.4" and substitute: "6.5".

At the end of paragraph, Add:

"The dimension of the operators manual, shall be 5-1/2 inches long by 4 inches wide by 5/16 of an inch thick. A uniform distance around the perimeter shall be maintained between the border and the print. The staple, when placed, shall not obscure any of the print."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

3.3.15, at the end of paragraph, Add: "Six D-rings are required for each vest."

3.3.16, line 2, after "see", Delete: "6.5" and substitute: "6.4", and at the end of paragraph, Add: "Two V-rings are required for each vest."

3.3.17, at the end of paragraph, Add: "Two snap ejectors are required for each vest."

3.3.18, at the end of paragraph, Add: "One adapter is required for each vest."

Page 8

3.3.19, line 2, Delete: "chest" and substitute: "top loops of the leg", and line 3, at the end of paragraph, Add: "One piton is required for each vest."

TABLE I, Vest components. Delete: "Life preserver, underarm, LPU-10/P, pneumatic (4220-00-850-8655) 3.3.20.1 Each 1"

substitute:
"Knife, pocket, general purpose (5110-00-162-2205) MIL-K-818 Each 1".

Page 9

3.4, line 2, after "(see 6.2)", Delete: "the vest components shall have been manufactured within one year prior to the date of delivery." and substitute: "All components with an expiration date shall have a minimum of one year shelf life after date of assembly."

3.6.1 List of pattern parts, under "Nomenclature", Delete: "Radio set pocket back 1".

Page 10

3.6.1 List of pattern parts, under: "Material", Delete: "Cloth, plain weave, aramid" and substitute: "Cloth, ballistic, nylon, lightweight, water-repellent treated", and under "Nomenclature", delete: "Radio set pocket 1".

After, "webbing, textile, woven nylon,", Add to table:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

"Material	Nomenclature	Parts
Templates	Right front inside	0
	Left front inside	0
	Left front strap	0
	Left Front shoulder strap	0
	Right Front strap	0
	Right Front Shoulder strap	0
	4 point Stitch guide	0
NOTE: The following pattern parts are for back of vest, (clarity purposes)	Channel adjustment strap tunnel	0
	Left back shoulder strap	0
	Right back shoulder strap	0"

3.8 Fit., line 2-4, Delete: "The components required for the fit examination shall be obtained from the contracting activity (see 6.4)" and substitute: "Wood blocks meeting the dimensions specified below shall be used for the fit examination of the pockets. See Figure 1, for pocket number and component assignment.

Fit examination

Pocket Number	Component Number	Component Name	Block Dimensions (In.)
1.	1.	Signal, Smoke and Illumination	5-1/4 x 1-1/4 x 1
2.	2.	Radio Set	8 x 3-7/8 x 1- 1/2
3.	3.	Survival Packet, Type I	4 x 5 x 1-1/4
4.	4.	Compass, Magnetic	2-1/4 x 3-3/8 x 1-1/4
5.	5.	Mirror, Emergency Signaling	2-1/4 x 3-3/8 x 1-1/4
6.	6.	Survival Packet, Type II	4 x 5 x 1-1/4
7.	7.	Light Marker Distress	2-1/2 x 4-3/4 x 1
8.	8.	Paper, Chemical Agent	
8.	9.	Operator's Manual	
8.	10.	Signal Kit, Pocket Knife	5-1/4 x 5-1/4 x 1-3/4
9.	11.	Sea Dye Marker	5 x 2-3/4 x 1-1/2
10.	12.	Spare Pocket	5-1/4 x 1-1/4 x 1
11.	13.	Survival Packet, Type III	7 x 4 1-1/2
12.	14.	Survival Packet, Type IV	7 x 4 x 1-1/2"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

TABLE II, operation 1.b, line 2, Delete: "plain weave aramid" and substitute: nylon, ballistic lightweight, water-repellent treated".

Operation 1.e, line 2, Delete: "in the following lengths" and substitute: "in accordance with the patterns",

Reduce all (5) sizes by three inches:

Delete: " 57, 61, 65, 69, and 73" and substitute: "54, 58, 62, 66 and 70".

Operation 1.f, line 1 and 2, Delete: "in the following lengths" and substitute: "in accordance with the patterns".

Page 13

Operation 1.f, Cutting., reduce all (5) sizes by six inches:

Delete: "126, 128, 130. 132 and 134" and substitute: "120, 122, 124, 126 and 128".

Operation 1.h, line 3, Delete: "five" and substitute: "three".

After, operation 1.k, Add: "operation 1.l. The webbing for the LPU-21 attachment straps shall be cut 9 inches long (2 for each vest) and two, 2 inch reinforcement pieces."

Page 14

Operation 4.a, Delete: "At each of the first loop mid point measurements found on the following chart, fold the edges of the webbing together so that they meet at the middle of the webbing.

Size	Length	Tog loop	Bottom loop
X-small	126 inches	14-1/2 inches	32-1/2 inches
Small	128 inches	14-1/2 inches	32-1/2 inches
Medium	130 inches	14-1/2 inches	32-1/2 inches
Large	132 inches	14-1/2 inches	32-1/2 inches
X-large	134 inches	14-1/2 inches	32-1/2 inches"

and substitute: "Refer to pattern of size to determine top and bottom loop mid point measurements. The top and bottom loop shall extend 1 inch from the edge of the vest."

Page 15

Operation 4. d, line 1-4, Delete: "at the bottom loop midpoint, however, curl the edges over facing the opposite side of the webbing from the first." and substitute: "at the top loop. The folded edges of webbing shall be visible."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

Page 15

Operation 5.a, under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Page 16

Operation 5.c, line 3 and 4, Delete: "vertical stitch or place a 1 ± 1/16 inch", under "STITCH TYPE", Delete: "301 or", under "SEAM AND STITCHING TYPE", Delete: "SSa-2", under "STITCHES PER INCH", delete: "10-12" and substitute: "8-10".

Operation 5.d, line 3 and 4, Delete: "boxstitch with a 1-1/2 by 3/4 inch boxstitch.", and substitute: "stitch a 1-1/2 by 3/4 inch box-X stitch.", under "SEAM AND STITCHING TYPE", Delete: "LSb-2" and substitute: "EFb-1", under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Operation 5.e, under "STITCHES PER INCH", Delete: "10-12 and substitute: "8-10".

Operation 6., under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Page 17

Operation 7.a and 7.b, under "STITCHES PER INCH", Delete: "10-12" and "8-10".

Operation 8.a, under "STITCHES PER INCH", Delete: "10-12" and "8-10"

Page 18

Operation 8.c, line 1, Delete: "waist" and substitute: "chest" also, line 2, delete: "webbing" and substitute: "tape". Under: "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Operation 8.d, line 2, after "bartack", add: "1/4 inch".

Operation 9., line 3, after "the", Add: "back"
line 4, after "the", Add: "front"
line 5, delete: "tape." and substitute: "tape stitching through all plies of material." Under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Page 19

Operation 10., "Attach chest adjustment strap.", and "11. "Attach leg straps.", Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

Add: new operation

"10. Attach leg straps."

Operation 10.a, line 1, Delete: "first" and substitute: "top"
line 2 and 3, Delete: "folded edges are outside the loop and free end is underneath." and substitute: "strap is superimposed, straddling the vest front."
line 4 and 5, Delete: "vest, just above the slide fastener on the left side." and substitute: "as specified on pattern. This shall result in the top loop extending 1 ± 1/4 inch from top edge of the vest.".

Operation 10.b, under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Operation 10.c, Delete in its entirety and substitute: "Insert the free end of the leg strap into the narrow slot of the "V" ring and slide it all the way to the loop center."

Operation 10.d, Delete in its entirety and substitute: "Stitch around the entire piece, of webbing in a box pattern, holding it to the vest as indicated on pattern. This should result in the second loop mid point falling 2 ± 1/4 inches below the bottom edge of the vest.".

Operation 10.e, and 10.f, under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Operation 10.g, Delete in its entirety.

Operation 10.i, line 4, after "point", Delete: "4" and substitute: "3".

Operation 11., "Attach leg straps.", Delete in its entirety.

Add: new operation

"11. Attach chest adjustment strap."

Operation 11.a, line 3, Delete: "2 - 1/2" and substitute: "4". Under "STITCHES PER INCH, Delete"10-12" and substitute: "8-10".

Operation 11.b, Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

Add: new operation

"12. Attach hook portion of fastener tape

301	LSbj-1	8-10	E	E

Position the hook portion of fastener tape for the inside pockets on the body of the vest, as indicated on patterns. Stitch on all four sides 1/16 to 3/32 inch from the edge of tape."

Page 21

Under operation "NO.", Delete: "12." and substitute: Operation 13.a, and 13.b, under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Under operation "NO.", Delete: "13." and substitute: "14.". On line 1, Delete: "17 ± 1/8 inches long" and substitute: "within 1/8 inch tolerance". Under "SEAM AND STITCHING TYPE", Delete: "LSb-2" and substitute: "SSau-2". And under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Under operation, Delete: "14. Attach waist adjustment straps.", in its entirety and substitute: Operation:

"15. Attach dee rings to bottom of vest.

301	LSd-1	8-10	E	E

Cut six 4-1/2 ± 1/8 inch pieces of 3/4 inch webbing. Attach one small dee ring on each piece, fold with 3/4 inch of one side folded under and box-X stitch with a 1/2 to 9/16 inch by 3/4 to 7/8 inch box-X stitch. The inner edge of the box-X stitch must penetrate through the webbing and raschel in locations indicated on patterns."

Page 22

Top of page, before operation, "14. Attach waist adjustment straps. (cont'd)", Add: new operation:

"16. Attach the LPU-21 attachments straps.

a. Fold one end of the webbing under 2 inches and stitch the folded end on the vest with a 1-1/2 inch Box-X stitch securing the 2 inch reinforcement piece (inside of vest).

b. Fold under the other end 1 inch in the opposite direction and stitch a 3/4 inch Box-X.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

c. Pull slide through webbing followed by the 3/4 inch D-ring. Fold over the D-ring and pull the webbing back through the slide. To ensure that the folded under edge faces the vest when in the finished configuration."

Under operation "NO.", Delete: "14." and substitute: "17.". Operation, "Attach waist adjustment straps." Delete: "(cont'd)", and Add the following paragraphs:

a. Diagonally cut the webbing for the tunnels for the waist adjustment straps 3-3/4 ± 1/8 inches, to match the shape indicated on the pattern. Position as indicated on the pattern and stitch the webbing to the inside of the vest on the diagonal ends.

301	LSbj-1	8-10	FF	FF

b. Align the bare end of the loop waist adjustment strap 3/4 inch in back of the side seam below the right armhole, 1/2 inch above the bottom edge of the vest. The loop fastener tape shall face the inside of the vest. Stitch to vest with a 1-1/2 by 1/4 inch box-X stitch.

301	LSb-2	8-10	FF	FF

Under operation "17.c", line 2, Delete: "12.b." and substitute: "17.b.", line 3, after "hook", Add: "fastener tape".

Operation, "15. Attach dee rings to bottom of vest." Delete in its entirety.

Under operation "NO.", Delete: "16." and substitute: "18.".

Under operation "NO.", Delete: "16." and substitute: "18.", and operation 18.b. through 18.h., under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

Page 24

Under operation "NO.", Delete: "17." and substitute: "19.".

Operation 19.b., Delete: "The two pieces cut for radio set pocket shall be superimposed and overedged on all four sides." And substitute: "Superimposed oxford radio set pocket on top of nylon radio set pocket and overedge on all 4 sides, such that the nylon lining is on the inside of the pocket.".

Operation 19.c, line 1, Delete: "1/2" and substitute: "1/4".

Operation 19.d, line 2, after "mirror pocket", Add: "signal pocket, sea marker pocket,".

Operation 19.e, line 1, Delete: "seven".

Operation 19.a, through 19.e, under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Page 25

Under operation "NO.", Delete: "17." and substitute: "19.".

Operation 19.(3), under "SEAM AND STITCHING TYPE", Delete: "LSd-2" and substitute: "LSd-1".

Operation 20.b., line 4 through 6, Delete: "Superimposed the two pieces cut for the radio set pocket and overedge on all four sides." and substitute: "Superimpose nylon radio set pocket back on top of oxford radio set pocket and overedge on all 4 sides, such that the nylon lining is on the inside of the pocket.".

Operation 19.(1) through 20.c., under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Page 26

Under operation "NO.", Delete: "18." and substitute: "20.".

Under operation "NO.", Delete: "19." and substitute: "21.".

Operation 21.b., under "SEAM AND STITCHING TYPE", Delete: "EFa-1" and substitute: "EFb-1".

Operation 20.d. through 21.b., under "STITCHES PER INCH", Delete: "10-12" and substitute: "8-10".

Page 27

Under operation "NO.", Delete: "19." and substitute: "21.".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

Operation 21.d., Delete in its entirety and substitute:

"d. Position the loop portion of fastener tape on each pocket, as indicated on patterns. Stitch on all four sides 1/16 to 3/32 inch from the edge of tape."	301	LSbj-1	8-10	E	E

Add new operation:

"e. Stitch the pockets directly to the vest, as indicated on patterns. Turn the edges of the pocket in 3/8 ± 1/8 and topstitch around the three sides 1/16 to 3/32 inch from the edge. For the small and x-small vest, refer to patterns."	301	LSd-1	8-10	E	E

Page 27

Add the following new operations:

"21.1 Make front slide fastener pull tabs.

a. Cut thong for slide fastener 6 ± 1/4 inch length for all sizes.

b. Fabricate the thong to finish 1/2 inch wide by 3 inches long.	301	EFp-2	8-10	E	E

c. Insert one end of the thong halfway through the tab. Fold ends together so they are even in length. Then sew a lengthwise 1/2 inch bartack, 1 inch from their ends.

21.2 Attach reinforced tape for ejector snap.

a. Thread tape for the reinforcement of the leg strap around the tension bar of the ejection snap until the ends are even. Stitch 1/2 ± 1/16 inch away from the bar.	301	SSa-2	8-10	E	E

b. Thread leg strap through the adapter of the ejector snap.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

301	LSb-2	8-10	FF	FF	

c. At the end of the webbing turn under the end of 1 ± 1/8 inch, then turn onto itself 3 times and box stitch with a 1-1/2 by 3/4 inch box stitch.

NOTE: The ejector snaps shall be threaded in such a manner that the release lever is facing away from the body and also the end has no twist in the strap.

22. Connect Piton

a. Insert Piton through the top two loops of the leg straps, as shown on Figure 1, components for vest, aircrew survival, item 16."

Under operation "NO.", Delete: "20." and substitute: "23.".

Page 37

5.1.3. Delete: "Components, preserved as specified in Table V, shall be placed in the pockets of vest as specified in Figure 1. The life preserver shall not be attached to the vest." and substitute: "Components shall be preserved as specified in Table V."

Under TABLE V., Preservation of components, Delete:

"Life preserver, underarm, LPU-IO/P, pneumatic	MIL-L-38484	1/	5.1.3.6"

and substitute:

"Knife, Pocket General Purpose	MIL-K-818		5.1.3.8"

Under "Footnote 1/", Delete in its entirety.

Page 38

5.1.3.6 Life preserver., Delete in its entirety.

Add new paragraph 5.1.3.8 the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.

Page 38

"5.1.3.8 Knife. The knife shall be unit packed in a plastic bag, .003 inch thickness conforming to type I or type II, style I of PPP-B-26."

5.2.1.2, line 1 and 2, Delete: "and life preserver,".

Page 39

5.2.2.2, line 1 and 2, Delete: "and life preserver,".

Page 41

Figure 1, "COMPONENTS FOR VEST, AIRCREW, SURVIVAL." Item number 3, after "TYPE I" Add: "KNIFE POCKET, GENERAL PURPOSE".

Preparing Activity:
DLA - CT

(Project 8470 - A160)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:57Z
Check the source to verify that this is the current version before use.