INCH-POUND

MIL-M-38510/12G
AMENDMENT 1
17 November 1992

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR,
TTL, MONOSTABLE MULTIVIBRATORS,
MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/12G, dated 20 August 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

TABLE II: Delete "Initial electrical parameters (pre burn-in) (method 5004)" and substitute "Interim electrical parameters (method 5004)".

TABLE II, group A test requirements (method 5005), class B devices: Add "10, 11".

TABLE II, additional electrical subgroups for group C periodic inspections: Delete in its entirety.

4.2a(1), delete and substitute as follows:

"(1) Test condition D or E, using the circuit shown on figure 10, or equivalent. Test condition A and the applicable burn-in circuit shall be allowed with the approval of the qualifying activity."

4.2b, delete "Initial" and substitute "Interim". (two places)

PAGE 9

4.4.3b(1), delete and substitute as follows:

"(1) Test condition D or E, using the circuit shown on figure 10, or equivalent. Test condition A and the applicable burn-in circuit shall be allowed with the approval of the qualifying activity."

4.4.3c, delete in its entirety.

PAGE 44

TABLE III, device type 01, subgroup 7, symbol column, after truth table test: Add "14/".

TABLE III, device type 01, subgroup 7, test numbers 21 through 37, A_1, A_2, and B columns: Delete all "2.0 V" and substitute "A". Delete all "0.8 V" and substitute "B".

TABLE III, device type 01, subgroup 8, after T_C = -55°C: Add "14/".

PAGE 45

TABLE III, device type 01, $t_{P(OUT)3}$ and $t_{P(OUT)4}$, test numbers 44 and 45, R_I column: Delete "∞".

TABLE III, device type 01, $t_{P(OUT)3}$ and $t_{P(OUT)4}$, test numbers 52 and 53, R_I column: Delete "∞".

TABLE III, device type 01, footnote 10/: Delete "15 pF" and substitute "25 pF".

TABLE III, device type 01, at end of the table: Add footnote 14/ as follows:

"14/ A = 2.0 V and B = 0.8 V for subgroup 7. A = 2.4 V and B = 0.4 V for subgroup 8."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:50Z
Check the source to verify that this is the current version before use.

PAGE 47

TABLE III, device type 02, t_W, test number 50, maximum limits column: Delete "3.76" and substitute "4.0".

TABLE III, device type 02, $t_{W(MIN)}$, test number 58, R_XC_X column: Add "1/".

PAGE 49

TABLE III, device type 03, t_W, test numbers 60 and 61, minimum limits column: Delete "3.08" and substitute "3.10".

TABLE III, device type 03, t_W, test numbers 60 and 61, maximum limits column: Delete "3.76" and substitute "3.80".

PAGE 50

TABLE III, device type 03, $t_{W(MIN)}$, test number 75, symbol column: Delete "14/" and substitute "13/".

TABLE III, device type 03, $t_{W(MIN)}$, test number 76, symbol column: Delete "13/" and substitute "14/".

TABLE III, device type 03, at end of footnotes 6/ and 8/: Add the following:

"At manufacturers option, this may be verified in subgroups 9, 10, and 11."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1310)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:50Z
Check the source to verify that this is the current version before use.