TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions $-55°C \le T_C \le +125°C$	Device type	Limits Min	Limits Max	Units
Propagation delay time high-to-low level output from A, B, or C to W	t_{PHL1}	R_L = 390Ω±5%, C_L = 50 pF minimum (figure 5)	02	6	40	ns
			06	6	48	
Propagation delay time low-to-high level output from A, B, or C to W	t_{PLH1}		02	6	38	ns
			06	6	43	
Propagation delay time high-to-low level output from A, B, or C to Y	t_{PHL2}		02	8	49	ns
			06	8	60	
Propagation delay time low-to-high level output from A, B, or C to Y	t_{PLH2}		02	8	45	ns
			06	8	58	
Propagation delay time high-to-low level output from strobe to W	t_{PHL3}		02	6	37	ns
			06	6	38	
Propagation delay time low-to-high level output from strobe to W	t_{PLH3}		02, 06	6	35	ns
Propagation delay time high-to-low level output from strobe to Y	t_{PHL4}		02	8	46	ns
			06	8	52	
Propagation delay time low-to-high level output from strobe to Y	t_{PLH4}		02	8	42	ns
			06	8	52	
Propagation delay time high-to-low level output from D_0-D_7 to W	t_{PHL5}		02, 06	3	32	ns
Propagation delay time low-to-high level output from D_0-D_7 to W	t_{PLH5}		02, 06	3	26	ns
Propagation delay time high-to-low level output from D_0-D_7 to Y	t_{PHL6}		02	6	41	ns
			06	6	44	
Propagation delay time low-to-high level output from D_0-D_7 to Y	t_{PLH6}		02	6	33	ns
			06	6	36	
Propagation delay time high-to-low level output from data to Y	t_{PHL1}	R_L = 390Ω±5%, C_L = 50 pF minimum (figure 6)	03	3	29	ns
Propagation delay time low-to-high level output from data to Y	t_{PLH1}		03	3	28	ns
Propagation delay time high-to-low level output from A or B to Y	t_{PHL2}		03	6	44	ns
Propagation delay time low-to-high level output from A or B to Y	t_{PLH2}		03	6	42	ns
Propagation delay time high-to-low level output from strobe to Y	t_{PHL3}		03	6	32	ns
Propagation delay time low-to-high level output from strobe to Y	t_{PLH3}		03	6	42	ns

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:51Z
Check the source to verify that this is the current version before use.