MIL-M-38510/5C
AMENDMENT 2
31 July 1999
SUPERSEDING
AMENDMENT 1
6 November 1987

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, TTL

AND-OR-INVERT GATES, MONOLITHIC SILICON

INACTIVE FOR NEW DESIGN AFTER 07 September 1995

This amendment forms a part of MIL-M-38510/5C,
dated 20 May 1985, and is approved for used by
all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete and substitute as printed above.

1.2.3, case outline F-3: Delete "1/8" and substitute "1/4".

1.3: Delete "2/" reference. Also delete footnote at bottom of page.

PAGE 3

* TABLE I, test conditions for V_{OH}: Delete "V_{IN} = 0.8 V" and substitute "V_{IN} = 0.8 V for device type 01, 02, 04; V_{IN} = 0.7 V
* for device type 03".

PAGE 4

TABLE II, group A test requirements, class B devices: Add "10, 11".

TABLE II: Delete entry for "Additional electrical subgroups for group C periodic inspection" in its entirety.

PAGE 10

TABLE III, subgroup 1, add "T_C = +25°C".

PAGE 11

TABLE III, subgroup 1, add "T_C = +25°C".

TABLE III, test number 35, pin 2C: Add 5.5 V.

TABLE III, test number 35, pin 2D: Add "GND".

TABLE III, test number 36, pin 2C: Delete "5.5 V" and substitute "GND".

TABLE III, test number 36, pin 2D: Delete "GND" and substitute "5.5 V".

TABLE III, test number 37, pin 2C: Delete "GND".

TABLE III, test number 37, pin 2D: Delete "5.5 V".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:47Z
Check the source to verify that this is the current version before use.

TABLE III, test number 51, measured terminal column: Delete "X" and substitute "$\overline{X}$".

TABLE III, test number 51, max limits column: Delete "2.9" and substitute "-2.9 mA".

TABLE III, test number 51a, max limits column: Delete "2.58" and substitute "-2.58 mA".

TABLE II, subgroups 9 and 10, test numbers "53, 54, 55, 56, 55, 56, 55, 56:
Delete and substitute "53, 54, 55, 56, 57, 58, 59, 60".

PAGE 12

TABLE III, subgroup 1, add "T_C = +25°C".

PAGE 13

TABLE III, subgroup 1, add "T_C = +25°C".

PAGE 14

- TABLE III, title, terminal condition low: Delete "0.8 V" and substitute "0.7 V".
- TABLE III, subgroup 1, V_{OH}, test no. 1: Delete "0.8 V" in four places (inputs A, C, E, G) and substitute "0.7 V".
- TABLE III, subgroup 1, V_{OH}, test no. 2: Delete "0.8 V" in four places (inputs B, D, F, H) and substitute "0.7 V".

TABLE III, subgroup 1 add "T_C = +25°C".

TABLE III, test number 7, pins G and H: Delete "2.7 V" and substitute "2.0 V".

TABLE III, I_{OS}, subgroup column: Delete "1" and extra ditto mark.

PAGE 15

- TABLE III, title, terminal condition low: Delete "0.8 V" and substitute "0.7 V".

PAGE 17

TABLE III, subgroup 1, add "T_C = +25°C".

PAGE 21

4.4.3b: Delete in its entirety.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI
Navy - *AS, CG, MC, OS, SH*
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5962-1858)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:47Z
Check the source to verify that this is the current version before use.