NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/375A
24 March 2021
SUPERSEDING
MIL-DTL-3943/375
2 June 2016

DETAIL SPECIFICATION SHEET


MEDAL, EBOLA CAMPAIGN MEDAL, USPHS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230)

FINISH: Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER (Excluding lug):
-1: 1-3/8 inches (REF)
-2: 11/16 inch (REF)
THICKNESS:
-1: 0.120 inch $\pm$ 0.010 inch
-2: 0.080 inch $\pm$ 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:18Z
Check the source to verify that this is the current version before use.

DECORATION SET: The decoration set shall consist of a regular size medal, miniature size medal, service ribbon and lapel button all packaged in a decoration case conforming to MIL-DTL-14633, Type XVI, with a Class 1 or 3 pad.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the pendant drape and service ribbon is MIL-DTL-11589/673.

3. The specification slash sheet for the lapel button is MIL-DTL-11484/374.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-346)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:18Z
Check the source to verify that this is the current version before use.