INCH-POUND

MIL-DTL-3943/385
27 July 2016

DETAIL SPECIFICATION SHEET

MEDAL, DISTINGUISHED PUBLIC SERVICE MEDAL,
DEFENSE POW/MIA ACCOUNTING AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT:
-1: 1-1/2 inches (REF)
-2: 3/4 inch (REF)
WIDTH:
-1: 1-1/2 inches (REF)
-2: 3/4 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:21Z
Check the source to verify that this is the current version before use.

THICKNESS:
-1: 0.156 inch ± 0.010 inch
-2: 0.095 inch ± 0.010 inch

DECORATION SET: The decoration set shall consist of a regular size medal, miniature size medal, service ribbon, and lapel button all packaged in a decoration case conforming to MIL-C-14633, Type XV, Style 3, with a Class 1 pad. The following text shall be inscribed on the top of the presentation case using 2 lines: (Line 1) DISTINGUISHED PUBLIC (Line 2) SERVICE MEDAL.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape and for the service ribbon is MIL-DTL-11589/679.

3. The specification slash sheet for the lapel button is MIL-DTL-11484/385.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2016-690)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:21Z
Check the source to verify that this is the current version before use.