NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/395A
05 April 2022
SUPERSEDING
MIL-DTL-3943/395
13 February 2017

DETAIL SPECIFICATION SHEET

DECORATION, SECRETARY'S DISTINGUISHED HONOR AWARD, DEPARTMENT OF STATE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy No. C230)

FINISH (-1 and -2) Will have two tone plating:
OBVERSE: The 6 armed stars and center seal, Epoxy resin, 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
Rays: Nickel Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 18.
REVERSE: The 6 armed stars and center circle, Epoxy resin, 24K Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:24Z
Check the source to verify that this is the current version before use.

Rays: Nickel Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 18.

DIMENSIONS:
HEIGHT (Including lug):
-1: 1-11/16 inches (REF)
-2: 27/32 inch (REF)
WIDTH:
-1: 1-1/2 inches (REF)
-2: 3/4 inch (REF)
THICKNESS:
-1: 0.150 ± 0.010 inch
-2: 0.097 ± 0.010 inch

DECORATION SET: The decoration set shall consist of a regular size pendant with ribbon drape, miniature size medal with ribbon drape, service ribbon, ribbon attachment and lapel button all packaged in a decoration case conforming to MIL-C-14633, Type XV, Style 3, with a Class 1 pad. The following text shall be inscribed on the top of the presentation case using 2 lines: (Line 1) DISTINGUISHED HONOR (Line 2) MEDAL. Lettering shall be accomplished using Bodoni MT Bold type face, 24 point caps for the first letter in each word and 20 point caps for all other letters. The words "UNITED STATES OF AMERICA" shall be accomplished using upper case, Copper Plate, 10 Point Gothic.

EPOXY: Epoxy resin shall be applied to the Decoration as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below. Hard cloisonné enamel may be used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210).

TIOH HARD ENAMEL COLOR CHIP NUMBER	LOCATION
Blue #20	Outline of Cloud (Shaded)
White #28	6 Arcs and Stars

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon, for the pendant drape and for the service ribbon is MIL-DTL-11589/683.

3. The specification slash sheet for the lapel button is MIL-DTL-11484/397.

4. The specification slash sheet for the ribbon attachment is MIL-DTL-41819/62

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:24Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-093)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:24Z
Check the source to verify that this is the current version before use.