MIL-P-50718B (AR)
AMENDMENT 4
18 January 1981
SUPERSEDING
Amendment 3
9 June 1980

MILITARY SPECIFICATION

PROJECTILE, 4.2 INCH, HE, M329A2
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-P-50718B (MU) dated 10 September 1976.

PAGE 1

2.1, under Specifications, add:

FEDERAL

TT-C-490 - Cleaning Methods and Pre-treatment of Ferrous Surfaces for Organic Coatings

Under Military Specifications, add:

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

In comments block, delete: Frankford Arsenal, ATTN: SARFA-MDM, Philadelphia, PA 19137; add: US Army Armament Research and Development Command, ATTN: DRDAR-QA, Dover, NJ 07801.

PAGE 2

2.1 Under Drawings

Delete: Armament Command; add: U.S. Army Armament Research and Development Command (ARRADCOM)

PRODUCT AND PACKAGING DRAWINGS

Delete: LI 11738359 - Inspection Equipment List for Projectile, 4.2 Inch, HE, M329A2, Metal Parts Assembly

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

Add: INSPECTION EQUIPMENT DRAWINGS

9278618 - Alignment Gage

2.2, delete:

ASTM B 117 - Salt Spray (Fog) Testing

PAGE 6

4.3.2.2, delete: 11738399, add: 11738360-1; delete: Critical 1 in its entirety; add: Critical 1. Metal defective (band seat area) Visual (Probe Light)

PAGE 7

4.3.2.3 delete: Critical 1 in its entirety; add: Critical 1. Metal defective (after cleaning and surface preparation for painting). Visual (Probe Light)

PAGE 9

* 4.3.2.5, delete: Paragraph in its entirety.

PAGE 10

* 4.3.2.5 (Cont'd), delete: Paragraph in its entirety.

4.3.2.7, delete: in a Government certified chamber gage; add: in chamber gage (dwg 9278168).

PAGE 12

4.3.3.5, delete: the applicable specification; add: TT-C-490

4.3.3.5.1, line 2, delete: the applicable specification; add: TT-C-490

Line 4, delete: by the applicable specification; add: therein

PAGE 13

4.3.5, delete: Paragraph in its entirety; add: new paragraph 4.3.5 Inspection equipment.-The inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

equipment required to perform the examinations and tests prescribed herein is described in the "Method of Inspection" column in the tables starting with paragraph 4.3.2.2. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.10 herein.

PAGE 14

4.4.3.1, delete: paragraph in its entirety; add: new paragraph 4.4.3.1 Band seat. - The sample selected for this test after heat treatment shall have the band removed as defined herein. The procedure for performing this test shall be as specified MIL-I-6868 for wet flourescent method by either the continuous or residual methods. The band seat shall be inspected after inducing a circular magnetic field in the body and after inducing a longitudinal magnetic field in the body.

4.4.3.1.1 Etching method. The band shall be removed by machining the band and chemically etching without damaging the base metal of the band seat (see 6.3).

4.4.3.1.2 Alternate machining method. The band shall be removed by machining to the band seat diameter to produce alternate areas of base metal and band material (latticelike effect). Sample not able to be machined to the latticelike effect condition shall be chemically etched as specified in 4.4.3.1.1.

4.4.3.2 - line 4, delete: and after inducing a longitudinal magnetic field in the body.

4.4.5, delete: on the applicable specification; add: in TT-C-490.

PAGE 15

4.4.5.1 delete: utilizing the equipment and procedures specified by ASTM Method B-117; add: as specified in TT-C-490.

PAGE 16

* 6.9, delete: Paragraph in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

Add: new paragraph 6.10 Submission of designs for approval. See MIL-A-48078, Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

DD FORM 1426

Address: delete: Commander, Frankford Arsenal, ATTN: SARFA-MDM, Philadelphia, PA 19137; add: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from previous amendments were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amandment.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1315-A364

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.