MILITARY SPECIFICATION

PROJECTILE, 4.2 INCH, HE, M329A2
METAL PARTS ASSEMBLY

This Amendment forms a part of Military Specification MIL-P-50718B (AR) dated 10 September 1976, and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, Specification: Add

"FEDERAL

TT-C-490 - Cleaning Methods and Pre-treatment of Ferrous Surface for Organic Coatings"

Military Specifications: Add

"MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions"

Comments block: Delete "Frankford Arsenal, ATTN: SARFA-MDM, Philadelphia, PA 19137" and substitute "U.S. Army Armament Reserch and Development Command, ATTN: DRDAR-QA, Dover, NJ 07801".

PAGE 2

2.1, Drawings: Delete "Armament Command" and substitute "US Army Armament Research and Development Command (ARRADCOM)"

PRODUCT AND PACKAGING DRAWINGS:

Delete "LI 11738359 - Inspection Equipment List for Projectile, 4.2 Inch, HE, M329A2, Metal Parts Assembly" and substitute

"INSPECTION EQUIPMENT DRAWINGS

9278618 - Alignment gage"

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

2.2: Delete "ASTM B 117 - Salt Spray (Fog) Testing"

PAGE 5

4.3.1.2, line 4: Delete "the same length of time" and substitute "the specified time (see 4.3.3.1.2.1)"

PAGE 6

4.3.2.2: Delete "11738399" and substitute "11738360-1"

Critical 1: Delete in its entirety and substitute "1. Metal defective (band seat area) Visual (Probe Light)"

PAGE 7

4.3.2.3, Critical 1: Delete in its entirety and substitute "1. Metal defective (after cleaning and surface prepara tion for painting) Visual (Probe light)"

PAGE 9

* 4.3.2.3, Major 104: Delete in its entirety and substitute "104 Minor diameter of fuze thread, max."

Major 107: Delete in its entirety and substitute "107 Major diameter of boss thread, min."

4.3.2.5: Delete paragraph in its entirety.

PAGE 10

4.3.2.5 (Cont'd): Delete paragraph in its entirety

4.3.2.7: Delete "in a government certified chamber gage" and substitute "in chamber gage (dwg. 9278168)".

PAGE 11

4.3.3.1.2.1, line 6: Delete "and time have been established, the furnace temperature and time" and substitute "has been established, the furnace temperature"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

PAGE 12

4.3.3.5: Delete "the applicable specification" and substitute "TT-C-490"

4.3.3.5.1, line 2: Delete "the applicable specification" and substitute "TT-C-490"

line 4: Delete "the applicable specification" and substitute "therein"

PAGE 13

4.3.5: Delete paragraph in its entirety and substitute

"4.3.5 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Method of Inspection" column in the tables starting with paragraph 4.3.2.2. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.10 herein."

4.4.3.1: Delete paragraph in its entirety and substitute

"4.4.3.1 Band seat. The sample selected for this test after heat treatment shall have the band removed as defined herein. The procedure for performing this test shall be as specified in MIL-I-6868 for wet flourescent method by either the continuous or residual methods. The band seat shall be inspected after inducing a circular magnetic field in the body and after inducing a longitudinal magnetic field in the body.

4.4.3.1.1 Etching method. The band shall be removed by machining the band and chemically etching without damaging the base metal of the band seat (see 6.3).

4.4.3.1.2 Alternate machining method. The band shall be removed by machining to the band seat diameter to produce alternate areas of base metal and band material (latticelike effect). Samples not able to be machined to the latticelike effect condition shall be chemically etched as specified in 4.4.3.1.1."

4.4.3.2, line 4: Delete "and after inducing a longitudinal magnetic field in the body"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.

4.4.5: Delete "on the applicable specification" and substitute "in TT-C-490."

PAGE 15

4.4.5.1: Delete "utilizing the equipment and procedures specified by ASTM Method B-117" and substitute "as specified in TT-C-490."

PAGE 16

6.9: Delete paragraph in its entirety.

Add new paragraph 6.10 as follows:

"6.10 Submission of designs for approval. See MIL-A-48078, Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, NJ 07801."

Form DD Form 1426, Address: Delete "Commander Frankford Arsenal, ATTN: SARFA-MDM" and substitute "Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAT-A, Dover, NJ 07801."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A487)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:35Z
Check the source to verify that this is the current version before use.