MIL-B-2128C(SHIPS)
8 March 1966
SUPERSEDING
MIL-B-2128B(SHIPS)
11 September 1956
(See 6.3)

MILITARY SPECIFICATION

BURNERS, STEAM AND OIL PRESSURE, ATOMIZING

1. SCOPE

1.1 Scope. - This specification covers pressure atomizing oil burners for use in propulsion boilers aboard Naval ships.

1.2 Classification. - Burners shall be of the following types and classes as specified (see 6.1):

Type A - Straight pressure atomizing fuel oil burners.
Class A-1-1 – For boiler outer front casing suspension service.
Class A-1-2 - For boiler outer front casing suspension service, with hinged air register for access to the furnace.
Type B - Return flow, constant supply, variable return, and variable differential, pressure atomizing fuel oil burners.
Class B-1-1 - For boiler outer front casing suspension service.
Class B-1-2 - For boiler outer front casing suspension service with hinged air register for access to the furnace.
Type C - Steam pressure atomizing burners, nonreturn flow.
Class C-1-1 - For boiler outer front casing suspension service.
Class C-1-2 - For boiler outer front casing suspension service, with hinged air register for access to the furnace.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL
FF-N-836 - Nut, Plain: (Hexagon, Square, Cap and Welding) Nut, Slotted, and Castellated, Hexagon.
FF-S-85 - Screw, Cap, Slotted-And Hexagon-Head.
FF-S-86 - Screw, Cap, Socket-Head.
FF-S-92 - Screws, Machine: Slotted, Cross-Recessed or Hexagon Head.
FF-S-200 - Set Screws; Hexagon Socket and Spline, Socket, Headless.
FF-S-210 - Set Screws; Square Head and Slotted Headless.
QQ-S-763 - Steel Bars, Shapes and Forgings, Corrosion-Resisting.

MILITARY
MIL-R-196 - Repair Parts For Internal Combustion Engines, Packaging of.
MIL-B-857 - Bolts, Nuts, and Studs.
MIL-D-963 - Drawings, Electrical, Hull and Mechanical Equipment for Naval Shipboard Use.
MIL-P-15024 - Plates, Identification Information and Marking For Identification of Electrical, Electronic and Mechanical Equipment.
MIL-M-15071 - Manuals, Equipment and Systems.
MIL-P-17286 - Propulsion and Auxiliary Steam Turbines and Gears (Including Repair Parts, Tools, Accessories and Instruments); Packaging of.
MIL-E-17555 - Electronic and Electrical Equipment and Associated Repair Parts, Preparation For Delivery of.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129 - Marking For Shipment and Storage.

DRAWINGS

BUREAU OF SHIPS

11-Y-1298 to 11-Y-1364 - Standards for Fuel Oil Atomizer and Sprayer Plates.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

OFFICIAL CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies should be addressed to the Official Classification Committee, 1 Park Avenue at 33rd Street, New York, N.Y. 10016.)

3. REQUIREMENTS

3.1 Preproduction sample. - Prior to beginning production a sample shall be tested as specified in 4.2 (see 6.2).

3.2 General design. - Reliability in service is paramount. Design and construction shall be light and compact to the greatest extent practicable and consistent with requirements herein.

3.2.1 All burners specified herein shall consist of an adjustable air register and an atomizer assembly. Design and construction shall be such that possibilities of buckling, warping, or jamming of parts requiring adjustments are reduced to a minimum. Material shall be of the type best suited for the conditions encountered. The material of burner parts subjected to radiant heat from the furnace shall be of a heat-resisting alloy approved by the bureau or agency concerned. All burners shall be designed for burning Navy grade fuel oil or other fuel as specified in the contract or order. When intended for use with Navy grade fuel oil, the operating characteristics based on 135 Saybolt seconds universal (SSU) viscosity oil shall be provided. All burners shall be provided with an observation port of sufficient size to be used as a lighting off port.

3.2.2 The design shall be such that the oil may be shut off on each individual burner and the atomizer removed from the air register and replaced without the use of a wrench. Provision shall be incorporated to prevent discharge of furnace gases into the fireroom when the atomizer barrel is removed from the burner. The fuel oil shall be supplied to the burner by means of a branch line connection between the fuel oil supply manifold and the burner.

3.2.3 Provision for shutting off the fuel oil shall be provided as follows:

(a) A flanged manifold root valve, located at the burner fuel oil manifold end of the branch piping.
(b) A quick closing valve located at the burner end of the branch line or as a part of the burner. This valve shall be so designed that one turn or less will give full opening of the valve from fully closed position.
(c) A device that prevents removal of the atomizer barrel prior to shutting off the fuel oil to the burner and also prevents accidental turning on the fuel oil with the atomizer removed from the air register, or with the atomizer not fully secured in position. The quick closing valve shall be designed as an integral part of the safety shut off device.

3.2.4 The branch lines connecting the burners to the fuel oil manifold shall be of seamless steel tubing with welded, shielded take down flanges. These branch lines shall be flexible enough to permit adjustment of the atomizer barrel and impeller plate assemblies by a man using one hand only applying a pull or push force not greater than 30 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

3.2.5 Provision shall be made for locking the atomizer barrel in proper position with respect to the impeller plate to maintain the optimum atomizer (tip) setting. The burner shall also include a device for automatically locking and unlocking the atomizer-barrel impeller-plate assembly in its in and out stops. "Snaps" for that purpose will be considered.

3.2.6 Oil burners shall be provided with satisfactory allowance for relative movement between the connections to the inner and outer burner front casing plates, in such a way that the atomizers cannot be thrown out of alignment by warping or expansion of the casings under maximum temperature conditions. Suitable provisions shall be made in the design to prevent accumulations of fuel oil drip between inner and outer casings under any condition of operation. The design of the burners shall permit convenient withdrawal of the entire burner through the burner front plate.

3.2.7 The air doors in the air register shall be easily operable under all operating conditions. Multi-turn-crank operation of the air doors is not considered satisfactory.

3.2.8 The hinged air registers, specified for classes A-1-2, B-1-2 and C-1-2 shall be so designed that the burner can be easily swung out to provide access to the furnace through the burner opening, and be swung into position with equal facility.

3.2.9 Weight factor. - Each burner at rated capacity shall deliver at least eight poinds of fuel oil per hour per pound of burner weight. All parts of the burner necessary for satisfactory operation are considered part of the burner weight except refractory material comprising the burner throat, the retaining devices for this refractory material, and the branch fuel oil line(s).

3.2.10 Area factor. - Each burner at rated capacity shall deliver at least 304 pounds of oil per hour per square inch of circular area covered by the closed burner (air doors shut) at the burner inner front plate exclusive of holding ears or points in the case of polygonal base rings. This ratio shall apply in the case of 1000 pound per hour capacity burners but shall be increased oil pound of oil per hour per square inch for each 100 pound increase in burner capacity.

3.2.11 The minimum capacity shall not be more than 240 pounds of fuel oil burned per hour.

3.2.12 The minimum firing distances shall be defined as the least permissible distances for a service (multiple burner) installation. Such limiting firing distances shall be determined for each type and size of burner during preproduction tests (see 4.2.1.6) and shall govern the determination of the position of burners in any boiler. These limiting firing distances shall not be less than those specified in table I.

Table I - Minimum limiting firing distances

Centerline of burner to	Maximum burner capacities in pounds of oil/hour.			
	Up to and including 2100	From 2100 to 3300, incl.	From 3301 to 6000, incl.	Above 6000
	Inches	Inches	Inches	Inches
Centerline of burner	22	25-1/2	30	36-1/2
Furnace floor	25	25	25	25
To nearest tube surface towards which gas is flowing	31	31	31	31
To water-cooled side wall	--	26	28	28
To side wall refractory	25	25	--	------

3.2.13 The air pressure drop across the burner shall be as low as practicable and compatible with good mixing of the air and fuel oil.

3.2.14 The burners shall be suitable for both single and multiple burner operation and for both manual and automatic combustion control. Changes in oil rate throughout the range of sprayer plates shall be accomplished by operation of a single valve or lever.

3.2.15 For design and evaluation purposes the following ultimate analysis, heating values, and furnace heat releases shall be used:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

C	87.75 percent
H	10.50 percent
O	0.40 percent
S	1.20 percent
N	0.15 percent
British thermal units (B.t.u.)/pound of fuel oil	18500 higher heating value (bomb)
Total furnace heat release at maximum capacity of burner (s) B.t.u./cubic foot of furnace volume	700 kilo B.t.u.

3.2.16 Threaded parts. - Unless otherwise specified herein, or approved by the bureau or agency concerned, all bolts, nuts, studs and machine screws shall conform to FF-N-836, FF-S-85, FF-S-86, FF-S-92, FF-S-200, FF-S-210 or MIL-B-857, as applicable.

3.2.17 Accessories. - Unless otherwise specified in the contract or order, the following accessories shall be supplied with the burners, in the quantities indicated:

(a) Quick closing (atomizer) valve if not part of the burner	1 for each burner.
(b) Atomizer barrel assemblies	250 percent of number of burners installed on each boiler.
(c) Sprayer plates	300 percent of each size sprayer plate intended for use per burner; for sizes and capacities (see 6.1).
(d) Swing check valve in the oil return branch line if not part of the burner (for type B burners only)	1 for each burner.

3.3 Type A - straight pressure atomizing fuel oil burners. -

3.3.1 Type A burners shall utilize the fuel oil pressure mechanical atomizing principle exclusively where all oil supplied to the burner is atomized. They shall employ Navy standard sprayer plates, atomizer nozzles and nuts at a fuel oil operating range of 1000 pounds per square inch gage (p.s.i.g.) to 150 p.s.i.g. All details of sprayer plates, for classes A-1-1 and A-1-2 shall be in strict accordance with Drawings 11-Y-1298 to 11-Y-1307, inclusive, and 11-Y-1310 or 11-Y-1300 to 11-Y-1364, inclusive. Standard atomizer nozzles shall be in accordance with Drawing 11-Y-1309 and standard atomizer nuts shall be in accordance with Drawing 11-Y-1308. Sprayer plates shall be stenciled to indicate the drill size and ratio as indicated on above drawings.

3.4 Type B -Return flow, constant supply, variable return, and variable differential, pressure atomizing fuel oil burners. -

3.4.1 These burners shall utilize the fuel oil pressure mechanical atomizing principle exclusively where part of the oil supplied to the sprayer assembly is atomized and sprayed into the furnace and the remaining oil is returned to the suction line of the fuel pump or to the service tank. The supply pressure shall remain constant and the firing rate controlled by varying the return flow pressure. Wide range atomizers operating with 1000 p.s.i.g. supply pressure shall have an operating range of at least 1 to 10 without changing atomizers. Minimum firing rate shall be achieved with a return oil pressure of not less than 50 p.s.i.g. The quantity of oil burned at the maximum firing rate shall not be less than 87 percent of the quantity of oil supplied to the burner. Maximum capacity shall be considered the flow rate obtained when the return oil pressure is 10 pounds per square inch (p.s.i.) less than that obtained when the return valve is closed.

3.4.2 A swing check valve either incorporated in the burner, or located in the return oil line close to the burner, shall be provided.

3.4.3 Adapters capable of converting the atomizer to straight pressure atomizing (type A) shall be provided.

3.5 Type C - Steam pressure atomizing burners, nonreturn flow. -

3.5.1 Type C burners shall employ steam as the atomizing medium, or as supplemental pressure atomization. The source of atomizing steam shall be the 150 p.s.i.g. steam main. Atomizers shall be designed

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

to operate with steam pressures up to 150 p. s. i. g. and oil pressures up to 350 p. s. i. g. at the supply header. They shall have a satisfactory operating range of not less than 16 to 1 based on oil flow.

3. 5. 2 The burners shall be designed so that the flow of fuel oil and steam will automatically be shut off when the atomizer is removed from the burner. Provisions shall be made against either the accidential discharge of oil or steam into the fireroom with the atomizer not fully secured in position. In conjunction with this device, provision shall be made for the purging of fuel oil from the burner by means of the atomizing steam. The purging mechanism shall permit the flow of steam through the oil side of the burner (sufficiently long enough to clear the burner of oil) after the oil flow is secured when shutting down and before oil is introduced into the burner when lighting off. The purging mechanism shall be capable of local and remote operation.

3. 5. 3 Steam used by the atomizers shall be kept to a minimum. Atomizers shall be capable of spraying oil at the rate of not less than 7. 7 pounds of oil sprayed for each pound of atomizing steam used when the burner is operated at firing rates in excess of 30 percent of the capacity of the atomizer.

3. 5. 4 When atomizers using steam are employed, one size sprayer plate shall be required for the entire range from light off up to and including 100 percent boiler full power rating. A second sprayer plate shall be required for the 100 percent to 120 percent boiler full power rating. Sprayer plates shall be sized so as to restrict the oil flow from exceeding the 100 percent and 120 percent fuel rates by no more than 5 percent.

3. 5. 5 A swing check valve located in the steam supply line to the atomizer shall be installed to prevent fuel oil from contaminating the atomizing steam.

3. 5. 6 Adapters capable of converting the atomizer to straight pressure atomizing (atomizer type A) shall be provided.

3. 5. 7 Steam control equipment including manual and automatic control valves and pressure reducing equipment for use with steam atomizers shall be supplied by the burner manufacturer. Sufficient equipment shall be supplied so that steam pressure is controlled automatically in response to oil pressure so as to permit single valve control. Sufficient manual control valves shall be provided to permit operation manually if the need for operation under this condition should arise.

3. 5. 8 The minimum firing rate shall be that quantity of oil fired when the supply oil pressure is 10 p. s. i. g. at supply header.

3. 6 Designation and marking. -

3. 6. 1 Identification and designation plates. - Identification plates and other designating marking, in accordance with MIL-P-15024 shall be provided. These plates shall be installed on and furnished as a part of the burners. They shall be attached to a part of the burner which will not ordinarily be renewed during its normal service life and be located in a readily accessible position where they can be read at all times without danger to personnel.

3. 6. 2 Identification plate markings. - Data marked on identification plates shall include the following items:

(a) Manufacturer's name, identification, symbols, and serial number.
(b) Contract number and date of manufacture, and type of burner.
(c) Blank space for inspector's official stamping. The classification letters and numbers specified herein shall be shown on the burner identification plate, as applicable.

3. 6. 3 Designation plates. - Each burner shall have a designation plate, bearing a number or letter, attached in a conspicuous location, to designate the lighting-off sequence. A small brass plate, bearing a number or letter corresponding to the number or letter of the burner which the root valve serves, shall be attached to the handwheel of each root valve.

3. 7 Identification of repair parts. -

3. 7. 1 Marking. - Unless otherwise approved by the bureau of agency concerned, all repair parts shall be clearly and permanently marked with identification data (nomenclature including part number and the contract or order number).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

3.7.2 Identification data. - Identification data for repair parts shall be sufficiently complete to fix the character, the use, and the apparatus for which the repair parts are suitable; where a repair part is suitable for more than one item of equipment on the same ship, the identification data shall give full information in regard thereto.

3.8 Manuals. - Manuals when specified (see 6.1), shall be furnished in accordance with type I of MIL-M-15071.

3.9 Drawings. - Drawings shall be class A in accordance with MIL-D-963, and shall be complete in such detail as to permit the manufacture of all parts by a repair activity.

3.10 Onboard repair parts and special tools. -

3.10.1 Onboard repair parts. - Each set of onboard repair parts shall consist of the following: (These are items over and above those accessories specified in 3.2.17).

(a) Atomizers, complete except sprayer plates, 10 percent of the number of burners installed or ordered.
(b) Impeller plates, 25 percent of number installed or ordered.
(c) Air regulating shutters, 10 percent of number installed or ordered.
(d) Gaskets of each size and type used for oil tightness, 200 percent of the number installed or ordered.
(e) Gaskets of each size and type used for air and watertightness, 10 percent of the number installed or ordered.
(f) Quick closing valves, complete, 10 percent of the number installed or ordered.
(g) Check valves for return flow line for type B burners, 10 percent of number installed or ordered.
(h) Gears for air doors, 10 percent of number installed or ordered.
(i) Repair parts for device called for in 3.2.3(c), 10 percent of number installed or ordered.

3.10.2 Special tools. - Each set of special tools shall consist of the following:

Special tools are defined as those tools not listed in the Federal Supply Catalog (copies of this catalog may be consulted in the office of the Government Inspector).

(a) One open-end nozzle wrench and one closed end tip wrench for each boiler on order, or as specified (see 6.1).
(b) One each of all special tools required for assembly or for normal maintenance cleaning, repair, and adjustment of the equipment shall be furnished for each fire room or as specified (see 6.1). This includes wire brushes and tools for cleaning sprayer plates of such type and material as not to damage the burner parts.
(c) Slide trough for burner, spanning space between outer and inner front boiler casing to facilitate access to furnace through burner opening; one for each fire room or as specified (see 6.1).
(d) One set of forms for installation of burner throat refractory for each ship, or as specified in the contract or order; each set shall consist of a conical or cylindrical form for use in pounding refractory in place and a sweep to cut refractory to required finished form which shall be supported in such a manner as to be easily installed and withdrawn without detaching burner air registers. The number of forms in each set shall be the total number of burners installed in one boiler (only one sweep per ship shall be required regardless of the number of burners).
(e) "Go-No Go" gage shall be supplied to determine that sprayer plate orifices have not exceeded a .005 inch tolerance. The "Go-No Go" gage shall be fabricated from machineable stainless steel conforming to class 303 or 303Se of QQ-S-763; one for each fire room or as specified (see 6.1).

Note:- The number of burners per boiler and number of boilers per fire room shall be as specified (see 6.1).

3.11 Workmanship. - The workmanship shall be first class in every respect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction inspection. - Preproduction inspection shall consist of the examination and tests specified in 4.3 and 4.2.1 through 4.2.1.7.

4.2.1 The approved maximum, minimum, and rated capacities, in pounds of oil fired per burner per hour (using fuel oil with a viscosity of 135 SSU for which any type tested may be used in service, shall be definitely fixed. Pressure drop across the burner over its operating range shall be measured to verify conformance with 3.2.13.

4.2.1.1 Maximum capacity shall be the amount of fuel oil which can be satisfactorily burned per hour per burner with a drop of 1 percent in CO_2 percentage in the combustion gases from the maximum as determined by a smooth performance curve based on test data. Loss of ignition, excessive carbon laying, improper flame conditions, or necessity for difficult adjustments will be adjudged evidence of unsatisfactory firing.

4.2.1.2 Rated capacity of the burners shall be the amount of fuel oil which can be satisfactorily burned per hour per burner with a multiple burner installation (the number of burners to be based on probable number required for service installation) at "trace smoke" condition with a draft loss (pressure drop from fireroom or double front to the furnace) of 8 inches of water. The rated capacity is intended for comparative purposes only.

4.2.1.3 Minimum capacity (not more than 240 pounds of fuel oil burned per hour per burner or 8 percent of maximum capacity, whichever is greater) shall be obtained with one burner without difficult special adjustments. Operation at this capacity shall be "trace smokeless and shall operate carbon free or with such small carbon deposits (as built-up in at least 4 hours of continuous operation) as not to affect burner performance or result in excessive accumulation upon furnace refractories.

4.2.1.4 The burners shall be capable of smokeless operation over the full operating range from minimum to maximum capacity when such smokeless operation is required and shall function under all operating conditions without depositing carbon to such an extent as to affect the burner performance or result in excessive accumulation upon furnace refractories.

4.2.1.5 The maximum CO_2 percentage obtained during the tests shall be not less than 13-1/2 percent.

4.2.1.6 The burner size shall be officially determined and classified during the preproduction tests, and such designation shall thereafter apply to similar burners which may be supplied to the Navy.

4.2.1.7 The minimum permissible firing distances for each burner shall be determined at the maximum capacity and included in the official approval of the design.

4.3 Quality conformance inspection. -

4.3.1 Examination. - Each burner shall be examined to determine compliance with the requirements of this specification not involving tests. All repair parts and tools shall be examined to verify all identifying markings. Interchangeability of repair parts shall be demonstrated and the suitability of the tools by actual use.

4.3.2 Tests. - Each burner and all parts shall be tested to determine compliance with the requirements of this specification and with approved drawings.

4.3.2.1 Leakage test of valves. - All quick-closing valves shall be tested before shipment by hydrostatic pressure of 150 percent of designed operating pressure.

4.3.2.2 Valve operation. - All valves shall be operated in the manner in which they will be used for normal and also emergency boiler operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Domestic shipment and early equipment installation and for storage of onboard repair parts. -

5.1.1 Burner and accessories. -

5.1.1.1 Preservation and packaging. - Preservation and packaging which may be the supplier's commercial practice, shall be sufficient to afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the using activity and until early installation.

5.1.1.2 Packing. - Packing shall be accomplished in a manner which will insure acceptance by common carrier at the lowest rate and will afford protection against physical or mechanical damage during direct shipment from the supply source to the using activity for early installation. The shipping containers or method of packing shall conform to the Uniform Freight Classification Ratings, Rules and Regulations or other carrier regulations as applicable to the mode of transportation and may conform to the suppliers commercial practice.

5.1.1.3 Marking. - Shipment marking information shall be provided on interior packages and exterior shipping containers in accordance with the contractor's commercial practice. The information shall include nomenclature, Federal stock number or manufacturer's part number, contract or order number, contractor's name and destination.

5.1.2 Onboard repair and tools. - Mechanical repair parts and tools shall be preserved and packaged level A in accordance with MIL-P-17286 and MIL-R-196 as applicable. Electrical repair parts shall be preserved and packaged level A in accordance with MIL-E-17555. Packing of repair parts shall be in accordance with the applicable processing specification, level C shall apply. Marking of interior packages and exterior shipping containers shall be level A or C respectively in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. - Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type and class required (see 1.2).
(c) Sizes and capacities of sprayer plates required and the quantity of each if other than as specified (see 3.2.17 (c)).
(d) Whether manuals are required (see 3.8).
(e) Number of special tools required if other than as specified, number of burners per boiler, and number of boilers per fire room (see 3.10.2).

6.2 Preproduction. - Invitations for bids should provide that the Government reserves the right to waive the requirement for preproduction samples as to those bidders offering a product which has been previously procured or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending procurement.

6.3 Changes from previous issue. - The extent of changes (deletions, additions, etc.) preclude the annotation of the individual changes from the previous issue of this document.

Preparing activity:
Navy - SH
(Project 4530-N003SH)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8279

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:25Z
Check the source to verify that this is the current version before use.