MIL-C-2156C (PA)
7 May 1976
Superseding
MIL-C-2156B (MU)
26 October 1970

MILITARY SPECIFICATION

CHARGE, DEMOLITION, SHAPED, 15 LB. PRACTICE, M2A3 AND HE, M2A4 LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of demolition item designated as Charge, Demolition, Shaped, 15 lb., Practice, M2A3 and HE, M2A4.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods Of
*MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

*(For meaning of asterisk (*) see paragraph 6.4)

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

8861565 - Charge, Demolition, Shaped, 15 lb., M2A4 Loading Assembly
8861566 - Charge, Demolition, Shaped, 15 lb., M2A3 Practice, Loading Assembly
*8861569 - Body Assembly
*9281170 - Packing and Marking for Charge, Demolition, Shaped, 15 lb. M2A4 or M2A3 (Practice)

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assemblies. - The assemblies shall comply with all requirements specified on Drawing (dwg.) 8861565 or 8861566, and with all requirements specified in applicable specifications.

3.3 Workmanship. - Loading and assembling shall be accomplished in a thorough workmanlike manner. All parts and assemblies shall be free of explosive on exterior, cracks, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coating shall be continuous except for a few light scratches not exposing base material. All required marking shall be neat and sharply defined. Required packing shall be dry.

3.4 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

*4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First Article Inspection

*4.3.1 Submission. - The contractor shall submit a first article (see 6.1b) as designated by the Contracting Officer. The first article sample shall consist of twenty-five (25) sets of parts assemblies; ten (10) boosters and twenty-five (25) loading assemblies. The first article shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

*4.3.2 Inspections to be performed. - See MIL-A-48078, the paragraphs of 4.4.2 and Table I specified herein.

*4.3.3 Rejection. - (See MIL-A-48078).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH *	TITLE Charge Demolition, Shaped 15 Lb. Practice M2A3 and HE M2A4		SHEET 1 OF 1		DRAWING NUMBER See Below / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Parts Assemblies Examination of defects (where applicable) and Average Weight	25			4.4.2.2 & 4.4.2.3
	Booster Examination of defects and Specific Gravity (dwg. 8858393)	10			4.4.2.1 & 4.4.3.1
	Loading Assemblies Examination of defects (where applicable) and Weight of Charge (dwg. 8861565 or 8861566)	25			4.4.2.3 thru 4.4.2.5 & 4.4.3.2

NOTES:

SARPA-QA FORM 2567 FEB 74 4B10

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of loaded shaped demolition charges shall contain:

a. Parts or part assemblies from not more than one lot interfix number from one manufacturer.

b. Composition B of the same grade from one lot interfix number from one manufacturer which contains TNT from not more than one lot interfix number from one manufacturer.

c. Composition A-3 from not more than two lots from one manufacturer.

d. Inert filler of the same type from one manufacturer (M2A3).

*4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.1	Booster		8858393
			NEXT HIGHER ASSEMBLY 8861565

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Concentricity of small cavity to outside diameter		0.40%	3.2	Gage
132	Diameter of small cavity, minimum		0.40%	3.2	Gage
133	Depth of large cavity, min.		0.40%	3.2	Gage
Minor					
201	Depth of small cavity, min.		0.65%	3.2	Gage
202	Diameter of large cavity, min.		0.65%	3.2	Gage
203	Total length, max		0.65%	3.2	Gage
204	Radius missing		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.2	Body Assembly, Prior to Loading		8861569
			NEXT HIGHER ASSEMBLY: 8861565 and 8861566

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter, max		0.40%	3.2	Gage
132	Interior protective finish, discontinuous, scratched or contains bare spots		0.40%	3.2	Visual
133	Foreign matter present in interior		0.40%	3.2	Visual
134	Carrying strap damaged		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.3	H.E. Loading Assembly Prior to Assembly of Closing Cap		8861565
			NEXT HIGHER ASSEMBLY 8861565

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Practice charge in H.E. assembly		0.40%	3.2	Visual
Major B					
131	Component missing, loose or improperly assembled		0.40%	3.2	Visual/Manual
132	Body assembly damaged		0.40%	3.2	Visual
Minor					
201	Depth to charge, min		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C(PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.4	Practice Loading Assembly Prior to Assembly of Closing Cap				8861566
					NEXT HIGHER ASSEMBLY 8861566
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	H.E. charge in practice assembly		100.0%	3.2	Visual
Major A					
101	Component missing, loose or improperly assembled		0.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.5	Assembly (as applicable)		8861565 or 8861566
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Gage does not enter detonator well freely to full length		0.40%	3.2	Visual
Major B					
131	Closing cap assembly loose		0.40%	3.2	Manual
132	Protective tape missing		0.40%	3.2	Visual
Minor					
201	Total length		0.65%	3.2	Gage
202	Marking missing, incorrect or illegible		0.65%	3.2	Visual
203	Color coding improper (see dwg. 8861569)		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9281170
*4.4.2.6	Box, Fiberboard, Prior to Sealing				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Component missing or improperly packed		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.7	Box, Fiberboard		9281170
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Sealing strip incomplete or loose		0.40%	3.2	Visual
132	Box punctured, torn or cut		0.40%	3.2	Visual
133	Corner not blunted		0.40%	3.2	Visual
Minor					
201	Marking missing, incorrect or illegible		0.65%	3.2	Visual
202	Contents loose		0.65%	3.2	Manual
203	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.8	Sealed Packed Barrier Bag, Prior to Packing in Box		9281170
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Waterproofness of barrier bag destroyed by rupture, puncture or separation of heat seal		0.40%	3.2	Visual
102	Evidence of crushed box (see Note)		0.40%	3.2	Visual
103	All excess air not exhausted from bag prior to sealing		0.40%	3.2	Visual
Minor					
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202	Marking of bag misleading, or unidentifiable		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.3	Visual
Note:	Package should be opened if there is evidence of crushing.				

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.9	Packing Box, Prior to Securing Top	1 OF 1	9281170
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Number of sealed bags incorrect		0.40%	3.2	Visual
132	Any packing component missing		0.40%	3.2	Visual
Minor					
201	Insufficient filler material		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4B10

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2156C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.10	Packing Box		9281170
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Board broken or split		0.40%	3.2	Visual
132	Contents exposed or loose		0.40%	3.2	Visual/Manual
133	Hardware or strapping missing, loose or broken		0.40%	3.2	Visual/Manual
Minor					
201	Marking missing, incorrect or illegible		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Specific gravity of booster (see dwg. 8858393) - Major A defect. - A sample of five boosters shall be selected from each lot for this test. If any booster fails to meet the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.1 using test equipment specified in 4.4.4.

4.4.3.2 Weight of charge (see dwg. 8861565 or dwg. 8861566, as applicable) - Major A defect. - A sample of 25 loading assemblies shall be selected from each lot for this test. If any loading assembly fails to meet the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.2 using test equipment specified in 4.4.4.

4.4.3.3 Heat seal test of sealed bag (see dwg. 8861209) - Major A defect. - Sampling, acceptance criteria and test procedures for this test shall be as specified in MIL-P-116.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.2 herein.

4.5 Test methods and procedures

*4.5.1 Specific gravity of booster. - The booster shall be weighed on a balance and the weight recorded as dry weight. The booster shall then be weighed while completely submerged in water. The temperature of the water shall be 68 degrees Fahrenheit (F) plus or minus 2 degrees F. This weight shall be recorded as weight under water. (When submerged, the position of the booster shall be such that no air is entrapped.) Specific gravity shall be calculated as follows:

$$\text{Specific gravity at } 68°F = \frac{0.9982A}{A-B}$$

where: A = dry weight
B = weight under water

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

4.5.2 Weight of charge. - The loading assembly shall be weighed on a scale capable of determining weights within an accuracy of 2 ounces. The average weight shall be obtained from 25 parts assemblies and subtracted from the weight of the loading assembly to determine compliance with the requirement. Any assembly failing to meet the weight requirement, shall be classed defective.

5. PREPARATION FOR DELIVERY

*5.1 Preservation, packaging, packing and marking, Level A. - Preservation, packaging, packing and marking shall be in accordance with Dwg. 9281170.

6. NOTES

*6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

*6.2 Submission of Inspection Equipment Designs for Approval. - (See MIL-A-48078). Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T-T Dover, New Jersey 07801.

*6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

*6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-169

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:28Z
Check the source to verify that this is the current version before use.