INCH-POUND

MIL-DTL-2156E(AR)
w/INT. AMENDMENT 1
30 September 2026
USED IN LIEU OF
MIL-DTL-2156E
16 January 2026

INTERIM SPECIFICATION

CHARGE, DEMOLITION: SHAPED, 15 LB, M2A4
PARTS, LOADING, ASSEMBLING AND PACKING

This interim specification is approved for use by the U.S. Army Armaments Center and is available for use by all Departments and Agencies of the Department of War within the distribution limitations noted at the bottom of the page.

1. SCOPE

1.1 Scope. This specification covers the parts, loading, assembling and packing of the Charge, Demolition: Shaped, 15 LB, M2A4.

2. APPLICABLE PUBLICATIONS

2.1 General. The publications listed in this section are specified in sections 3, 4 and 5 of this specification. This section does not include publications in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all requirements publications cited in sections 3, 4 and 5 of this specification, whether they are listed or not.

2.2 Government publications.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to: U.S. Army DEVCOM-AC, ATTN: FCDD-ACE-QSA , Picatinny Arsenal, New Jersey 07806-5000 or emailed to usarmy.pica.devcom-ac.list.ardec-stdzn-branch@army.mil. Since contact information can change, you may want to verify the currency of this information using ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1375
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF WAR STANDARDS

MIL-STD-1168	-	Ammunition Lot Numbering and Ammunition Data Card
MIL-STD-1916	-	DOD Preferred Method for Acceptance of Product
MIL-STD-2073-1	-	Standard Practice for Military Packaging

DEPARTMENT OF WAR SPECIFICATIONS

MIL-DTL-12560	-	Armor Plate, Steel, Wrought, Homogeneous (for use in combat-vehicles and for ammunition testing)

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.2.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation (see 6.2).

U.S. ARMY ARMAMENT CENTER DRAWINGS

8858393	-	Booster
8858397	-	Detonator well assembly
8858398	-	Adaptor, well, detonator
8858399	-	Well, detonator
8858400	-	Well, detonator, alternative
8861565	-	Charge, Demolition: Shaped, 15 LB, M2A4 Loading Assembly
8861567	-	Sleeve, stand-off
8861568	-	Closing cap assembly
8861569	-	Body Assembly
8861570	-	Container, cone
8861572	-	Cone assembly
8861579	-	Cone
8861582	-	Cap, closing
9230162	-	Charge, Demolition: Shaped, 15 LB, M2A4, Parts Arrangement
9281170	-	Packing and Marking for Charge, Demolition: Shaped, 15 LB, M2A4
13021902	-	Adapter, priming M1A5

(Copies of these drawings are available email at usarmy.pica.devcom-ac.list.drawing-request-help-desk@army.mil.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

US ARMY DEFENSE AMMUNITION CENTER (DAC) DRAWINGS

19-48-4116/120H – Unitization Procedures for Boxed Ammunition and Components on 4-Way Entry Pallet

(Copies of these documents may be requested online at https://www.dau.edu/cop/ammo/Pages/Default.aspx .)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM E1742/1742M - Standard Practice for Radiographic Examination

(Copies of this document are available from https://www.astm.org.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Required inspections.

3.1.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.1.2 Conformance inspection. A sample shall be subjected to conformance inspection in accordance with 4.3.

3.2 Material, parts and, assemblies. Materials, parts and assemblies shall comply with all requirements specified in drawings cited in section 2.2.2.

3.2.1 Specific gravity of glass cone. The glass, from which the cone is made, shall be clear potash-soda-lead-silicate having a minimum specific gravity of 3.00.

3.2.2 Specific gravity of booster. The specific gravity of the booster shall be not less than 1.50.

3.2.3 Average explosive weight of loading assemblies. The average explosive weight of the loading assemblies shall be not less than 10.1 lbs (Minimum 10 lbs of Comp B plus 48 grams of booster material).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

3.2.4 Annealing of glass cone. The glass cone shall be fully annealed to relieve strains which might cause failure.

3.2.5 Heat shock test of glass cone. The glass cone shall not break or show cracks when tested for resistance to heat shock.

3.2.6 Radiographic examination. Cavitation shall be permitted only at the top side of the body where the explosive mixture is poured. Cavitation or voids in the loading assembly shall be not greater than ¼ inch depth and 1 inch width in any direction.

3.3 Leakproofness of body assembly. The body assembly, when pressurized to 2.5 pounds per square inch gauge (psig) internally with air, shall not exhibit leakage greater than an amount indicated by a drop of more than 60 percent in 5 seconds.

3.4 Leakproofness of closing cap assembly. The closing cap assembly shall not exhibit leakage when pressurized 2 to 3 psig internally with air for not less than10 seconds.

3.5 Fit of closing cap assembly. The closing cap assembly shall require a force fit to be inserted into the body assembly which does not leave the assembly loose or damaged.

3.6 Fit of stand-off sleeve. The gap between the body and the stand-off sleeve shall not be greater than 0.3 inches when a static load of 20 plus or minus 1/2 pounds is applied.

3.7 Functioning test. The loaded M2A4 shall detonate high order with penetration of a target of Rolled Homogeneous Armor (RHA) in accordance with MIL-DTL-12560, Class 1 or 2, when initiated by an M6 or M7 blasting cap or equivalent military initiation device held in place with the priming adapter. The penetration hole in the plates shall exhibit no evidence of double- or multi-jets and have a minimum penetration of 4 inches. The entrance and exit of the penetration hole diameters of each plate will be two readings at 90 degrees apart for each diameter of the first 4 inches. Any penetration depth and diameter measurements beyond the minimum 4 inch plate thickness requirement will be for performance data collection purposes only.

3.8 Workmanship. All parts and assemblies shall be clean and free of explosive on exterior, chips, cracks, crazes, dirt, grease, rust, corrosion products, and other defects and foreign matter which would affect their serviceability. The cleaning method used shall not be injurious to any part or assembly nor shall the cleaning agent contaminate them. Exterior surface coatings shall be continuous except for a few light scratches not exposing the base material. All required markings shall be neat and sharply defined. Slight discoloration of the plunger and mold surfaces will be allowed; provide they do not indicate flaws or imperfections which would adversely affect the function of the case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirements/verification cross reference matrix.

Method of Verification		Classes of Verification
1- Analysis 2- Examination 3- Test 4- Demonstration		A - First article B - Conformance

Section 3 Requirements	Description	Verification Method				Verification Class		Section 4
		1	2	3	4	A	B	
3.1.1	First article	X	X	X		X		4.2
3.1.2	Conformance inspection			X			X	4.3
3.2	Material, parts and, assemblies	X	X	X		X	X	4.3 - 4.3.3.22
3.2.1	Specific gravity of glass cone	X				X	X	4.4.5
3.2.2	Specific gravity of booster	X				X	X	4.4.8
3.2.3	Average weight of loading assemblies		X			X	X	4.4.9
3.2.4	Annealing of glass cone		X			X	X	4.4.6
3.2.5	Heat shock test of glass cone			X		X	X	4.4.7
3.2.6	Radiographic examination		X			X	X	4.4.10
3.3	Leakproofness of body assembly		X	X		X	X	4.4.1
3.4	Leakproofness of cap assembly		X	X		X	X	4.4.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

Table I. Requirements/verification cross reference matrix (continued).

Method of Verification		Classes of Verification
1- Analysis 2- Examination 3- Test 4- 4 – Demonstration		A - First article B – Conformance

Section 3 Requirements	Description	Verification Method				Verification Class		Section 4
		1	2	3	4	A	B	
3.5	Fit of closing cap assembly		X			X	X	4.4.3
3.6	Fit of stand-off sleeve		X	X		X	X	4.4.4
3.7	Functioning test			X		X	X	4.4.11
3.8	Workmanship		X			X	X	4.3.3.1-4.3.3.22
5.1	Packaging and marking		X			X	X	4.3.3.18 – 4.3.3.22
5.2	Unitization		X				X	4.3.3.23

4.1 Classification of verification. The verification requirements specified herein are classified as follows:

a. First Article Inspection (see 4.2)

b. Conformance Inspection (see 4.3)

4.2 First article inspection. A sample shall be subjected to first article inspection in accordance with Table II. First article samples shall be manufactured using the same vendors, methods, materials, equipment, processes, procedures and facilities as will be used during regular production.

4.2.1 First article rejection. The first article sample shall be rejected if any of the inspections/tests fail to meet specification or drawing requirements. The Government reserves the right to terminate inspection or test upon failure of any sample to comply with any requirement.

4.2.2 Inspections to be performed. The first article samples shall be subjected to all of the examinations and tests specified in Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection.

Examination or test	Drawing	Sample Size	Requirement paragraph	Inspection method
Glass Examination of defects Specific gravity of glass	9230178	 1 10	 3.2.1	 4.3.3.1 4.4.5
Well, detonator	8858399	25	3.2	4.3.3.2
Adapter, well, detonator	8858398	25	3.2	4.3.3.3
Detonator well assembly	8858397	25	3.2	4.3.3.4
Well, detonator (alternative)	8858400	25	3.2	4.3.3.5
Cap, closing	8861582	4.3.2.6	3.2	4.3.3.6
Closing, cap assembly Examination of defects Leakproofness of closing cap assembly	8861568	 25 1/ 100%	 3.2 3.4	 4.3.3.7 4.4.2
Cone Examination of defects Annealing of cone Heat shock	8861579	 25 1/ 100% 25	 3.2 3.2.4 3.2.5	 4.3.3.8 4.4.6 4.4.7
Cone assembly	8861572	25	3.2	4.3.3.9
Container, cone	8861570	25	3.2	4.3.3.10
Body assembly, prior to attaching carrying straps Examination of defects Leakproofness Fit of closing cap	8861569	 25 1/ 100% 25	 3.2 3.3 3.5	 4.3.3.11 4.4.3
Body assembly	8861569	25	3.2	4.3.3.12
Sleeve, stand-off Examination of defects Fit of stand-off sleeve	8861567	 25 1/ 25	 3.2 3.6	 4.3.3.13 4.4.4
Booster Examination of defects Specific gravity	8858393	 25 1/ 10	 3.2 3.2.2	 4.3.3.14 4.4.8
Body assembly prior to loading	8861569	25	3.2	4.3.3.15
Loading assembly prior to assembly of closing cap Examination of defects Average weight	8861565	 25 25	 3.2 3.2.3	 4.3.3.16 4.4.9

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection (continued).

Examination or test	Drawing	Sample Size	Requirement paragraph	Inspection method
Charge, Demolition: Shaped, 15 LB, M2A4 Loading Assembly	8861565			
Examination of defects		25 1/	3.3.1	4.3.3.17
Radiographic examination		10	3.2.6	4.4.10
Function test		10	3.7	4.4.11
Box, fiberboard prior to sealing	9281170	4.3.3.18	5.1	4.3.3.18
Box, fiberboard	9281170	4.3.3.19	5.1	4.3.3.19
Sealed packed barrier bag prior to packing in box	9281170		5.1	
Examination of defects		4.3.3.20		4.3.3.20
Heat seal test		2/		4.4.12
Packing box prior to securing top	9281170	4.3.3.21	5.1	4.3.3.21
Packing box	9281170	4.3.3.22	5.1	4.3.3.22
Unitization	19-48-4116 19-48-4116/120H	4.3.3.23	5.2	4.3.3.23

NOTE:
1/ 100% inspection of all drawing characteristics shall be performed.
2/ The test shall be performed at the beginning of each shift on three (3) sealed barrier bags from each sealer.

4.3 Conformance inspection.

4.3.1 Inspection lot formation. Inspection lots shall conform to the requirements of MIL-STD-1916. Inspection lots shall contain materials from not more than one lot interfix number from one manufacturer (when applicable). When not applicable, lot formation shall be homogeneous. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings and revisions, and the same specifications and revisions. In addition, each lot shall contain materials from not more than one lot interfix number from one manufacturer.

4.3.2 Ammunition lot numbering. Visually verify that a unique ammunition lot number has been assigned to each lot as described in MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection requirements by classification of characteristics.

a. For the conformance inspection paragraphs 4.3.3.1 through 4.3.3.22, the definitions of critical, major, and minor defects are provided in paragraph "Definitions" of MIL-STD-1916.
b. The acceptance criteria for sampling inspection shall be in accordance with the levels provided in conformance examination/test paragraph and MIL-STD-1916.
c. Alternative conformance acceptance. Alternate conformance procedures may be proposed (See paragraph "Acceptance by contractor-proposed provisions" of MIL-STD-1916).

4.3.3.1 Glass.				Drawing number 9230178 Next higher assembly 8861579
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Specific gravity of glass	10	3.2.1	4.4.5
Minor				
201	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.2 Well, detonator.				Drawing number 8858399 Next higher assembly 8858397
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Diameter of cavity	VL IV	3.2	Gage
102	Depth of cavity, minimum (min.)	VL IV	3.2	Gage
103	Outside diameter of body, maximum (max.)	VL IV	3.2	Gage
Minor				
201	Diameter of flange, max.	VL II	3.2	Gage
202	Thickness of flange, max.	VL II	3.2	Gage
203	Length of closed end, max.	VL II	3.2	Gage
204	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.3 Adapter, well, detonator.				Drawing number 8858398 Next higher assembly 8858397
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Pitch diameter of thread, min.	VL IV	3.2	Gage
102	Minor diameter of thread, max.	VL IV	3.2	Gage
Minor				
201	Overall length, min.	VL II	3.2	Gage
202	Evidence of poor workmanship	VL II	3.8	Visual

4.3.3.4 Detonator well assembly.				Drawing number 8858397 Next higher assembly 8861568
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Concentricity of inside diameter with thread	VL IV	3.2	Gage
Minor				
201	Assembled length of adapter, min.	VL II	3.2	Gage
202	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.5 Well, detonator (alternative).				Drawing number 8858400 Next higher assembly 8861568
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Pitch diameter of thread, min	VL IV	3.2	Gage
102	Minor diameter of thread, max.	VL IV	3.2	Gage
103	Diameter of small cavity, min.	VL IV	3.2	Gage
104	Depth of cavity, min.	VL IV	3.2	Gage
105	Outside diameter of small end, min.	VL IV	3.2	Gage
106	Depth of thread cavity, min.	VL IV	3.2	Gage
107	Concentricity of inside diameter with thread	VL IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	VL II	3.8	Visual

4.3.3.6 Cap, closing.				Drawing number 8861582 Next higher assembly 8861568
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major	None defined			
Minor				
201	Internal depth, min.	VL II	3.2	Gage
202	Flange improperly formed	VL II	3.2	Visual
203	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.7 Closing cap assembly.				Drawing number 8861568 Next higher assembly 8861565
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Concentricity of inside diameter of cap with thread	VL IV	3.2	Gage
102	Leakproofness of closing cap assembly	100%	3.4	4.4.2
Minor				
201	Evidence of poor workmanship	VL II	3.8	Visual

4.3.3.8 Cone.				Drawing number 8861579 Next higher assembly 8861572
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Concentricity of large outside diameter with basic diameters	VL IV	3.2	Gage
102	Location of large basic diameter	VL IV	3.2	Gage
103	Excessive wall thickness variation	VL IV	3.2	Gage
104	Location of small basic diameter	VL IV	3.2	Gage
105	Annealing of cone	100%	3.2.6	4.4.6
106	Heat shock test of cone	25	3.2.7	4.4.7
Minor				
201	Large outside diameter, max.	VL II	3.2	Gage
202	Total height, max.	VL II	3.2	Gage
203	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.9 Cone assembly.				Drawing number 8861572
				Next higher assembly 8861569
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Excessive misalignment between ring, bottom and retainer ring, cone	VL IV	3.2	Visual
102	Cone loose	VL IV	3.2	Manual
Minor				
201	Protective coating missing	VL II	3.2	Visual
202	Evidence of poor workmanship	VL II	3.8	Visual

4.3.3.10 Container, cone.				Drawing number 8861570
				Next higher assembly 8861569
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Location of upper basic diameter	VL IV	3.2	Gage
102	Concentricity of small inside diameter with basic diameter	VL IV	3.2	Gage
103	Large inside diameter	VL IV	3.2	Gage
104	Location of lower basic diameter	VL IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.11 Body assembly, prior to attaching carrying straps.				Drawing number 8861569 Next higher assembly 8861565
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Concentricity of container of cone	VL IV	3.2	Gage
102	Cone assembly insecure	VL IV	3.2	Manual
103	Reinforcing ring missing or improperly crimped	VL IV	3.2	Visual
104	Bare spot on interior surface	VL IV	3.2	Visual
105	Leakproofness of body assembly	100%	3.3	4.4.1
106	Fit of closing cap assembly	25	3.5	4.4.3
Minor				
201	Gap at base, max.	VL II	3.2	Gage
202	Evidence of poor workmanship	VL II	3.8	Visual

4.3.3.12 Body assembly.				Drawing number 8861569 Next higher assembly 8861565
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major	None defined			
Minor				
201	Carrying strap missing or improperly assembled	VL II	3.2	Visual/Manual
202	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.13 Sleeve, stand-off.				Drawing number 8861567 Next higher assembly 9230162
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Total length, max.	VL IV	3.2	Gage
102	Distance shoulder to end	VL IV	3.2	Gage
103	Fit of stand-off sleeve	25	3.6	4.4.4
Minor				
202	Evidence of poor workmanship	VL II	3.8	Visual

4.3.3.14 Booster.				Drawing number 8858393 Next higher assembly 8861565
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Concentricity of small cavity to outside diameter	VL IV	3.2	Gage
102	Diameter of small cavity, min.	VL IV	3.2	Gage
103	Depth of Large cavity, min.	VL IV	3.2	Gage
104	Specific gravity	4.4.8	3.2.4	4.4.8
Minor				
201	Depth of small cavity, min.	VL II	3.2	Gage
202	Diameter of large cavity, min.	VL II	3.2	Gage
203	Total length, max.	VL II	3.2	Gage
204	Radius missing	VL II	3.2	Visual
205	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.15 Body assembly prior to loading.				Drawing number 8861569 Next higher assembly 8861565
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Outside diameter, max.	VL IV	3.2	Gage
102	Interior protective finish discontinuous, scratched or contains bare spots	VL IV 1/	3.2	Visual
103	Foreign matter present in interior	VL IV	3.2	Visual
104	Carrying strap damaged	VL IV	3.2	Visual
Minor				
201	Evidence of poor workmanship	VL II	3.8	Visual
NOTE: 1/ Any scratch deep enough to show the base material of the item				

4.3.3.16 Loading assembly prior to assembly of closing cap.				Drawing number 8861565 Next higher assembly 9281170
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Component missing, loose or improperly assembled	VL IV	3.2	Visual/Manual
102	Body assembly damaged	VL IV	3.2	Visual
103	Average weight	25	3.2.5	4.4.9
Minor				
201	Depth to charge, min.	VL II	3.2	Gage
202	Evidence of poor workmanship	VL II	3.8	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.17 Charge, Demolition: Shaped, 15 LB, M2A4 Loading Assembly.				Drawing number 8861565 Next higher assembly 9281170
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Gage does not enter detonator well freely to full length	VL IV	3.2	Gage
102	Closing cap assembly loose	VL IV	3.2	Manual
103	Protective tape missing	VL IV	3.2	Visual
104	Radiographic examination	25	3.2.6	4.4.10
105	Functioning test	10 1/	3.7	4.4.11
Minor				
201	Total length	VL II	3.2	Gage
202	Marking missing, incorrect or illegible	VL II	3.2	Visual
203	Evidence of poor workmanship	VL II	3.8	Visual

NOTE:
1/ After three (3) consecutive lots have met the criteria, a sample of five (5) test units shall be selected and function tested out of each lot produced. If one or more loaded units fail to function (or a new First Article is required), the sampling shall return to the original test plan and continue until three (3) consecutive lots have complied with the acceptance criteria specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.18 Box, fiberboard prior to sealing.				Drawing number 9281170 Next higher assembly 19-48-4116 19-48-4116/120H
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Component missing or improperly packed	VL IV	5.1	Visual
Minor				
201	Presence of M1A5 adapters (Dwg #13021902)	VL II	5.1	Visual
202	Evidence of poor workmanship	VL II	5.1	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.19 Box, fiberboard.				Drawing number 9281170 Next higher assembly 19-48-4116 19-48-4116/120H
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Sealing strip incomplete or loose	VL IV	5.1	Visual
102	Box punctured, torn or cut	VL IV	5.1	Visual
103	Corner not blunted	VL IV	5.1	Visual
Minor				
201	Marking missing, incorrect or illegible	VL II	5.1	Visual
202	Contents loose	VL II	5.1	Manual
203	Evidence of poor workmanship	VL II	5.1	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.20 Sealed packed barrier bag prior to packing in box.				Drawing number 9281170 Next higher assembly 19-48-4116 19-48-4116/120H
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Waterproofness of barrier bag destroyed by rupture, puncture or separation of heat seal	VL IV	5.1	Visual
102	Evidence of crushed box (see 1/)	VL IV	5.1	Visual
103	All excess air not exhausted from bag prior to sealing	VL IV	5.1	Visual
104	Heat seal test	2/	5.1	4.4.12
Minor				
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied	VL II	5.1	Visual
202	Marking of bag improper or unidentifiable	VL II	5.1	Visual
203	Evidence of poor workmanship	VL II	5.1	Visual

NOTE:
1/ Evidence of visible dents or deformations, torn or punctured surfaces and or collapsed regions on the box
2/ The test shall be performed at the beginning of each shift on one (1) sealed barrier bag from each sealer. For sampling purposes, consider a shift to be no be more than ten (10) hours

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.21 Packing box prior to securing top.				Drawing number 9281170 Next higher assembly 19-48-4116 19-48-4116/120H
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Number of sealed bags incorrect	VL IV	5.1	Visual
102	Any packing component missing	VL IV	5.1	Visual
Minor				
201	Insufficient filler material	VL II	5.1	Visual
202	Evidence of poor workmanship	VL II	5.1	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.22 Packing box.				Drawing number 9281170 Next higher assembly 19-48-4116 19-48-4116/120H
	Examination or test	Conformance criteria	Requirement paragraph	Inspection method
Critical	None defined			
Major				
101	Board broken or split	VL IV	5.1	Visual
102	Contents exposed or loose	VL IV	5.1	Visual/Manual
103	Hardware or strapping missing, loose or broken	VL IV	5.1	Visual/Manual
104	NSN number missing or misleading	VL IV	5.1	Visual
Minor				
201	Marking missing, incorrect or illegible	VL II	5.1	Visual
202	Evidence of poor workmanship	VL II	5.1	Visual
203	Metallic seal missing, missing manufacturer's identification, incorrect, not secured, or not applied correctly	VL II	5.1	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.23 Unitization.			Drawing Number 19-48-4116 19-48-4116/120H Next Higher Assembly 13025692	
	Examination	Conformance Criteria	Requirement Paragraph	Inspection method
Critical	None defined			
Major				
101	Wood preservative and heat treatment markings for the pallet missing, incorrect, illegible, or not in proper location	VL II	5.2	Visual
102	Pallet load markings -including 2D bar codes - missing, incorrect, illegible, or not in proper location	VL II	5.2	Visual
103	Filler assembly not built, treated, or marked correctly	VL II	5.2	Visual
104	Boxes incorrectly oriented or positioned on pallet	VL II	5.2	Visual
105	Strapping not applied correctly or incorrect type	VL II	5.2	Visual
106	Unit load not tightly strapped or any strap loose	VL II	5.2	Visual / Manual
Minor				
201	Workmanship	VL I	5.1	Visual

4.4 Test methods and procedures.

4.4.1 Leakproofness of body assembly. The unit shall be assembled to the test equipment, the required internal pressure applied, and observation made for leakage for the specified period. Any assembly exhibiting more than the specified leakage shall be classified defective and removed from the lot.

4.4.2 Leakproofness of closing cap assembly. The unit shall be assembled to the test equipment, the required internal pressure applied, and observation made for leakage for the specified period. Any assembly exhibiting leakage shall be classified defective and removed from the lot.

4.4.3 Fit of closing cap assembly. Unless otherwise noted, a sample of twenty-five (25) closing cap assemblies and twenty-five (25) body assemblies minus cone assembly shall be selected from each lot for this test. The closing cap assembly shall be assembled to its cone container using applicable equipment. Failure to require a force fit that leaves the assembly loose or damaged shall class the full assembly defective. Failure of one or more full assemblies in meeting the requirement shall reject both lots of components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.4.4 Fit of stand-off sleeve. Unless otherwise noted, a sample of twenty-five (25) stand-off sleeves and twenty-five (25) body assemblies shall be selected during first article and from each lot for this test. The samples of stand-off sleeves and body assemblies shall be segregated into random combinations of one unit of each. The stand-off sleeve shall be placed on a level surface, the body assembly placed thereon, and the required load applied to the top of the body assembly. The gap between the components shall be measured, the assembly picked up and given a sharp shake toward ejection of the sleeve. If the gap is excessive or the sleeve disassembles when shaken, the assembly shall be classed defective. Failure of one or more combinations in meeting either requirement shall reject both lots of components.

4.4.5 Specific gravity of glass cone. Ten (10) sample cones in each lot shall be checked to determine compliance with the density requirements. The density shall be obtained by weighing the sample cone, first in air and then, while freely suspended in distilled water. The temperature of the distilled water shall be 68 degrees Fahrenheit (ºF) +/- 2 ºF (see TABLE III). The weight of the cone should be to the nearest .01 grams. The density shall be calculated by means of the following formula:

$$\textit{Specific gravity} = \frac{\textit{Weight of glass cone dry}}{\textit{(Weight of glass cone dry minus Weight of glass cone immersed in water)}} \times \textit{Specific gravity of } H_2O \textit{ at test temperature (see Table III)}$$

If any sample cone fails to meet this requirement, this failure shall be considered cause for rejection of the lot represented.

4.4.6 Annealing of glass cone. The cones shall be examined by means of a polariscope to determine whether the glass has been relieved of all strains. Cones showing evidence of unrelieved strains shall be rejected. Any glass cone which fails to comply with the applicable requirements shall be classed defective, and this sample shall be rejected.

4.4.7 Heat shock test of glass cone. The sample cone shall be conditioned at 45 degrees Fahrenheit (ºF) +/- 4 ºF for twenty (20) minutes minimum. Only the convex exterior surface of the cones (which will have direct contact with Composition B) shall then be placed for two (2) minutes, minimum, into water maintained at 203 degrees Fahrenheit (ºF) +/- 9 ºF. Any sample cone which breaks or shows cracks shall be cause for rejection of the sample and lot of cones.

4.4.8 Specific gravity of booster. (See Drawing (dwg.) 8858393) A sample of ten (10) boosters shall be selected from each lot for this test. If any booster fails to meet the requirement specified, the lot shall be rejected. The booster shall be weighed on a balance and the weight recorded as dry weight. The booster shall then be weighed while completely submerged in water, taking care to remove all air bubbles remaining on the surfaces of the booster. The temperature of the distilled water shall be 68 degrees ºF +/- 2 ºF. This weight shall be recorded as weight under water. (When submerged, the position of the booster shall be such that no air is

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

entrapped.)The weight of the booster should be to the nearest .01 grams. Specific gravity shall be calculated as follows:

$$\textit{Specific gravity} = \frac{\textit{Weight of booster dry}}{\textit{(Weight of booster dry minus Weight of booster immersed in water)}} \times \textit{Specific gravity of } H_2O \textit{ at test temperature (see Table III)}$$

Table III. Specific gravity of water in test temperature range.

Temp °F	Temp °C	Specific Gravity of H_2O
66	18.89	0.9984
67	19.44	0.9983
68	20.00	0.9982
69	20.56	0.9981
70	21.11	0.9980

4.4.9 Weight of charge and average weight. The loading assembly shall be weighed on a scale capable of determining weights within an accuracy of two (2) ounces. The mean average weight shall be obtained from twenty-five (25) parts assemblies (dwg. 8861569) and subtracted from the weight of the loading assembly (dwg. 8861565) to determine compliance with the requirement. If the mean average weight of the sample assemblies fails to meet the weight requirement, all samples shall be classified as defective and the lot shall be rejected.

4.4.10 Radiographic examination. Radiographic equipment, operations and procedures shall be in accordance with ASTM E1742/E1742M. The radiographic examination shall detect voids, cracks, cavitation, separation, and cracking of the explosive and presence of any foreign material. The assembly shall be radiographically inspected two (2) times. The assembly shall be inspected along its length, rotated approximately ninety degrees (90°) on its cylindrical axis, and inspected a second time. Any assembly which does not meet the criteria shall reject the sample(s).

4.4.11 Functioning test. Ten (10) test units shall be selected from each lot. The test shall be detonated using an M6 or M7 blasting cap (see 6.2j) or equivalent military initiation device held in place with the priming adapter. The test shall also be conducted at local temperatures and temperatures shall be recorded for data collection purposes only. Any test unit which fails to detonate high order shall be classified as defective and the lot is to be rejected. Observation shall be made for the presence of undetonated charge and for evidence of double- or multi-jets. Presence of either shall classify a unit defective. The RHA target shall be of a size not less than twelve (12) inches in total thickness with a maximum of six (6) plates making up that thickness. The first four (4) inches shall be made up of a maximum of two (2) plates at two (2) inches minimum thickness each. The surface area shall not be less than 144 inches made up with one (1) plate. Any penetration depth not meeting the requirements shall be classified as a unit failure and the lot is to be rejected. After three (3) consecutive lots have met the criteria, a sample of five (5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

test units shall be selected and function tested out of each lot produced. If one or more loaded units fail to function, the lot shall be rejected and the sampling shall return to the original test plan.

4.4.12 Heat seal test of sealed bag (destructive). Sampling, acceptance criteria and test procedures for this test shall be as specified in MIL-STD-2073-1, para 5.2.3.6.1 Method 41 Water vaporproof bag, heat sealed. Samples that do not meet the heat seal requirement shall be rejected and all samples tested to last successful test.

5. PACKAGING

5.1 Packaging and marking. The materials, components, and assemblies shall comply with Drawing 9281170 for the M2A4 and all their subsidiary drawings.

5.2 Unitization. Unitize M2A4 in accordance with Drawing 19-48-4116/120H and their subsidiary drawings.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The 15 lb. Shaped Demolition Charge is primarily employed for burring holes in earth, metal, concrete, and paved or unpaved roads

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Requirement for acceptance inspection equipment (AIE) designs.

d. Requirement for Alternate Acceptance Plans.

e. Requirements for Ammunition Lot Numbering, if applicable.

f. Requirement for propellant and energetic materials IAW MIL-STD-1171

g. Certificate of Conformance for each lot or shipment of product.

h. Preservation and packaging. Preservation, packaging, packing and marking should be in accordance with Dwg. 9281170.

i. Radiographic personnel should be qualified in accordance with NAS 410.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

j. The 15 lb. Shaped Demolition Charge should be functioned with either an M6 Blasting Cap in accordance with MIL-PRF-32293A or an M7 Blasting Cap in accordance with MIL-DTL-45469F and Drawing 8830948.

6.3 Radiographic examination. Complete results of the radiographic examination should be available to the Government through the Contracting Officer. Distribution should include: DEVCOM-AC, ATTN: FCDD-ACE-QEA & FCDD-ACE-QWE, Picatinny, NJ 07806-5000.

6.4 Acceptance inspection equipment. Complete results of the acceptance inspection equipment should be available to the Government through the Contracting Officer. Distribution should include: DEVCOM-AC, ATTN: FCDD-ACE-QWE , Picatinny, NJ 07806-5000.

6.5 Superseding explanatory note. This revision combines MIL-DTL-13139F with MIL-DTL-2156D into a single specification. MIL-DTL-13139F covered the parts for manufacturing the CHARGE, DEMOLITION, SHAPED, 15LB.-M2A4, and MIL-DTL-2156D covered the loading, assembling and packing for the same item. As a result of the combination of the two specifications, MIL-DTL-13139F has been cancelled.

6.6 Interim specification. This interim specification has an expiration date two (2) years from its date on the cover sheet. Afterwards, this interim specification is planned to be cancelled by the Preparing Activity Standardization Office, or the Defense Standardization Program Office, if not already superseded by a final specification. The Standardization Project Number for the final specification is 1375-2026-017. Standardization policy prohibits any amendments to this interim specification after (1) year from its publication. Standardization policy prohibits any revisions to an interim specification.

6.7 Subject term (key word) listing.

Explosive
Composition B

6.8 Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodian:
Army-AR

Preparing Activity:
Army-AR
(Project 1375-2026-016)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.