MIL-F-2096
10 March 1950

MILITARY SPECIFICATION

FUZE, POINT DETONATING, M75, METAL PARTS FOR

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments, and supersedes the following specification:

Army 50-40-21
29 November 1948

This specification consists of this cover sheet and Specification 50-40-21, dated 29 November 1948, attached hereto, without modification.

Copies of this specification may be obtained upon application to the Office, Chief of Ordnance, Washington 25, D. C.

When a request for this specification is received by a supplying activity it will be necessary to attach this cover sheet to the pertinent specification before issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:20Z
Check the source to verify that this is the current version before use.

No. 50-40-21
29 November 1948

U. S. ARMY SPECIFICATION

FUZE, POINT DETONATING, M75, METAL PARTS FOR

1. SCOPE.

1.1 This specification covers metal parts for one type of fuze.

2. APPLICABLE SPECIFICATIONS AND DRAWINGS.

2.1 The Ordnance Department Drawing 73-1-193 and all drawings and specifications listed or referred to thereon pertaining to metal parts, form a part of this specification.

2.2 All drawings and specifications shall be of the issue in effect on the date of invitation for bids.

3. REQUIREMENTS.

3.1 Materials and parts shall meet all requirements prescribed on applicable specifications and drawings.

3.2 All parts shall be free from chips, dirt, grease, and other foreign material before any assembling operations are conducted. Parts which are assembled by the metal parts contractor shall be thoroughly cleaned before assembling is performed. When cleaning is necessary, the method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent used.

3.3 Where parts are required to be lacquered, the lacquer shall be applied when the part to be lacquered is sufficiently hot to drive off any excess of solvent. The lacquer shall adhere firmly and present a smooth, clean and dry surface, free from cracks, flaws, impurities and other imperfections.

3.4 Plated Parts. No plated part shall show any rust after being subjected to a salt spray for a period of 24 hours.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES.

4.1 Inspection.

4.1.1 Inspection shall be as specified in General Specification for Ammunition Except Small Arms Ammunition, No. 50-0-1.

4.1.2 The inspector shall assure himself that the lacquer coating of surfaces required to be lacquered is satisfactory.

4.2 Size of Lots. Parts for 100,000 fuzes, maximum. A smaller quantity may constitute a lot at the discretion of the inspector. Parts for 2000 plus or minus 500 fuzes shall constitute the first lot manufactured on any contract, except when a new contract immediately follows the manufacture of satisfactory material of the same character.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:20Z
Check the source to verify that this is the current version before use.

4.3 Test of Plated or Painted Parts. Thirty of each plated or painted part selected by the inspector from each lot shall be subjected to a salt spray test which shall be conducted in accordance with the applicable provisions of Specification No. 57-0-2.

5. PREPARATION FOR DELIVERY.

5.1 Packing.

5.1.1 Fuze parts shall be delivered in cartons constructed from double-faced, type A or B flute corrugated, fiberboard having a minimum Mullen strength of 200 pounds. The inside packing for the assembly (partial) and magazine shall be die-cut chipboard pads. Sheets of grease-proof paper shall be so placed as to prevent contact of the top and bottom of the carton with the metal parts in the top and bottom layers. Each container shall contain only one kind of part or sub-assembly.

5.1.2 Data Card. Data cards, 5 by 8 inches, made of commercial manila tag board, approximately 200 pounds ream weight, shall be prepared for each lot of accepted parts to provide the information specified below. Quantities (approximately 50 cards per lot) and distribution of data cards shall be in accordance with instructions issued by the Office, Chief of Ordnance.

DATA CARD

Kind _____ Lot No. _____

Quantity in Lot _____

Dwg. No.* _____ Spec. No.* _____

Manufactured by _____ Date _____

Contract No. _____ Order No. _____

Packed _____ in a box.

Remarks _____

Certified to by _____ Inspector.
(Print here name of Inspector, District, Arsenal, or Loading Plant, and Sub-District where applicable)

* Include revision and amendments.

(NOTE: When the contractor of metal parts for the Fuze, Point, Detonating, M75, is also the contractor for loading, assembling, and packing of the fuzes, no data cards will be required for the metal parts.)

5.2 Marking. The marking for shipment shall be in accordance with Standard Specification for Marking Shipments, No. 100-2.

6. NOTES.

6.1 This specification replaces Ordnance Department Tentative Specification AXS-1209.

6.2 The use of this specification, whenever applicable, is mandatory on all procuring agencies of the Army.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:20Z
Check the source to verify that this is the current version before use.

NOTICE: This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions is intended for use only in connection with procurement by the United States Government, and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

NOTE: Copies of this specification may be obtained from the Office, Chief of Ordnance, Department of the Army, Washington 25, D. C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:20Z
Check the source to verify that this is the current version before use.