MIL-F-2150C(MU)
20 September 1968
SUPERSEDING
MIL-F-2150B(MU)
23 May 1966

MILITARY SPECIFICATION

FUZE, PD, M503A2
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of fuze designated as Fuze, PD, M503A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of
MIL-P-46464 - Pellets, Tetryl

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

9215031 - Fuze, PD, M503A2 (Loading)
9215630 - Box, Fiber, Packing, Ammunition, For Fuze, PD, M503A2 Without Booster
9215631 - Box, Wire Bound, Packing, For Fuze, PD, M503A2 Without Booster

PUBLICATIONS

ARMY

ET-9215031 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly.-The assembly shall comply with all requirements specified on drawing (dwg.) 9215031 and with all requirements specified in applicable specifications.

3.3 Jolt and Jumble.-The fuze assembly shall comply with the requirements of MIL-STD-331, Test 101 and Test 102 respectively.

3.4 Transportation Vibration.-The fuze assembly shall comply with the requirements of MIL-STD-331, Test 104.

3.5 Waterproofness.-The fuze shall comply with the requirements of MIL-STD-331, Test No. 108.

3.6 Proving ground test

3.6.1 Ballistic functioning.-The fuze shall not premature function (see 6.5) and shall cause the projectile to function high order upon impact against a target located 100 feet from the muzzle of the weapon.

3.6.2 Ballistic graze functioning.-The fuze shall not premature function and shall cause the projectile to function high order upon graze impact. The angle of impact shall not exceed 5 degrees (^{o}).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

3.6.3 Ballistic non-functioning.-The fuze shall not premature function nor cause the projectile to function high order upon impact against a target located 60 feet from the muzzle of the weapon.

3.7 First article inspection.-This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship.-All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 50 assemblies and 50 complete sets of parts (i.e. 50 each of every component and every subassembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in 4.3.2 and 4.4.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only thatquantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specifications, or drawings, not affecting safety, performance, interchangeability, or storage, as determined by the design agency, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

a. Parts and assemblies of one lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.-Inspection for Critical defects shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Fuze, PD, M503A2, Less Pellets, Booster and Booster Lead (see dwg. 9234644 covering a detail of dwg. 9215031)

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:			
1.	Scribe line on rotor assembly not in line with scribe line on housing assembly	Visual	01001
Major:	None defined.		
Minor:	None defined.		

4.3.2.2 Pellet, Booster Lead (see dwg. 9234643 covering a detail of dwg. 9215031).-Inspection shall be in accordance with MIL-P-46464.

4.3.2.3 Pellet, Booster (see dwg. 9215036 covering a detail of dwg. 9215031) - Inspection shall be in accordance with MIL-P-46464.

4.3.2.4 Booster Lead Assembly (see dwg. 9234642 covering a detail of dwg. 9215031)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Booster lead cup pellet above flush, max	Visual	04001
2.	Split, cut or hole through wall or bottom	Visual	04002
Major:	AQL 0.40 percent		
101.	Length under flange, max. ...	Gage	04003

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

Minor:	AQL 0.65 percent		
201.	Booster lead cup charge below flush, max.	Visual	04004
202.	Evidence of poor workmanship (see 3.8)	Visual	04005

4.3.2.5 Fuze, PD, M503A2 prior to assembly of booster cup and disc (see dwg. 9215031)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Booster lead cup assembly missing	Visual	05001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.8)	Visual	05002

4.3.2.6 Assembly prior to assembly of booster cup (see dwg. 9215031)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Booster disc missing	Visual	06001
Major:	AQL 0.40 percent		
101.	Booster pellet missing	Visual	06002
Minor:	AQL 1.0 percent		
201.	Booster pellet below flush ..	Visual	06003
202.	Evidence of poor workmanship (see 3.8)	Visual	06004

4.3.2.7 Fuze, PD, M503A2 (see dwg. 9215031)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Distance to flange, max.	Gage	07001
102.	Booster cup loose or not staked	Manual-Visual	07002

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.8)	Visual	07003
202.	Marking, misleading or unidentifiable	Visual	07004

4.3.2.8 Sealed fiber container (see dwg. 9215630)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Container cut or damaged through all impregnated layers	Visual-Manual	08001
102.	Metal end loose or distorted	Visual-Manual	08002
103.	Tape incomplete or badly wrinkled	Visual	08003
Minor:	AQL 1.5 percent		
201.	Tear tab length, min.	Scale	08004
202.	Contents move when shaken	Manual	08005
203.	Marking misleading or unidentifiable	Visual	08006
204.	Gap between cover and body of container exceeds 1/8 inch	Visual	08007

4.3.2.9 Sealed wood packing box (see dwg. 9215631)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Hardware missing, broken or loose	Visual-Manual	09001
102.	Strapping missing, broken or loose	Visual-Manual	09002
103.	Board broken or split	Visual	09003
104.	Contents exposed	Visual	09004
105.	DOD marking misleading or unidentifiable	Visual	09005
Minor:	AQL 2.5 percent		
201.	Hardware improperly engaged	Visual-Manual	09006

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

202.	Strapping improperly engaged	Visual-Manual	09007
203.	Car seal missing, unsealed or improperly positioned ...	Visual-Manual	09008
204.	Contents move when shaken ..	Manual	09009
205.	Marking misleading or unidentifiable	Visual	09010

4.3.3 Testing

4.3.3.1 Jolt and jumble (see 3.3) - Critical defect - Code No. 07010.

4.3.3.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with 3.3, thirty samples shall be randomly selected from each lot for this test. If one or more samples fail to comply with the applicable requirements, the lot shall be rejected. The test shall be performed as specified in 4.4.1.

4.3.3.1.2 After three consecutive lots have complied with 3.3, twelve samples shall be randomly selected from each lot for this test. If one or more samples fail to comply with the applicable requirements, the lot shall be rejected. The test shall be performed as specified in 4.4.1.

4.3.3.2 Transportation-vibration (see 3.4) - Safety deficiency - Critical defect - Code No. 07005 - Operability deficiency - Major defect - Code No. 07006.

4.3.3.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with 3.4, thirty samples shall be randomly selected from each lot for this test. If one or more samples fail to comply with the safety or operability requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.2.

4.3.3.2.2 After three consecutive lots have complied with 3.4, twelve samples shall be randomly selected from each lot for this test. If one or more samples fail to comply with the safety or operability requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.2.

4.3.3.3 Waterproofness (see 3.5) - Operability deficiency - Major defect - Code No. 07011.

4.3.3.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with 3.5, thirty samples shall be randomly selected from each lot for this test. If one or more samples fail to comply with the requirements, the lot shall be rejected. The test shall be performed as specified in 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.3.2 After three consecutive lots have complied with 3.5, twelve samples shall be randomly selected from each lot for this test. If one or more samples fail to comply with the requirements, the lot shall be rejected. The test shall be performed as specified in 4.4.3.

4.3.3.4 Specific gravity of booster pellet - Major defect, Code No. 10001.-Fifty samples shall be selected from each lot for this test. If one or more samples fail to comply with the specific gravity requirement on dwg. 9215036, the lot shall be rejected. The test shall be performed as specified in 4.4.4.

4.3.3.5 Composition of pellets.-The sampling plan shall be as specified in MIL-P-46464. The test shall be performed as specified in 4.4.5.

4.3.3.6 Determination of total graphite of binding lubricant content of pellets.-The sampling plan shall be as specified in MIL-P-46464. The test shall be performed as specified in 4.4.6.

4.3.3.7 Proving ground test (see 3.6) - Functioning failure - Major defect - Code No. 07007 - Non-functioning failure - Critical defect - Code No. 07008 - Premature function-Critical defect - Code No. 07009.-The sample plan shall be in accordance with 4.3.3.7.1 through 4.3.3.7.3. The test shall be performed as specified in 4.4.7.

4.3.3.7.1 Ballistic functioning test

4.3.3.7.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with 3.6.1, one hundred twenty five samples shall be randomly selected from each lot. If four or more samples fail to function the projectile high order upon impact or one or more samples premature function, the lot shall be rejected. The test shall be performed as specified in 4.4.7.1.

4.3.3.7.1.2 After three consecutive lots have complied with 3.6.1, fifty samples shall be randomly selected from each lot. If two or more samples fail to function the projectile high order upon impact or one or more sample premature function, the lot shall be rejected. The test shall be performed as specified in 4.4.7.1.

4.3.3.7.2 Ballistic graze functioning

4.3.3.7.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with 3.6.2, one hundred twenty five samples shall be randomly selected from each lot. If four or more samples fail to function the projectile high order upon impact or one or more samples premature function, the lot shall be rejected. The test shall be performed as specified in 4.4.7.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.3.3.7.2.2 After three consecutive lots have complied with 3.6.2, fifty samples shall be randomly selected from each lot. If two or more samples fail to function the projectile high order upon impact or one or more samples premature function, the lot shall be rejected. The test shall be performed as specified in 4.4.7.2.

4.3.3.7.3 Ballistic non-functioning test

4.3.3.7.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with 3.6.3, one hundred twenty five samples shall be randomly selected from each lot. If one or more samples cause the projectile to function high order upon impact or one or more samples premature function, the lot shall be rejected. The test shall be performed as specified in 4.4.7.3.

4.3.3.7.3.2 After three consecutive lots have complied with 3.6.3, fifty samples shall be selected randomly from each lot. If one or more samples cause the projectile to function high order upon impact or one or more samples premature function, the lot shall be rejected. The test shall be performed as specified in 4.4.7.3.

4.3.4 Inspection Equipment - Equipment Tabulation Number ET-9215031 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.3.4.3 Government use of contractor's inspection equipment.-The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.4 Test method and procedures

4.4.1 Jolt and jumble.-The sample shall be subjected to the jolt test in accordance with MIL-STD-331. After completion of the jolt test, the sample shall not be disassembled but shall be subjected to the jumble test in accordance with MIL-STD-331. After the jolt and jumble test have been accomplished, the sample shall be disassembled and examined to determine compliance with 3.3. The equipment used for this test shall be in accordance with 4.3.4.

4.4.2 Transportation-vibration.-The sample shall be subjected to the transportation-vibration test in accordance with MIL-STD-331. Upon completion of the test the sample shall be disassembled and examined to determine compliance with 3.4. The equipment used for this test shall be in accordance with 4.3.4.

4.4.3 Waterproofness.-The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 108.

4.4.4 Specific gravity of booster pellet.-The sample shall be weighed on a balance and the weight recorded as dry weight. Then the sample shall be weighed while completely submerged in water (the temperature of the water shall be 68° Fahrenheit (F) ± 20° F. Specific gravity shall be calculated as follows.

$$\text{Specific gravity} = \frac{A}{A-B}$$

where:

A = dry weight of sample
B = weight of sample under water

4.4.5 Composition of pellets.-The test shall be performed as specified in MIL-P-46464.

4.4.6 Determination of total graphite or binding lubricant content of pellets.-The test shall be performed as specified in MIL-P-46464.

4.4.7 Proving ground test

4.4.7.1 Ballistic functioning test.-The fuze assembly shall be assembled to the 57MM Ctg, HE, M306A1 and fired from the 57MM recoilless rifle loaded to standard service velocity and pressure. The sample shall be fired at a one inch thick bursting screen located 100 feet from the muzzle of the weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

4.4.7.2 Ballistic graze functioning test.-The fuze assembly shall be assembled to the 57MM Ctg, HE, M306A1 and fired from the 57MM recoilless rifle loaded to standard service velocity and pressure. The angle of impact shall not be greater than 5°.

4.4.7.3 Ballistic non-functioning test.-The fuze assembly shall be assembled to the 57MM Ctg, HE, M306A1 and fired from the 57MM recoilless rifle loaded to standard service velocity and pressure. The sample shall be fired at a one inch thick bursting screen located 60 feet from the muzzle of the weapon.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packing

5.1.1 Level A.-The fuze assembly shall be preserved and packaged in accordance with dwg. 9215630.

5.2 Packing

5.2.1 Level A.-The packaged fuze assembly shall be packed in accordance with dwg. 9215631.

5.3 Marking.-The marking shall be in accordance with dwgs. 9215630 and 9215631.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications: mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND1. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Submission of test data.-In addition to the normal distribution of records and test results, when the fuze is procured by the Department of the Army, one copy of the ammunition data card, in accordance with MIL-STD-1167, one copy of the jolt, jumble and transportation vibration test results, one copy of ballistic test data and one copy of the delay time, temperature humidity and extreme temperature storage test results will be forward to each of the following:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-ND7 and SMUPA-DJ3
Dover, New Jersey 07801

6.5 Premature function.-Premature functioning is defined as functioning of the fuze in the weapon or along the trajectory prior to impact.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1390-A-751

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

343-220 (A-405)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:27Z
Check the source to verify that this is the current version before use.