MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, MARK 8 MOD 0

This amendment forms a part of Military Specification MIL-C-24017B(AS), dated 10 December 1985, and is approved for use within the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.8.1: Delete "velocity shall be 16.0 feet per second" and substitute "velocity shall be 7.2 feet per second". Delete the following sentence: "The upper limit (UL) of velocity shall be 25.0 feet per second."

3.8.2: Delete in its entirety

3.8.3: Delete in its entirety

3.8.4: Delete "not greater than 0.020 second" and substitute "not greater than 0.030 second."

PAGE 6

4.6.7: Delete in its entirety and substitute:

"**4.6.7 Ballistic test.** The number of cartridges selected from each production lot for the ballistic test shall be in accordance with table II. For test firing the Mark 8 impulse cartridges, a 2000-pound general purpose inertly loaded store shall be mounted on a standard Aero 3A bomb ejector rack. The position of the ejector shall be such that when a bomb is mounted on the ejector nose down and axis vertical, its nose shall be held 7 feet 6 inches from the ground. Suitable instrumentation for measuring chamber pressure and for determining the time from the closing of the firing circuit to the complete opening of one of the ejector hooks shall be installed. The cartridges shall be conditioned for 12 hours at 70° ± 5°F prior to firing in the ejector rack. Firing current shall be 10 ± 0.5 amperes dc. Any cartridge which fails the requirements stated in 3.8 shall be cause for rejection of the lot represented."

4.6.7.1 Delete in its entirety and substitute:

"**4.6.7.1 Velocity at ejection.** The velocity (V) shall be computed using the equation

$$V = d\sqrt{\frac{g}{2h}} = 1.465d = \text{individual velocity at ejection in feet per second}$$

where

h = vertical height of nose of store (7.5 feet)

g = 32.2 ft/s^2

d = horizontal ejection distance in feet.

The horizontal distance ejected (d) is measured in feet."

AMSC N/A

FSC 1377

Distribution Statement A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:44Z
Check the source to verify that this is the current version before use.

PAGE 8

6.4.5: Delete "is greater than 0.020 second" and substitute "is greater than 0.030 second"

Preparing activity
Navy-AS
(Project 1377-N938)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:44Z
Check the source to verify that this is the current version before use.